

Problem 1:

	C ₄	C ₃	C ₂	C ₁	C ₀	C ₄ ⊕ C ₃ ⊕ I	C ₄ ⊕ C ₁ ⊕ I	C ₄ ⊕ I	I=input
Initial	0	0	0	0	0	1	1	1	1
Step 1	1	0	1	0	1	1	1	1	0
Step 2	1	1	1	1	1	1	1	0	1
Step 3	1	1	1	1	0	0	0	1	0
Step 4	0	1	0	0	1	1	0	0	0
Step 5	1	0	0	1	0	1	0	1	0
Step 6	1	0	0	0	1	0	0	0	1
Step 7	0	0	0	1	0	1	0	1	1
Step 8	1	0	0	0	1	1	1	1	0
Step 9	1	0	1	1	1	0	1	0	1
Step 10	0	1	1	1	0				

$$C_4 \oplus C_3 \oplus I = 1 \oplus 0 \oplus 0 = 1$$

$$C_4 \oplus C_1 \oplus I = 1 \oplus 0 \oplus 0 = 1$$

$$C_4 \oplus I = 1 \oplus 0 = 1$$

$$C_4 \oplus C_3 \oplus I = 1 \oplus 1 \oplus 1 = 1$$

$$C_4 \oplus C_1 \oplus I = 1 \oplus 1 \oplus 1 = 1$$

$$C_4 \oplus I = 1 \oplus 1 = 0$$

$$C_4 \oplus C_3 \oplus I = 1 \oplus 1 \oplus 0 = 0$$

$$C_4 \oplus C_1 \oplus I = 1 \oplus 1 \oplus 0 = 0$$

$$C_4 \oplus I = 1 \oplus 0 = 1$$

$$C_4 \oplus C_3 \oplus I = 0 \oplus 1 \oplus 0 = 1$$

$$C_4 \oplus C_1 \oplus I = 0 \oplus 0 \oplus 0 = 0$$

$$C_4 \oplus I = 0 \oplus 0 = 0$$

$$C_4 \oplus C_3 \oplus I = 1 \oplus 0 \oplus 0 = 1$$

$$C_4 \oplus C_1 \oplus I = 1 \oplus 1 \oplus 0 = 0$$

$$C_4 \oplus I = 1 \oplus 0 = 1$$

$$C_4 \oplus C_3 \oplus I = 1 \oplus 0 \oplus 1 = 0$$

$$C_4 \oplus C_1 \oplus I = 1 \oplus 0 \oplus 1 = 0$$

$$C_4 \oplus I = 1 \oplus 1 = 0$$

$$C_4 \oplus C_3 \oplus I = 0 \oplus 0 \oplus 1 = 1$$

$$C_4 \oplus C_1 \oplus I = 0 \oplus 1 \oplus 1 = 0$$

$$C_4 \oplus I = 0 \oplus 1 = 1$$

$$C_4 \oplus C_3 \oplus I = 1 \oplus 0 \oplus 0 = 1$$

$$C_4 \oplus C_1 \oplus I = 1 \oplus 0 \oplus 0 = 1$$

$$C_4 \oplus I = 1 \oplus 0 = 1$$

$$C_4 \oplus C_3 \oplus I = 1 \oplus 0 \oplus 1 = 0$$

$$C_4 \oplus C_1 \oplus I = 1 \oplus 1 \oplus 1 = 1$$

$$C_4 \oplus I = 1 \oplus 1 = 0$$

Problem 2:

The receiver will not detect the error because it uses single-bit even parity check. Because there are 2 bits that were changed, it will be unable to detect the error.

Problem 3: $P = n - k + 1$ $T = 2^{n-k} D + R$

$$P = n - k + 1 \rightarrow 6 = n - 8 + 1 \rightarrow n = 13$$


$$T = 2^{n-k} D + R = 2^{13-8} D + R = 2^5 D + R$$

$$\begin{array}{r}
 10110110 \\
 110011 \overline{) 1110001100000} \\
 \underline{110011} \\
 00101111 \\
 \underline{110011} \\
 0111000 \\
 \underline{110011} \\
 00101100 \\
 \underline{110011} \\
 0111110 \\
 \underline{110011} \\
 0011010
 \end{array}$$

$$\text{CRC} = 11010$$

Problem 4: $P = n - k + 1$ $T = 2^{n-k} D + R$

A)



B)

$$K = 9$$

$$P = n - k + 1 \rightarrow 5 = n - 9 + 1 \rightarrow n = 13$$

```

      101110100
11001|1110110010000
      11001
      ----
      0010010
        11001
        ----
        010110
          11001
          ----
          011111
            11001
            ----
            0011000
              11001
              ----
              0000100|

```

$$T = 1110110010100$$

$$\begin{aligned}
 T(x) &= 2^{n-k} D + R = 2^{13-9} D + R = 2^4 D + R = 2^4(x^8 + x^7 + x^6 + x^4 + x^3 + 1) + x^2 \\
 &= x^{12} + x^{11} + x^{10} + x^8 + x^7 + x^4 + x^2
 \end{aligned}$$

C)

```

      101110011|
11001|1110111010000
      11001
      ----
      0010011
        11001
        ----
        010100
          11001
          ----
          011011
            11001
            ----
            00010000
              11001
              ----
              010010
                11001
                ----
                01011

```

Because the remainder is 1011 and not 0 the detection algorithm will detect the error.

Problem 5:

A)

Hamming Distance:

$$01010 \rightarrow 00000 = 2 \quad 10101 \rightarrow 01010 = 5 \quad 10101 \rightarrow 00000 = 3$$

Minimum Hamming Distance:

The smallest hamming distance from the above values is 2.

B)

Hamming Distance:

$$110110 \rightarrow 000000 = 4$$

$$101010 \rightarrow 000000 = 3$$

$$010101 \rightarrow 000000 = 3$$

$$110110 \rightarrow 010101 = 3$$

$$110110 \rightarrow 101010 = 3$$

$$101010 \rightarrow 010101 = 6$$

Minimum Hamming Distance:

The minimum hamming distance from the above values is 3.

Problem 6:



Michael Lankford

RE: Robotics

Just now

1. There are 5 distinct types of robots: pre-programmed robots, humanoid robots, autonomous robots, teleoperated robots, augmenting robots.
2. The main components of a robot are: the CPU, sensors, actuators, a power supply, and end effectors.
3. Social robots interact with humans for a variety of tasks. These robots can respond to human behavior and emotions, and some believe they should also be able to differentiate between right and wrong.
4. As the AI field continuously gets better and closer to replicating human thought, there is the opportunity to power robots using this and let them be able to become intelligent and learn from everything around it, as humans do. For the present however, robots are only able to perform basic tasks using very basic AI, like problem-solving.
5. The future of robots is very large. Every day, humans are working to improve them in some way, like Boston Dynamics. Boston Dynamics have been developing a humanoid robot that is able to walk, run, and jump. This mobility has been one of the biggest breakthroughs in recent times because replicating the stability of a biped is extremely difficult, especially compared to quadrupeds who have 4 legs and distribute weight more evenly from front to back.

[Reply](#) [Quote](#)