



NavoX

Make sense of your day, across the tools you already use.

NavoX brings email, meetings, coursework and recurring costs into one daily view and a persistent conversation. A person can find a commitment, prepare for a meeting, locate a source or draft a reply without manually reconstructing context across separate applications.

The problem

A useful assistant needs trustworthy context and a clear boundary between suggesting an action and taking it. Information belongs to different accounts, source evidence can be incomplete, and retrying an ambiguous email send can produce a real mistake.

What you can do

A daily view with sources Priorities, upcoming meetings and follow-ups retain references to the information behind them. Attention preferences stay under the user's control.	A conversation that persists Saved sessions support source-linked retrieval, bounded multi-intent plans and clarification when available evidence is ambiguous.
Voice and a Chrome side panel Recorded microphone input, speech-to-text, text-to-speech and read-aloud controls accompany a Manifest V3 side panel. Page-note capture is explicitly initiated.	Actions you can review Email approval shows the exact recipient, subject and body. Material changes invalidate that approval before execution.

How it works

01 / Connect Authorize Gmail, Calendar or institution-configured Canvas; permissions remain scoped to the connected account.	02 / Retrieve Resolve owned source references and assemble relevant context rather than trusting client-supplied resource identifiers.
03 / Plan A qualified AI gateway and conversation runtime form a bounded plan or ask for clarification.	04 / Approve and verify Consequential actions require exact-action approval, worker rechecks and provider verification. Ambiguous send failures enter manual review.

TECHNOLOGY / TypeScript · Next.js · React · Python · FastAPI · PostgreSQL · Temporal · Docker · OpenAI · Anthropic · Google Gemini · Google Chrome

Decisions that shape the system

One provider boundary

OpenAI, Anthropic Claude and Google Gemini adapters sit behind model/task/prompt/schema qualification, sensitivity grants, token budgets and circuit breakers. An adapter alone does not enable a serving route.

Durable work, explicit authority

Temporal coordinates source processing, timers and bounded workflows. The assistant goal worker receives an opaque goal ID and rechecks saved state; it cannot approve or execute an action.

Owned state in PostgreSQL

Sessions, plans, source references, approval versions and audit events share clear ownership boundaries. Retrieval and action services revalidate access.

Observed validation

The reviewed hosted CI checkpoint df9397d recorded 2,820 API tests, 437 web tests with 14 skipped, and 8 extension tests. These are regression results for one source checkpoint, not a claim about production accuracy or availability.

Scope of this evidence

The portfolio walkthrough uses authored example data. It demonstrates the interface, not authenticated account retrieval or sending. Live connectors, AI routes and voice acceptance depend on workspace configuration and separate qualification.

Explore the implementation

Open NavoX

navox.net

Source code and local setup

github.com/michaelbawuah/NavoX

Approval and execution design

github.com/michaelbawuah/NavoX/blob/main/docs/architecture/milestone-6-approval-execution.md

Gateway qualification

github.com/michaelbawuah/NavoX/blob/main/docs/architecture/spec-005-live-acceptance.md

Recorded CI checkpoint

github.com/michaelbawuah/NavoX/actions/runs/37160769439

This brief explains the project using its public source and retained validation records. It is an engineering overview, not a research publication.