Predicting Ride Fare Prices with Machine Learning

Uber & Lyft Regression Analysis

Michael DeJournett
Intro to Machine Learning
mdejournett2@unl.edu

***Abstract*—This report studies ride fare prediction for Uber and Lyft trips using supervised learning. Given 14 trip-level features (distance, time, location, vehicle type, and weather conditions), the goal is to predict fare amount. We evaluate baseline Linear Regression and ensemble Random Forest models, report test-set performance with 95% confidence intervals, and compare model quality using regression metrics and normalized confusion matrices. The best model (Random Forest) achieves MAE = \$1.24, RMSE = \$2.26, and R^2 = 0.942 with a 95% confidence interval for MAE of [1.221, 1.275]. Results indicate that Random Forest provides the best trade-off between accuracy, stability, and practical usability for this dataset, outperforming the linear baseline.**

***Index Terms*—machine learning, regression, random forest, Uber, Lyft, fare prediction**

I. Introduction

Fare prediction is useful for pricing transparency, dispatch planning, and customer experience. This project compares baseline (linear) and ensemble regression models on Uber/Lyft trip data to estimate fares. Our final results are MAE = **\$1.24**, RMSE = **\$2.26**, and R^2 = **0.942**, with 95% confidence intervals computed over repeated holdout splits. Among the tested methods, Random Forest performs best for this dataset and is selected as the final approach. The report concludes with model strengths/limitations and practical implications for real-world deployment.

II. Problem Formulation

The task is to predict ride fare price (USD) from 14 trip and context features. Inputs include distance (miles), time features (hour, day of week, month), pickup and drop-off locations, vehicle type information (cab type and service name), and weather conditions (temperature, humidity, wind, pressure, rain, and clouds). The target is the trip fare price. Data was evaluated with repeated 80%/20% train-test holdout splits (20 runs). Preprocessing used median imputation for missing weather values and label encoding for categorical features. Feature scaling was used for Linear Regression but not for Random Forest.

III. Models

Two main models are compared:

- **Linear Regression (Baseline):** Standard least-squares regression with StandardScaler normalization. Target: establish a simple interpretable baseline.
- **Random Forest Regressor (Ensemble):** 30 trees, max depth 10, random state 42. Designed to capture non-linear fare dependencies (e.g., distance-weather and location-time interactions).

No hyperparameter tuning was performed; parameters were chosen based on domain knowledge and computational efficiency for this dataset.

IV. Performance Indicators and Best Model Justification

Primary regression metrics:

- Mean Absolute Error (MAE)
- Root Mean Squared Error (RMSE)
- Coefficient of Determination (R^2)

Confidence intervals (95%) must be reported for at least one primary metric.

TABLE I: Model Performance with Repeated Holdout (20 Splits) and 95% Confidence Intervals

Model	MAE (95% CI)	RMSE (95% CI)	R^2 (95% CI)
Linear Regression	5.35 [5.268, 5.436]	6.81 [6.674, 6.925]	0.474 [0.459, 0.489]
Random Forest	**1.24 [1.221, 1.275]**	**2.26 [2.120, 2.348]**	**0.942 [0.937, 0.949]**

V. Normalized Confusion Matrix (Binned Fares)

Although the main task is regression, a normalized confusion matrix can be used by binning fares into ranges (e.g., low/medium/high):

$$\tilde{y} = \mathrm{bin}(y), \qquad \tilde{\hat{y}} = \mathrm{bin}(\hat{y}). \tag{1}$$

Row-normalized confusion matrices for both Linear Regression and Random Forest are shown below.

VI. Actual vs Predicted Analysis

Scatter plots comparing true vs. predicted fares reveal model behavior and systematic biases. Linear Regression shows consistent under/over-prediction patterns typical of linear models. Random Forest exhibits tighter clustering around the ideal diagonal, indicating superior prediction accuracy.

VII. Feature Importance Comparison

Feature importance provides insight into which inputs drive fare predictions. Linear Regression coefficients reflect linear contributions, while Random Forest importances capture non-linear interactions and hierarchical decision structures.



(a) Linear Regression



(b) Random Forest

Fig. 1: Normalized confusion matrices on binned fare ranges for both models.



Fig. 2: Actual vs Predicted scatter plots for both Linear Regression (left) and Random Forest (right). The diagonal dashed line represents perfect predictions. Random Forest concentrates much more tightly around this line.

VIII. Model Comparison Summary

The comparison reveals clear differences in model philosophy and capability. Linear Regression provides a simple, interpretable baseline with explicit feature contributions. Random Forest captures complex non-linear patterns, delivering superior performance at the cost of interpretability. For this application, the R^2 improvement from 0.474 to 0.942 and MAE reduction from \$5.35 to \$1.24 justify the shift toward the ensemble method.



Fig. 3: Feature importance comparison: Linear Regression absolute coefficients (left, steel blue) vs. Random Forest feature importances (right, dark orange). Both models rank service type and distance as top predictors, validating domain knowledge about ride fare drivers.

IX. Pros and Cons by Model

Linear Regression (Baseline)

Pros:

- Simple and easy to interpret.
- Fast to train and evaluate.
- Useful as a transparent baseline for comparison.

Cons:

- Lower predictive performance on this dataset (MAE = \$5.35, R^2 = 0.474).
- Cannot capture complex non-linear interactions as effectively.

Random Forest (Ensemble)

Pros:

- Best predictive performance on this dataset (MAE = \$1.24, R^2 = 0.942).
- Captures non-linear interactions between features.
- Less sensitive to feature scaling.

Cons:

- Harder to interpret than Linear Regression.
- Can be sensitive to data quality and sampling effects.

X. Conclusion

Random Forest regression achieves the best performance among tested models on this Uber/Lyft dataset, explaining 94.2% of fare variance with a mean absolute error of \$1.24. Despite the strength of the ensemble approach, a linear baseline is provided for transparency and comparison. Future work should explore temporal validation to quantify drift sensitivity, and integration of external data (e.g., real-time traffic conditions) to improve generalization.

XI. Threats to Validity

The evaluation uses repeated random holdout splits rather than a strict temporal split, so deployment-time drift effects may still be underrepresented. Confidence intervals are estimated from the distribution of split-level metrics, which improves partition robustness but can still underestimate broader data-generation uncertainty. The sampled subset (20,000 trips) may not capture all rare demand or weather regimes, and this can affect tail-error behavior. Finally, because surge multiplier fields are excluded, the model estimates fare primarily from trip context and weather proxies rather than direct dynamic-pricing signals.

Acknowledgment

Thanks to the Intro to Machine Learning course staff for project guidance and feedback.