MOBSF

ANDROID STATIC ANALYSIS REPORT

app_icon

Seers Lodge (1.1.4)

File Name: chat.seers.app_7.apk

Package Name:	chat.seers.app
Scan Date:	May 1, 2026, 5:54 a.m.
App Security Score:	51/100 (MEDIUM RISK)
Grade:	B

FINDINGS SEVERITY

HIGH	MEDIUM	INFO	SECURE	HOTSPOT
1	10	1	1	1

FILE INFORMATION

File Name: chat.seers.app_7.apk
Size: 25.07MB
MD5: 56b1b071ef8210269cc1aa8353a1764d
SHA1: 878499145c248784d4833c61a3e3425eb0e184fb
SHA256: 2e096f8acc2673d95c236dbe7d67004beea795d182588126c037afc963f502b9

APP INFORMATION

App Name: Seers Lodge
Package Name: chat.seers.app
Main Activity: nand.apps.chat.MainActivity
Target SDK: 35
Min SDK: 26
Max SDK:
Android Version Name: 1.1.4
Android Version Code: 7

APP COMPONENTS

Activities: 2
Services: 2
Receivers: 1
Providers: 3
Exported Activities: 0
Exported Services: 0

Exported Receivers: 1
Exported Providers: 0

CERTIFICATE INFORMATION

Binary is signed
v1 signature: False
v2 signature: True
v3 signature: False
v4 signature: False
X.509 Subject: C=US, ST=NY, L=Syracuse, O=NAND Apps, OU=Cat Psychiatry, CN=Cale Stockman
Signature Algorithm: rsassa_pkcs1v15
Valid From: 2024-09-29 03:14:26+00:00
Valid To: 2074-09-17 03:14:26+00:00
Issuer: C=US, ST=NY, L=Syracuse, O=NAND Apps, OU=Cat Psychiatry, CN=Cale Stockman
Serial Number: 0x31c249e6f31a3f61
Hash Algorithm: sha384
md5: 3b7e59ceda748d3c1682a905bb679fc2
sha1: ea6865a9f0cb9ce928f8c0597a9ed13fd064cbc9
sha256: f0385c2195240e01d0800399e734a0573b7f52204900f6d65245ac37754d2fb5
sha512: 6fdc76cfe32c6c50580cc60af3c5f31920d5707cb984a9db95ef88fcd6bb2dd4e2d120cd70d0f44aadf325a436923c1e7b4373e23451ff2c5b238fee3b419f22
PublicKey Algorithm: rsa
Bit Size: 2048
Fingerprint: 4eb382b2a388a1313b156a95d7bd74c0a33852c642cb9c147381e725387767bb
Found 1 unique certificates

APPLICATION PERMISSIONS

PERMISSION	STATUS	INFO	DESCRIPTION
android.permission.FOREGROUND_SERVICE	normal	enables regular apps to use Service.startForeground.	Allows a regular application to use Service.startForeground.
android.permission.FOREGROUND_SERVICE_SPECIAL_USE	normal	enables special-use foreground services.	Allows a regular application to use Service.startForeground with the type "specialUse".

PERMISSION	STATUS	INFO	DESCRIPTION
android.permission.INTERNET	normal	full Internet access	Allows an application to create network sockets.
android.permission.POST_NOTIFICATIONS	dangerous	allows an app to post notifications.	Allows an app to post notifications
android.permission.VIBRATE	normal	control vibrator	Allows the application to control the vibrator.
android.permission.CAMERA	dangerous	take pictures and videos	Allows application to take pictures and videos with the camera. This allows the application to collect images that the camera is seeing at any time.
android.permission.MODIFY_AUDIO_SETTINGS	normal	change your audio settings	Allows application to modify global audio settings, such as volume and routing.
android.permission.RECORD_AUDIO	dangerous	record audio	Allows application to access the audio record path.
chat.seers.app.DYNAMIC_RECEIVER_NOT_EXPORTED_PERMISSION	unknown	Unknown permission	Unknown permission from android reference

APKID ANALYSIS

FILE	DETAILS

<table>
<tr><th>FILE</th><th>DETAILS</th></tr>
<tr><td>classes.dex</td><td>
<table>
<tr><th>FINDINGS</th><th>DETAILS</th></tr>
<tr><td>Anti-VM Code</td><td>Build.FINGERPRINT check
Build.MODEL check
Build.MANUFACTURER check
Build.PRODUCT check
Build.HARDWARE check
possible VM check</td></tr>
<tr><td>Compiler</td><td>r8</td></tr>
</table>
</td></tr>
<tr><td>classes2.dex</td><td>
<table>
<tr><th>FINDINGS</th><th>DETAILS</th></tr>
<tr><td>Anti-VM Code</td><td>Build.FINGERPRINT check
Build.MANUFACTURER check</td></tr>
<tr><td>Compiler</td><td>r8 without marker (suspicious)</td></tr>
</table>
</td></tr>
<tr><td>classes3.dex</td><td>
<table>
<tr><th>FINDINGS</th><th>DETAILS</th></tr>
<tr><td>Compiler</td><td>r8 without marker (suspicious)</td></tr>
</table>
</td></tr>
<tr><td>classes4.dex</td><td>
<table>
<tr><th>FINDINGS</th><th>DETAILS</th></tr>
<tr><td>Compiler</td><td>r8 without marker (suspicious)</td></tr>
</table>
</td></tr>
</table>

NETWORK SECURITY

NO	SCOPE	SEVERITY	DESCRIPTION

CERTIFICATE ANALYSIS

HIGH: 0 | WARNING: 0 | INFO: 1

TITLE	SEVERITY	DESCRIPTION
Signed Application	info	Application is signed with a code signing certificate

MANIFEST ANALYSIS

HIGH: 0 | WARNING: 3 | INFO: 0 | SUPPRESSED: 0

NO	ISSUE	SEVERITY	DESCRIPTION
1	App can be installed on a vulnerable Android version 8.0, minSdk=26]	warning	This application can be installed on an older version of android that has multiple vulnerabilities. Support an Android version => 10, API 29 to receive reasonable security updates.
2	Application Data can be Backed up [android:allowBackup=true]	warning	This flag allows anyone to backup your application data via adb. It allows users who have enabled USB debugging to copy application data off of the device.
3	Broadcast Receiver (androidx.profileinstaller.ProfileInstallReceiver) is Protected by a permission, but the protection level of the permission should be checked. Permission: android.permission.DUMP [android:exported=true]	warning	A Broadcast Receiver is found to be shared with other apps on the device therefore leaving it accessible to any other application on the device. It is protected by a permission which is not defined in the analysed application. As a result, the protection level of the permission should be checked where it is defined. If it is set to normal or dangerous, a malicious application can request and obtain the permission and interact with the component. If it is set to signature, only applications signed with the same certificate can obtain the permission.

CODE ANALYSIS

HIGH: **1** | WARNING: **6** | INFO: **1** | SECURE: **0** | SUPPRESSED: **0**

NO	ISSUE	SEVERITY	STANDARDS	FILES
1	Files may contain hardcoded sensitive information like usernames, passwords, keys etc.	warning	CWE: CWE-312: Cleartext Storage of Sensitive Information OWASP Top 10: M9: Reverse Engineering OWASP MASVS: MSTG-STORAGE-14	coil3/intercept/EngineInterceptor.java coil3/memory/MemoryCache.java coil3/memory/MemoryCacheService.java coil3/request/ImageRequest.java coil3/request/Options.java coil3/request/SuccessResult.java coil3/transform/Transformation.java com/fleeksoft/ksoup/internal/SharedConstants.java com/fleeksoft/ksoup/nodes/DocumentType.java com/hoc081098/kmp/viewmodel/safe/NonNullSavedStateHandleKey.java com/hoc081098/kmp/viewmodel/safe/NullableSavedStateHandleKey.java io/github/alexzhirkevich/compottie/DotLottieCompositionSpec.java io/ktor/client/request/forms/FormPart.java io/ktor/http/HttpHeaders.java io/ktor/http/auth/HttpAuthHeader.java io/ktor/server/engine/ConfigKeys.java io/ktor/util/PlatformUtilsJvmKt.java io/ktor/utils/io/ByteChannel_jvmKt.java nand/apps/chat/engine/event/JoinGroupEvent.java nand/apps/chat/model/avatar/ChatUserAvatar.java nand/apps/chat/model/event/SetGroupPasswordEvent.java nand/apps/chat/model/group/ChatGroupInvite.java nand/apps/chat/model/group/PersistedChatGroupData.java nand/apps/chat/model/group/PersistedChatGroupInviteData.java nand/apps/chat/model/settings/GeneralSettingsData.java nand/apps/chat/model/settings/filetransfer/FileTransferUploadConfig.java nand/apps/chat/model/user/ChatProfileData.java nand/apps/chat/profile/AndroidCredentialsStoreKt.java nand/apps/chat/profile/ProfileSelectionData.java nand/apps/chat/ui/login/LoginScreenState.java nand/apps/chat/ui/profile/selector/ProfileSelectorRowData.java

NO	ISSUE	SEVERITY	STANDARDS	FILES
				nand/apps/chat/ui/profile/username/LoginUsernameDialogState.java nand/apps/chat/ui/settings/filetransfer/FormField.java nand/apps/chat/ui/shortcut/ChatKeyEvent.java nand/apps/chat/ui/tutorial/TutorialState.java nand/apps/tox/net/ToxBootstrapNode.java org/slf4j/LoggerFactory.java org/slf4j/helpers/Reporter.java org/slf4j/simple/SimpleLogger.java
2	The App logs information. Sensitive information should never be logged.	info	CWE: CWE-532: Insertion of Sensitive Information into Log File OWASP MASVS: MSTG-STORAGE-3	com/ashampoo/xmp/XMPMeta.java com/caverock/androidsvg/CSSParser.java com/caverock/androidsvg/SVG.java com/caverock/androidsvg/SVGAndroidRenderer.java com/caverock/androidsvg/SVGImageView.java com/caverock/androidsvg/SVGParser.java com/caverock/androidsvg/SimpleAssetResolver.java com/goterl/resourceloader/Main.java com/sun/jna/Native.java com/typesafe/config/impl/ConfigImpl.java io/github/alexzhirkevich/compottie/LottieLogger.java io/github/alexzhirkevich/compottie/LottiePainter.java io/github/alexzhirkevich/compottie/internal/animation/expressions/ExpressionInterpreterImpl.java io/github/alexzhirkevich/compottie/internal/animation/expressions/operations/OpGlobalContext.java io/ktor/http/parsing/DebugKt.java io/ktor/server/engine/internal/ApplicationUtilsJvmKt.java io/ktor/util/CoroutinesUtilsKt.java nand/apps/chat/log/AndroidAppLogger.java org/fusesource/jansi/AnsiMain.java org/fusesource/jansi/internal/JansiLoader.java org/fusesource/jansi/internal/MingwSupport.java org/fusesource/jansi/internal/OSInfo.java org/jetbrains/compose/resources/ResourceReader_androidKt.java org/koin/android/logger/AndroidLogger.java org/slf4j/helpers/Util.java

NO	ISSUE	SEVERITY	STANDARDS	FILES
3	IP Address disclosure	warning	CWE: CWE-200: Information Exposure OWASP MASVS: MSTG-CODE-2	com/ashampoo/xmp/XMPConst.java io/ktor/network/sockets/TcpSocketBuilder.java io/ktor/network/sockets/UDPSocketBuilder.java io/ktor/server/application/ApplicationConfigExtensionsKt.java io/ktor/server/engine/CommandLineKt.java io/ktor/server/engine/EmbeddedServerKt.java io/ktor/server/engine/EngineConnectorBuilder.java io/ktor/server/engine/internal/EngineUtilsJvmKt.java nand/apps/chat/model/settings/net/ChatRemoteSettingsDataKt.java nand/apps/chat/util/HtmlUtilKt.java
4	The App uses an insecure Random Number Generator.	warning	CWE: CWE-330: Use of Insufficiently Random Values OWASP Top 10: M5: Insufficient Cryptography OWASP MASVS: MSTG-CRYPTO-6	org/fusesource/jansi/internal/JansiLoader.java
5	SHA-1 is a weak hash known to have hash collisions.	warning	CWE: CWE-327: Use of a Broken or Risky Cryptographic Algorithm OWASP Top 10: M5: Insufficient Cryptography OWASP MASVS: MSTG-CRYPTO-4	io/ktor/util/CryptoKt__CryptoJvmKt.java io/ktor/util/NonceKt$nonceGeneratorJob$1.java
6	The App uses the encryption mode CBC with PKCS5/PKCS7 padding. This configuration is vulnerable to padding oracle attacks.	high	CWE: CWE-649: Reliance on Obfuscation or Encryption of Security-Relevant Inputs without Integrity Checking OWASP Top 10: M5: Insufficient Cryptography OWASP MASVS: MSTG-CRYPTO-3	nand/apps/chat/profile/AndroidCredentialsStore.java
7	App creates temp file. Sensitive information should never be written into a temp file.	warning	CWE: CWE-276: Incorrect Default Permissions OWASP Top 10: M2: Insecure Data Storage OWASP MASVS: MSTG-STORAGE-2	coil3/decode/SourceImageSource.java com/sun/jna/Native.java
8	App can read/write to External Storage. Any App can read data written to External Storage.	warning	CWE: CWE-276: Incorrect Default Permissions OWASP Top 10: M2: Insecure Data Storage OWASP MASVS: MSTG-STORAGE-2	nand/apps/chat/io/AndroidFilePaths.java

SHARED LIBRARY BINARY ANALYSIS

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
1	arm64-v8a/libandroidjni.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
2	arm64-v8a/libjnidispatch.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	False high This binary does not have a stack canary value added to the stack. Stack canaries are used to detect and prevent exploits from overwriting return address. Use the option -fstack-protector-all to enable stack canaries. Not applicable for Dart/Flutter libraries unless Dart FFI is used.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
3	arm64-v8a/libsurface_util_jni.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
4	arm64-v8a/libgifjni.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
5	arm64-v8a/libimage_processing_util_jni.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['__memcpy_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
6	arm64-v8a/libsodium.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
7	arm64-v8a/libandroidx.graphics.path.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
8	arm64-v8a/libzxingcpp_android.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['__strchr_chk', '__vsnprintf_chk', '__memcpy_chk', '__memmove_chk', '__strlen_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
9	arm64-v8a/libopusjni.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['__memcpy_chk', '__memset_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
10	arm64-v8a/libtoxjni.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['__memcpy_chk', '__strlen_chk', '__memset_chk', '__vsnprintf_chk', '__recvfrom_chk', '__sendto_chk', '__strrchr_chk', '__memmove_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
11	arm64-v8a/liboboe.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['__vsprintf_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
12	arm64-v8a/libc++_shared.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	False high This binary does not have a stack canary value added to the stack. Stack canaries are used to detect and prevent exploits from overwriting return address. Use the option -fstack-protector-all to enable stack canaries. Not applicable for Dart/Flutter libraries unless Dart FFI is used.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
13	arm64-v8a/libandroidjni.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
14	arm64-v8a/libjnidispatch.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	False high This binary does not have a stack canary value added to the stack. Stack canaries are used to detect and prevent exploits from overwriting return address. Use the option -fstack-protector-all to enable stack canaries. Not applicable for Dart/Flutter libraries unless Dart FFI is used.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
15	arm64-v8a/libsurface_util_jni.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
16	arm64-v8a/libgifjni.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
17	arm64-v8a/libimage_processing_util_jni.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['__memcpy_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
18	arm64-v8a/libsodium.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
19	arm64-v8a/libandroidx.graphics.path.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
20	arm64-v8a/libzxingcpp_android.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['__strchr_chk', '__vsnprintf_chk', '__memcpy_chk', '__memmove_chk', '__strlen_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
21	arm64-v8a/libopusjni.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['__memcpy_chk', '__memset_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
22	arm64-v8a/libtoxjni.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['__memcpy_chk', '__strlen_chk', '__memset_chk', '__vsnprintf_chk', '__recvfrom_chk', '__sendto_chk', '__strrchr_chk', '__memmove_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
23	arm64-v8a/liboboe.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['__vsprintf_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
24	arm64-v8a/libc++_shared.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	False high This binary does not have a stack canary value added to the stack. Stack canaries are used to detect and prevent exploits from overwriting return address. Use the option -fstack-protector-all to enable stack canaries. Not applicable for Dart/Flutter libraries unless Dart FFI is used.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NIAP ANALYSIS v1.3

NO	IDENTIFIER	REQUIREMENT	FEATURE	DESCRIPTION

BEHAVIOUR ANALYSIS

RULE ID	BEHAVIOUR	LABEL	FILES
00022	Open a file from given absolute path of the file	file	coil3/util/FileSystems_androidKt.java com/fleeksoft/ksoup/KsoupJvmExtKt.java com/goterl/resourceloader/ResourceLoader.java com/goterl/resourceloader/SharedLibraryLoader.java com/sun/jna/Native.java com/sun/jna/NativeLibrary.java io/ktor/server/http/content/LocalFileContent.java io/ktor/server/http/content/PreCompressedKt.java org/fusesource/jansi/internal/JansiLoader.java org/fusesource/jansi/internal/MingwSupport.java
00013	Read file and put it into a stream	file	com/ashampoo/kim/android/KimAndroid.java com/goterl/resourceloader/ResourceLoader.java com/typesafe/config/impl/Parseable.java io/ktor/client/plugins/cache/storage/FileCacheStorage.java io/ktor/server/engine/EnvironmentUtilsJvmKt.java nand/apps/chat/io/ZipUtil_androidKt.java okio/Okio__JvmOkioKt.java org/fusesource/jansi/AnsiMain.java org/fusesource/jansi/internal/JansiLoader.java
00091	Retrieve data from broadcast	collection	nand/apps/chat/notification/AndroidCallNotificationReceiver.java
00028	Read file from assets directory	file	com/caverock/androidsvg/SimpleAssetResolver.java org/jetbrains/compose/resources/ResourceReader_androidKt.java
00162	Create InetSocketAddress object and connecting to it	socket	io/ktor/network/sockets/SocketImpl.java
00163	Create new Socket and connecting to it	socket	io/ktor/network/sockets/SocketImpl.java

RULE ID	BEHAVIOUR	LABEL	FILES
00047	Query the local IP address	network collection	io/ktor/network/sockets/SocketImpl.java
00063	Implicit intent(view a web page, make a phone call, etc.)	control	nand/apps/chat/camera/QrCodeCameraActivity.java
00051	Implicit intent(view a web page, make a phone call, etc.) via setData	control	nand/apps/chat/camera/QrCodeCameraActivity.java
00178	Execute Linux commands via ProcessBuilder	command	org/fusesource/jansi/internal/MingwSupport.java
00012	Read data and put it into a buffer stream	file	com/ashampoo/kim/android/KimAndroid.java io/ktor/client/plugins/cache/storage/FileCacheStorage.java
00001	Initialize bitmap object and compress data (e.g. JPEG) into bitmap object	camera	qrcode/render/QRCodeGraphics.java

ABUSED PERMISSIONS

TYPE	MATCHES	PERMISSIONS
Malware Permissions	4/25	android.permission.INTERNET, android.permission.VIBRATE, android.permission.CAMERA, android.permission.RECORD_AUDIO
Other Common Permissions	2/44	android.permission.FOREGROUND_SERVICE, android.permission.MODIFY_AUDIO_SETTINGS

Malware Permissions:
Top permissions that are widely abused by known malware.

Other Common Permissions:
Permissions that are commonly abused by known malware.

OFAC SANCTIONED COUNTRIES

This app may communicate with the following OFAC sanctioned list of countries.

DOMAIN	COUNTRY/REGION

DOMAIN MALWARE CHECK

DOMAIN	STATUS	GEOLOCATION
a.4cdn.org	ok	**IP:** 104.19.234.32 **Country:** United States of America **Region:** California **City:** San Francisco **Latitude:** 37.775700 **Longitude:** -122.395203 **View:** Google Map
www.slf4j.org	ok	**IP:** 31.97.181.89 **Country:** United Kingdom of Great Britain and Northern Ireland **Region:** England **City:** Bowness-on-Windermere **Latitude:** 54.363312 **Longitude:** -2.918590 **View:** Google Map
schemas.android.com	ok	No Geolocation information available.
www.w3.org	ok	**IP:** 104.18.22.19 **Country:** United States of America **Region:** California **City:** San Francisco **Latitude:** 37.775700 **Longitude:** -122.395203 **View:** Google Map

DOMAIN	STATUS	GEOLOCATION
www.aiim.org	ok	**IP:** 199.60.103.31 **Country:** United States of America **Region:** Massachusetts **City:** Cambridge **Latitude:** 42.370129 **Longitude:** -71.086304 **View:** Google Map
android.googlesource.com	ok	**IP:** 192.178.223.82 **Country:** United States of America **Region:** California **City:** Mountain View **Latitude:** 37.405991 **Longitude:** -122.078514 **View:** Google Map
ns.ashampoo.com	ok	No Geolocation information available.
schema.org	ok	**IP:** 216.58.223.206 **Country:** United States of America **Region:** California **City:** Mountain View **Latitude:** 37.405991 **Longitude:** -122.078514 **View:** Google Map
xmlpull.org	ok	**IP:** 185.199.108.153 **Country:** United States of America **Region:** Pennsylvania **City:** California **Latitude:** 40.065632 **Longitude:** -79.891708 **View:** Google Map

DOMAIN	STATUS	GEOLOCATION
www.metadataworkinggroup.com	ok	**IP:** 184.106.215.244 **Country:** United States of America **Region:** Illinois **City:** Chicago **Latitude:** 41.850029 **Longitude:** -87.650047 **View:** Google Map
fonts.gstatic.com	ok	**IP:** 142.251.216.35 **Country:** United States of America **Region:** California **City:** Mountain View **Latitude:** 37.405991 **Longitude:** -122.078514 **View:** Google Map
www.youtube.com	ok	**IP:** 216.58.223.238 **Country:** United States of America **Region:** California **City:** Mountain View **Latitude:** 37.405991 **Longitude:** -122.078514 **View:** Google Map
s.ytimg.com	ok	**IP:** 142.251.216.110 **Country:** United States of America **Region:** California **City:** Mountain View **Latitude:** 37.405991 **Longitude:** -122.078514 **View:** Google Map

DOMAIN	STATUS	GEOLOCATION
iptc.org	ok	**IP:** 108.156.46.116 **Country:** United States of America **Region:** Washington **City:** Redmond **Latitude:** 47.682899 **Longitude:** -122.120903 **View:** Google Map
i.4cdn.org	ok	**IP:** 104.19.234.32 **Country:** United States of America **Region:** California **City:** San Francisco **Latitude:** 37.775700 **Longitude:** -122.395203 **View:** Google Map
nodes.tox.chat	ok	**IP:** 198.199.93.42 **Country:** United States of America **Region:** California **City:** San Francisco **Latitude:** 37.774929 **Longitude:** -122.419418 **View:** Google Map
ns.acdsee.com	ok	No Geolocation information available.
purl.org	ok	**IP:** 207.241.225.157 **Country:** United States of America **Region:** California **City:** San Francisco **Latitude:** 37.781734 **Longitude:** -122.459435 **View:** Google Map

DOMAIN	STATUS	GEOLOCATION
xml.org	ok	**IP:** 172.67.205.113 **Country:** United States of America **Region:** California **City:** San Francisco **Latitude:** 37.775700 **Longitude:** -122.395203 **View:** Google Map
gitlab.com	ok	**IP:** 172.65.251.78 **Country:** United States of America **Region:** California **City:** San Francisco **Latitude:** 37.775700 **Longitude:** -122.395203 **View:** Google Map
ns.useplus.org	ok	**IP:** 54.83.4.77 **Country:** United States of America **Region:** Virginia **City:** Ashburn **Latitude:** 39.043720 **Longitude:** -77.487488 **View:** Google Map
www.digikam.org	ok	**IP:** 85.10.198.55 **Country:** Germany **Region:** Bayern **City:** Gunzenhausen **Latitude:** 48.323330 **Longitude:** 11.601220 **View:** Google Map

DOMAIN	STATUS	GEOLOCATION
github.com	ok	**IP:** 140.82.121.3 **Country:** United States of America **Region:** California **City:** San Francisco **Latitude:** 37.775700 **Longitude:** -122.395203 **View:** Google Map
i.ytimg.com	ok	**IP:** 216.58.205.182 **Country:** United States of America **Region:** California **City:** Mountain View **Latitude:** 37.405991 **Longitude:** -122.078514 **View:** Google Map
www.npes.org	ok	**IP:** 172.67.183.61 **Country:** United States of America **Region:** California **City:** San Francisco **Latitude:** 37.775700 **Longitude:** -122.395203 **View:** Google Map
s.4cdn.org	ok	**IP:** 104.19.235.32 **Country:** United States of America **Region:** California **City:** San Francisco **Latitude:** 37.775700 **Longitude:** -122.395203 **View:** Google Map
ns.adobe.com	ok	No Geolocation information available.

DOMAIN	STATUS	GEOLOCATION
youtrack.jetbrains.com	ok	**IP:** 63.33.88.220 **Country:** Ireland **Region:** Dublin **City:** Dublin **Latitude:** 53.343990 **Longitude:** -6.267190 **View:** Google Map
ns.microsoft.com	ok	No Geolocation information available.
ns.narrative.so	ok	No Geolocation information available.
seers.chat	ok	**IP:** 3.214.188.39 **Country:** United States of America **Region:** Virginia **City:** Ashburn **Latitude:** 39.043720 **Longitude:** -77.487488 **View:** Google Map
cipa.jp	ok	**IP:** 118.82.81.189 **Country:** Japan **Region:** Tokyo **City:** Tokyo **Latitude:** 35.689507 **Longitude:** 139.691696 **View:** Google Map
ns.mylollc.com	ok	**IP:** 75.126.101.254 **Country:** United States of America **Region:** Texas **City:** Dallas **Latitude:** 32.939491 **Longitude:** -96.838730 **View:** Google Map

DOMAIN	STATUS	GEOLOCATION
ktor.io	ok	**IP:** 108.139.200.125 **Country:** United States of America **Region:** Washington **City:** Seattle **Latitude:** 47.606209 **Longitude:** -122.332069 **View:** Google Map

HARDCODED SECRETS

POSSIBLE SECRETS
eaf42b5e1c984b88b9fbb7dc406e4d16
be7acfcb97a942e89c71999491e3afac
85c0b687820f11e08111f4ce462b6a48
258EAFA5-E914-47DA-95CA-C5AB0DC85B11

SCAN LOGS

Timestamp	Event	Error
2026-05-01 05:54:08	Generating Hashes	OK
2026-05-01 05:54:09	Extracting APK	OK

2026-05-01 05:54:09	Unzipping	OK
2026-05-01 05:54:12	Parsing APK with androguard	OK
2026-05-01 05:54:12	Extracting APK features using aapt/aapt2	OK
2026-05-01 05:54:13	Getting Hardcoded Certificates/Keystores	OK
2026-05-01 05:54:32	Parsing AndroidManifest.xml	OK
2026-05-01 05:54:32	Extracting Manifest Data	OK
2026-05-01 05:54:32	Manifest Analysis Started	OK
2026-05-01 05:54:32	Performing Static Analysis on: Seers Lodge (chat.seers.app)	OK
2026-05-01 05:54:36	Fetching Details from Play Store: chat.seers.app	OK
2026-05-01 05:54:37	Checking for Malware Permissions	OK
2026-05-01 05:54:37	Fetching icon path	OK
2026-05-01 05:54:37	Library Binary Analysis Started	OK

2026-05-01 05:54:38	Analyzing lib/arm64-v8a/libandroidjni.so	OK
2026-05-01 05:54:38	Analyzing lib/arm64-v8a/libjnidispatch.so	OK
2026-05-01 05:54:38	Analyzing lib/arm64-v8a/libsurface_util_jni.so	OK
2026-05-01 05:54:38	Analyzing lib/arm64-v8a/libgifjni.so	OK
2026-05-01 05:54:38	Analyzing lib/arm64-v8a/libimage_processing_util_jni.so	OK
2026-05-01 05:54:38	Analyzing lib/arm64-v8a/libsodium.so	OK
2026-05-01 05:54:38	Analyzing lib/arm64-v8a/libandroidx.graphics.path.so	OK
2026-05-01 05:54:38	Analyzing lib/arm64-v8a/libzxingcpp_android.so	OK
2026-05-01 05:54:39	Analyzing lib/arm64-v8a/libopusjni.so	OK
2026-05-01 05:54:39	Analyzing lib/arm64-v8a/libtoxjni.so	OK
2026-05-01 05:54:39	Analyzing lib/arm64-v8a/liboboe.so	OK
2026-05-01 05:54:39	Analyzing lib/arm64-v8a/libc++_shared.so	OK

2026-05-01 05:54:39	Analyzing apktool_out/lib/arm64-v8a/libandroidjni.so	OK
2026-05-01 05:54:39	Analyzing apktool_out/lib/arm64-v8a/libjnidispatch.so	OK
2026-05-01 05:54:39	Analyzing apktool_out/lib/arm64-v8a/libsurface_util_jni.so	OK
2026-05-01 05:54:40	Analyzing apktool_out/lib/arm64-v8a/libgifjni.so	OK
2026-05-01 05:54:40	Analyzing apktool_out/lib/arm64-v8a/libimage_processing_util_jni.so	OK
2026-05-01 05:54:40	Analyzing apktool_out/lib/arm64-v8a/libsodium.so	OK
2026-05-01 05:54:40	Analyzing apktool_out/lib/arm64-v8a/libandroidx.graphics.path.so	OK
2026-05-01 05:54:40	Analyzing apktool_out/lib/arm64-v8a/libzxingcpp_android.so	OK
2026-05-01 05:54:40	Analyzing apktool_out/lib/arm64-v8a/libopusjni.so	OK
2026-05-01 05:54:40	Analyzing apktool_out/lib/arm64-v8a/libtoxjni.so	OK
2026-05-01 05:54:40	Analyzing apktool_out/lib/arm64-v8a/liboboe.so	OK
2026-05-01 05:54:40	Analyzing apktool_out/lib/arm64-v8a/libc++_shared.so	OK

2026-05-01 05:54:40	Reading Code Signing Certificate	OK
2026-05-01 05:54:44	Running APKiD 3.0.0	OK
2026-05-01 05:55:27	Detecting Trackers	OK
2026-05-01 05:56:13	Decompiling APK to Java with JADX	OK
2026-05-01 06:04:40	Converting DEX to Smali	OK
2026-05-01 06:04:41	Code Analysis Started on - java_source	OK
2026-05-01 06:05:54	Android SBOM Analysis Completed	OK
2026-05-01 06:07:15	Android SAST Completed	OK
2026-05-01 06:07:15	Android API Analysis Started	OK
2026-05-01 06:07:32	Android API Analysis Completed	OK
2026-05-01 06:07:33	Android Permission Mapping Started	OK
2026-05-01 06:07:43	Android Permission Mapping Completed	OK

2026-05-01 06:07:44	Android Behaviour Analysis Started	OK
2026-05-01 06:08:02	Android Behaviour Analysis Completed	OK
2026-05-01 06:08:02	Extracting Emails and URLs from Source Code	OK
2026-05-01 06:08:24	Email and URL Extraction Completed	OK
2026-05-01 06:08:24	Extracting String data from APK	OK
2026-05-01 06:08:24	Extracting String data from SO	OK
2026-05-01 06:08:24	Extracting String data from Code	OK
2026-05-01 06:08:24	Extracting String values and entropies from Code	OK
2026-05-01 06:08:39	Performing Malware check on extracted domains	OK
2026-05-01 06:08:55	Saving to Database	OK

Report Generated by - MobSF v4.5.0

Mobile Security Framework (MobSF) is an automated, all-in-one mobile application (Android/iOS/Windows) pen-testing, malware analysis and security assessment framework capable of performing static and dynamic analysis.

© 2026 Mobile Security Framework - MobSF | Ajin Abraham | OpenSecurity.

MOBSF

ANDROID STATIC ANALYSIS REPORT

ShareX (2.3.8)

File Name:	com.akansh.fileserversuit_32.apk
Package Name:	com.akansh.fileserversuit
Scan Date:	May 1, 2026, 6:12 a.m.

App Security Score: 52/100 (MEDIUM RISK)

Grade: B

FINDINGS SEVERITY

HIGH	MEDIUM	INFO	SECURE	HOTSPOT
1	8	2	1	1

FILE INFORMATION

File Name: com.akansh.fileserversuit_32.apk

Size: 6.68MB
MD5: a0665438224386696 69fd5a5f33adb6c
SHA1: 0328de948f2759261d92139b561b91c6fa06b7df
SHA256: 2d6424f47b58cded43e25331400c130f463356946c555bf53e3b56074a3c2736

APP INFORMATION

App Name: ShareX
Package Name: com.akansh.fileserversuit
Main Activity: com.akansh.fileserversuit.Splash
Target SDK: 33
Min SDK: 21
Max SDK:
Android Version Name: 2.3.8
Android Version Code: 32

APP COMPONENTS

Activities: 4
Services: 1
Receivers: 0
Providers: 2
Exported Activities: 0
Exported Services: 1
Exported Receivers: 0
Exported Providers: 0

CERTIFICATE INFORMATION

Binary is signed
v1 signature: True
v2 signature: True
v3 signature: False
v4 signature: False
X.509 Subject: C=91, ST=U.P, OU=Software Development, CN=Akansh Sirohi
Signature Algorithm: rsassa_pkcs1v15
Valid From: 2020-06-25 06:25:07+00:00
Valid To: 2045-06-19 06:25:07+00:00
Issuer: C=91, ST=U.P, OU=Software Development, CN=Akansh Sirohi
Serial Number: 0x31b70d9d
Hash Algorithm: sha256
md5: d7e882b29b1338a3958ccd8477501f97
sha1: 0873550199118e4b2cd7606ee472269b4e26ad88
sha256: e661f52d552c0e5bce2f953cac0b545e23017f3318daa2a86c96402ee1bce07b
sha512: 95bb0527066ed7f308759a6bd1a51729d8e721fe5847ef1158b666673c82002d31e23f1c391a24e7334e6ee6a956ef08a4c18c6d37a13a7030e522768c5f49db
PublicKey Algorithm: rsa
Bit Size: 2048

Fingerprint: 190e46646dd3f9624493c9a751d065225384b3846311061b9467b32cf43b4f7f
Found 1 unique certificates

APPLICATION PERMISSIONS

PERMISSION	STATUS	INFO	DESCRIPTION
android.permission.INTERNET	normal	full Internet access	Allows an application to create network sockets.
android.permission.CAMERA	dangerous	take pictures and videos	Allows application to take pictures and videos with the camera. This allows the application to collect images that the camera is seeing at any time.
android.permission.ACCESS_WIFI_STATE	normal	view Wi-Fi status	Allows an application to view the information about the status of Wi-Fi.
android.permission.CHANGE_WIFI_STATE	normal	change Wi-Fi status	Allows an application to connect to and disconnect from Wi-Fi access points and to make changes to configured Wi-Fi networks.
android.permission.ACCESS_NETWORK_STATE	normal	view network status	Allows an application to view the status of all networks.
android.permission.WRITE_EXTERNAL_STORAGE	dangerous	read/modify/delete external storage contents	Allows an application to write to external storage.
android.permission.READ_EXTERNAL_STORAGE	dangerous	read external storage contents	Allows an application to read from external storage.
android.permission.MANAGE_EXTERNAL_STORAGE	dangerous	Allows an application a broad access to external storage in scoped storage	Allows an application a broad access to external storage in scoped storage. Intended to be used by few apps that need to manage files on behalf of the users.
android.permission.FOREGROUND_SERVICE	normal	enables regular apps to use Service.startForeground.	Allows a regular application to use Service.startForeground.
android.permission.REQUEST_IGNORE_BATTERY_OPTIMIZATIONS	normal	permission for using Settings.ACTION_REQUEST_IGNORE_BATTERY_OPTIMIZATIONS.	Permission an application must hold in order to use Settings.ACTION_REQUEST_IGNORE_BATTERY_OPTIMIZATIONS.
android.permission.QUERY_ALL_PACKAGES	normal	enables querying any normal app on the device.	Allows query of any normal app on the device, regardless of manifest declarations.
com.akansh.fileserversuit.DYNAMIC_RECEIVER_NOT_EXPORTED_PERMISSION	unknown	Unknown permission	Unknown permission from android reference

APKID ANALYSIS

FILE	DETAILS
classes.dex	<table><tr><th>FINDINGS</th><th>DETAILS</th></tr><tr><td>Anti-VM Code</td><td>Build.FINGERPRINT check Build.MANUFACTURER check</td></tr><tr><td>Compiler</td><td>r8</td></tr></table>

NETWORK SECURITY

NO	SCOPE	SEVERITY	DESCRIPTION

CERTIFICATE ANALYSIS

HIGH: **0** | WARNING: **1** | INFO: **1**

TITLE	SEVERITY	DESCRIPTION
Signed Application	info	Application is signed with a code signing certificate
Application vulnerable to Janus Vulnerability	warning	Application is signed with v1 signature scheme, making it vulnerable to Janus vulnerability on Android 5.0-8.0, if signed only with v1 signature scheme. Applications running on Android 5.0-7.0 signed with v1, and v2/v3 scheme is also vulnerable.

MANIFEST ANALYSIS

HIGH: **1** | WARNING: **2** | INFO: **0** | SUPPRESSED: **0**

NO	ISSUE	SEVERITY	DESCRIPTION
1	App can be installed on a vulnerable unpatched Android version 5.0-5.0.2, [minSdk=21]	high	This application can be installed on an older version of android that has multiple unfixed vulnerabilities. These devices won't receive reasonable security updates from Google. Support an Android version => 10, API 29 to receive reasonable security updates.
2	Application Data can be Backed up [android:allowBackup=true]	warning	This flag allows anyone to backup your application data via adb. It allows users who have enabled USB debugging to copy application data off of the device.

NO	ISSUE	SEVERITY	DESCRIPTION
3	Service (com.akansh.fileserversuit.ServerService) is not Protected. [android:exported=true]	warning	A Service is found to be shared with other apps on the device therefore leaving it accessible to any other application on the device.

CODE ANALYSIS

HIGH: **0** | WARNING: **5** | INFO: **2** | SECURE: **0** | SUPPRESSED: **0**

NO	ISSUE	SEVERITY	STANDARDS	FILES
				a0/d.java a0/m.java b3/e.java b3/g.java c0/j.java c1/d.java c1/o.java com/bumptech/glide/b.java com/bumptech/glide/c.java com/bumptech/glide/d.java com/bumptech/glide/k.java com/bumptech/glide/l.java com/bumptech/glide/load/data/b.java com/bumptech/glide/load/data/l.java com/bumptech/glide/manager/s.java com/bumptech/glide/manager/t.java com/bumptech/glide/n.java com/dlazaro66/qrcodereaderview/QRCodeReaderV iew.java d/c.java d/e0.java d/f0.java d/j0.java d/n.java d/s.java d/s0.java d2/a.java d3/f.java d3/k.java e0/f.java f1/d.java f1/g0.java f1/j0.java f1/s.java f1/t.java f1/v.java g/a.java g/k.java g/l.java

NO	ISSUE	SEVERITY	STANDARDS	FILES
1	The App logs information. Sensitive information should never be logged.	info	CWE: CWE-532: Insertion of Sensitive Information into Log File OWASP MASVS: MSTG-STORAGE-3	g0/c.java g0/j0.java g0/p1.java g0/q.java g0/q1.java g0/u0.java g0/u1.java g0/x0.java g1/b.java g2/a.java h/i.java h/o.java h1/d.java h1/e.java i1/d.java i1/e.java i2/c.java j0/c.java k0/u.java k1/c.java k3/b.java k3/c.java k3/d.java l0/d.java l1/b0.java l1/k0.java l1/m.java l1/n.java l1/q.java l1/r.java m1/h.java m1/i.java n/d.java n0/e.java o2/c.java p/f.java p1/g.java p1/i.java p1/l.java r1/b.java s/b.java s/d.java s/e.java s/f.java s/i.java s/m.java s0/b.java s0/c.java s0/g.java s1/b.java s1/d.java s1/d0.java s1/l.java s1/p.java s1/t.java u1/a.java

NO	ISSUE	SEVERITY	STANDARDS	FILES
				u1/j.java v2/b.java w/e.java w/f.java w/l.java x1/i.java y/p.java y2/d.java z/f.java z/g.java z/h.java z/i.java z/j.java z2/a.java z2/e.java
2	The App uses an insecure Random Number Generator.	warning	CWE: CWE-330: Use of Insufficiently Random Values OWASP Top 10: M5: Insufficient Cryptography OWASP MASVS: MSTG-CRYPTO-6	a4/a.java a4/b.java a4/c.java b4/a.java
3	Files may contain hardcoded sensitive information like usernames, passwords, keys etc.	warning	CWE: CWE-312: Cleartext Storage of Sensitive Information OWASP Top 10: M9: Reverse Engineering OWASP MASVS: MSTG-STORAGE-14	j1/l.java l1/f.java l1/h0.java l1/z.java
4	App can read/write to External Storage. Any App can read data written to External Storage.	warning	CWE: CWE-276: Incorrect Default Permissions OWASP Top 10: M2: Insecure Data Storage OWASP MASVS: MSTG-STORAGE-2	com/akansh/fileserversuit/ServerService.java com/bumptech/glide/c.java d/s0.java f1/d.java f1/j0.java f1/p.java f1/s.java f1/t.java g/a.java
5	App uses SQLite Database and execute raw SQL query. Untrusted user input in raw SQL queries can cause SQL Injection. Also sensitive information should be encrypted and written to the database.	warning	CWE: CWE-89: Improper Neutralization of Special Elements used in an SQL Command ('SQL Injection') OWASP Top 10: M7: Client Code Quality	d/s0.java f1/b.java
6	IP Address disclosure	warning	CWE: CWE-200: Information Exposure OWASP MASVS: MSTG-CODE-2	d5/b.java
7	This App copies data to clipboard. Sensitive data should not be copied to clipboard as other applications can access it.	info	OWASP MASVS: MSTG-STORAGE-10	f1/s.java

SHARED LIBRARY BINARY ANALYSIS

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
1	x86_64/libandroidndkgif.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.
2	armeabi/libandroidndkgif.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
3	x86/libandroidndkgif.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.
4	arm64-v8a/libandroidndkgif.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
5	armeabi-v7a/libandroidndkgif.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.
6	mips/libandroidndkgif.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	False high This binary does not have a stack canary value added to the stack. Stack canaries are used to detect and prevent exploits from overwriting return address. Use the option -fstack-protector-all to enable stack canaries. Not applicable for Dart/Flutter libraries unless Dart FFI is used.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
7	mips64/libandroidndkgif.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	False high This binary does not have a stack canary value added to the stack. Stack canaries are used to detect and prevent exploits from overwriting return address. Use the option -fstack-protector-all to enable stack canaries. Not applicable for Dart/Flutter libraries unless Dart FFI is used.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.
8	x86_64/libandroidndkgif.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
9	armeabi/libandroidndkgif.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.
10	x86/libandroidndkgif.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
11	arm64-v8a/libandroidndkgif.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.
12	armeabi-v7a/libandroidndkgif.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
13	mips/libandroidndkgif.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	False high This binary does not have a stack canary value added to the stack. Stack canaries are used to detect and prevent exploits from overwriting return address. Use the option -fstack-protector-all to enable stack canaries. Not applicable for Dart/Flutter libraries unless Dart FFI is used.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.
14	mips64/libandroidndkgif.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	False high This binary does not have a stack canary value added to the stack. Stack canaries are used to detect and prevent exploits from overwriting return address. Use the option -fstack-protector-all to enable stack canaries. Not applicable for Dart/Flutter libraries unless Dart FFI is used.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NIAP ANALYSIS v1.3

NO	IDENTIFIER	REQUIREMENT	FEATURE	DESCRIPTION

BEHAVIOUR ANALYSIS

RULE ID	BEHAVIOUR	LABEL	FILES
00183	Get current camera parameters and change the setting.	camera	k3/c.java k3/d.java
00054	Install other APKs from file	reflection	com/akansh/fileserversuit/TransferHistory.java g1/b.java
00022	Open a file from given absolute path of the file	file	d/s0.java f1/d.java f1/j0.java f1/t.java g/a.java g1/b.java q4/h.java u4/a.java
00013	Read file and put it into a stream	file	a0/d.java com/bumptech/glide/c.java com/bumptech/glide/d.java d/c.java f1/d.java f1/j0.java h1/e.java h1/g.java j1/h.java p1/i.java s0/g.java u4/a.java x4/a.java z/h.java z/i.java
00063	Implicit intent(view a web page, make a phone call, etc.)	control	com/akansh/fileserversuit/MainActivity.java d2/a.java l1/q.java
00051	Implicit intent(view a web page, make a phone call, etc.) via setData	control	com/akansh/fileserversuit/MainActivity.java d2/a.java l1/q.java
00147	Get the time of current location	collection location	d/e0.java
00075	Get location of the device	collection location	d/e0.java
00115	Get last known location of the device	collection location	d/e0.java
00036	Get resource file from res/raw directory	reflection	com/bumptech/glide/c.java p1/l.java

RULE ID	BEHAVIOUR	LABEL	FILES
00079	Hide the current app's icon	evasion	d/n.java
00192	Get messages in the SMS inbox	sms	com/bumptech/glide/c.java
00191	Get messages in the SMS inbox	sms	com/bumptech/glide/c.java
00028	Read file from assets directory	file	f1/h0.java
00012	Read data and put it into a buffer stream	file	s0/g.java x4/a.java
00089	Connect to a URL and receive input stream from the server	command network	com/bumptech/glide/load/data/l.java
00030	Connect to the remote server through the given URL	network	com/bumptech/glide/load/data/l.java
00109	Connect to a URL and get the response code	network command	com/bumptech/glide/load/data/l.java
00024	Write file after Base64 decoding	reflection file	com/bumptech/glide/d.java l1/q.java
00125	Check if the given file path exist	file	com/akansh/fileserversuit/ServerService.java

ABUSED PERMISSIONS

TYPE	MATCHES	PERMISSIONS
Malware Permissions	6/25	android.permission.INTERNET, android.permission.CAMERA, android.permission.ACCESS_WIFI_STATE, android.permission.ACCESS_NETWORK_STATE, android.permission.WRITE_EXTERNAL_STORAGE, android.permission.READ_EXTERNAL_STORAGE
Other Common Permissions	3/44	android.permission.CHANGE_WIFI_STATE, android.permission.FOREGROUND_SERVICE, android.permission.REQUEST_IGNORE_BATTERY_OPTIMIZATIONS

Malware Permissions:
Top permissions that are widely abused by known malware.

Other Common Permissions:
Permissions that are commonly abused by known malware.

OFAC SANCTIONED COUNTRIES

This app may communicate with the following OFAC sanctioned list of countries.

DOMAIN	COUNTRY/REGION

DOMAIN MALWARE CHECK

DOMAIN	STATUS	GEOLOCATION
schemas.android.com	ok	No Geolocation information available.
ns.adobe.com	ok	No Geolocation information available.
akanshsirohi.github.io	ok	**IP:** 185.199.109.153 **Country:** United States of America **Region:** Pennsylvania **City:** California **Latitude:** 40.065632 **Longitude:** -79.891708 **View:** Google Map

EMAILS

EMAIL	FILE
akanshsirohi18@gmail.com	l1/q.java

SCAN LOGS

Timestamp	Event	Error
2026-05-01 06:13:00	Generating Hashes	OK
2026-05-01 06:13:00	Extracting APK	OK

2026-05-01 06:13:00	Unzipping	OK
2026-05-01 06:13:01	Parsing APK with androguard	OK
2026-05-01 06:13:02	Extracting APK features using aapt/aapt2	OK
2026-05-01 06:13:02	Getting Hardcoded Certificates/Keystores	OK
2026-05-01 06:13:08	Parsing AndroidManifest.xml	OK
2026-05-01 06:13:08	Extracting Manifest Data	OK
2026-05-01 06:13:08	Manifest Analysis Started	OK
2026-05-01 06:13:08	Performing Static Analysis on: ShareX (com.akansh.fileserversuit)	OK
2026-05-01 06:13:13	Checking for Malware Permissions	OK
2026-05-01 06:13:13	Fetching icon path	OK
2026-05-01 06:13:13	Library Binary Analysis Started	OK
2026-05-01 06:13:13	Analyzing lib/x86_64/libandroidndkgif.so	OK
2026-05-01 06:13:13	Analyzing lib/armeabi/libandroidndkgif.so	OK
2026-05-01 06:13:13	Analyzing lib/x86/libandroidndkgif.so	OK
2026-05-01 06:13:13	Analyzing lib/arm64-v8a/libandroidndkgif.so	OK

2026-05-01 06:13:13	Analyzing lib/armeabi-v7a/libandroidndkgif.so	OK
2026-05-01 06:13:13	Analyzing lib/mips/libandroidndkgif.so	OK
2026-05-01 06:13:13	Analyzing lib/mips64/libandroidndkgif.so	OK
2026-05-01 06:13:13	Analyzing apktool_out/lib/x86_64/libandroidndkgif.so	OK
2026-05-01 06:13:13	Analyzing apktool_out/lib/armeabi/libandroidndkgif.so	OK
2026-05-01 06:13:13	Analyzing apktool_out/lib/x86/libandroidndkgif.so	OK
2026-05-01 06:13:14	Analyzing apktool_out/lib/arm64-v8a/libandroidndkgif.so	OK
2026-05-01 06:13:14	Analyzing apktool_out/lib/armeabi-v7a/libandroidndkgif.so	OK
2026-05-01 06:13:14	Analyzing apktool_out/lib/mips/libandroidndkgif.so	OK
2026-05-01 06:13:14	Analyzing apktool_out/lib/mips64/libandroidndkgif.so	OK
2026-05-01 06:13:14	Reading Code Signing Certificate	OK
2026-05-01 06:13:15	Running APKiD 3.0.0	OK
2026-05-01 06:13:24	Detecting Trackers	OK
2026-05-01 06:13:26	Decompiling APK to Java with JADX	OK
2026-05-01 06:13:57	Converting DEX to Smali	OK

2026-05-01 06:13:57	Code Analysis Started on - java_source	OK
2026-05-01 06:13:59	Android SBOM Analysis Completed	OK
2026-05-01 06:14:07	Android SAST Completed	OK
2026-05-01 06:14:07	Android API Analysis Started	OK
2026-05-01 06:14:09	Android API Analysis Completed	OK
2026-05-01 06:14:09	Android Permission Mapping Started	OK
2026-05-01 06:14:11	Android Permission Mapping Completed	OK
2026-05-01 06:14:12	Android Behaviour Analysis Started	OK
2026-05-01 06:14:19	Android Behaviour Analysis Completed	OK
2026-05-01 06:14:19	Extracting Emails and URLs from Source Code	OK
2026-05-01 06:14:22	Email and URL Extraction Completed	OK
2026-05-01 06:14:22	Extracting String data from APK	OK
2026-05-01 06:14:22	Extracting String data from SO	OK
2026-05-01 06:14:22	Extracting String data from Code	OK
2026-05-01 06:14:22	Extracting String values and entropies from Code	OK

2026-05-01 06:14:23	Performing Malware check on extracted domains	OK
2026-05-01 06:14:34	Saving to Database	OK

Report Generated by - MobSF v4.5.0

Mobile Security Framework (MobSF) is an automated, all-in-one mobile application (Android/iOS/Windows) pen-testing, malware analysis and security assessment framework capable of performing static and dynamic analysis.

© 2026 Mobile Security Framework - MobSF | Ajin Abraham | OpenSecurity.

MOBSF

ANDROID STATIC ANALYSIS REPORT

DankChat (4.0.36)

File Name: com.flxrs.dankchat_40036.apk

Package Name:	com.flxrs.dankchat
Scan Date:	May 1, 2026, 6:23 a.m.
App Security Score:	66/100 (LOW RISK)
Grade:	A

FINDINGS SEVERITY

HIGH	MEDIUM	INFO	SECURE	HOTSPOT

0	10	4	3	2

FILE INFORMATION

File Name: com.flxrs.dankchat_40036.apk
Size: 9.45MB
MD5: 95ea551c9dba3e3a63331dbe34ab5693
SHA1: 396a487c5d8c1c5f0637a900327de0d7fef9552d
SHA256: 19c24efde55f7aa73e7f6231cff9a0a4a484da8f686edc0be62b3151869682b6

APP INFORMATION

App Name: DankChat
Package Name: com.flxrs.dankchat
Main Activity: com.flxrs.dankchat.ui.main.MainActivity
Target SDK: 35
Min SDK: 30
Max SDK:
Android Version Name: 4.0.36
Android Version Code: 40036

APP COMPONENTS

Activities: 3
Services: 3
Receivers: 1
Providers: 3
Exported Activities: 1
Exported Services: 0
Exported Receivers: 1
Exported Providers: 0

CERTIFICATE INFORMATION

Binary is signed
v1 signature: False
v2 signature: False
v3 signature: True
v4 signature: False
X.509 Subject: C=UK, ST=ORG, L=ORG, O=fdroid.org, OU=FDroid, CN=FDroid
Signature Algorithm: rsassa_pkcs1v15
Valid From: 2019-07-30 11:01:37+00:00
Valid To: 2046-12-15 11:01:37+00:00
Issuer: C=UK, ST=ORG, L=ORG, O=fdroid.org, OU=FDroid, CN=FDroid
Serial Number: 0x36486006
Hash Algorithm: sha256
md5: afd4dee6066831fe43ce6d3614b86a78
sha1: 3cf7274ae87516115b7c25084f43a3f905fcb102
sha256: 2b812144018f4491fac74151c9090962c2f5c3dabe529d564febe54556d8ba48
sha512: 67e26ca14a9b83251cedcb3f3f52a053d3dc270c5ee5493bbefcd79887242d08ddd7e511f650348c6ef3c9365b1a06d9ea3000a6b96c95dccbdf7645efe7cb27
PublicKey Algorithm: rsa
Bit Size: 2048
Fingerprint: d14e2b8840e0770ff2763242349c24670648e0b31a0e7559572f441327af955e
Found 1 unique certificates

APPLICATION PERMISSIONS

PERMISSION	STATUS	INFO	DESCRIPTION
android.permission.INTERNET	normal	full Internet access	Allows an application to create network sockets.
android.permission.FOREGROUND_SERVICE	normal	enables regular apps to use Service.startForeground.	Allows a regular application to use Service.startForeground.
android.permission.FOREGROUND_SERVICE_DATA_SYNC	normal	permits foreground services for data synchronization.	Allows a regular application to use Service.startForeground with the type "dataSync".
android.permission.POST_NOTIFICATIONS	dangerous	allows an app to post notifications.	Allows an app to post notifications
com.flxrs.dankchat.DYNAMIC_RECEIVER_NOT_EXPORTED_PERMISSION	unknown	Unknown permission	Unknown permission from android reference

APKID ANALYSIS

FILE	DETAILS
classes.dex	<table><tr><th>FINDINGS</th><th>DETAILS</th></tr><tr><td>yara_issue</td><td>yara issue - dex file recognized by apkid but not yara module</td></tr><tr><td>Anti-VM Code</td><td>Build.FINGERPRINT check Build.MANUFACTURER check</td></tr><tr><td>Compiler</td><td>unknown (please file detection issue!)</td></tr></table>

NETWORK SECURITY

HIGH: **0** | WARNING: **1** | INFO: **2** | SECURE: **1**

NO	SCOPE	SEVERITY	DESCRIPTION
1	*	secure	Base config is configured to disallow clear text traffic to all domains.
2	*	info	Base config is configured to trustbundled certs @raw/isrg_root_x2.
3	*	info	Base config is configured to trustbundled certs @raw/isrg_root_x1.
4	*	warning	Base config is configured to trust system certificates.

CERTIFICATE ANALYSIS

HIGH: **0** | WARNING: **0** | INFO: **1**

TITLE	SEVERITY	DESCRIPTION
Signed Application	info	Application is signed with a code signing certificate

MANIFEST ANALYSIS

HIGH: **0** | WARNING: **3** | INFO: **0** | SUPPRESSED: **0**

NO	ISSUE	SEVERITY	DESCRIPTION
1	App has a Network Security Configuration[android:networkSecurityConfig=@xml/network_security_config]	info	The Network Security Configuration feature lets apps customize their network security settings in a safe, declarative configuration file without modifying app code. These settings can be configured for specific domains and for a specific app.
2	Application Data can be Backed up [android:allowBackup=true]	warning	This flag allows anyone to backup your application data via adb. It allows users who have enabled USB debugging to copy application data off of the device.
3	Activity (com.flxrs.dankchat.ui.share.ShareUploadActivity) is not Protected. [android:exported=true]	warning	An Activity is found to be shared with other apps on the device therefore leaving it accessible to any other application on the device.
4	Broadcast Receiver (androidx.profileinstaller.ProfileInstallReceiver) is Protected by a permission, but the protection level of the permission should be checked. Permission: android.permission.DUMP [android:exported=true]	warning	A Broadcast Receiver is found to be shared with other apps on the device therefore leaving it accessible to any other application on the device. It is protected by a permission which is not defined in the analysed application. As a result, the protection level of the permission should be checked where it is defined. If it is set to normal or dangerous, a malicious application can request and obtain the permission and interact with the component. If it is set to signature, only applications signed with the same certificate can obtain the permission.

CODE ANALYSIS

HIGH: **0** | WARNING: **5** | INFO: **2** | SECURE: **1** | SUPPRESSED: **0**

NO	ISSUE	SEVERITY	STANDARDS	FILES
1	Files may contain hardcoded sensitive information like usernames, passwords, keys etc.	warning	CWE: CWE-312: Cleartext Storage of Sensitive Information OWASP Top 10: M9: Reverse Engineering OWASP MASVS: MSTG-STORAGE-14	ch/qos/logback/classic/joran/action/ConfigurationAction.java ch/qos/logback/classic/sift/ContextBasedDiscriminator.java ch/qos/logback/core/CoreConstants.java ch/qos/logback/core/net/ssl/SSL.java ch/qos/logback/core/rolling/helper/DateTokenConverter.java ch/qos/logback/core/rolling/helper/IntegerTokenConverter.java com/flxrs/dankchat/data/api/helix/dto/ModVipDto.java defpackage/al4.java defpackage/bl4.java defpackage/ci4.java defpackage/ck4.java defpackage/dk4.java defpackage/dl4.java defpackage/dx0.java defpackage/dz0.java defpackage/ff.java defpackage/gf.java defpackage/gg2.java defpackage/gt.java defpackage/hd2.java defpackage/hh4.java defpackage/ju.java defpackage/kk4.java defpackage/ko4.java defpackage/kt.java defpackage/l41.java defpackage/lu2.java defpackage/mg.java defpackage/mh4.java defpackage/mk4.java defpackage/nf.java defpackage/oi4.java defpackage/pg4.java defpackage/r94.java defpackage/ru3.java defpackage/sg4.java defpackage/te4.java defpackage/tl.java

NO	ISSUE	SEVERITY	STANDARDS	FILES
				defpackage/ug.java defpackage/vl.java defpackage/w90.java defpackage/xb2.java defpackage/zh4.java defpackage/zk4.java defpackage/zx.java org/slf4j/LoggerFactory.java org/slf4j/helpers/Reporter.java
2	The App logs information. Sensitive information should never be logged.	info	CWE: CWE-532: Insertion of Sensitive Information into Log File OWASP MASVS: MSTG-STORAGE-3	ch/qos/logback/classic/android/LogcatAppender.java ch/qos/logback/classic/net/SimpleSocketServer.java ch/qos/logback/classic/pattern/TargetLengthBasedClassNameAbbreviator.java ch/qos/logback/classic/spi/ThrowableProxy.java ch/qos/logback/core/joran/util/ConfigurationWatchListUtil.java ch/qos/logback/core/net/DefaultSocketConnector.java ch/qos/logback/core/net/SocketConnectorBase.java ch/qos/logback/core/recovery/ResilientOutputStreamBase.java ch/qos/logback/core/spi/ContextAwareBase.java ch/qos/logback/core/spi/ContextAwareImpl.java ch/qos/logback/core/subst/Node.java com/flxrs/dankchat/preferences/about/AboutScreenKt$AboutScreen$2$libraries$1$1.java defpackage/a01.java defpackage/a80.java defpackage/be.java defpackage/cd2.java defpackage/ck0.java defpackage/d91.java defpackage/db.java defpackage/df4.java defpackage/e31.java defpackage/ef4.java defpackage/eg3.java defpackage/fd2.java defpackage/h83.java defpackage/ha3.java defpackage/hm2.java defpackage/hs3.java defpackage/i1.java defpackage/i21.java

NO	ISSUE	SEVERITY	STANDARDS	FILES
				defpackage/i6.java defpackage/ia3.java defpackage/ih.java defpackage/j6.java defpackage/k21.java defpackage/lm2.java defpackage/o21.java defpackage/o22.java defpackage/o41.java defpackage/o53.java defpackage/o8.java defpackage/px1.java defpackage/q32.java defpackage/q70.java defpackage/qp3.java defpackage/r91.java defpackage/rf3.java defpackage/tj0.java defpackage/tj2.java defpackage/ty0.java defpackage/u81.java defpackage/uf.java defpackage/uk0.java defpackage/wj.java defpackage/wp1.java defpackage/x13.java org/slf4j/helpers/Util.java
3	App uses SQLite Database and execute raw SQL query. Untrusted user input in raw SQL queries can cause SQL Injection. Also sensitive information should be encrypted and written to the database.	warning	CWE: CWE-89: Improper Neutralization of Special Elements used in an SQL Command ('SQL Injection') OWASP Top 10: M7: Client Code Quality	ch/qos/logback/classic/android/SQLiteAppender.java defpackage/ta1.java
4	The App uses an insecure Random Number Generator.	warning	CWE: CWE-330: Use of Insufficiently Random Values OWASP Top 10: M5: Insufficient Cryptography OWASP MASVS: MSTG-CRYPTO-6	defpackage/d93.java defpackage/ep4.java defpackage/j8.java defpackage/k23.java defpackage/m0.java defpackage/p41.java defpackage/rr2.java defpackage/u53.java

NO	ISSUE	SEVERITY	STANDARDS	FILES
5	This App copies data to clipboard. Sensitive data should not be copied to clipboard as other applications can access it.	info	OWASP MASVS: MSTG-STORAGE-10	com/flxrs/dankchat/ui/main/i.java com/flxrs/dankchat/ui/share/ShareUploadActivityKt$SuccessContent$1$1.java defpackage/jy.java defpackage/no2.java
6	App can read/write to External Storage. Any App can read data written to External Storage.	warning	CWE: CWE-276: Incorrect Default Permissions OWASP Top 10: M2: Insecure Data Storage OWASP MASVS: MSTG-STORAGE-2	ch/qos/logback/core/android/AndroidContextUtil.java com/flxrs/dankchat/DankChatApplication$onCreate$2.java defpackage/fd2.java
7	App creates temp file. Sensitive information should never be written into a temp file.	warning	CWE: CWE-276: Incorrect Default Permissions OWASP Top 10: M2: Insecure Data Storage OWASP MASVS: MSTG-STORAGE-2	defpackage/fd2.java
8	This App uses SSL certificate pinning to detect or prevent MITM attacks in secure communication channel.	secure	OWASP MASVS: MSTG-NETWORK-4	ch/qos/logback/core/net/ssl/SSLContextFactoryBean.java defpackage/rr2.java

SHARED LIBRARY BINARY ANALYSIS

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
1	x86_64/libdatastore_shared_counter.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	False high This binary does not have a stack canary value added to the stack. Stack canaries are used to detect and prevent exploits from overwriting return address. Use the option -fstack-protector-all to enable stack canaries. Not applicable for Dart/Flutter libraries unless Dart FFI is used.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	False warning Symbols are available.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
2	x86_64/libandroidx.graphics.path.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
3	x86/libdatastore_shared_counter.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	False warning Symbols are available.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
4	x86/libandroidx.graphics.path.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
5	arm64-v8a/libdatastore_shared_counter.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	False high This binary does not have a stack canary value added to the stack. Stack canaries are used to detect and prevent exploits from overwriting return address. Use the option -fstack-protector-all to enable stack canaries. Not applicable for Dart/Flutter libraries unless Dart FFI is used.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	False warning Symbols are available.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
6	arm64-v8a/libandroidx.graphics.path.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
7	armeabi-v7a/libdatastore_shared_counter.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	False high This binary does not have a stack canary value added to the stack. Stack canaries are used to detect and prevent exploits from overwriting return address. Use the option -fstack-protector-all to enable stack canaries. Not applicable for Dart/Flutter libraries unless Dart FFI is used.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	False warning Symbols are available.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
8	armeabi-v7a/libandroidx.graphics.path.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
9	x86_64/libdatastore_shared_counter.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	False high This binary does not have a stack canary value added to the stack. Stack canaries are used to detect and prevent exploits from overwriting return address. Use the option -fstack-protector-all to enable stack canaries. Not applicable for Dart/Flutter libraries unless Dart FFI is used.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	False warning Symbols are available.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
10	x86_64/libandroidx.graphics.path.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
11	x86/libdatastore_shared_counter.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	False warning Symbols are available.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
12	x86/libandroidx.graphics.path.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
13	arm64-v8a/libdatastore_shared_counter.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	False high This binary does not have a stack canary value added to the stack. Stack canaries are used to detect and prevent exploits from overwriting return address. Use the option -fstack-protector-all to enable stack canaries. Not applicable for Dart/Flutter libraries unless Dart FFI is used.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	False warning Symbols are available.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
14	arm64-v8a/libandroidx.graphics.path.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
15	armeabi-v7a/libdatastore_shared_counter.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	False high This binary does not have a stack canary value added to the stack. Stack canaries are used to detect and prevent exploits from overwriting return address. Use the option -fstack-protector-all to enable stack canaries. Not applicable for Dart/Flutter libraries unless Dart FFI is used.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	False warning Symbols are available.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
16	armeabi-v7a/libandroidx.graphics.path.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NIAP ANALYSIS v1.3

NO	IDENTIFIER	REQUIREMENT	FEATURE	DESCRIPTION

BEHAVIOUR ANALYSIS

RULE ID	BEHAVIOUR	LABEL	FILES
00013	Read file and put it into a stream	file	ch/qos/logback/core/joran/GenericConfigurator.java ch/qos/logback/core/joran/action/PropertyAction.java ch/qos/logback/core/rolling/helper/Compressor.java ch/qos/logback/core/util/FileUtil.java com/flxrs/dankchat/data/api/cache/EmoteDiskCache$read$2.java com/flxrs/dankchat/ui/log/LogViewerViewModel$state$2.java defpackage/be.java defpackage/dn0.java defpackage/fd2.java defpackage/hv3.java defpackage/kp0.java defpackage/o21.java defpackage/qv1.java defpackage/w53.java defpackage/wb3.java
00012	Read data and put it into a buffer stream	file	ch/qos/logback/core/rolling/helper/Compressor.java ch/qos/logback/core/util/FileUtil.java defpackage/fd2.java defpackage/o21.java
00039	Start a web server	control network	ch/qos/logback/classic/net/SimpleSocketServer.java
00063	Implicit intent(view a web page, make a phone call, etc.)	control	defpackage/ff2.java defpackage/lm2.java defpackage/m8.java defpackage/nz1.java defpackage/sm.java defpackage/w1.java
00036	Get resource file from res/raw directory	reflection	defpackage/ie.java defpackage/sm.java defpackage/w1.java

RULE ID	BEHAVIOUR	LABEL	FILES
00022	Open a file from given absolute path of the file	file	ch/qos/logback/classic/android/SQLiteAppender.java ch/qos/logback/core/FileAppender.java ch/qos/logback/core/android/AndroidContextUtil.java ch/qos/logback/core/rolling/helper/Compressor.java ch/qos/logback/core/rolling/helper/FileFinder.java ch/qos/logback/core/rolling/helper/RenameUtil.java defpackage/fd2.java defpackage/o21.java defpackage/ol4.java defpackage/tq1.java defpackage/ug0.java defpackage/v1.java
00065	Get the country code of the SIM card provider	collection	sh/calvin/autolinktext/c.java
00051	Implicit intent(view a web page, make a phone call, etc.) via setData	control	defpackage/ff2.java defpackage/nz1.java defpackage/w1.java
00023	Start another application from current application	reflection control	defpackage/wi0.java
00162	Create InetSocketAddress object and connecting to it	socket	defpackage/jb0.java
00163	Create new Socket and connecting to it	socket	defpackage/jb0.java
00114	Create a secure socket connection to the proxy address	network command	defpackage/jb0.java

ABUSED PERMISSIONS

TYPE	MATCHES	PERMISSIONS
Malware Permissions	1/25	android.permission.INTERNET
Other Common Permissions	1/44	android.permission.FOREGROUND_SERVICE

Malware Permissions:
Top permissions that are widely abused by known malware.
Other Common Permissions:
Permissions that are commonly abused by known malware.

❗ OFAC SANCTIONED COUNTRIES

This app may communicate with the following OFAC sanctioned list of countries.

DOMAIN	COUNTRY/REGION

🔍 DOMAIN MALWARE CHECK

DOMAIN	STATUS	GEOLOCATION
twitch.tv	ok	**IP:** 151.101.2.167 **Country:** United States of America **Region:** California **City:** San Francisco **Latitude:** 37.775700 **Longitude:** -122.395203 **View:** Google Map

DOMAIN	STATUS	GEOLOCATION
api.frankerfacez.com	ok	**IP:** 104.26.7.201 **Country:** United States of America **Region:** California **City:** San Francisco **Latitude:** 37.775700 **Longitude:** -122.395203 **View:** Google Map
kappa.lol	ok	**IP:** 195.201.111.124 **Country:** Germany **Region:** Sachsen **City:** Falkenstein **Latitude:** 50.477879 **Longitude:** 12.371290 **View:** Google Map
www.slf4j.org	ok	**IP:** 31.97.181.89 **Country:** United Kingdom of Great Britain and Northern Ireland **Region:** England **City:** Bowness-on-Windermere **Latitude:** 54.363312 **Longitude:** -2.918590 **View:** Google Map
schemas.android.com	ok	No Geolocation information available.
chatvau.lt	ok	**IP:** 172.67.198.91 **Country:** United States of America **Region:** California **City:** San Francisco **Latitude:** 37.775700 **Longitude:** -122.395203 **View:** Google Map

DOMAIN	STATUS	GEOLOCATION
7tv.io	ok	**IP:** 65.109.41.220 **Country:** United States of America **Region:** Massachusetts **City:** Andover **Latitude:** 42.648373 **Longitude:** -71.161453 **View:** Google Map
www.w3.org	ok	**IP:** 104.18.23.19 **Country:** United States of America **Region:** California **City:** San Francisco **Latitude:** 37.775700 **Longitude:** -122.395203 **View:** Google Map
id.twitch.tv	ok	**IP:** 52.10.219.160 **Country:** United States of America **Region:** Oregon **City:** Portland **Latitude:** 45.523449 **Longitude:** -122.676208 **View:** Google Map
supinic.com	ok	**IP:** 78.47.52.88 **Country:** Germany **Region:** Sachsen **City:** Falkenstein **Latitude:** 50.477879 **Longitude:** 12.371290 **View:** Google Map
api.twitch.tv	ok	**IP:** 18.64.221.92 **Country:** United States of America **Region:** Washington **City:** Seattle **Latitude:** 47.627499 **Longitude:** -122.346199 **View:** Google Map

DOMAIN	STATUS	GEOLOCATION
cdn.betterttv.net	ok	**IP:** 104.26.1.19 **Country:** United States of America **Region:** California **City:** San Francisco **Latitude:** 37.775700 **Longitude:** -122.395203 **View:** Google Map
wiki.chatterino.com	ok	**IP:** 104.21.8.82 **Country:** United States of America **Region:** California **City:** San Francisco **Latitude:** 37.775700 **Longitude:** -122.395203 **View:** Google Map
badges.twitch.tv	ok	No Geolocation information available.
betterttv.com	ok	**IP:** 104.21.71.37 **Country:** United States of America **Region:** California **City:** San Francisco **Latitude:** 37.775700 **Longitude:** -122.395203 **View:** Google Map
goo.gle	ok	**IP:** 67.199.248.13 **Country:** United States of America **Region:** New York **City:** New York City **Latitude:** 40.739288 **Longitude:** -73.984955 **View:** Google Map

DOMAIN	STATUS	GEOLOCATION
www.frankerfacez.com	ok	**IP:** 104.26.7.201 **Country:** United States of America **Region:** California **City:** San Francisco **Latitude:** 37.775700 **Longitude:** -122.395203 **View:** Google Map
www.twitch.tv	ok	**IP:** 146.75.74.214 **Country:** Sweden **Region:** Vastra Gotalands lan **City:** Goeteborg **Latitude:** 57.707161 **Longitude:** 11.966790 **View:** Google Map
player.twitch.tv	ok	**IP:** 146.75.74.167 **Country:** Sweden **Region:** Vastra Gotalands lan **City:** Goeteborg **Latitude:** 57.707161 **Longitude:** 11.966790 **View:** Google Map
xml.org	ok	**IP:** 104.21.66.164 **Country:** United States of America **Region:** California **City:** San Francisco **Latitude:** 37.775700 **Longitude:** -122.395203 **View:** Google Map
static-cdn.jtvnw.net	ok	**IP:** 146.75.74.214 **Country:** Sweden **Region:** Vastra Gotalands lan **City:** Goeteborg **Latitude:** 57.707161 **Longitude:** 11.966790 **View:** Google Map

DOMAIN	STATUS	GEOLOCATION
flxrs.com	ok	**IP:** 172.67.221.179 **Country:** Japan **Region:** Tokyo **City:** Tokyo **Latitude:** 35.689507 **Longitude:** 139.691696 **View:** Google Map
github.com	ok	**IP:** 140.82.121.4 **Country:** United States of America **Region:** California **City:** San Francisco **Latitude:** 37.775700 **Longitude:** -122.395203 **View:** Google Map
7tv.app	ok	**IP:** 95.217.175.63 **Country:** Finland **Region:** Uusimaa **City:** Helsinki **Latitude:** 60.169521 **Longitude:** 24.935450 **View:** Google Map
api.betterttv.net	ok	**IP:** 104.26.0.19 **Country:** United States of America **Region:** California **City:** San Francisco **Latitude:** 37.775700 **Longitude:** -122.395203 **View:** Google Map
issuetracker.google.com	ok	**IP:** 172.217.20.238 **Country:** United States of America **Region:** California **City:** Mountain View **Latitude:** 37.405991 **Longitude:** -122.078514 **View:** Google Map

DOMAIN	STATUS	GEOLOCATION
ns.adobe.com	ok	No Geolocation information available.
logback.qos.ch	ok	**IP:** 31.97.181.89 **Country:** United Kingdom of Great Britain and Northern Ireland **Region:** England **City:** Bowness-on-Windermere **Latitude:** 54.363312 **Longitude:** -2.918590 **View:** Google Map
ktor.io	ok	**IP:** 108.139.200.96 **Country:** United States of America **Region:** Washington **City:** Seattle **Latitude:** 47.606209 **Longitude:** -122.332069 **View:** Google Map
recent-messages.robotty.de	ok	**IP:** 78.47.52.88 **Country:** Germany **Region:** Sachsen **City:** Falkenstein **Latitude:** 50.477879 **Longitude:** 12.371290 **View:** Google Map

EMAILS

EMAIL	FILE
dankchat@flxrs.com	defpackage/w1.java
dankchat@flxrs.com	defpackage/sm.java

🔑 HARDCODED SECRETS

POSSIBLE SECRETS
"preference_show_username_key" : "show_username_key"
"automod_ban_user" : "□□□□□BAN□□"
"highlights_entry_username" : "□□□□□□□□□□"
"username" : "Käyttäjänimi"
"search_filter_user" : "Карыстальнік"
"preference_developer_category_auth" : "Аўтарызацыя"
"preference_supibot_suggestions_key" : "supibot_suggestions_key"
"preference_tts_queue_key" : "tts_queue_key"
"preference_show_changelogs_key" : "show_changelogs_key"
"search_filter_user" : "Felhasználó"
"preference_tts_force_english_key" : "tts_force_english_key"
"tts_ignore_list_add_user" : "□□□□□"
"preference_revoke_token_title" : "□□□□□□□□□□"
"preference_repeated_sending_key" : "repeated_sending_key"
"preference_mention_format_key" : "mention_format"
"oauth_token" : "OAuth-tunnus"

POSSIBLE SECRETS
"preference_roomstate_key" : "show_roomstate"
"preference_line_separator_key" : "line_seperator_key"
"search_filter_user" : "Пользователь"
"preference_true_dark_theme_key" : "true_dark_mode"
"tts_ignore_list_remove_user" : "□□□□□□□"
"preference_debug_mode_key" : "debug_mode_key"
"highlights_entry_username" : "Käyttäjänimesi"
"preference_revoke_token_summary" : "□□□□□□□□□□□□□□□□□□□□□□□□□□□□"
"search_filter_user" : "□□□"
"shared_preference_key" : "com.flxrs.dankchat_preferences"
"preference_user_long_click_key" : "preference_mention_long_click_key"
"search_filter_user" : "Kullanıcı"
"preference_timestamp_key" : "show_timestamp"
"preference_commands_key" : "custom_commands_key"
"preference_developer_category_auth" : "Autenticació"
"tts_ignore_list_add_user" : "□□□□□□□"
"oauth_verify_failed" : "□□□□□□□□□□□□□□□□"
"search_filter_user" : "Корисник"

POSSIBLE SECRETS
"search_filter_user" : "Käyttäjä"
"search_filter_user" : "Użytkownik"
"oauth_expired_title" : "□□□□□□□□"
"preference_fetch_streams_key" : "fetch_streams_key"
"preference_visible_badges_key" : "visible_badges_key"
"preference_tts_key" : "tts_key"
"preference_revoke_token_title" : "□□□□□□□□□□□□□□"
"preference_follow_system_key" : "follow_system_mode"
"preference_rm_host_key" : "rm_host_key"
"preference_animate_gifs_key" : "animate_gifs_key"
"preference_scrollback_length_key" : "scrollback_length_key"
"preference_pip_key" : "pip_key"
"preference_auto_disable_input_key" : "auto_disable_input_key"
"username" : "Přezdívka"
"preference_suggestions_key" : "suggestions_key"
"search_filter_user" : "[redacted]"
"oauth_token" : "OAuth□□token"
"preference_dark_theme_key" : "enable_dark_mode"

POSSIBLE SECRETS
"preference_light_theme_key" : "enable_light_mode"
"preference_developer_category_auth" : "Аутентификација"
"search_filter_user" : "User"
"search_filter_user" : "Utilizador"
"username" : "Benutzername"
"preference_developer_category_auth" : "Авторизація"
"preference_developer_category_auth" : "Authentifizierung"
"search_filter_by_username" : "□□□□□□□□□□□□"
"search_filter_user" : "Usuario"
"oauth_expired_title" : "□□□□□"
"preference_developer_category_auth" : "Авторизация"
"username" : "Usuario"
"preference_font_size_key" : "font_size_key"
"preference_developer_category_auth" : "Todennus"
"preference_developer_category_auth" : "Auth"
"preference_show_input_key" : "show_input_key"
"highlights_entry_username" : "Felhasználóneved"
"preference_notification_key" : "notification_key"

POSSIBLE SECRETS
"search_filter_user" : "Користувач"
"automod_ban_user" : "□□□□□"
"preference_unlisted_emotes_key" : "unlisted_emotes_key"
"username" : "Username"
"preference_developer_category_auth" : "Autenticazione"
"oauth_verify_failed" : "□□□□□

POSSIBLE SECRETS
"preference_developer_category_auth" : "□□"
"preference_developer_category_auth" : "Ověření"
"preference_developer_category_auth" : "Autenticação"
"search_filter_user" : "Uživatel"
"oauth_token" : "OAuth-Token"
"preference_notification_whisper_key" : "notification_whisper_key"
"username" : "Felhasználónév"
"oauth_token" : "OAuth□□□□"
"preference_developer_category_auth" : "□□"
"preference_developer_category_auth" : "Autoryzacja"
"preference_visible_emotes_key" : "visible_emotes_key"
"username" : "□□□□□"
"preference_tts_user_ignore_list_key" : "tts_user_ignore_list_key"
"username" : "□□□□□"
"preference_revoke_token_summary" : "□□□□□□□□□□□□□□□□□□□"
"preference_streaminfo_key" : "show_streaminfo"
"search_filter_user" : "□□□□"
"preference_developer_category_auth" : "Autenticación"

POSSIBLE SECRETS
"search_filter_user" : "Utente"
"search_filter_user" : "Usuari"
"search_filter_user" : "Utilisateur"
"preference_bypass_command_handling_key" : "bypass_command_handling_key"
"search_filter_by_username" : "□□□□□□□□"
"search_filter_user" : "Пайдаланушы"
"preference_timestamp_format_key" : "timestamp_format_key"
"highlights_entry_username" : "□□□□□□□"
258EAFA5-E914-47DA-95CA-C5AB0DC85B11
6a6710155f6e95378180ba5e768da071
94a9c4f3e12e5916026708f0139cdb1f

PLAYSTORE INFORMATION

Title: DankChat

Score: 4.34 **Installs:** 100,000+ **Price:** 0 **Android Version Support:** **Category:** Entertainment **Play Store URL:** com.flxrs.dankchat

Developer Details: Felix Schmid, Felix+Schmid, None, https://dank.chat, dankchat@flxrs.com,

Release Date: Jun 9, 2019 **Privacy Policy:** Privacy link

Description:

Chat in multiple channels at once, regardless if the streamers are live or offline, with FrankerFaceZ, BTTV and 7TV emote support built-in!

SCAN LOGS

Timestamp	Event	Error
2026-05-01 06:23:20	Generating Hashes	OK
2026-05-01 06:23:20	Extracting APK	OK
2026-05-01 06:23:20	Unzipping	OK
2026-05-01 06:23:21	Parsing APK with androguard	OK
2026-05-01 06:23:24	Extracting APK features using aapt/aapt2	OK
2026-05-01 06:23:25	Getting Hardcoded Certificates/Keystores	OK
2026-05-01 06:23:34	Parsing AndroidManifest.xml	OK
2026-05-01 06:23:34	Extracting Manifest Data	OK
2026-05-01 06:23:34	Manifest Analysis Started	OK
2026-05-01 06:23:34	Reading Network Security config from network_security_config.xml	OK

2026-05-01 06:23:34	Parsing Network Security config	OK
2026-05-01 06:23:34	Performing Static Analysis on: DankChat (com.flxrs.dankchat)	OK
2026-05-01 06:23:42	Fetching Details from Play Store: com.flxrs.dankchat	OK
2026-05-01 06:23:45	Checking for Malware Permissions	OK
2026-05-01 06:23:45	Fetching icon path	OK
2026-05-01 06:23:45	Library Binary Analysis Started	OK
2026-05-01 06:23:45	Analyzing lib/x86_64/libdatastore_shared_counter.so	OK
2026-05-01 06:23:45	Analyzing lib/x86_64/libandroidx.graphics.path.so	OK
2026-05-01 06:23:45	Analyzing lib/x86/libdatastore_shared_counter.so	OK
2026-05-01 06:23:45	Analyzing lib/x86/libandroidx.graphics.path.so	OK
2026-05-01 06:23:45	Analyzing lib/arm64-v8a/libdatastore_shared_counter.so	OK
2026-05-01 06:23:45	Analyzing lib/arm64-v8a/libandroidx.graphics.path.so	OK

2026-05-01 06:23:45	Analyzing lib/armeabi-v7a/libdatastore_shared_counter.so	OK
2026-05-01 06:23:45	Analyzing lib/armeabi-v7a/libandroidx.graphics.path.so	OK
2026-05-01 06:23:45	Analyzing apktool_out/lib/x86_64/libdatastore_shared_counter.so	OK
2026-05-01 06:23:45	Analyzing apktool_out/lib/x86_64/libandroidx.graphics.path.so	OK
2026-05-01 06:23:45	Analyzing apktool_out/lib/x86/libdatastore_shared_counter.so	OK
2026-05-01 06:23:46	Analyzing apktool_out/lib/x86/libandroidx.graphics.path.so	OK
2026-05-01 06:23:46	Analyzing apktool_out/lib/arm64-v8a/libdatastore_shared_counter.so	OK
2026-05-01 06:23:46	Analyzing apktool_out/lib/arm64-v8a/libandroidx.graphics.path.so	OK
2026-05-01 06:23:46	Analyzing apktool_out/lib/armeabi-v7a/libdatastore_shared_counter.so	OK
2026-05-01 06:23:46	Analyzing apktool_out/lib/armeabi-v7a/libandroidx.graphics.path.so	OK
2026-05-01 06:23:46	Reading Code Signing Certificate	OK
2026-05-01 06:23:47	Running APKiD 3.0.0	OK

2026-05-01 06:23:51	Detecting Trackers	OK
2026-05-01 06:23:53	Decompiling APK to Java with JADX	OK
2026-05-01 06:25:50	Converting DEX to Smali	OK
2026-05-01 06:25:50	Code Analysis Started on - java_source	OK
2026-05-01 06:25:59	Android SBOM Analysis Completed	OK
2026-05-01 06:26:28	Android SAST Completed	OK
2026-05-01 06:26:28	Android API Analysis Started	OK
2026-05-01 06:26:43	Android API Analysis Completed	OK
2026-05-01 06:26:43	Android Permission Mapping Started	OK
2026-05-01 06:26:55	Android Permission Mapping Completed	OK
2026-05-01 06:26:56	Android Behaviour Analysis Started	OK
2026-05-01 06:27:17	Android Behaviour Analysis Completed	OK

2026-05-01 06:27:17	Extracting Emails and URLs from Source Code	OK
2026-05-01 06:27:30	Email and URL Extraction Completed	OK
2026-05-01 06:27:30	Extracting String data from APK	OK
2026-05-01 06:27:31	Extracting String data from SO	OK
2026-05-01 06:27:31	Extracting String data from Code	OK
2026-05-01 06:27:31	Extracting String values and entropies from Code	OK
2026-05-01 06:27:34	Performing Malware check on extracted domains	OK
2026-05-01 06:27:56	Saving to Database	OK

Report Generated by - MobSF v4.5.0

Mobile Security Framework (MobSF) is an automated, all-in-one mobile application (Android/iOS/Windows) pen-testing, malware analysis and security assessment framework capable of performing static and dynamic analysis.

© 2026 Mobile Security Framework - MobSF | Ajin Abraham | OpenSecurity.

MOBSF

ANDROID STATIC ANALYSIS REPORT

app_icon

Easter Eggs (4.5.0)

File Name: com.dede.android_eggs_74.apk

Package Name:	com.dede.android_eggs
Scan Date:	May 1, 2026, 6:19 a.m.
App Security Score:	50/100 (MEDIUM RISK)
Grade:	B

FINDINGS SEVERITY

HIGH	MEDIUM	INFO	SECURE	HOTSPOT

1	68	2	1	1

FILE INFORMATION

File Name: com.dede.android_eggs_74.apk
Size: 5.43MB
MD5: d83729aadee86d6260c7bce2c8e82c42
SHA1: ea369d484a7418a5e87a7db2eabd75f3b8f5f845
SHA256: 3a385957a7738e61c9560eb934f112bb7fc91bc96ec7c8e687c2970027c9f4cc

APP INFORMATION

App Name: Easter Eggs
Package Name: com.dede.android_eggs
Main Activity: com.dede.android_eggs.views.main.EasterEggsActivity
Target SDK: 36
Min SDK: 23
Max SDK:
Android Version Name: 4.5.0
Android Version Code: 74

APP COMPONENTS

Activities: 54
Services: 15
Receivers: 6
Providers: 1
Exported Activities: 44
Exported Services: 13
Exported Receivers: 5
Exported Providers: 0

CERTIFICATE INFORMATION

Binary is signed
v1 signature: True
v2 signature: True
v3 signature: True
v4 signature: False
X.509 Subject: C=99, L=nanjing, O=china, CN=hsh
Signature Algorithm: rsassa_pkcs1v15
Valid From: 2017-06-24 10:56:47+00:00
Valid To: 2042-06-18 10:56:47+00:00
Issuer: C=99, L=nanjing, O=china, CN=hsh
Serial Number: 0x5dbac7d2
Hash Algorithm: sha256
md5: ce8ad2a6cf1a2fa66749f8169782c717
sha1: 03748dd0b02c7bfd554513310376e24bdf2a4a02
sha256: 2e9e0ce7c37d0502aa5173ae9f96a190005099f1adb9f89c68d0ca01f63fa61d
sha512: 7a392f0bee8ef82ccd8dc66109eac8b019c226da3b851933a00fabd4cb5ec1c247aa3b4f0ff6e06bd7ed3af2b87caa396a62348745439ddcb57e70281b343224
PublicKey Algorithm: rsa
Bit Size: 2048
Fingerprint: ba5141159b26732da0de4a0b014253099713470d78dbddc83880ddab6517cc3d
Found 1 unique certificates

APPLICATION PERMISSIONS

PERMISSION	STATUS	INFO	DESCRIPTION
android.permission.INTERNET	normal	full Internet access	Allows an application to create network sockets.
com.android.launcher.permission.INSTALL_SHORTCUT	unknown	Unknown permission	Unknown permission from android reference
android.permission.POST_NOTIFICATIONS	dangerous	allows an app to post notifications.	Allows an app to post notifications
android.permission.VIBRATE	normal	control vibrator	Allows the application to control the vibrator.

PERMISSION	STATUS	INFO	DESCRIPTION
android.permission.SUBSTITUTE_NOTIFICATION_APP_NAME	unknown	Unknown permission	Unknown permission from android reference
android.permission.WRITE_EXTERNAL_STORAGE	dangerous	read/modify/delete external storage contents	Allows an application to write to external storage.
android.permission.BIND_CONTROLS	SignatureOrSystem	Allows SystemUI to request third party controls.	Allows SystemUI to request third party controls. Should only be requested by the System and required by ControlsProviderService declarations.
android.permission.READ_EXTERNAL_STORAGE	dangerous	read external storage contents	Allows an application to read from external storage.
com.dede.android_eggs.DYNAMIC_RECEIVER_NOT_EXPORTED_PERMISSION	unknown	Unknown permission	Unknown permission from android reference

APKID ANALYSIS

FILE	DETAILS
classes.dex	FINDINGS: Anti-VM Code — DETAILS: Build.FINGERPRINT check FINDINGS: Compiler — DETAILS: r8

BROWSABLE ACTIVITIES

ACTIVITY	INTENT
com.dede.android_eggs.views.main.EasterEggsActivity	Schemes: egg://, Hosts: easter_egg,

NETWORK SECURITY

NO	SCOPE	SEVERITY	DESCRIPTION

CERTIFICATE ANALYSIS

HIGH: 0 | WARNING: 1 | INFO: 1

TITLE	SEVERITY	DESCRIPTION
Signed Application	info	Application is signed with a code signing certificate
Application vulnerable to Janus Vulnerability	warning	Application is signed with v1 signature scheme, making it vulnerable to Janus vulnerability on Android 5.0-8.0, if signed only with v1 signature scheme. Applications running on Android 5.0-7.0 signed with v1, and v2/v3 scheme is also vulnerable.

MANIFEST ANALYSIS

HIGH: 1 | WARNING: 63 | INFO: 0 | SUPPRESSED: 0

NO	ISSUE	SEVERITY	DESCRIPTION
1	App can be installed on a vulnerable unpatched Android version 6.0-6.0.1, [minSdk=23]	high	This application can be installed on an older version of android that has multiple unfixed vulnerabilities. These devices won't receive reasonable security updates from Google. Support an Android version => 10, API 29 to receive reasonable security updates.

NO	ISSUE	SEVERITY	DESCRIPTION
2	Application Data can be Backed up [android:allowBackup=true]	warning	This flag allows anyone to backup your application data via adb. It allows users who have enabled USB debugging to copy application data off of the device.
3	Activity (com.android.launcher2.RocketLauncher) is not Protected. [android:exported=true]	warning	An Activity is found to be shared with other apps on the device therefore leaving it accessible to any other application on the device.
4	Service (com.android.launcher2.RocketLauncherDream) is Protected by a permission, but the protection level of the permission should be checked. Permission: android.permission.BIND_DREAM_SERVICE [android:exported=true]	warning	A Service is found to be shared with other apps on the device therefore leaving it accessible to any other application on the device. It is protected by a permission which is not defined in the analysed application. As a result, the protection level of the permission should be checked where it is defined. If it is set to normal or dangerous, a malicious application can request and obtain the permission and interact with the component. If it is set to signature, only applications signed with the same certificate can obtain the permission.
5	Broadcast Receiver (com.dede.android_eggs.neko_controls_widget.NekoControlsAppWidget) is not Protected. [android:exported=true]	warning	A Broadcast Receiver is found to be shared with other apps on the device therefore leaving it accessible to any other application on the device.
6	Broadcast Receiver (com.dede.android_eggs.crash.CrashNotificationActionsReceiver) is not Protected. [android:exported=true]	warning	A Broadcast Receiver is found to be shared with other apps on the device therefore leaving it accessible to any other application on the device.
7	Activity (com.android_cinnamon_bun.egg.PlatLogoActivity) is not Protected. [android:exported=true]	warning	An Activity is found to be shared with other apps on the device therefore leaving it accessible to any other application on the device.
8	Activity (com.android_baklava.egg.PlatLogoActivity) is not Protected. [android:exported=true]	warning	An Activity is found to be shared with other apps on the device therefore leaving it accessible to any other application on the device.
9	Service (com.android_baklava.egg.landroid.DreamUniverse) is Protected by a permission, but the protection level of the permission should be checked. Permission: android.permission.BIND_DREAM_SERVICE [android:exported=true]	warning	A Service is found to be shared with other apps on the device therefore leaving it accessible to any other application on the device. It is protected by a permission which is not defined in the analysed application. As a result, the protection level of the permission should be checked where it is defined. If it is set to normal or dangerous, a malicious application can request and obtain the permission and interact with the component. If it is set to signature, only applications signed with the same certificate can obtain the permission.
10	Activity (com.android_baklava.egg.landroid.MainActivity) is not Protected. [android:exported=true]	warning	An Activity is found to be shared with other apps on the device therefore leaving it accessible to any other application on the device.

NO	ISSUE	SEVERITY	DESCRIPTION
11	Activity (com.android_v.egg.PlatLogoActivity) is not Protected. [android:exported=true]	warning	An Activity is found to be shared with other apps on the device therefore leaving it accessible to any other application on the device.
12	Service (com.android_v.egg.landroid.DreamUniverse) is Protected by a permission, but the protection level of the permission should be checked. Permission: android.permission.BIND_DREAM_SERVICE [android:exported=true]	warning	A Service is found to be shared with other apps on the device therefore leaving it accessible to any other application on the device. It is protected by a permission which is not defined in the analysed application. As a result, the protection level of the permission should be checked where it is defined. If it is set to normal or dangerous, a malicious application can request and obtain the permission and interact with the component. If it is set to signature, only applications signed with the same certificate can obtain the permission.
13	Activity (com.android_v.egg.landroid.MainActivity) is not Protected. [android:exported=true]	warning	An Activity is found to be shared with other apps on the device therefore leaving it accessible to any other application on the device.
14	Activity (com.android_u.egg.PlatLogoActivity) is not Protected. [android:exported=true]	warning	An Activity is found to be shared with other apps on the device therefore leaving it accessible to any other application on the device.
15	Activity (com.android_u.egg.landroid.MainActivity) is not Protected. [android:exported=true]	warning	An Activity is found to be shared with other apps on the device therefore leaving it accessible to any other application on the device.
16	Activity (com.android_t.egg.PlatLogoActivity) is not Protected. [android:exported=true]	warning	An Activity is found to be shared with other apps on the device therefore leaving it accessible to any other application on the device.
17	Activity (com.android_t.egg.beta.PlatLogoActivity) is not Protected. [android:exported=true]	warning	An Activity is found to be shared with other apps on the device therefore leaving it accessible to any other application on the device.
18	Activity (com.android_t.egg.neko.NekoLand) is not Protected. [android:exported=true]	warning	An Activity is found to be shared with other apps on the device therefore leaving it accessible to any other application on the device.
19	Service (com.android_t.egg.neko.NekoService) is Protected by a permission, but the protection level of the permission should be checked. Permission: android.permission.BIND_JOB_SERVICE [android:exported=true]	warning	A Service is found to be shared with other apps on the device therefore leaving it accessible to any other application on the device. It is protected by a permission which is not defined in the analysed application. As a result, the protection level of the permission should be checked where it is defined. If it is set to normal or dangerous, a malicious application can request and obtain the permission and interact with the component. If it is set to signature, only applications signed with the same certificate can obtain the permission.

NO	ISSUE	SEVERITY	DESCRIPTION
20	Activity (com.android_t.egg.ComponentActivationActivity) is not Protected. [android:exported=true]	warning	An Activity is found to be shared with other apps on the device therefore leaving it accessible to any other application on the device.
21	Service (com.android_t.egg.neko.NekoControlsService) is Protected by a permission, but the protection level of the permission should be checked. Permission: android.permission.BIND_CONTROLS [android:exported=true]	warning	A Service is found to be shared with other apps on the device therefore leaving it accessible to any other application on the device. It is protected by a permission which is not defined in the analysed application. As a result, the protection level of the permission should be checked where it is defined. If it is set to normal or dangerous, a malicious application can request and obtain the permission and interact with the component. If it is set to signature, only applications signed with the same certificate can obtain the permission.
22	Activity (com.android_t.egg.widget.PaintChipsActivity) is not Protected. [android:exported=true]	warning	An Activity is found to be shared with other apps on the device therefore leaving it accessible to any other application on the device.
23	Broadcast Receiver (com.android_t.egg.widget.PaintChipsWidget) is not Protected. [android:exported=true]	warning	A Broadcast Receiver is found to be shared with other apps on the device therefore leaving it accessible to any other application on the device.
24	Activity (com.android_s.egg.PlatLogoActivity) is not Protected. [android:exported=true]	warning	An Activity is found to be shared with other apps on the device therefore leaving it accessible to any other application on the device.
25	Activity (com.android_s.egg.neko.NekoLand) is not Protected. [android:exported=true]	warning	An Activity is found to be shared with other apps on the device therefore leaving it accessible to any other application on the device.
26	Service (com.android_s.egg.neko.NekoService) is Protected by a permission, but the protection level of the permission should be checked. Permission: android.permission.BIND_JOB_SERVICE [android:exported=true]	warning	A Service is found to be shared with other apps on the device therefore leaving it accessible to any other application on the device. It is protected by a permission which is not defined in the analysed application. As a result, the protection level of the permission should be checked where it is defined. If it is set to normal or dangerous, a malicious application can request and obtain the permission and interact with the component. If it is set to signature, only applications signed with the same certificate can obtain the permission.
27	Activity (com.android_s.egg.ComponentActivationActivity) is not Protected. [android:exported=true]	warning	An Activity is found to be shared with other apps on the device therefore leaving it accessible to any other application on the device.

NO	ISSUE	SEVERITY	DESCRIPTION
28	Service (com.android_s.egg.neko.NekoControlsService) is Protected by a permission, but the protection level of the permission should be checked. Permission: android.permission.BIND_CONTROLS [android:exported=true]	warning	A Service is found to be shared with other apps on the device therefore leaving it accessible to any other application on the device. It is protected by a permission which is not defined in the analysed application. As a result, the protection level of the permission should be checked where it is defined. If it is set to normal or dangerous, a malicious application can request and obtain the permission and interact with the component. If it is set to signature, only applications signed with the same certificate can obtain the permission.
29	Activity (com.android_s.egg.widget.PaintChipsActivity) is not Protected. [android:exported=true]	warning	An Activity is found to be shared with other apps on the device therefore leaving it accessible to any other application on the device.
30	Broadcast Receiver (com.android_s.egg.widget.PaintChipsWidget) is not Protected. [android:exported=true]	warning	A Broadcast Receiver is found to be shared with other apps on the device therefore leaving it accessible to any other application on the device.
31	Activity (com.android_r.egg.PlatLogoActivity) is not Protected. [android:exported=true]	warning	An Activity is found to be shared with other apps on the device therefore leaving it accessible to any other application on the device.
32	Activity (com.android_r.egg.neko.NekoLand) is not Protected. [android:exported=true]	warning	An Activity is found to be shared with other apps on the device therefore leaving it accessible to any other application on the device.
33	Service (com.android_r.egg.neko.NekoService) is Protected by a permission, but the protection level of the permission should be checked. Permission: android.permission.BIND_JOB_SERVICE [android:exported=true]	warning	A Service is found to be shared with other apps on the device therefore leaving it accessible to any other application on the device. It is protected by a permission which is not defined in the analysed application. As a result, the protection level of the permission should be checked where it is defined. If it is set to normal or dangerous, a malicious application can request and obtain the permission and interact with the component. If it is set to signature, only applications signed with the same certificate can obtain the permission.
34	Service (com.android_r.egg.neko.NekoControlsService) is Protected by a permission, but the protection level of the permission should be checked. Permission: android.permission.BIND_CONTROLS [android:exported=true]	warning	A Service is found to be shared with other apps on the device therefore leaving it accessible to any other application on the device. It is protected by a permission which is not defined in the analysed application. As a result, the protection level of the permission should be checked where it is defined. If it is set to normal or dangerous, a malicious application can request and obtain the permission and interact with the component. If it is set to signature, only applications signed with the same certificate can obtain the permission.
35	Activity (com.android_q.egg.PlatLogoActivity) is not Protected. [android:exported=true]	warning	An Activity is found to be shared with other apps on the device therefore leaving it accessible to any other application on the device.

NO	ISSUE	SEVERITY	DESCRIPTION
36	Activity (com.android_p.egg.PlatLogoActivity) is not Protected. [android:exported=true]	warning	An Activity is found to be shared with other apps on the device therefore leaving it accessible to any other application on the device.
37	Activity (com.android_o.egg.PlatLogoActivity) is not Protected. [android:exported=true]	warning	An Activity is found to be shared with other apps on the device therefore leaving it accessible to any other application on the device.
38	Activity (com.android_o.egg.PlatLogoActivity$Point1) is not Protected. [android:exported=true]	warning	An Activity is found to be shared with other apps on the device therefore leaving it accessible to any other application on the device.
39	Activity (com.android_o.egg.octo.Ocquarium) is not Protected. [android:exported=true]	warning	An Activity is found to be shared with other apps on the device therefore leaving it accessible to any other application on the device.
40	Activity (com.android_n.egg.PlatLogoActivity) is not Protected. [android:exported=true]	warning	An Activity is found to be shared with other apps on the device therefore leaving it accessible to any other application on the device.
41	Activity (com.android_n.egg.preview.PlatLogoActivity) is not Protected. [android:exported=true]	warning	An Activity is found to be shared with other apps on the device therefore leaving it accessible to any other application on the device.
42	Activity (com.android_n.egg.neko.NekoLand) is not Protected. [android:exported=true]	warning	An Activity is found to be shared with other apps on the device therefore leaving it accessible to any other application on the device.
43	Service (com.android_n.egg.neko.NekoService) is Protected by a permission, but the protection level of the permission should be checked. Permission: android.permission.BIND_JOB_SERVICE [android:exported=true]	warning	A Service is found to be shared with other apps on the device therefore leaving it accessible to any other application on the device. It is protected by a permission which is not defined in the analysed application. As a result, the protection level of the permission should be checked where it is defined. If it is set to normal or dangerous, a malicious application can request and obtain the permission and interact with the component. If it is set to signature, only applications signed with the same certificate can obtain the permission.
44	Service (com.android_n.egg.neko.NekoTile) is Protected by a permission, but the protection level of the permission should be checked. Permission: android.permission.BIND_QUICK_SETTINGS_TILE [android:exported=true]	warning	A Service is found to be shared with other apps on the device therefore leaving it accessible to any other application on the device. It is protected by a permission which is not defined in the analysed application. As a result, the protection level of the permission should be checked where it is defined. If it is set to normal or dangerous, a malicious application can request and obtain the permission and interact with the component. If it is set to signature, only applications signed with the same certificate can obtain the permission.

NO	ISSUE	SEVERITY	DESCRIPTION
45	Activity (com.android_m.egg.PlatLogoActivity) is not Protected. [android:exported=true]	warning	An Activity is found to be shared with other apps on the device therefore leaving it accessible to any other application on the device.
46	Activity (com.android_m.egg.MLandActivity) is not Protected. [android:exported=true]	warning	An Activity is found to be shared with other apps on the device therefore leaving it accessible to any other application on the device.
47	Activity (com.android_m.egg.preview.PlatLogoActivity) is not Protected. [android:exported=true]	warning	An Activity is found to be shared with other apps on the device therefore leaving it accessible to any other application on the device.
48	Activity (com.android_m.egg.preview.ShruggyActivity) is not Protected. [android:exported=true]	warning	An Activity is found to be shared with other apps on the device therefore leaving it accessible to any other application on the device.
49	Activity (com.android_l.egg.preview.PlatLogoActivity) is not Protected. [android:exported=true]	warning	An Activity is found to be shared with other apps on the device therefore leaving it accessible to any other application on the device.
50	Activity (com.android_l.egg.PlatLogoActivity) is not Protected. [android:exported=true]	warning	An Activity is found to be shared with other apps on the device therefore leaving it accessible to any other application on the device.
51	Activity (com.android_l.egg.LLandActivity) is not Protected. [android:exported=true]	warning	An Activity is found to be shared with other apps on the device therefore leaving it accessible to any other application on the device.
52	Activity (com.android_k.egg.PlatLogoActivity) is not Protected. [android:exported=true]	warning	An Activity is found to be shared with other apps on the device therefore leaving it accessible to any other application on the device.
53	Activity (com.android_k.egg.DessertCase) is not Protected. [android:exported=true]	warning	An Activity is found to be shared with other apps on the device therefore leaving it accessible to any other application on the device.
54	Service (com.android_k.egg.DessertCaseDream) is Protected by a permission, but the protection level of the permission should be checked. Permission: android.permission.BIND_DREAM_SERVICE [android:exported=true]	warning	A Service is found to be shared with other apps on the device therefore leaving it accessible to any other application on the device. It is protected by a permission which is not defined in the analysed application. As a result, the protection level of the permission should be checked where it is defined. If it is set to normal or dangerous, a malicious application can request and obtain the permission and interact with the component. If it is set to signature, only applications signed with the same certificate can obtain the permission.
55	Activity (com.android_k.egg.preview.PlatLogoActivity) is not Protected. [android:exported=true]	warning	An Activity is found to be shared with other apps on the device therefore leaving it accessible to any other application on the device.

NO	ISSUE	SEVERITY	DESCRIPTION
56	Activity (com.android_j.egg.PlatLogoActivity) is not Protected. [android:exported=true]	warning	An Activity is found to be shared with other apps on the device therefore leaving it accessible to any other application on the device.
57	Activity (com.android_j.egg.BeanBag) is not Protected. [android:exported=true]	warning	An Activity is found to be shared with other apps on the device therefore leaving it accessible to any other application on the device.
58	Service (com.android_j.egg.BeanBagDream) is Protected by a permission, but the protection level of the permission should be checked. Permission: android.permission.BIND_DREAM_SERVICE [android:exported=true]	warning	A Service is found to be shared with other apps on the device therefore leaving it accessible to any other application on the device. It is protected by a permission which is not defined in the analysed application. As a result, the protection level of the permission should be checked where it is defined. If it is set to normal or dangerous, a malicious application can request and obtain the permission and interact with the component. If it is set to signature, only applications signed with the same certificate can obtain the permission.
59	Activity (com.android_i.egg.PlatLogoActivity) is not Protected. [android:exported=true]	warning	An Activity is found to be shared with other apps on the device therefore leaving it accessible to any other application on the device.
60	Activity (com.android_i.egg.Nyandroid) is not Protected. [android:exported=true]	warning	An Activity is found to be shared with other apps on the device therefore leaving it accessible to any other application on the device.
61	Activity (com.android_i.egg.preview.PlatLogoActivity) is not Protected. [android:exported=true]	warning	An Activity is found to be shared with other apps on the device therefore leaving it accessible to any other application on the device.
62	Activity (com.android_h.egg.PlatLogoActivity) is not Protected. [android:exported=true]	warning	An Activity is found to be shared with other apps on the device therefore leaving it accessible to any other application on the device.
63	Activity (com.android_g.egg.PlatLogoActivity) is not Protected. [android:exported=true]	warning	An Activity is found to be shared with other apps on the device therefore leaving it accessible to any other application on the device.
64	Broadcast Receiver (androidx.profileinstaller.ProfileInstallReceiver) is Protected by a permission, but the protection level of the permission should be checked. Permission: android.permission.DUMP [android:exported=true]	warning	A Broadcast Receiver is found to be shared with other apps on the device therefore leaving it accessible to any other application on the device. It is protected by a permission which is not defined in the analysed application. As a result, the protection level of the permission should be checked where it is defined. If it is set to normal or dangerous, a malicious application can request and obtain the permission and interact with the component. If it is set to signature, only applications signed with the same certificate can obtain the permission.

CODE ANALYSIS

HIGH: 0 | WARNING: 3 | INFO: 2 | SECURE: 0 | SUPPRESSED: 0

NO	ISSUE	SEVERITY	STANDARDS	FILES
1	The App uses an insecure Random Number Generator.	warning	CWE: CWE-330: Use of Insufficiently Random Values OWASP Top 10: M5: Insufficient Cryptography OWASP MASVS: MSTG-CRYPTO-6	defpackage/an2.java defpackage/br3.java defpackage/fb3.java defpackage/fh.java defpackage/gy2.java defpackage/gz2.java defpackage/hy2.java defpackage/iy2.java defpackage/jy2.java defpackage/le.java defpackage/lq.java defpackage/m8.java defpackage/nn3.java defpackage/r0.java defpackage/sj2.java defpackage/t21.java defpackage/tj2.java defpackage/uj2.java defpackage/uz.java defpackage/vz.java defpackage/wt2.java defpackage/wz.java defpackage/yz.java defpackage/zc.java
2	Files may contain hardcoded sensitive information like usernames, passwords, keys etc.	warning	CWE: CWE-312: Cleartext Storage of Sensitive Information OWASP Top 10: M9: Reverse Engineering OWASP MASVS: MSTG-STORAGE-14	defpackage/fo3.java defpackage/gs.java defpackage/m13.java defpackage/mi2.java defpackage/r92.java defpackage/sp0.java defpackage/tw0.java defpackage/u01.java defpackage/wo2.java defpackage/ya0.java
				defpackage/a90.java

NO	ISSUE	SEVERITY	STANDARDS	FILES
				defpackage/ak2.java defpackage/an2.java defpackage/b63.java defpackage/b73.java defpackage/b94.java defpackage/bk.java defpackage/c63.java defpackage/c83.java defpackage/c94.java defpackage/cb4.java defpackage/cf4.java defpackage/co.java defpackage/ct3.java defpackage/cy2.java defpackage/d20.java defpackage/d42.java defpackage/d64.java defpackage/d94.java defpackage/de0.java defpackage/e32.java defpackage/e52.java defpackage/e90.java defpackage/e94.java defpackage/ek.java defpackage/el.java defpackage/ev2.java defpackage/f10.java defpackage/f3.java defpackage/f32.java defpackage/f33.java defpackage/f4.java defpackage/f73.java defpackage/fv0.java defpackage/fy2.java defpackage/g94.java defpackage/gi1.java defpackage/gj.java defpackage/h94.java defpackage/hg4.java defpackage/hp.java defpackage/hx0.java defpackage/i91.java defpackage/ia0.java defpackage/ia2.java defpackage/ib0.java defpackage/ii0.java

NO	ISSUE	SEVERITY	STANDARDS	FILES
3	The App logs information. Sensitive information should never be logged.	info	CWE: CWE-532: Insertion of Sensitive Information into Log File OWASP MASVS: MSTG-STORAGE-3	defpackage/il4.java defpackage/iy0.java defpackage/j50.java defpackage/j83.java defpackage/jk.java defpackage/jl2.java defpackage/jq.java defpackage/jx2.java defpackage/jy0.java defpackage/k40.java defpackage/k90.java defpackage/kc4.java defpackage/kq.java defpackage/kx2.java defpackage/l33.java defpackage/l63.java defpackage/l73.java defpackage/lb0.java defpackage/lm1.java defpackage/lm2.java defpackage/lq.java defpackage/lz.java defpackage/m6.java defpackage/m80.java defpackage/m9.java defpackage/m90.java defpackage/m91.java defpackage/ma2.java defpackage/mc2.java defpackage/n21.java defpackage/n83.java defpackage/n90.java defpackage/ng4.java defpackage/nn3.java defpackage/no.java defpackage/o13.java defpackage/o3.java defpackage/o91.java defpackage/ob2.java defpackage/od0.java defpackage/on.java defpackage/p80.java defpackage/p9.java defpackage/pi.java defpackage/pi4.java defpackage/q9.java

NO	ISSUE	SEVERITY	STANDARDS	FILES
				defpackage/qb.java defpackage/qd1.java defpackage/qm2.java defpackage/r53.java defpackage/r63.java defpackage/ra2.java defpackage/rc1.java defpackage/rl.java defpackage/ro1.java defpackage/s21.java defpackage/s93.java defpackage/sc3.java defpackage/si2.java defpackage/t3.java defpackage/t34.java defpackage/t40.java defpackage/t52.java defpackage/t64.java defpackage/tj.java defpackage/u00.java defpackage/u80.java defpackage/ub.java defpackage/ub2.java defpackage/uw3.java defpackage/v61.java defpackage/v63.java defpackage/v9.java defpackage/vg.java defpackage/vj.java defpackage/vj2.java defpackage/vl.java defpackage/vw3.java defpackage/vx2.java defpackage/w34.java defpackage/w53.java defpackage/wd0.java defpackage/wj2.java defpackage/wk0.java defpackage/wy0.java defpackage/x91.java defpackage/xa0.java defpackage/xi4.java defpackage/xj1.java defpackage/xj2.java defpackage/xk.java defpackage/y3.java

NO	ISSUE	SEVERITY	STANDARDS	FILES
				defpackage/y71.java defpackage/y73.java defpackage/ye4.java defpackage/yj2.java defpackage/yx2.java defpackage/z61.java defpackage/z80.java defpackage/za0.java defpackage/za3.java defpackage/zb.java defpackage/zd.java defpackage/ze2.java defpackage/zj2.java defpackage/zm2.java defpackage/zn3.java defpackage/zx0.java
4	App can read/write to External Storage. Any App can read data written to External Storage.	warning	CWE: CWE-276: Incorrect Default Permissions OWASP Top 10: M2: Insecure Data Storage OWASP MASVS: MSTG-STORAGE-2	defpackage/zx2.java defpackage/xj1.java
5	This App copies data to clipboard. Sensitive data should not be copied to clipboard as other applications can access it.	info	OWASP MASVS: MSTG-STORAGE-10	defpackage/u80.java defpackage/w8.java

SHARED LIBRARY BINARY ANALYSIS

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
1	x86_64/libdatastore_shared_counter.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	False high This binary does not have a stack canary value added to the stack. Stack canaries are used to detect and prevent exploits from overwriting return address. Use the option -fstack-protector-all to enable stack canaries. Not applicable for Dart/Flutter libraries unless Dart FFI is used.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
2	x86_64/libandroidx.graphics.path.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
3	x86/libdatastore_shared_counter.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
4	x86/libandroidx.graphics.path.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
5	arm64-v8a/libdatastore_shared_counter.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	False high This binary does not have a stack canary value added to the stack. Stack canaries are used to detect and prevent exploits from overwriting return address. Use the option -fstack-protector-all to enable stack canaries. Not applicable for Dart/Flutter libraries unless Dart FFI is used.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
6	arm64-v8a/libandroidx.graphics.path.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
7	armeabi-v7a/libdatastore_shared_counter.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	False high This binary does not have a stack canary value added to the stack. Stack canaries are used to detect and prevent exploits from overwriting return address. Use the option -fstack-protector-all to enable stack canaries. Not applicable for Dart/Flutter libraries unless Dart FFI is used.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
8	armeabi-v7a/libandroidx.graphics.path.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
9	x86_64/libdatastore_shared_counter.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	False high This binary does not have a stack canary value added to the stack. Stack canaries are used to detect and prevent exploits from overwriting return address. Use the option -fstack-protector-all to enable stack canaries. Not applicable for Dart/Flutter libraries unless Dart FFI is used.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
10	x86_64/libandroidx.graphics.path.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
11	x86/libdatastore_shared_counter.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
12	x86/libandroidx.graphics.path.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
13	arm64-v8a/libdatastore_shared_counter.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	False high This binary does not have a stack canary value added to the stack. Stack canaries are used to detect and prevent exploits from overwriting return address. Use the option -fstack-protector-all to enable stack canaries. Not applicable for Dart/Flutter libraries unless Dart FFI is used.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
14	arm64-v8a/libandroidx.graphics.path.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
15	armeabi-v7a/libdatastore_shared_counter.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	False high This binary does not have a stack canary value added to the stack. Stack canaries are used to detect and prevent exploits from overwriting return address. Use the option -fstack-protector-all to enable stack canaries. Not applicable for Dart/Flutter libraries unless Dart FFI is used.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
16	armeabi-v7a/libandroidx.graphics.path.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NIAP ANALYSIS v1.3

NO	IDENTIFIER	REQUIREMENT	FEATURE	DESCRIPTION

BEHAVIOUR ANALYSIS

RULE ID	BEHAVIOUR	LABEL	FILES
00014	Read file into a stream and put it into a JSON object	file	defpackage/y3.java
00013	Read file and put it into a stream	file	defpackage/c23.java defpackage/c94.java defpackage/d60.java defpackage/d94.java defpackage/ed3.java defpackage/il4.java defpackage/j83.java defpackage/lp0.java defpackage/n90.java defpackage/o33.java defpackage/wk0.java defpackage/x7.java defpackage/y3.java
00063	Implicit intent(view a web page, make a phone call, etc.)	control	com/dede/android_eggs/views/main/EasterEggsActivity.java defpackage/m80.java defpackage/n83.java defpackage/pu1.java defpackage/qe.java
00036	Get resource file from res/raw directory	reflection	defpackage/m80.java defpackage/n83.java defpackage/pu1.java
00022	Open a file from given absolute path of the file	file	defpackage/an0.java defpackage/k31.java defpackage/lm1.java defpackage/ok0.java defpackage/r6.java defpackage/rc1.java defpackage/xj1.java
00051	Implicit intent(view a web page, make a phone call, etc.) via setData	control	defpackage/m80.java defpackage/pu1.java
00096	Connect to a URL and set request method	command network	defpackage/u8.java

RULE ID	BEHAVIOUR	LABEL	FILES
00187	Query a URI and check the result	collection sms calllog calendar	defpackage/xj1.java
00077	Read sensitive data(SMS, CALLLOG, etc)	collection sms calllog calendar	defpackage/xj1.java
00177	Check if permission is granted and request it	permission	defpackage/il4.java
00091	Retrieve data from broadcast	collection	defpackage/j50.java
00079	Hide the current app's icon	evasion	defpackage/n.java
00147	Get the time of current location	collection location	defpackage/bk.java
00075	Get location of the device	collection location	defpackage/bk.java
00115	Get last known location of the device	collection location	defpackage/bk.java

ABUSED PERMISSIONS

TYPE	MATCHES	PERMISSIONS
Malware Permissions	4/25	android.permission.INTERNET, android.permission.VIBRATE, android.permission.WRITE_EXTERNAL_STORAGE, android.permission.READ_EXTERNAL_STORAGE
Other Common Permissions	1/44	com.android.launcher.permission.INSTALL_SHORTCUT

Malware Permissions:

Top permissions that are widely abused by known malware.

Other Common Permissions:

Permissions that are commonly abused by known malware.

❗ OFAC SANCTIONED COUNTRIES

This app may communicate with the following OFAC sanctioned list of countries.

DOMAIN	COUNTRY/REGION

🔍 DOMAIN MALWARE CHECK

DOMAIN	STATUS	GEOLOCATION
api.github.com	ok	**IP:** 140.82.121.6 **Country:** United States of America **Region:** California **City:** San Francisco **Latitude:** 37.775700 **Longitude:** -122.395203 **View:** Google Map
crowdin.com	ok	**IP:** 34.192.182.144 **Country:** United States of America **Region:** Virginia **City:** Ashburn **Latitude:** 39.043720 **Longitude:** -77.487488 **View:** Google Map
www.slf4j.org	ok	**IP:** 31.97.181.89 **Country:** United Kingdom of Great Britain and Northern Ireland **Region:** England **City:** Bowness-on-Windermere **Latitude:** 54.363312 **Longitude:** -2.918590 **View:** Google Map
schemas.android.com	ok	No Geolocation information available.

DOMAIN	STATUS	GEOLOCATION
zh.crowdin.com	ok	**IP:** 34.192.182.144 **Country:** United States of America **Region:** Virginia **City:** Ashburn **Latitude:** 39.043720 **Longitude:** -77.487488 **View:** Google Map
keepandroidopen.org	ok	**IP:** 185.199.108.153 **Country:** United States of America **Region:** Pennsylvania **City:** California **Latitude:** 40.065632 **Longitude:** -79.891708 **View:** Google Map
www.pgyer.com	ok	**IP:** 155.102.150.27 **Country:** United States of America **Region:** California **City:** San Mateo **Latitude:** 37.547424 **Longitude:** -122.330589 **View:** Google Map
goo.gle	ok	**IP:** 67.199.248.13 **Country:** United States of America **Region:** New York **City:** New York City **Latitude:** 40.739288 **Longitude:** -73.984955 **View:** Google Map
github.com	ok	**IP:** 140.82.121.3 **Country:** United States of America **Region:** California **City:** San Francisco **Latitude:** 37.775700 **Longitude:** -122.395203 **View:** Google Map

DOMAIN	STATUS	GEOLOCATION
www.w3.org	ok	**IP:** 104.18.22.19 **Country:** United States of America **Region:** California **City:** San Francisco **Latitude:** 37.775700 **Longitude:** -122.395203 **View:** Google Map
issuetracker.google.com	ok	**IP:** 172.217.20.238 **Country:** United States of America **Region:** California **City:** Mountain View **Latitude:** 37.405991 **Longitude:** -122.078514 **View:** Google Map
ktor.io	ok	**IP:** 108.139.200.67 **Country:** United States of America **Region:** Washington **City:** Seattle **Latitude:** 47.606209 **Longitude:** -122.332069 **View:** Google Map
youtrack.jetbrains.com	ok	**IP:** 63.33.88.220 **Country:** Ireland **Region:** Dublin **City:** Dublin **Latitude:** 53.343990 **Longitude:** -6.267190 **View:** Google Map

🔑 HARDCODED SECRETS

POSSIBLE SECRETS
"k_key_lime_pie" : "KeyLimePie"
c863f8a64263bc5a9a7ca0aed89755bd
55c69db652d5a645e3e90baf920c6d63

PLAYSTORE INFORMATION

Title: Easter Eggs

Score: 4.712871 **Installs:** 100,000+ **Price:** 0 **Android Version Support:** **Category:** Entertainment **Play Store URL:** com.dede.android_eggs

Developer Details: Hu Shenghao, Hu+Shenghao, None, https://github.com/hushenghao/AndroidEasterEggs, dede.hu@qq.com,

Release Date: Nov 5, 2020 **Privacy Policy:** Privacy link

Description:

Collections the Android release Easter Egg. This project contains the complete code for all Android Easter eggs, aiming to organize and ensure compatibility with all Android Easter eggs. The goal is to enable most devices to experience different versions of the Easter eggs with minimal modifications to the Easter egg's code. GitHub https://github.com/hushenghao/AndroidEasterEggs System source code: https://cs.android.com/android/platform/superproject/main

SCAN LOGS

Timestamp	Event	Error
2026-05-01 06:19:24	Generating Hashes	OK
2026-05-01 06:19:24	Extracting APK	OK
2026-05-01 06:19:24	Unzipping	OK

2026-05-01 06:19:25	Parsing APK with androguard	OK
2026-05-01 06:19:25	Extracting APK features using aapt/aapt2	OK
2026-05-01 06:19:25	Getting Hardcoded Certificates/Keystores	OK
2026-05-01 06:19:32	Parsing AndroidManifest.xml	OK
2026-05-01 06:19:32	Extracting Manifest Data	OK
2026-05-01 06:19:32	Manifest Analysis Started	OK
2026-05-01 06:19:32	Performing Static Analysis on: Easter Eggs (com.dede.android_eggs)	OK
2026-05-01 06:19:39	Fetching Details from Play Store: com.dede.android_eggs	OK
2026-05-01 06:19:43	Checking for Malware Permissions	OK
2026-05-01 06:19:43	Fetching icon path	OK
2026-05-01 06:19:44	Library Binary Analysis Started	OK
2026-05-01 06:19:44	Analyzing lib/x86_64/libdatastore_shared_counter.so	OK

2026-05-01 06:19:44	Analyzing lib/x86_64/libandroidx.graphics.path.so	OK
2026-05-01 06:19:44	Analyzing lib/x86/libdatastore_shared_counter.so	OK
2026-05-01 06:19:44	Analyzing lib/x86/libandroidx.graphics.path.so	OK
2026-05-01 06:19:44	Analyzing lib/arm64-v8a/libdatastore_shared_counter.so	OK
2026-05-01 06:19:44	Analyzing lib/arm64-v8a/libandroidx.graphics.path.so	OK
2026-05-01 06:19:44	Analyzing lib/armeabi-v7a/libdatastore_shared_counter.so	OK
2026-05-01 06:19:44	Analyzing lib/armeabi-v7a/libandroidx.graphics.path.so	OK
2026-05-01 06:19:44	Analyzing apktool_out/lib/x86_64/libdatastore_shared_counter.so	OK
2026-05-01 06:19:44	Analyzing apktool_out/lib/x86_64/libandroidx.graphics.path.so	OK
2026-05-01 06:19:44	Analyzing apktool_out/lib/x86/libdatastore_shared_counter.so	OK
2026-05-01 06:19:44	Analyzing apktool_out/lib/x86/libandroidx.graphics.path.so	OK
2026-05-01 06:19:44	Analyzing apktool_out/lib/arm64-v8a/libdatastore_shared_counter.so	OK

2026-05-01 06:19:44	Analyzing apktool_out/lib/arm64-v8a/libandroidx.graphics.path.so	OK
2026-05-01 06:19:44	Analyzing apktool_out/lib/armeabi-v7a/libdatastore_shared_counter.so	OK
2026-05-01 06:19:44	Analyzing apktool_out/lib/armeabi-v7a/libandroidx.graphics.path.so	OK
2026-05-01 06:19:44	Reading Code Signing Certificate	OK
2026-05-01 06:19:45	Running APKiD 3.0.0	OK
2026-05-01 06:19:52	Detecting Trackers	OK
2026-05-01 06:19:54	Decompiling APK to Java with JADX	OK
2026-05-01 06:21:05	Converting DEX to Smali	OK
2026-05-01 06:21:05	Code Analysis Started on - java_source	OK
2026-05-01 06:21:11	Android SBOM Analysis Completed	OK
2026-05-01 06:21:28	Android SAST Completed	OK
2026-05-01 06:21:28	Android API Analysis Started	OK

2026-05-01 06:21:35	Android API Analysis Completed	OK
2026-05-01 06:21:35	Android Permission Mapping Started	OK
2026-05-01 06:21:40	Android Permission Mapping Completed	OK
2026-05-01 06:21:41	Android Behaviour Analysis Started	OK
2026-05-01 06:21:57	Android Behaviour Analysis Completed	OK
2026-05-01 06:21:57	Extracting Emails and URLs from Source Code	OK
2026-05-01 06:22:03	Email and URL Extraction Completed	OK
2026-05-01 06:22:03	Extracting String data from APK	OK
2026-05-01 06:22:03	Extracting String data from SO	OK
2026-05-01 06:22:03	Extracting String data from Code	OK
2026-05-01 06:22:03	Extracting String values and entropies from Code	OK
2026-05-01 06:22:05	Performing Malware check on extracted domains	OK

2026-05-01 06:22:31	Saving to Database	OK

Report Generated by - MobSF v4.5.0

Mobile Security Framework (MobSF) is an automated, all-in-one mobile application (Android/iOS/Windows) pen-testing, malware analysis and security assessment framework capable of performing static and dynamic analysis.

© 2026 Mobile Security Framework - MobSF | Ajin Abraham | OpenSecurity.

MOBSF

ANDROID STATIC ANALYSIS REPORT

Gotify (2.9.0)

File Name:	com.github.gotify_34.apk
Package Name:	com.github.gotify
Scan Date:	May 1, 2026, 6:30 a.m.
App Security Score:	45/100 (MEDIUM RISK)
Grade:	B

FINDINGS SEVERITY

HIGH	MEDIUM	INFO	SECURE	HOTSPOT
4	8	2	2	1

FILE INFORMATION

File Name: com.github.gotify_34.apk
Size: 6.74MB
MD5: 602fe30d9885d06f149f1ca8ab71d7e1
SHA1: a2260f5827fda61259585da78e9102effa62ece2
SHA256: dbc91d55692416db05b6aac5063389a69da0dcddce723855ca1f2d1064c75f49

APP INFORMATION

App Name: Gotify
Package Name: com.github.gotify
Main Activity: com.github.gotify.init.InitializationActivity
Target SDK: 36
Min SDK: 23
Max SDK:
Android Version Name: 2.9.0
Android Version Code: 34

APP COMPONENTS

Activities: 7
Services: 1
Receivers: 2
Providers: 1
Exported Activities: 1
Exported Services: 0
Exported Receivers: 2
Exported Providers: 0

CERTIFICATE INFORMATION

Binary is signed
v1 signature: True
v2 signature: True
v3 signature: True
v4 signature: False
X.509 Subject: C=UK, ST=ORG, L=ORG, O=fdroid.org, OU=FDroid, CN=FDroid
Signature Algorithm: rsassa_pkcs1v15
Valid From: 2018-11-06 09:15:04+00:00
Valid To: 2046-03-24 09:15:04+00:00
Issuer: C=UK, ST=ORG, L=ORG, O=fdroid.org, OU=FDroid, CN=FDroid
Serial Number: 0x29b43be6
Hash Algorithm: sha256
md5: a895b74ccaf5f37d7a9e18a2786b76fa
sha1: 9b77d4fdf46f1a4cc68340a5c709150a8c3de747
sha256: 5d73c22fa3a466d602c5041774dcb05be624ea8e080ded752c1425b1a39c996b
sha512: 6564fb38b0cb9b7ec8e30fca98e5ebc586656caf2340b3a4a7bcdd0233bdf37d6ab2d79b4e9ede3c1c3abdf3598f94237e825f49044915d4acd70edac20109ac
PublicKey Algorithm: rsa
Bit Size: 2048
Fingerprint: 7fc37bf82e8fa40c05928e141e9e007e7c2aa1f37bb6e4cde835c4b8e175eabd
Found 1 unique certificates

APPLICATION PERMISSIONS

PERMISSION	STATUS	INFO	DESCRIPTION
android.permission.INTERNET	normal	full Internet access	Allows an application to create network sockets.
android.permission.SYSTEM_ALERT_WINDOW	dangerous	display system-level alerts	Allows an application to show system-alert windows. Malicious applications can take over the entire screen of the phone.
android.permission.FOREGROUND_SERVICE	normal	enables regular apps to use Service.startForeground.	Allows a regular application to use Service.startForeground.
android.permission.RECEIVE_BOOT_COMPLETED	normal	automatically start at boot	Allows an application to start itself as soon as the system has finished booting. This can make it take longer to start the phone and allow the application to slow down the overall phone by always running.
android.permission.ACCESS_NETWORK_STATE	normal	view network status	Allows an application to view the status of all networks.
android.permission.POST_NOTIFICATIONS	dangerous	allows an app to post notifications.	Allows an app to post notifications
android.permission.SCHEDULE_EXACT_ALARM	normal	permits exact alarm scheduling for background work.	Allows an app to use exact alarm scheduling APIs to perform timing sensitive background work.
android.permission.FOREGROUND_SERVICE_SPECIAL_USE	normal	enables special-use foreground services.	Allows a regular application to use Service.startForeground with the type "specialUse".

PERMISSION	STATUS	INFO	DESCRIPTION
com.github.gotify.DYNAMIC_RECEIVER_NOT_EXPORTED_PERMISSION	unknown	Unknown permission	Unknown permission from android reference

APKID ANALYSIS

FILE	DETAILS
classes.dex	FINDINGS: Anti-VM Code — DETAILS: Build.FINGERPRINT check Build.MANUFACTURER check FINDINGS: Compiler — DETAILS: r8
classes2.dex	FINDINGS: Compiler — DETAILS: unknown (please file detection issue!)

FILE	DETAILS
classes3.dex	<table><tr><th>FINDINGS</th><th>DETAILS</th></tr><tr><td>Compiler</td><td>r8 without marker (suspicious)</td></tr></table>

NETWORK SECURITY

HIGH: 2 | WARNING: 1 | INFO: 0 | SECURE: 0

NO	SCOPE	SEVERITY	DESCRIPTION
1	*	high	Base config is insecurely configured to permit clear text traffic to all domains.
2	*	warning	Base config is configured to trust system certificates.
3	*	high	Base config is configured to trust user installed certificates.

CERTIFICATE ANALYSIS

HIGH: 0 | WARNING: 1 | INFO: 1

TITLE	SEVERITY	DESCRIPTION
Signed Application	info	Application is signed with a code signing certificate

TITLE	SEVERITY	DESCRIPTION
Application vulnerable to Janus Vulnerability	warning	Application is signed with v1 signature scheme, making it vulnerable to Janus vulnerability on Android 5.0-8.0, if signed only with v1 signature scheme. Applications running on Android 5.0-7.0 signed with v1, and v2/v3 scheme is also vulnerable.

MANIFEST ANALYSIS

HIGH: **2** | WARNING: **3** | INFO: **0** | SUPPRESSED: **0**

NO	ISSUE	SEVERITY	DESCRIPTION
1	App can be installed on a vulnerable unpatched Android version 6.0-6.0.1, [minSdk=23]	high	This application can be installed on an older version of android that has multiple unfixed vulnerabilities. These devices won't receive reasonable security updates from Google. Support an Android version => 10, API 29 to receive reasonable security updates.
2	Clear text traffic is Enabled For App[android:usesCleartextTraffic=true]	high	The app intends to use cleartext network traffic, such as cleartext HTTP, FTP stacks, DownloadManager, and MediaPlayer. The default value for apps that target API level 27 or lower is "true". Apps that target API level 28 or higher default to "false". The key reason for avoiding cleartext traffic is the lack of confidentiality, authenticity, and protections against tampering; a network attacker can eavesdrop on transmitted data and also modify it without being detected.
3	App has a Network Security Configuration[android:networkSecurityConfig=@xml/network_security_config]	info	The Network Security Configuration feature lets apps customize their network security settings in a safe, declarative configuration file without modifying app code. These settings can be configured for specific domains and for a specific app.

NO	ISSUE	SEVERITY	DESCRIPTION
4	Activity (com.github.gotify.sharing.ShareActivity) is not Protected. [android:exported=true]	warning	An Activity is found to be shared with other apps on the device therefore leaving it accessible to any other application on the device.
5	Broadcast Receiver (com.github.gotify.init.BootCompletedReceiver) is not Protected. [android:exported=true]	warning	A Broadcast Receiver is found to be shared with other apps on the device therefore leaving it accessible to any other application on the device.
6	Broadcast Receiver (androidx.profileinstaller.ProfileInstallReceiver) is Protected by a permission, but the protection level of the permission should be checked. Permission: android.permission.DUMP [android:exported=true]	warning	A Broadcast Receiver is found to be shared with other apps on the device therefore leaving it accessible to any other application on the device. It is protected by a permission which is not defined in the analysed application. As a result, the protection level of the permission should be checked where it is defined. If it is set to normal or dangerous, a malicious application can request and obtain the permission and interact with the component. If it is set to signature, only applications signed with the same certificate can obtain the permission.

CODE ANALYSIS

HIGH: **0** | WARNING: **2** | INFO: **2** | SECURE: **1** | SUPPRESSED: **0**

NO	ISSUE	SEVERITY	STANDARDS	FILES
1	Files may contain hardcoded sensitive information like usernames, passwords, keys etc.	warning	CWE: CWE-312: Cleartext Storage of Sensitive Information OWASP Top 10: M9: Reverse Engineering OWASP MASVS: MSTG-STORAGE-14	coil/decode/SvgDecoder.java coil/memory/MemoryCache.java coil/memory/MemoryCacheService.java coil/request/Parameters.java com/github/gotify/SSLSettings.java org/tinylog/configuration/Configuration.java

NO	ISSUE	SEVERITY	STANDARDS	FILES
2	This App copies data to clipboard. Sensitive data should not be copied to clipboard as other applications can access it.	info	OWASP MASVS: MSTG-STORAGE-10	com/github/gotify/log/LogsActivity.java com/github/gotify/messages/ListMessageAdapter.java
3	App creates temp file. Sensitive information should never be written into a temp file.	warning	CWE: CWE-276: Incorrect Default Permissions OWASP Top 10: M2: Insecure Data Storage OWASP MASVS: MSTG-STORAGE-2	coil/decode/SourceImageSource.java io/noties/markwon/image/DefaultDownScalingMediaDecoder.java
4	The App logs information. Sensitive information should never be logged.	info	CWE: CWE-532: Insertion of Sensitive Information into Log File OWASP MASVS: MSTG-STORAGE-3	com/caverock/androidsvg/CSSParser.java com/caverock/androidsvg/SVG.java com/caverock/androidsvg/SVGAndroidRenderer.java com/caverock/androidsvg/SVGImageView.java com/caverock/androidsvg/SVGParser.java com/caverock/androidsvg/SimpleAssetResolver.java io/noties/markwon/LinkResolverDef.java io/noties/markwon/PrecomputedTextSetterCompat.java io/noties/markwon/image/AsyncDrawableLoaderImpl.java io/noties/markwon/image/gif/GifSupport.java io/noties/markwon/image/svg/SvgSupport.java org/slf4j/helpers/MessageFormatter.java org/slf4j/helpers/Util.java org/threeten/bp/zone/TzdbZoneRulesCompiler.java org/tinylog/provider/InternalLogger.java org/tinylog/writers/ConsoleWriter.java
5	This App uses SSL certificate pinning to detect or prevent MITM attacks in secure communication channel.	secure	OWASP MASVS: MSTG-NETWORK-4	com/github/gotify/api/CertUtils.java com/github/gotify/client/ApiClient.java

NIAP ANALYSIS v1.3

NO	IDENTIFIER	REQUIREMENT	FEATURE	DESCRIPTION

BEHAVIOUR ANALYSIS

RULE ID	BEHAVIOUR	LABEL	FILES
00063	Implicit intent(view a web page, make a phone call, etc.)	control	com/github/gotify/init/InitializationActivity.java com/github/gotify/login/LoginActivity.java com/github/gotify/messages/IntentUrlDialogActivity.java com/github/gotify/messages/MessagesActivity.java com/github/gotify/service/WebSocketService.java com/github/gotify/settings/SettingsActivity.java io/noties/markwon/LinkResolverDef.java
00013	Read file and put it into a stream	file	coil/fetch/ContentUriFetcher.java com/github/gotify/api/CertUtils.java com/github/gotify/login/LoginActivity.java io/noties/markwon/image/DefaultDownScalingMediaDecoder.java io/noties/markwon/image/file/FileSchemeHandler.java okio/Okio__JvmOkioKt.java org/threeten/bp/chrono/HijrahDate.java org/tinylog/configuration/PropertiesConfigurationLoader.java org/tinylog/converters/GzipEncoder.java

RULE ID	BEHAVIOUR	LABEL	FILES
00022	Open a file from given absolute path of the file	file	coil/disk/DiskCache.java com/github/gotify/GotifyApplication.java com/github/gotify/log/LoggerHelper.java com/github/gotify/login/LoginActivity.java org/tinylog/converters/GzipEncoder.java org/tinylog/path/DynamicPath.java org/tinylog/writers/RollingFileWriter.java
00089	Connect to a URL and receive input stream from the server	command network	io/noties/markwon/image/network/NetworkSchemeHandler.java
00030	Connect to the remote server through the given URL	network	io/noties/markwon/image/network/NetworkSchemeHandler.java
00109	Connect to a URL and get the response code	network command	io/noties/markwon/image/network/NetworkSchemeHandler.java
00036	Get resource file from res/raw directory	reflection	coil/map/ResourceIntMapper.java com/github/gotify/settings/SettingsActivity.java io/noties/markwon/LinkResolverDef.java
00012	Read data and put it into a buffer stream	file	io/noties/markwon/image/DefaultDownScalingMediaDecoder.java io/noties/markwon/image/file/FileSchemeHandler.java
00051	Implicit intent(view a web page, make a phone call, etc.) via setData	control	com/github/gotify/messages/IntentUrlDialogActivity.java com/github/gotify/service/WebSocketService.java
00028	Read file from assets directory	file	com/caverock/androidsvg/SimpleAssetResolver.java
00175	Get notification manager and cancel notifications	notification	com/github/gotify/messages/MessagesActivity.java

ABUSED PERMISSIONS

TYPE	MATCHES	PERMISSIONS
Malware Permissions	4/25	android.permission.INTERNET, android.permission.SYSTEM_ALERT_WINDOW, android.permission.RECEIVE_BOOT_COMPLETED, android.permission.ACCESS_NETWORK_STATE
Other Common Permissions	1/44	android.permission.FOREGROUND_SERVICE

Malware Permissions:
Top permissions that are widely abused by known malware.

Other Common Permissions:
Permissions that are commonly abused by known malware.

OFAC SANCTIONED COUNTRIES

This app may communicate with the following OFAC sanctioned list of countries.

DOMAIN	COUNTRY/REGION

DOMAIN MALWARE CHECK

DOMAIN	STATUS	GEOLOCATION
android.asset	ok	No Geolocation information available.

DOMAIN	STATUS	GEOLOCATION
xml.org	ok	**IP:** 172.67.205.113 **Country:** United States of America **Region:** California **City:** San Francisco **Latitude:** 37.775700 **Longitude:** -122.395203 **View:** Google Map
www.slf4j.org	ok	**IP:** 159.100.250.151 **Country:** Switzerland **Region:** Vaud **City:** Lausanne **Latitude:** 46.515999 **Longitude:** 6.632820 **View:** Google Map
example.com	ok	**IP:** 104.20.23.154 **Country:** United States of America **Region:** California **City:** San Francisco **Latitude:** 37.775700 **Longitude:** -122.395203 **View:** Google Map
xmlpull.org	ok	**IP:** 185.199.108.153 **Country:** United States of America **Region:** Pennsylvania **City:** California **Latitude:** 40.065632 **Longitude:** -79.891708 **View:** Google Map

DOMAIN	STATUS	GEOLOCATION
gotify.net	ok	**IP:** 185.199.108.153 **Country:** United States of America **Region:** Pennsylvania **City:** California **Latitude:** 40.065632 **Longitude:** -79.891708 **View:** Google Map
www.w3.org	ok	**IP:** 104.18.23.19 **Country:** United States of America **Region:** California **City:** San Francisco **Latitude:** 37.775700 **Longitude:** -122.395203 **View:** Google Map

🔑 HARDCODED SECRETS

POSSIBLE SECRETS
"password" : "Password"
"setting_key_exclude_from_recent" : "exclude_from_recent"
"setting_key_intent_dialog_permission" : "intent_dialog_permission"
"setting_key_notification_channels" : "notification_channels"
"setting_key_theme" : "theme"

POSSIBLE SECRETS
"setting_key_time_format" : "time_format"
"username" : "Username"
ae9512b6b6feea56a110d59a3353ea3b9c293864
258EAFA5-E914-47DA-95CA-C5AB0DC85B11

PLAYSTORE INFORMATION

Title: Gotify

Score: 4.745763 **Installs:** 10,000+ **Price:** 0 **Android Version Support:** **Category:** Tools **Play Store URL:** com.github.gotify

Developer Details: Gotify, Gotify, None, https://gotify.net/, gotify@protonmail.com,

Release Date: Jul 1, 2018 **Privacy Policy:** Privacy link

Description:

Gotify is a server for sending and receiving messages in real-time per web socket. This app subscribes to the web socket and creates push notifications on new messages. Gotify and this app are open source. You can view the source code on GitHub https://github.com/gotify Note: A self-hosted Gotify-server is needed for this app to work, an explanation on "how to set up Gotify server" is displayed on https://gotify.net/docs/install

SCAN LOGS

Timestamp	Event	Error
2026-05-01 06:30:55	Generating Hashes	OK

2026-05-01 06:30:55	Extracting APK	OK
2026-05-01 06:30:55	Unzipping	OK
2026-05-01 06:30:56	Parsing APK with androguard	OK
2026-05-01 06:30:56	Extracting APK features using aapt/aapt2	OK
2026-05-01 06:30:56	Getting Hardcoded Certificates/Keystores	OK
2026-05-01 06:31:05	Parsing AndroidManifest.xml	OK
2026-05-01 06:31:05	Extracting Manifest Data	OK
2026-05-01 06:31:05	Manifest Analysis Started	OK
2026-05-01 06:31:05	Reading Network Security config from network_security_config.xml	OK
2026-05-01 06:31:05	Parsing Network Security config	OK
2026-05-01 06:31:05	Performing Static Analysis on: Gotify (com.github.gotify)	OK

2026-05-01 06:31:08	Fetching Details from Play Store: com.github.gotify	OK
2026-05-01 06:31:09	Checking for Malware Permissions	OK
2026-05-01 06:31:09	Fetching icon path	OK
2026-05-01 06:31:09	Library Binary Analysis Started	OK
2026-05-01 06:31:09	Reading Code Signing Certificate	OK
2026-05-01 06:31:11	Running APKiD 3.0.0	OK
2026-05-01 06:31:16	Detecting Trackers	OK
2026-05-01 06:31:22	Decompiling APK to Java with JADX	OK
2026-05-01 06:32:42	Converting DEX to Smali	OK
2026-05-01 06:32:42	Code Analysis Started on - java_source	OK
2026-05-01 06:32:45	Android SBOM Analysis Completed	OK

2026-05-01 06:33:18	Android SAST Completed	OK
2026-05-01 06:33:19	Android API Analysis Started	OK
2026-05-01 06:33:28	Android API Analysis Completed	OK
2026-05-01 06:33:29	Android Permission Mapping Started	OK
2026-05-01 06:33:35	Android Permission Mapping Completed	OK
2026-05-01 06:33:36	Android Behaviour Analysis Started	OK
2026-05-01 06:33:43	Android Behaviour Analysis Completed	OK
2026-05-01 06:33:43	Extracting Emails and URLs from Source Code	OK
2026-05-01 06:33:45	Email and URL Extraction Completed	OK
2026-05-01 06:33:45	Extracting String data from APK	OK
2026-05-01 06:33:46	Extracting String data from Code	OK

2026-05-01 06:33:46	Extracting String values and entropies from Code	OK
2026-05-01 06:33:49	Performing Malware check on extracted domains	OK
2026-05-01 06:33:57	Saving to Database	OK

Report Generated by - MobSF v4.5.0

Mobile Security Framework (MobSF) is an automated, all-in-one mobile application (Android/iOS/Windows) pen-testing, malware analysis and security assessment framework capable of performing static and dynamic analysis.

© 2026 Mobile Security Framework - MobSF | Ajin Abraham | OpenSecurity.

ANDROID STATIC ANALYSIS REPORT

app_icon

Athena (1.80)

File Name:	com.kin.athena_306.apk
Package Name:	com.kin.athena
Scan Date:	May 2, 2026, 9:20 a.m.

App Security Score: 55/100 (MEDIUM RISK)

Grade: B

FINDINGS SEVERITY

HIGH	MEDIUM	INFO	SECURE	HOTSPOT
2	15	2	3	1

FILE INFORMATION

File Name: com.kin.athena_306.apk
Size: 5.98MB
MD5: 3bda899229cd0e792a9cbc2ef8d75326
SHA1: 5a4ccf115d64d25a96db0cdef263e5100c400ed0
SHA256: ff0cf9b520fb4dd2459033bd8ace400a9181c61bb53ce8751c6d7796fa0eb69b

APP INFORMATION

App Name: Athena
Package Name: com.kin.athena
Main Activity: com.kin.athena.presentation.MainActivity
Target SDK: 36
Min SDK: 24
Max SDK:
Android Version Name: 1.80
Android Version Code: 306

APP COMPONENTS

Activities: 1
Services: 10
Receivers: 10
Providers: 2
Exported Activities: 0
Exported Services: 3
Exported Receivers: 3
Exported Providers: 1

CERTIFICATE INFORMATION

Binary is signed
v1 signature: False
v2 signature: True
v3 signature: True
v4 signature: False
X.509 Subject: C=UK, ST=ORG, L=ORG, O=fdroid.org, OU=FDroid, CN=FDroid
Signature Algorithm: rsassa_pkcs1v15
Valid From: 2025-11-15 07:39:44+00:00
Valid To: 2053-04-02 07:39:44+00:00
Issuer: C=UK, ST=ORG, L=ORG, O=fdroid.org, OU=FDroid, CN=FDroid
Serial Number: 0xfef3e77c6f805022
Hash Algorithm: sha256
md5: e4e9bb40eaf1edb73ef4ffb6f50dcf02
sha1: cf0d279277220a1fd6e8eeb22632029bcd9e5ad5
sha256: b49f6ee0ac81a0678817ce6864567b0d1c0a2823cb2999f2a4ab0c17edbd2981

sha512: eb4fe7eaa6c166f812ea8f7d80d26d61c268e9a664d37ad77ebb1d67d4577c65c5f7ce3dd284bff040611e132bd746febaf1b15491bff9e6d57ed06dfedba050
PublicKey Algorithm: rsa
Bit Size: 2048
Fingerprint: 419a8a0fae0285492284b8c0a99eb11c772b4b653ff20b4185a80971cac21d36
Found 1 unique certificates

APPLICATION PERMISSIONS

PERMISSION	STATUS	INFO	DESCRIPTION
android.permission.INTERNET	normal	full Internet access	Allows an application to create network sockets.
android.permission.USE_BIOMETRIC	normal	allows use of device-supported biometric modalities.	Allows an app to use device supported biometric modalities.
android.permission.POST_NOTIFICATIONS	dangerous	allows an app to post notifications.	Allows an app to post notifications
android.permission.QUERY_ALL_PACKAGES	normal	enables querying any normal app on the device.	Allows query of any normal app on the device, regardless of manifest declarations.
android.permission.FOREGROUND_SERVICE	normal	enables regular apps to use Service.startForeground.	Allows a regular application to use Service.startForeground.
android.permission.ACCESS_NETWORK_STATE	normal	view network status	Allows an application to view the status of all networks.
android.permission.RECEIVE_BOOT_COMPLETED	normal	automatically start at boot	Allows an application to start itself as soon as the system has finished booting. This can make it take longer to start the phone and allow the application to slow down the overall phone by always running.
android.permission.REQUEST_IGNORE_BATTERY_OPTIMIZATIONS	normal	permission for using Settings.ACTION_REQUEST_IGNORE_BATTERY_OPTIMIZATIONS.	Permission an application must hold in order to use Settings.ACTION_REQUEST_IGNORE_BATTERY_OPTIMIZATIONS.
android.permission.FOREGROUND_SERVICE_SPECIAL_USE	normal	enables special-use foreground services.	Allows a regular application to use Service.startForeground with the type "specialUse".
android.permission.FOREGROUND_SERVICE_DATA_SYNC	normal	permits foreground services for data synchronization.	Allows a regular application to use Service.startForeground with the type "dataSync".
android.permission.CHANGE_NETWORK_STATE	normal	change network connectivity	Allows applications to change network connectivity state.
moe.shizuku.manager.permission.API_V23	unknown	Unknown permission	Unknown permission from android reference
android.permission.WAKE_LOCK	normal	prevent phone from sleeping	Allows an application to prevent the phone from going to sleep.

PERMISSION	STATUS	INFO	DESCRIPTION
android.permission.USE_FINGERPRINT	normal	allow use of fingerprint	This constant was deprecated in API level 28. Applications should request USE_BIOMETRIC instead.
com.kin.athena.DYNAMIC_RECEIVER_NOT_EXPORTED_PERMISSION	unknown	Unknown permission	Unknown permission from android reference

APKID ANALYSIS

FILE	DETAILS
classes.dex	FINDINGS: Anti-VM Code — DETAILS: Build.FINGERPRINT check Build.MANUFACTURER check possible ro.secure check FINDINGS: Compiler — DETAILS: r8
lib/arm64-v8a/libnflog.so	FINDINGS: anti_hook — DETAILS: syscalls

NETWORK SECURITY

NO	SCOPE	SEVERITY	DESCRIPTION

CERTIFICATE ANALYSIS

HIGH: 0 | WARNING: 0 | INFO: 1

TITLE	SEVERITY	DESCRIPTION
Signed Application	info	Application is signed with a code signing certificate

MANIFEST ANALYSIS

HIGH: **1** | WARNING: **8** | INFO: **0** | SUPPRESSED: **0**

NO	ISSUE	SEVERITY	DESCRIPTION
1	App can be installed on a vulnerable unpatched Android version 7.0, [minSdk=24]	high	This application can be installed on an older version of android that has multiple unfixed vulnerabilities. These devices won't receive reasonable security updates from Google. Support an Android version => 10, API 29 to receive reasonable security updates.
2	Application Data can be Backed up [android:allowBackup=true]	warning	This flag allows anyone to backup your application data via adb. It allows users who have enabled USB debugging to copy application data off of the device.
3	Content Provider (rikka.shizuku.ShizukuProvider) is Protected by a permission, but the protection level of the permission should be checked. Permission: android.permission.INTERACT_ACROSS_USERS_FULL [android:exported=true]	warning	A Content Provider is found to be shared with other apps on the device therefore leaving it accessible to any other application on the device. It is protected by a permission which is not defined in the analysed application. As a result, the protection level of the permission should be checked where it is defined. If it is set to normal or dangerous, a malicious application can request and obtain the permission and interact with the component. If it is set to signature, only applications signed with the same certificate can obtain the permission.
4	Service (com.kin.athena.service.vpn.service.VpnConnectionClient) is Protected by a permission, but the protection level of the permission should be checked. Permission: android.permission.BIND_VPN_SERVICE [android:exported=true]	warning	A Service is found to be shared with other apps on the device therefore leaving it accessible to any other application on the device. It is protected by a permission which is not defined in the analysed application. As a result, the protection level of the permission should be checked where it is defined. If it is set to normal or dangerous, a malicious application can request and obtain the permission and interact with the component. If it is set to signature, only applications signed with the same certificate can obtain the permission.
5	Service (com.kin.athena.service.tiles.DnsQuickSettingsTile) is Protected by a permission, but the protection level of the permission should be checked. Permission: android.permission.BIND_QUICK_SETTINGS_TILE [android:exported=true]	warning	A Service is found to be shared with other apps on the device therefore leaving it accessible to any other application on the device. It is protected by a permission which is not defined in the analysed application. As a result, the protection level of the permission should be checked where it is defined. If it is set to normal or dangerous, a malicious application can request and obtain the permission and interact with the component. If it is set to signature, only applications signed with the same certificate can obtain the permission.
6	Broadcast Receiver (com.kin.athena.data.service.BootReceiver) is not Protected. [android:exported=true]	warning	A Broadcast Receiver is found to be shared with other apps on the device therefore leaving it accessible to any other application on the device.

NO	ISSUE	SEVERITY	DESCRIPTION
7	Service (androidx.work.impl.background.systemjob.SystemJobService) is Protected by a permission, but the protection level of the permission should be checked. Permission: android.permission.BIND_JOB_SERVICE [android:exported=true]	warning	A Service is found to be shared with other apps on the device therefore leaving it accessible to any other application on the device. It is protected by a permission which is not defined in the analysed application. As a result, the protection level of the permission should be checked where it is defined. If it is set to normal or dangerous, a malicious application can request and obtain the permission and interact with the component. If it is set to signature, only applications signed with the same certificate can obtain the permission.
8	Broadcast Receiver (androidx.work.impl.diagnostics.DiagnosticsReceiver) is Protected by a permission, but the protection level of the permission should be checked. Permission: android.permission.DUMP [android:exported=true]	warning	A Broadcast Receiver is found to be shared with other apps on the device therefore leaving it accessible to any other application on the device. It is protected by a permission which is not defined in the analysed application. As a result, the protection level of the permission should be checked where it is defined. If it is set to normal or dangerous, a malicious application can request and obtain the permission and interact with the component. If it is set to signature, only applications signed with the same certificate can obtain the permission.
9	Broadcast Receiver (androidx.profileinstaller.ProfileInstallReceiver) is Protected by a permission, but the protection level of the permission should be checked. Permission: android.permission.DUMP [android:exported=true]	warning	A Broadcast Receiver is found to be shared with other apps on the device therefore leaving it accessible to any other application on the device. It is protected by a permission which is not defined in the analysed application. As a result, the protection level of the permission should be checked where it is defined. If it is set to normal or dangerous, a malicious application can request and obtain the permission and interact with the component. If it is set to signature, only applications signed with the same certificate can obtain the permission.

CODE ANALYSIS

HIGH: **1** | WARNING: **6** | INFO: **2** | SECURE: **2** | SUPPRESSED: **0**

NO	ISSUE	SEVERITY	STANDARDS	FILES
				com/kin/athena/service/vpn/service/TunnelManager.java defpackage/AbstractActivityC2386u7.java defpackage/AbstractC0829bk0.java defpackage/AbstractC0905cg0.java defpackage/AbstractC0939d4.java defpackage/AbstractC1309hT.java defpackage/AbstractC2114qx.java defpackage/AbstractC2147rK.java defpackage/AbstractC2709xy.java defpackage/AbstractComponentCallbacksC0647Yx.java defpackage/C0003Ac.java defpackage/C0079Da.java defpackage/C0169Gm.java defpackage/C0343Nf.java defpackage/C0391Pb.java defpackage/C0692a70.java defpackage/C0990dg0.java defpackage/C1074eg0.java defpackage/C1159fg0.java defpackage/C1267gy.java

NO	ISSUE	SEVERITY	STANDARDS	FILES
				defpackage/C1329hg0.java defpackage/C1439j00.java defpackage/C1517jv.java
1	The App logs information. Sensitive information should never be logged.	info	CWE: CWE-532: Insertion of Sensitive Information into Log File OWASP MASVS: MSTG-STORAGE-3	defpackage/C1639lL.java defpackage/C1772mv.java defpackage/C1809nL.java defpackage/C1894oL.java defpackage/C1945oy.java defpackage/C1950p1.java defpackage/C2105qo.java defpackage/C2199ry.java defpackage/C2374u1.java defpackage/C2395uD.java defpackage/C2405uN.java defpackage/C2418ua.java defpackage/C2539vy.java defpackage/C2558w8.java defpackage/C2714y1.java defpackage/C2799z1.java defpackage/C2804z30.java defpackage/CD.java defpackage/Cd0.java defpackage/Ce0.java defpackage/DE.java defpackage/DK.java defpackage/Dd0.java defpackage/DialogInterfaceOnCancelListenerC2530vp.java defpackage/DialogInterfaceOnClickListenerC1964p8.java defpackage/Ei0.java defpackage/Gl0.java defpackage/H7.java defpackage/I3.java defpackage/I8.java defpackage/InputConnectionC1524k00.java defpackage/InputConnectionC1609l00.java defpackage/J7.java defpackage/JG.java defpackage/Ki0.java defpackage/LayoutInflaterFactory2C1097ey.java defpackage/M8.java defpackage/MenuC0795bN.java defpackage/NE.java defpackage/OR.java defpackage/Q7.java defpackage/QD.java defpackage/RE.java defpackage/RW.java defpackage/RunnableC0335Mx.java defpackage/RunnableC0848c1.java defpackage/S8.java defpackage/SE.java defpackage/SY.java defpackage/TE.java

NO	ISSUE	SEVERITY	STANDARDS	FILES
				defpackage/U7.java defpackage/UY.java defpackage/V3.java defpackage/V4.java defpackage/V8.java defpackage/VP.java defpackage/Va0.java defpackage/ViewOnKeyListenerC0602Xe.java defpackage/ViewOnLongClickListenerC2427ue0.java defpackage/WR.java defpackage/Wa0.java defpackage/Wb0.java defpackage/Wj0.java defpackage/X7.java defpackage/XP.java defpackage/Xk0.java defpackage/Yf0.java defpackage/Z7.java org/slf4j/helpers/Util.java org/xbill/DNS/tools/Tools.java org/xbill/DNS/tools/dig.java org/xbill/DNS/tools/jnamed.java org/xbill/DNS/tools/lookup.java org/xbill/DNS/tools/primary.java org/xbill/DNS/tools/update.java org/xbill/DNS/tools/xfrin.java rikka/shizuku/Shizuku.java rikka/shizuku/ShizukuProvider.java rikka/shizuku/ShizukuRemoteProcess.java rikka/shizuku/SystemServiceHelper.java
2	The App uses an insecure Random Number Generator.	warning	CWE: CWE-330: Use of Insufficiently Random Values OWASP Top 10: M5: Insufficient Cryptography OWASP MASVS: MSTG-CRYPTO-6	defpackage/AbstractC0677a0.java defpackage/C0047Bu.java defpackage/C1651lX.java defpackage/O5.java defpackage/VY.java org/xbill/DNS/Header.java
3	Files may contain hardcoded sensitive information like usernames, passwords, keys etc.	warning	CWE: CWE-312: Cleartext Storage of Sensitive Information OWASP Top 10: M9: Reverse Engineering OWASP MASVS: MSTG-STORAGE-14	defpackage/C1224gT.java defpackage/QX.java
4	This App may request root (Super User) privileges.	warning	CWE: CWE-250: Execution with Unnecessary Privileges OWASP MASVS: MSTG-RESILIENCE-1	defpackage/AbstractC1164fj.java
5	This App may have root detection capabilities.	secure	OWASP MASVS: MSTG-RESILIENCE-1	defpackage/AbstractC1164fj.java

NO	ISSUE	SEVERITY	STANDARDS	FILES
6	The App uses the encryption mode CBC with PKCS5/PKCS7 padding. This configuration is vulnerable to padding oracle attacks.	high	CWE: CWE-649: Reliance on Obfuscation or Encryption of Security-Relevant Inputs without Integrity Checking OWASP Top 10: M5: Insufficient Cryptography OWASP MASVS: MSTG-CRYPTO-3	defpackage/Xk0.java
7	This App uses SSL certificate pinning to detect or prevent MITM attacks in secure communication channel.	secure	OWASP MASVS: MSTG-NETWORK-4	defpackage/C0166Gj.java defpackage/C0211Ic.java defpackage/C1394iT.java defpackage/RW.java
8	IP Address disclosure	warning	CWE: CWE-200: Information Exposure OWASP MASVS: MSTG-CODE-2	com/kin/athena/service/vpn/network/util/NetworkConstants.java com/kin/athena/service/vpn/service/TunnelManager.java com/kin/athena/service/vpn/service/VpnConnectionServer$initializeVpnComponents$1.java defpackage/AbstractC1309hT.java defpackage/C0354Nq.java defpackage/C1508jm.java defpackage/S8.java
9	App creates temp file. Sensitive information should never be written into a temp file.	warning	CWE: CWE-276: Incorrect Default Permissions OWASP Top 10: M2: Insecure Data Storage OWASP MASVS: MSTG-STORAGE-2	com/sun/jna/Native.java
10	SHA-1 is a weak hash known to have hash collisions.	warning	CWE: CWE-327: Use of a Broken or Risky Cryptographic Algorithm OWASP Top 10: M5: Insufficient Cryptography OWASP MASVS: MSTG-CRYPTO-4	org/xbill/DNS/DNSSEC.java org/xbill/DNS/NSEC3Record.java
11	This App copies data to clipboard. Sensitive data should not be copied to clipboard as other applications can access it.	info	OWASP MASVS: MSTG-STORAGE-10	defpackage/C2039q3.java defpackage/GE.java

SHARED LIBRARY BINARY ANALYSIS

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
1	x86_64/libdatastore_shared_counter.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.
2	x86_64/libandroidx.graphics.path.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
3	x86_64/libathena.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['__write_chk', '__vsnprintf_chk', '__vsprintf_chk', '__strlen_chk', '__memcpy_chk']	True info Symbols are stripped.
4	x86/libdatastore_shared_counter.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
5	x86/libandroidx.graphics.path.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.
6	x86/libathena.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['__write_chk', '__vsnprintf_chk', '__vsprintf_chk', '__strlen_chk', '__memcpy_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
7	arm64-v8a/libdatastore_shared_counter.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.
8	arm64-v8a/libandroidx.graphics.path.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
9	arm64-v8a/libathena.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['__write_chk', '__vsnprintf_chk', '__vsprintf_chk', '__strlen_chk', '__memcpy_chk']	True info Symbols are stripped.
10	arm64-v8a/libnflog.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Position Independent Executable (PIE) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	False high This binary does not have a stack canary value added to the stack. Stack canaries are used to detect and prevent exploits from overwriting return address. Use the option -fstack-protector-all to enable stack canaries. Not applicable for Dart/Flutter libraries unless Dart FFI is used.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
11	armeabi-v7a/libdatastore_shared_counter.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.
12	armeabi-v7a/libandroidx.graphics.path.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
13	armeabi-v7a/libathena.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['__write_chk', '__vsnprintf_chk', '__vsprintf_chk', '__strlen_chk', '__memcpy_chk']	True info Symbols are stripped.
14	armeabi-v7a/libnflog.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Position Independent Executable (PIE) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	False high This binary does not have a stack canary value added to the stack. Stack canaries are used to detect and prevent exploits from overwriting return address. Use the option -fstack-protector-all to enable stack canaries. Not applicable for Dart/Flutter libraries unless Dart FFI is used.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
15	x86_64/libdatastore_shared_counter.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.
16	x86_64/libandroidx.graphics.path.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
17	x86_64/libathena.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['__write_chk', '__vsnprintf_chk', '__vsprintf_chk', '__strlen_chk', '__memcpy_chk']	True info Symbols are stripped.
18	x86/libdatastore_shared_counter.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
19	x86/libandroidx.graphics.path.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.
20	x86/libathena.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['__write_chk', '__vsnprintf_chk', '__vsprintf_chk', '__strlen_chk', '__memcpy_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
21	arm64-v8a/libdatastore_shared_counter.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.
22	arm64-v8a/libandroidx.graphics.path.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
23	arm64-v8a/libathena.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['__write_chk', '__vsnprintf_chk', '__vsprintf_chk', '__strlen_chk', '__memcpy_chk']	True info Symbols are stripped.
24	arm64-v8a/libnflog.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Position Independent Executable (PIE) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	False high This binary does not have a stack canary value added to the stack. Stack canaries are used to detect and prevent exploits from overwriting return address. Use the option -fstack-protector-all to enable stack canaries. Not applicable for Dart/Flutter libraries unless Dart FFI is used.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
25	armeabi-v7a/libdatastore_shared_counter.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.
26	armeabi-v7a/libandroidx.graphics.path.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
27	armeabi-v7a/libathena.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['__write_chk', '__vsnprintf_chk', '__vsprintf_chk', '__strlen_chk', '__memcpy_chk']	True info Symbols are stripped.
28	armeabi-v7a/libnflog.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Position Independent Executable (PIE) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	False high This binary does not have a stack canary value added to the stack. Stack canaries are used to detect and prevent exploits from overwriting return address. Use the option -fstack-protector-all to enable stack canaries. Not applicable for Dart/Flutter libraries unless Dart FFI is used.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NIAP ANALYSIS v1.3

NO	IDENTIFIER	REQUIREMENT	FEATURE	DESCRIPTION

BEHAVIOUR ANALYSIS

RULE ID	BEHAVIOUR	LABEL	FILES
00022	Open a file from given absolute path of the file	file	com/sun/jna/Native.java defpackage/AbstractC1309hT.java defpackage/C0592Wu.java defpackage/C0917cn.java defpackage/C2146rJ.java defpackage/C2617wr.java defpackage/C2796z.java defpackage/NP.java defpackage/S8.java defpackage/SX.java
00063	Implicit intent(view a web page, make a phone call, etc.)	control	defpackage/AbstractC1309hT.java defpackage/C0521Ub.java defpackage/C2371u.java defpackage/C2620wu.java defpackage/T5.java defpackage/XP.java rikka/shizuku/ShizukuProvider.java
00114	Create a secure socket connection to the proxy address	network command	defpackage/ZZ.java
00013	Read file and put it into a stream	file	defpackage/AbstractC0939d4.java defpackage/AbstractC1309hT.java defpackage/C0462Ru.java defpackage/C0488Su.java defpackage/C0521Ub.java defpackage/C0990dg0.java defpackage/C1074eg0.java defpackage/C1842nj.java defpackage/C1851np.java defpackage/C2006pg.java defpackage/C2395uD.java defpackage/C2579wR.java defpackage/C2853zf.java defpackage/C2861zj.java defpackage/JG.java defpackage/TE.java defpackage/UY.java defpackage/WY.java defpackage/ZX.java defpackage/cm0.java org/xbill/DNS/Tokenizer.java org/xbill/DNS/dnssec/ValidatingResolver.java org/xbill/DNS/tools/jnamed.java org/xbill/DNS/tools/update.java

RULE ID	BEHAVIOUR	LABEL	FILES
00162	Create InetSocketAddress object and connecting to it	socket	defpackage/C1618l5.java defpackage/RW.java org/xbill/DNS/NioTcpClient.java org/xbill/DNS/NioUdpClient.java org/xbill/DNS/ZoneTransferIn.java
00163	Create new Socket and connecting to it	socket	defpackage/C1618l5.java defpackage/RW.java org/xbill/DNS/NioTcpClient.java org/xbill/DNS/NioUdpClient.java org/xbill/DNS/TCPClient.java org/xbill/DNS/ZoneTransferIn.java
00125	Check if the given file path exist	file	defpackage/C0521Ub.java defpackage/S8.java
00094	Connect to a URL and read data from it	command network	defpackage/C0521Ub.java
00036	Get resource file from res/raw directory	reflection	defpackage/AbstractC1309hT.java defpackage/C0521Ub.java rikka/shizuku/ShizukuProvider.java
00091	Retrieve data from broadcast	collection	defpackage/C2008ph.java defpackage/NE.java
00012	Read data and put it into a buffer stream	file	org/xbill/DNS/Tokenizer.java
00047	Query the local IP address	network collection	org/xbill/DNS/tools/jnamed.java
00147	Get the time of current location	collection location	defpackage/Q7.java
00075	Get location of the device	collection location	defpackage/Q7.java
00115	Get last known location of the device	collection location	defpackage/Q7.java
00108	Read the input stream from given URL	network command	org/xbill/DNS/DohResolver.java
00051	Implicit intent(view a web page, make a phone call, etc.) via setData	control	defpackage/AbstractC1309hT.java
00079	Hide the current app's icon	evasion	defpackage/AbstractC1733mU.java

ABUSED PERMISSIONS

TYPE	MATCHES	PERMISSIONS
Malware Permissions	4/25	android.permission.INTERNET, android.permission.ACCESS_NETWORK_STATE, android.permission.RECEIVE_BOOT_COMPLETED, android.permission.WAKE_LOCK
Other Common Permissions	3/44	android.permission.FOREGROUND_SERVICE, android.permission.REQUEST_IGNORE_BATTERY_OPTIMIZATIONS, android.permission.CHANGE_NETWORK_STATE

Malware Permissions:
Top permissions that are widely abused by known malware.

Other Common Permissions:
Permissions that are commonly abused by known malware.

OFAC SANCTIONED COUNTRIES

This app may communicate with the following OFAC sanctioned list of countries.

DOMAIN	COUNTRY/REGION

DOMAIN MALWARE CHECK

DOMAIN	STATUS	GEOLOCATION
www.slf4j.org	ok	**IP:** 159.100.250.151 **Country:** Switzerland **Region:** Vaud **City:** Lausanne **Latitude:** 46.515999 **Longitude:** 6.632820 **View:** Google Map
schemas.android.com	ok	No Geolocation information available.

DOMAIN	STATUS	GEOLOCATION
pgl.yoyo.org	ok	**IP:** 82.165.93.184 **Country:** Germany **Region:** Nordrhein-Westfalen **City:** Strang **Latitude:** 51.968700 **Longitude:** 8.753360 **View:** Google Map
discord.gg	ok	**IP:** 162.159.133.234 **Country:** United States of America **Region:** California **City:** San Francisco **Latitude:** 37.775700 **Longitude:** -122.395203 **View:** Google Map
hosted.weblate.org	ok	**IP:** 116.203.108.97 **Country:** Germany **Region:** Bayern **City:** Gunzenhausen **Latitude:** 48.323330 **Longitude:** 11.601220 **View:** Google Map
someonewhocares.org	ok	**IP:** 172.67.68.72 **Country:** United States of America **Region:** California **City:** San Francisco **Latitude:** 37.775700 **Longitude:** -122.395203 **View:** Google Map
blokada.org	ok	**IP:** 104.21.26.94 **Country:** United States of America **Region:** California **City:** San Francisco **Latitude:** 37.775700 **Longitude:** -122.395203 **View:** Google Map

DOMAIN	STATUS	GEOLOCATION
adaway.org	ok	**IP:** 185.199.108.153 **Country:** United States of America **Region:** Pennsylvania **City:** California **Latitude:** 40.065632 **Longitude:** -79.891708 **View:** Google Map
goo.gle	ok	**IP:** 67.199.248.12 **Country:** United States of America **Region:** New York **City:** New York City **Latitude:** 40.739288 **Longitude:** -73.984955 **View:** Google Map
raw.githubusercontent.com	ok	**IP:** 185.199.108.133 **Country:** United States of America **Region:** Pennsylvania **City:** California **Latitude:** 40.065632 **Longitude:** -79.891708 **View:** Google Map
hostfiles.frogeye.fr	ok	**IP:** 45.142.233.210 **Country:** Netherlands **Region:** Noord-Brabant **City:** Eindhoven **Latitude:** 51.440830 **Longitude:** 5.477780 **View:** Google Map
www.instagram.com	ok	**IP:** 57.144.38.34 **Country:** United States of America **Region:** California **City:** Palo Alto **Latitude:** 37.441879 **Longitude:** -122.143021 **View:** Google Map

DOMAIN	STATUS	GEOLOCATION
developer.android.com	ok	**IP:** 172.217.22.78 **Country:** United States of America **Region:** California **City:** Mountain View **Latitude:** 37.405991 **Longitude:** -122.078514 **View:** Google Map
github.com	ok	**IP:** 140.82.121.4 **Country:** United States of America **Region:** California **City:** San Francisco **Latitude:** 37.775700 **Longitude:** -122.395203 **View:** Google Map
easylist.to	ok	**IP:** 104.21.60.31 **Country:** United States of America **Region:** California **City:** San Francisco **Latitude:** 37.775700 **Longitude:** -122.395203 **View:** Google Map
ko-fi.com	ok	**IP:** 172.66.144.201 **Country:** United States of America **Region:** California **City:** San Francisco **Latitude:** 37.775700 **Longitude:** -122.395203 **View:** Google Map
issuetracker.google.com	ok	**IP:** 216.58.205.46 **Country:** United States of America **Region:** California **City:** Mountain View **Latitude:** 37.405991 **Longitude:** -122.078514 **View:** Google Map

DOMAIN	STATUS	GEOLOCATION
small.oisd.nl	ok	**IP:** 57.128.255.167 **Country:** United States of America **Region:** California **City:** Palo Alto **Latitude:** 37.441879 **Longitude:** -122.143021 **View:** Google Map
youtrack.jetbrains.com	ok	**IP:** 63.33.88.220 **Country:** Ireland **Region:** Dublin **City:** Dublin **Latitude:** 53.343990 **Longitude:** -6.267190 **View:** Google Map
www.gnu.org	ok	**IP:** 209.51.188.116 **Country:** United States of America **Region:** Massachusetts **City:** Boston **Latitude:** 42.358429 **Longitude:** -71.059769 **View:** Google Map
play.google.com	ok	**IP:** 172.217.22.110 **Country:** United States of America **Region:** California **City:** Mountain View **Latitude:** 37.405991 **Longitude:** -122.078514 **View:** Google Map
admin.easyapps.me	ok	**IP:** 104.21.12.156 **Country:** United States of America **Region:** California **City:** San Francisco **Latitude:** 37.775700 **Longitude:** -122.395203 **View:** Google Map

DOMAIN	STATUS	GEOLOCATION
example.com	ok	**IP:** 172.66.147.243 **Country:** United States of America **Region:** California **City:** San Francisco **Latitude:** 37.775700 **Longitude:** -122.395203 **View:** Google Map

EMAILS

EMAIL	FILE
support@easyapps.me	defpackage/C1947p.java

HARDCODED SECRETS

POSSIBLE SECRETS
B3312FA7E23EE7E4988E056BE3F82D19181D9C6EFE8141120314088F5013875AC656398D8A2ED19D2A85C8EDD3EC2AEF
cc31e80112e9fc88694cdd193c8087a7
1cbd3130fa23b59692c061c594c16cc0
8D91E471E0989CDA27DF505A453F2B7635294F2DDF23E3B122ACC99C9E9F1E14
5AC635D8AA3A93E7B3EBBD55769886BC651D06B0CC53B0F63BCE3C3E27D2604B
FFFFFFFF00000000FFFFFFFFFFFFFFFFBCE6FAADA7179E84F3B9CAC2FC632551
628704bf1c86130eff49ad991c1b4dc9006700112e5ebe692da3da43f074d8fd
9dcd51dc30ccb970fa9b012e11aa9a92
3dac74ea57cbf9d5dd10ac2f443036afd38581588dd4dafa02d230bddb4250dd

POSSIBLE SECRETS
a-95ed6082-b8e9-46e8-a73f-ff56f00f5d9d
3617DE4A96262C6F5D9E98BF9292DC29F8F41DBD289A147CE9DA3113B5F0B8C00A60B1CE1D7E819D7A431D7C90EA0E5F
6B17D1F2E12C4247F8BCE6E563A440F277037D812DEB33A0F4A13945D898C296
f8388448de6d3eb4831a60aa4194a0524cbb443fe5806090c1a403565f49a06b
4FE342E2FE1A7F9B8EE7EB4A7C0F9E162BCE33576B315ECECBB6406837BF51F5
AA87CA22BE8B05378EB1C71EF320AD746E1D3B628BA79B9859F741E082542A385502F25DBF55296C3A545E3872760AB7
86254750241babac4b8d52996a675549

PLAYSTORE INFORMATION

Title: Athena: Firewall DNS AdBlocker

Score: 2.9384615 **Installs:** 100,000+ **Price:** 0 **Android Version Support:** **Category:** Tools **Play Store URL:** com.kin.athena

Developer Details: Easy Apps (FOSS), Easy+Apps+(FOSS), None, https://easyapps.me, contact@easyapps.me,

Release Date: Jul 27, 2025 **Privacy Policy:** Privacy link

Description:

Athena Firewall combines powerful DNS-based ad blocking with complete network control. Block ads, trackers, and unwanted connections across all apps. Works with Root, Shizuku, or VPN mode - choose what fits your device. ✓ DNS ad & tracker blocking ✓ Custom & pre-made blocklists ✓ Per-app firewall rules ✓ Root, Shizuku & VPN modes ✓ Network monitor & kill switch ✓ Material 3 design DNS AD BLOCKING & FILTERING Stop ads and trackers before they load with powerful DNS filtering. Block ads in apps, games, and browsers system-wide. - DNS-based ad & tracker blocking - Pre-made blocklists (AdGuard, Steven Black, more) - Custom blocklists - add your own URLs - Auto-update blocklists daily - Custom DNS servers (Cloudflare, Quad9, AdGuard DNS, custom) - Block specific domains manually - Allow/block by IP address - DNS request logging - See every DNS query in real-time FIREWALL - THREE POWERFUL MODES Choose the mode that works for YOUR device: ROOT MODE (Rooted devices) - Direct iptables firewall control - Most powerful option - System-level blocking - Maximum control SHIZUKU MODE (No root needed) - Advanced features without rooting - Enhanced firewall capabilities - Works with Shizuku app - Power user features VPN MODE (Any device) - Works on stock Android - Local VPN only (no external servers) - No root or Shizuku needed - Privacy-focused PER-APP NETWORK CONTROL Control exactly which apps can access the internet. Block apps individually or by category. - Block apps from WiFi or mobile data - Separate rules for WiFi/data - Whitelist or blacklist mode - System app control - Show offline apps - Track install source - Real-time connection monitoring - Connection logs per app - See app permissions Perfect for stopping background data usage, preventing tracking, and saving battery. ADVANCED MONITORING Watch your network activity in real-time with comprehensive logging and monitoring. - Status bar network monitor - Real-time connection logs - DNS query logs - Per-app connection history - See which domains apps contact - Export logs for analysis - Live traffic statistics - Bandwidth usage tracking NETWORK SECURITY FEATURES - Kill switch - block all traffic when firewall stops - Allow local network IPs (for printers, smart home) - Block specific IP addresses - Screen protection bypass - VPN slot functions - Auto-start on boot - Background protection MODERN MATERIAL 3 DESIGN - Material You dynamic colors - AMOLED dark theme (true black) - Clean, intuitive interface - Smooth animations - Tablet optimized - Multi-language support CUSTOM DNS CONTROL Take full control of your DNS for privacy and speed. - Custom DNS servers (DoH coming soon) - Popular DNS providers built-in: - Custom DNS IPs - DNS leak protection - Encrypted DNS queries (roadmap) - Change DNS per network PRIVACY & OPEN SOURCE - 100% open-source (GPL) - No data collection - No analytics or tracking - No ads anywhere - Community-driven POWER USER FEATURES - Import/export blocklists - Backup/restore settings - Root OR non-root operation - Shizuku integration - Detailed logging - Custom filtering rules - Advanced DNS options - Developer options ⚡ LIGHTWEIGHT & EFFICIENT - Minimal battery drain - Low memory footprint - Runs efficiently in background - Optimized for performance - No bloat - focused features PERFECT FOR: - Blocking ads in apps & games - Stopping trackers & analytics - Reducing mobile data usage - Privacy-conscious users - Parents controlling kid's devices - Developers & security researchers - Users who want DNS control - Anyone wanting network visibility - Rooted AND non-rooted devices USE CASES Stop App Tracking: Block analytics and trackers in all apps Save Mobile Data: Block ads = less data used Parent Controls: Block inappropriate domains Gaming: Block ads in free games Privacy:Stop apps phoning home Security Research: Monitor all connections Custom Blocking: Block specific domains/IPs

SCAN LOGS

Timestamp	Event	Error
2026-05-02 09:20:07	Generating Hashes	OK
2026-05-02 09:20:07	Extracting APK	OK
2026-05-02 09:20:07	Unzipping	OK
2026-05-02 09:20:08	Parsing APK with androguard	OK
2026-05-02 09:20:09	Extracting APK features using aapt/aapt2	OK
2026-05-02 09:20:09	Getting Hardcoded Certificates/Keystores	OK
2026-05-02 09:20:22	Parsing AndroidManifest.xml	OK
2026-05-02 09:20:22	Extracting Manifest Data	OK
2026-05-02 09:20:22	Manifest Analysis Started	OK
2026-05-02 09:20:22	Performing Static Analysis on: Athena (com.kin.athena)	OK
2026-05-02 09:20:34	Fetching Details from Play Store: com.kin.athena	OK
2026-05-02 09:20:39	Checking for Malware Permissions	OK

2026-05-02 09:20:39	Fetching icon path	OK
2026-05-02 09:20:39	Library Binary Analysis Started	OK
2026-05-02 09:20:39	Analyzing lib/x86_64/libdatastore_shared_counter.so	OK
2026-05-02 09:20:39	Analyzing lib/x86_64/libandroidx.graphics.path.so	OK
2026-05-02 09:20:39	Analyzing lib/x86_64/libathena.so	OK
2026-05-02 09:20:39	Analyzing lib/x86/libdatastore_shared_counter.so	OK
2026-05-02 09:20:39	Analyzing lib/x86/libandroidx.graphics.path.so	OK
2026-05-02 09:20:39	Analyzing lib/x86/libathena.so	OK
2026-05-02 09:20:39	Analyzing lib/arm64-v8a/libdatastore_shared_counter.so	OK
2026-05-02 09:20:39	Analyzing lib/arm64-v8a/libandroidx.graphics.path.so	OK
2026-05-02 09:20:39	Analyzing lib/arm64-v8a/libathena.so	OK
2026-05-02 09:20:39	Analyzing lib/arm64-v8a/libnflog.so	OK
2026-05-02 09:20:39	Analyzing lib/armeabi-v7a/libdatastore_shared_counter.so	OK
2026-05-02 09:20:39	Analyzing lib/armeabi-v7a/libandroidx.graphics.path.so	OK

2026-05-02 09:20:39	Analyzing lib/armeabi-v7a/libathena.so	OK
2026-05-02 09:20:39	Analyzing lib/armeabi-v7a/libnflog.so	OK
2026-05-02 09:20:39	Analyzing apktool_out/lib/x86_64/libdatastore_shared_counter.so	OK
2026-05-02 09:20:39	Analyzing apktool_out/lib/x86_64/libandroidx.graphics.path.so	OK
2026-05-02 09:20:39	Analyzing apktool_out/lib/x86_64/libathena.so	OK
2026-05-02 09:20:39	Analyzing apktool_out/lib/x86/libdatastore_shared_counter.so	OK
2026-05-02 09:20:39	Analyzing apktool_out/lib/x86/libandroidx.graphics.path.so	OK
2026-05-02 09:20:39	Analyzing apktool_out/lib/x86/libathena.so	OK
2026-05-02 09:20:39	Analyzing apktool_out/lib/arm64-v8a/libdatastore_shared_counter.so	OK
2026-05-02 09:20:39	Analyzing apktool_out/lib/arm64-v8a/libandroidx.graphics.path.so	OK
2026-05-02 09:20:39	Analyzing apktool_out/lib/arm64-v8a/libathena.so	OK
2026-05-02 09:20:40	Analyzing apktool_out/lib/arm64-v8a/libnflog.so	OK
2026-05-02 09:20:40	Analyzing apktool_out/lib/armeabi-v7a/libdatastore_shared_counter.so	OK
2026-05-02 09:20:40	Analyzing apktool_out/lib/armeabi-v7a/libandroidx.graphics.path.so	OK

2026-05-02 09:20:40	Analyzing apktool_out/lib/armeabi-v7a/libathena.so	OK
2026-05-02 09:20:40	Analyzing apktool_out/lib/armeabi-v7a/libnflog.so	OK
2026-05-02 09:20:40	Reading Code Signing Certificate	OK
2026-05-02 09:20:42	Running APKiD 3.0.0	OK
2026-05-02 09:21:01	Detecting Trackers	OK
2026-05-02 09:21:06	Decompiling APK to Java with JADX	OK
2026-05-02 09:23:06	Converting DEX to Smali	OK
2026-05-02 09:23:06	Code Analysis Started on - java_source	OK
2026-05-02 09:23:17	Android SBOM Analysis Completed	OK
2026-05-02 09:24:09	Android SAST Completed	OK
2026-05-02 09:24:09	Android API Analysis Started	OK
2026-05-02 09:24:24	Android API Analysis Completed	OK
2026-05-02 09:24:25	Android Permission Mapping Started	OK
2026-05-02 09:24:34	Android Permission Mapping Completed	OK

2026-05-02 09:24:34	Android Behaviour Analysis Started	OK
2026-05-02 09:24:51	Android Behaviour Analysis Completed	OK
2026-05-02 09:24:51	Extracting Emails and URLs from Source Code	OK
2026-05-02 09:24:57	Email and URL Extraction Completed	OK
2026-05-02 09:24:57	Extracting String data from APK	OK
2026-05-02 09:24:58	Extracting String data from SO	OK
2026-05-02 09:24:58	Extracting String data from Code	OK
2026-05-02 09:24:58	Extracting String values and entropies from Code	OK
2026-05-02 09:25:00	Performing Malware check on extracted domains	OK
2026-05-02 09:25:20	Saving to Database	OK

Report Generated by - MobSF v4.5.0

Mobile Security Framework (MobSF) is an automated, all-in-one mobile application (Android/iOS/Windows) pen-testing, malware analysis and security assessment framework capable of performing static and dynamic analysis.

© 2026 Mobile Security Framework - MobSF | Ajin Abraham | OpenSecurity.

MOBSF

ANDROID STATIC ANALYSIS REPORT

app_icon

Booming Music (1.2.2)

File Name: com.mardous.booming_1220300.apk

Package Name:	com.mardous.booming
Scan Date:	May 2, 2026, 9:27 a.m.
App Security Score:	51/100 (MEDIUM RISK)
Grade:	B

FINDINGS SEVERITY

HIGH	MEDIUM	INFO	SECURE	HOTSPOT
2	19	2	2	1

FILE INFORMATION

File Name: com.mardous.booming_1220300.apk
Size: 21.54MB
MD5: 7bbb158b62edbc38988e730e23df44b3
SHA1: 90b92a7967e2b3373342fb71d3f6e0b0caaab86f
SHA256: 2cea56eb53c3080ada852b9ec5064e15d2e6ad37695c0c543bca8ddf60fc7e52

APP INFORMATION

App Name: Booming Music
Package Name: com.mardous.booming
Main Activity:
Target SDK: 36
Min SDK: 28
Max SDK:
Android Version Name: 1.2.2
Android Version Code: 1220300

APP COMPONENTS

Activities: 9
Services: 8
Receivers: 14
Providers: 4
Exported Activities: 2
Exported Services: 3

Exported Receivers: 3
Exported Providers: 1

CERTIFICATE INFORMATION

Binary is signed
v1 signature: False
v2 signature: True
v3 signature: False
v4 signature: False
X.509 Subject: CN=Christians Martínez Alvarado, L=Punto Fijo, ST=Falcón, C=58
Signature Algorithm: rsassa_pkcs1v15
Valid From: 2022-09-09 23:11:42+00:00
Valid To: 2047-09-03 23:11:42+00:00
Issuer: CN=Christians Martínez Alvarado, L=Punto Fijo, ST=Falcón, C=58
Serial Number: 0x1
Hash Algorithm: sha1
md5: 096d8c8c411dca23806c1c6d67a373f0
sha1: 1c5b5c6ee7d971467c586c054eae68cb9d85e786
sha256: 971e4ea01b40120df023d00e72111325dcd802def7a1e5e5dbdd192f3c60d7d7
sha512: 4f2322147baad7e180e43e0cf13024e6329b39680b2e1209a6ba41d8e82461726f3459db4c6ccafb2fb57faee261f62e5faf569071230240aaad60d768959aeb
PublicKey Algorithm: rsa
Bit Size: 2048
Fingerprint: 3e5ff307891f76211336cb4630427ae3c926c82c8b030c3230c8dc44e5e05bd4
Found 1 unique certificates

APPLICATION PERMISSIONS

PERMISSION	STATUS	INFO	DESCRIPTION
android.permission.BLUETOOTH	normal	create Bluetooth connections	Allows applications to connect to paired bluetooth devices.
android.permission.BLUETOOTH_CONNECT	dangerous	necessary for connecting to paired Bluetooth devices.	Required to be able to connect to paired Bluetooth devices.

PERMISSION	STATUS	INFO	DESCRIPTION
android.permission.POST_NOTIFICATIONS	dangerous	allows an app to post notifications.	Allows an app to post notifications
android.permission.READ_MEDIA_IMAGES	dangerous	allows reading image files from external storage.	Allows an application to read image files from external storage.
android.permission.READ_MEDIA_AUDIO	dangerous	allows reading audio files from external storage.	Allows an application to read audio files from external storage.
android.permission.READ_EXTERNAL_STORAGE	dangerous	read external storage contents	Allows an application to read from external storage.
android.permission.WRITE_EXTERNAL_STORAGE	dangerous	read/modify/delete external storage contents	Allows an application to write to external storage.
android.permission.WRITE_SETTINGS	dangerous	modify global system settings	Allows an application to modify the system's settings data. Malicious applications can corrupt your system's configuration.
android.permission.SCHEDULE_EXACT_ALARM	normal	permits exact alarm scheduling for background work.	Allows an app to use exact alarm scheduling APIs to perform timing sensitive background work.
android.permission.FOREGROUND_SERVICE	normal	enables regular apps to use Service.startForeground.	Allows a regular application to use Service.startForeground.
android.permission.FOREGROUND_SERVICE_MEDIA_PLAYBACK	normal	enables foreground services for media playback.	Allows a regular application to use Service.startForeground with the type "mediaPlayback".
android.permission.ACCESS_NETWORK_STATE	normal	view network status	Allows an application to view the status of all networks.
android.permission.INTERNET	normal	full Internet access	Allows an application to create network sockets.

PERMISSION	STATUS	INFO	DESCRIPTION
android.permission.WAKE_LOCK	normal	prevent phone from sleeping	Allows an application to prevent the phone from going to sleep.
android.permission.VIBRATE	normal	control vibrator	Allows the application to control the vibrator.
android.permission.RECEIVE_BOOT_COMPLETED	normal	automatically start at boot	Allows an application to start itself as soon as the system has finished booting. This can make it take longer to start the phone and allow the application to slow down the overall phone by always running.
com.mardous.booming.DYNAMIC_RECEIVER_NOT_EXPORTED_PERMISSION	unknown	Unknown permission	Unknown permission from android reference

APKID ANALYSIS

FILE	DETAILS
classes.dex	<table><tr><th>FINDINGS</th><th>DETAILS</th></tr><tr><td>yara_issue</td><td>yara issue - dex file recognized by apkid but not yara module</td></tr><tr><td>Anti-VM Code</td><td>Build.FINGERPRINT check Build.MANUFACTURER check</td></tr><tr><td>Compiler</td><td>unknown (please file detection issue!)</td></tr></table>

FILE	DETAILS
classes2.dex	<table><tr><th>FINDINGS</th><th>DETAILS</th></tr><tr><td>yara_issue</td><td>yara issue - dex file recognized by apkid but not yara module</td></tr><tr><td>Compiler</td><td>unknown (please file detection issue!)</td></tr></table>

BROWSABLE ACTIVITIES

ACTIVITY	INTENT
com.mardous.booming.activities.MainActivity	Schemes: content://, file://, http://, Mime Types: audio/*, application/ogg, application/x-ogg, application/itunes, vnd.android.cursor.dir/playlist, vnd.android.cursor.dir/albums, vnd.android.cursor.dir/artists, vnd.android.cursor.dir/audio,

NETWORK SECURITY

NO	SCOPE	SEVERITY	DESCRIPTION

CERTIFICATE ANALYSIS

HIGH: 1 | WARNING: 0 | INFO: 1

TITLE	SEVERITY	DESCRIPTION
Signed Application	info	Application is signed with a code signing certificate

TITLE	SEVERITY	DESCRIPTION
Certificate algorithm vulnerable to hash collision	high	Application is signed with SHA1withRSA. SHA1 hash algorithm is known to have collision issues.

MANIFEST ANALYSIS

HIGH: **0** | WARNING: **12** | INFO: **0** | SUPPRESSED: **0**

NO	ISSUE	SEVERITY	DESCRIPTION
1	App can be installed on a vulnerable Android version 9, minSdk=28]	warning	This application can be installed on an older version of android that has multiple vulnerabilities. Support an Android version => 10, API 29 to receive reasonable security updates.
2	Application Data can be Backed up [android:allowBackup=true]	warning	This flag allows anyone to backup your application data via adb. It allows users who have enabled USB debugging to copy application data off of the device.
3	Activity-Alias (com.mardous.booming.activities.MainActivity) is not Protected. [android:exported=true]	warning	An Activity-Alias is found to be shared with other apps on the device therefore leaving it accessible to any other application on the device.
4	Activity (com.mardous.booming.ui.screen.error.ErrorActivity) is not Protected. [android:exported=true]	warning	An Activity is found to be shared with other apps on the device therefore leaving it accessible to any other application on the device.
5	Service (com.mardous.booming.playback.PlaybackService) is not Protected. [android:exported=true]	warning	A Service is found to be shared with other apps on the device therefore leaving it accessible to any other application on the device.
6	Broadcast Receiver (androidx.media3.session.MediaButtonReceiver) is not Protected. [android:exported=true]	warning	A Broadcast Receiver is found to be shared with other apps on the device therefore leaving it accessible to any other application on the device.
7	Content Provider (com.mardous.booming.coil.CoverProvider) is not Protected. [android:exported=true]	warning	A Content Provider is found to be shared with other apps on the device therefore leaving it accessible to any other application on the device.
8	TaskAffinity is set for activity (androidx.glance.appwidget.action.InvisibleActionTrampolineActivity)	warning	If taskAffinity is set, then other application could read the Intents sent to Activities belonging to another task. Always use the default setting keeping the affinity as the package name in order to prevent sensitive information inside sent or received Intents from being read by another application.

NO	ISSUE	SEVERITY	DESCRIPTION
9	Service (androidx.glance.appwidget.GlanceRemoteViewsService) is Protected by a permission, but the protection level of the permission should be checked. Permission: android.permission.BIND_REMOTEVIEWS [android:exported=true]	warning	A Service is found to be shared with other apps on the device therefore leaving it accessible to any other application on the device. It is protected by a permission which is not defined in the analysed application. As a result, the protection level of the permission should be checked where it is defined. If it is set to normal or dangerous, a malicious application can request and obtain the permission and interact with the component. If it is set to signature, only applications signed with the same certificate can obtain the permission.
10	Service (androidx.work.impl.background.systemjob.SystemJobService) is Protected by a permission, but the protection level of the permission should be checked. Permission: android.permission.BIND_JOB_SERVICE [android:exported=true]	warning	A Service is found to be shared with other apps on the device therefore leaving it accessible to any other application on the device. It is protected by a permission which is not defined in the analysed application. As a result, the protection level of the permission should be checked where it is defined. If it is set to normal or dangerous, a malicious application can request and obtain the permission and interact with the component. If it is set to signature, only applications signed with the same certificate can obtain the permission.
11	Broadcast Receiver (androidx.work.impl.diagnostics.DiagnosticsReceiver) is Protected by a permission, but the protection level of the permission should be checked. Permission: android.permission.DUMP [android:exported=true]	warning	A Broadcast Receiver is found to be shared with other apps on the device therefore leaving it accessible to any other application on the device. It is protected by a permission which is not defined in the analysed application. As a result, the protection level of the permission should be checked where it is defined. If it is set to normal or dangerous, a malicious application can request and obtain the permission and interact with the component. If it is set to signature, only applications signed with the same certificate can obtain the permission.
12	Broadcast Receiver (androidx.profileinstaller.ProfileInstallReceiver) is Protected by a permission, but the protection level of the permission should be checked. Permission: android.permission.DUMP [android:exported=true]	warning	A Broadcast Receiver is found to be shared with other apps on the device therefore leaving it accessible to any other application on the device. It is protected by a permission which is not defined in the analysed application. As a result, the protection level of the permission should be checked where it is defined. If it is set to normal or dangerous, a malicious application can request and obtain the permission and interact with the component. If it is set to signature, only applications signed with the same certificate can obtain the permission.

CODE ANALYSIS

HIGH: **1** | WARNING: **6** | INFO: **2** | SECURE: **1** | SUPPRESSED: **0**

NO	ISSUE	SEVERITY	STANDARDS	FILES
1	Files may contain hardcoded sensitive information like usernames, passwords, keys etc.	warning	CWE: CWE-312: Cleartext Storage of Sensitive Information OWASP Top 10: M9: Reverse Engineering OWASP MASVS: MSTG-STORAGE-14	com/mardous/booming/data/remote/lastfm/model/LastFmSession.java defpackage/cg2.java defpackage/ct0.java defpackage/d64.java defpackage/gp1.java defpackage/k14.java defpackage/l76.java defpackage/pp3.java defpackage/q74.java defpackage/s46.java defpackage/sb3.java defpackage/sp5.java defpackage/tj4.java defpackage/vl0.java defpackage/we3.java defpackage/wh1.java org/jaudiotagger/tag/id3/ID3v22Frames.java org/jaudiotagger/tag/id3/ID3v23Frames.java org/jaudiotagger/tag/id3/ID3v24Frames.java
				cat/ereza/customactivityoncrash/provider/CaocInitProvider.java com/mardous/booming/coil/CoverProvider.java com/mardous/booming/coil/b.java com/mardous/booming/coil/c.java com/mardous/booming/coil/fetcher/b.java com/mardous/booming/data/local/AlbumCoverSaver$saveArtwork$2.java com/mardous/booming/data/local/MetadataWriter$write$2.java com/mardous/booming/data/local/repository/a.java com/mardous/booming/data/local/repository/b.java com/mardous/booming/data/local/repository/i.java com/mardous/booming/data/model/Playlist.java com/mardous/booming/data/remote/lyrics/a.java com/mardous/booming/playback/PersistentStorage$restoreState$1.java com/mardous/booming/playback/PersistentStorage$saveState$1.java com/mardous/booming/playback/PlaybackService$u

NO	ISSUE	SEVERITY	STANDARDS	FILES
				pdateGlanceWidgets$2.java com/mardous/booming/playback/equalizer/EqualizerManager$initializeEqualizer$2.java com/mardous/booming/playback/equalizer/a.java com/mardous/booming/playback/shuffle/a.java com/mardous/booming/ui/dialogs/songs/DeleteSongsDialog$onDeleteSongs$1.java com/mardous/booming/ui/screen/equalizer/EqualizerViewModel$requestAutoEqImport$1.java com/mardous/booming/ui/screen/library/LibraryViewModel$handleIntent$1.java com/mardous/booming/ui/screen/player/PlayerViewModel$generatePlayerScheme$1.java com/mardous/booming/ui/screen/settings/PreferenceScreenFragment$clearImageLoaderCache$1.java com/mikepenz/aboutlibraries/ui/compose/android/Extensions_androidKt$produceLibraries$3$1.java defpackage/a34.java defpackage/a43.java defpackage/ab1.java defpackage/ad2.java defpackage/am4.java defpackage/aq5.java defpackage/ax.java defpackage/ax4.java defpackage/b43.java defpackage/b7.java defpackage/be1.java defpackage/bs4.java defpackage/bv2.java defpackage/ca0.java defpackage/cj5.java defpackage/cl3.java defpackage/cm6.java defpackage/cp0.java defpackage/cs4.java defpackage/cy3.java defpackage/d24.java defpackage/d76.java defpackage/ds4.java defpackage/e0.java defpackage/e02.java defpackage/e62.java defpackage/e9.java defpackage/ea.java

NO	ISSUE	SEVERITY	STANDARDS	FILES
				defpackage/ee1.java defpackage/ek0.java defpackage/el.java defpackage/ew1.java defpackage/ex.java defpackage/f96.java defpackage/fg6.java defpackage/fu5.java defpackage/g34.java defpackage/g45.java defpackage/g52.java defpackage/ge1.java defpackage/gi4.java defpackage/gk4.java defpackage/gl.java defpackage/gl3.java defpackage/gy3.java defpackage/h40.java defpackage/h46.java defpackage/h86.java defpackage/h96.java defpackage/he3.java defpackage/hi3.java defpackage/hp0.java defpackage/hr.java defpackage/hv0.java defpackage/hy4.java defpackage/i11.java defpackage/i72.java defpackage/i96.java defpackage/ie4.java defpackage/im.java defpackage/iz3.java defpackage/j11.java defpackage/j65.java defpackage/j96.java defpackage/jc.java defpackage/k52.java defpackage/kc.java defpackage/km3.java defpackage/kx.java defpackage/l4.java defpackage/l53.java defpackage/li6.java defpackage/lk3.java
2	The App logs information. Sensitive information should never be logged.	info	CWE: CWE-532: Insertion of Sensitive Information into Log File OWASP MASVS: MSTG-STORAGE-3	

NO	ISSUE	SEVERITY	STANDARDS	FILES
				defpackage/lm3.java defpackage/lp0.java defpackage/ls.java defpackage/m02.java defpackage/m11.java defpackage/m7.java defpackage/ml.java defpackage/n20.java defpackage/nb.java defpackage/nc4.java defpackage/nd3.java defpackage/no1.java defpackage/o05.java defpackage/op1.java defpackage/or3.java defpackage/pb2.java defpackage/pk3.java defpackage/pl.java defpackage/pl1.java defpackage/pp0.java defpackage/pz5.java defpackage/q36.java defpackage/q61.java defpackage/ql1.java defpackage/qz1.java defpackage/r04.java defpackage/r15.java defpackage/re.java defpackage/re4.java defpackage/rh2.java defpackage/rk.java defpackage/rk3.java defpackage/rq3.java defpackage/rv1.java defpackage/sg3.java defpackage/sk3.java defpackage/sk4.java defpackage/st5.java defpackage/sw0.java defpackage/sz1.java defpackage/t02.java defpackage/td.java defpackage/td0.java defpackage/tk6.java defpackage/tl.java

NO	ISSUE	SEVERITY	STANDARDS	FILES
				defpackage/tu3.java defpackage/tu4.java defpackage/u.java defpackage/u52.java defpackage/uc.java defpackage/uk3.java defpackage/ul1.java defpackage/ut.java defpackage/v61.java defpackage/v73.java defpackage/va1.java defpackage/vf.java defpackage/vp3.java defpackage/vt3.java defpackage/vz1.java defpackage/vz5.java defpackage/w6.java defpackage/w73.java defpackage/wl3.java defpackage/wl6.java defpackage/wm5.java defpackage/wu4.java defpackage/xo0.java defpackage/xv0.java defpackage/xw1.java defpackage/y.java defpackage/y3.java defpackage/y83.java defpackage/yr3.java defpackage/yt0.java defpackage/za5.java defpackage/zs4.java defpackage/zu4.java defpackage/zx5.java io/noties/markwon/core/spans/LinkSpan.java org/jaudiotagger/audio/mp4/Flatten.java org/jaudiotagger/audio/ogg/OggFileReader.java org/jaudiotagger/audio/opus/OpusFileReader.java org/jaudiotagger/audio/wav/WavCleaner.java org/jaudiotagger/tag/images/StandardImageHandler.java org/jaudiotagger/test/ExtractID3TagFromFile.java org/jaudiotagger/test/MergeID3AndMP3Files.java org/jaudiotagger/test/TestAudioTagger.java org/jaudiotagger/utils/FileTypeUtil.java

NO	ISSUE	SEVERITY	STANDARDS	FILES
3	App uses SQLite Database and execute raw SQL query. Untrusted user input in raw SQL queries can cause SQL Injection. Also sensitive information should be encrypted and written to the database.	warning	CWE: CWE-89: Improper Neutralization of Special Elements used in an SQL Command ('SQL Injection') OWASP Top 10: M7: Client Code Quality	defpackage/f12.java defpackage/ky4.java defpackage/qt5.java
4	App can read/write to External Storage. Any App can read data written to External Storage.	warning	CWE: CWE-276: Incorrect Default Permissions OWASP Top 10: M2: Insecure Data Storage OWASP MASVS: MSTG-STORAGE-2	com/mardous/booming/data/local/AlbumCoverSaver$saveArtwork$2.java com/mardous/booming/data/local/repository/i.java com/mardous/booming/ui/dialogs/library/FolderChooserDialog.java com/mardous/booming/util/m3u/a.java defpackage/g0.java defpackage/sk4.java
5	This App copies data to clipboard. Sensitive data should not be copied to clipboard as other applications can access it.	info	OWASP MASVS: MSTG-STORAGE-10	defpackage/ac.java defpackage/c0.java defpackage/g0.java defpackage/yj4.java
6	The App uses an insecure Random Number Generator.	warning	CWE: CWE-330: Use of Insufficiently Random Values OWASP Top 10: M5: Insufficient Cryptography OWASP MASVS: MSTG-CRYPTO-6	com/mardous/booming/playback/shuffle/a.java defpackage/ef4.java defpackage/fg.java defpackage/g3.java defpackage/la5.java defpackage/rp1.java defpackage/uh.java defpackage/v01.java
7	App creates temp file. Sensitive information should never be written into a temp file.	warning	CWE: CWE-276: Incorrect Default Permissions OWASP Top 10: M2: Insecure Data Storage OWASP MASVS: MSTG-STORAGE-2	org/jaudiotagger/audio/generic/AudioFileWriter.java org/jaudiotagger/tag/id3/AbstractID3v2Tag.java
8	The App uses the encryption mode CBC with PKCS5/PKCS7 padding. This configuration is vulnerable to padding oracle attacks.	high	CWE: CWE-649: Reliance on Obfuscation or Encryption of Security-Relevant Inputs without Integrity Checking OWASP Top 10: M5: Insufficient Cryptography OWASP MASVS: MSTG-CRYPTO-3	com/mardous/booming/data/local/repository/a.java

NO	ISSUE	SEVERITY	STANDARDS	FILES
9	This App uses SSL certificate pinning to detect or prevent MITM attacks in secure communication channel.	secure	OWASP MASVS: MSTG-NETWORK-4	defpackage/t44.java
10	MD5 is a weak hash known to have hash collisions.	warning	CWE: CWE-327: Use of a Broken or Risky Cryptographic Algorithm OWASP Top 10: M5: Insufficient Cryptography OWASP MASVS: MSTG-CRYPTO-4	com/mardous/booming/data/remote/lastfm/a.java

SHARED LIBRARY BINARY ANALYSIS

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
1	x86_64/libtaglib.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['__readlink_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
2	x86_64/libandroidx.graphics.path.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
3	x86/libtaglib.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['__readlink_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
4	x86/libandroidx.graphics.path.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
5	arm64-v8a/libtaglib.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['__readlink_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
6	arm64-v8a/libandroidx.graphics.path.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
7	armeabi-v7a/libtaglib.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['__vsnprintf_chk', '__readlink_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
8	armeabi-v7a/libandroidx.graphics.path.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
9	x86_64/libtaglib.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['__readlink_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
10	x86_64/libandroidx.graphics.path.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
11	x86/libtaglib.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['__readlink_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
12	x86/libandroidx.graphics.path.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
13	arm64-v8a/libtaglib.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['__readlink_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
14	arm64-v8a/libandroidx.graphics.path.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
15	armeabi-v7a/libtaglib.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['__vsnprintf_chk', '__readlink_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
16	armeabi-v7a/libandroidx.graphics.path.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NIAP ANALYSIS v1.3

NO	IDENTIFIER	REQUIREMENT	FEATURE	DESCRIPTION

BEHAVIOUR ANALYSIS

RULE ID	BEHAVIOUR	LABEL	FILES
00022	Open a file from given absolute path of the file	file	com/mardous/booming/data/local/AlbumCoverSaver$saveArtwork$2.java com/mardous/booming/ui/dialogs/library/FolderChooserDialog.java com/mardous/booming/ui/screen/lyrics/LyricsViewModel$importCustomFont$1.java com/mardous/booming/util/a.java defpackage/g.java defpackage/g0.java defpackage/km3.java defpackage/pw2.java defpackage/v05.java defpackage/wm5.java defpackage/yq1.java org/jaudiotagger/audio/AudioFile.java org/jaudiotagger/audio/AudioFileIO.java org/jaudiotagger/audio/asf/AsfFileReader.java org/jaudiotagger/audio/flac/FlacInfoReader.java org/jaudiotagger/audio/generic/AudioFileReader.java org/jaudiotagger/audio/generic/AudioFileReader2.java org/jaudiotagger/audio/generic/AudioFileWriter.java org/jaudiotagger/audio/generic/AudioFileWriter2.java org/jaudiotagger/audio/generic/Utils.java org/jaudiotagger/audio/mp3/MP3File.java org/jaudiotagger/audio/wav/WavCleaner.java org/jaudiotagger/tag/id3/AbstractID3v2Tag.java
00063	Implicit intent(view a web page, make a phone call, etc.)	control	com/mardous/booming/ui/screen/permissions/PermissionsActivity.java defpackage/dj5.java defpackage/ig.java defpackage/rh2.java defpackage/sr0.java defpackage/ul3.java defpackage/v6.java defpackage/w6.java defpackage/y.java io/noties/markwon/core/spans/LinkSpan.java
00177	Check if permission is granted and request it	permission	defpackage/lm3.java
00104	Check if the given path is directory	file	com/mardous/booming/ui/dialogs/library/FolderChooserDialog.java defpackage/lm3.java

RULE ID	BEHAVIOUR	LABEL	FILES
00096	Connect to a URL and set request method	command network	defpackage/kz0.java
00089	Connect to a URL and receive input stream from the server	command network	defpackage/kz0.java
00030	Connect to the remote server through the given URL	network	defpackage/kz0.java
00109	Connect to a URL and get the response code	network command	defpackage/kz0.java
00094	Connect to a URL and read data from it	command network	defpackage/kz0.java
00108	Read the input stream from given URL	network command	defpackage/kz0.java
00051	Implicit intent(view a web page, make a phone call, etc.) via setData	control	com/mardous/booming/ui/screen/permissions/PermissionsActivity.java defpackage/dj5.java defpackage/v6.java defpackage/w6.java

RULE ID	BEHAVIOUR	LABEL	FILES
00013	Read file and put it into a stream	file	com/mardous/booming/coil/fetcher/b.java com/mardous/booming/data/local/repository/b.java com/mardous/booming/util/BackupHelper$zipAll$2.java defpackage/ad2.java defpackage/an2.java defpackage/ay2.java defpackage/bv2.java defpackage/d24.java defpackage/fy2.java defpackage/hq4.java defpackage/jq0.java defpackage/l61.java defpackage/om4.java defpackage/q65.java defpackage/sw0.java defpackage/ul1.java defpackage/wk4.java defpackage/xr2.java org/jaudiotagger/audio/asf/AsfFileReader.java org/jaudiotagger/audio/asf/io/AsfHeaderReader.java org/jaudiotagger/audio/generic/AudioFileWriter.java org/jaudiotagger/audio/generic/Utils.java org/jaudiotagger/audio/mp3/MP3AudioHeader.java org/jaudiotagger/audio/mp3/MP3File.java org/jaudiotagger/audio/mp4/Flatten.java org/jaudiotagger/tag/id3/AbstractID3v2Tag.java org/jaudiotagger/test/MergeID3AndMP3Files.java org/jaudiotagger/utils/FileTypeUtil.java org/jcodec/containers/mp4/MP4Util.java
00012	Read data and put it into a buffer stream	file	com/mardous/booming/data/local/repository/b.java com/mardous/booming/util/BackupHelper$zipAll$2.java defpackage/ul1.java org/jaudiotagger/audio/asf/AsfFileReader.java org/jaudiotagger/audio/asf/io/AsfHeaderReader.java org/jaudiotagger/test/MergeID3AndMP3Files.java

RULE ID	BEHAVIOUR	LABEL	FILES
00036	Get resource file from res/raw directory	reflection	defpackage/eq.java defpackage/gi3.java defpackage/hq4.java defpackage/v6.java io/noties/markwon/core/spans/LinkSpan.java
00028	Read file from assets directory	file	defpackage/bq.java
00187	Query a URI and check the result	collection sms calllog calendar	defpackage/g52.java defpackage/gr4.java
00077	Read sensitive data(SMS, CALLLOG, etc)	collection sms calllog calendar	defpackage/g52.java defpackage/rh2.java
00121	Create a directory	file command	defpackage/km3.java
00189	Get the content of a SMS message	sms	defpackage/gr4.java
00188	Get the address of a SMS message	sms	defpackage/gr4.java
00200	Query data from the contact list	collection contact	defpackage/gr4.java
00201	Query data from the call log	collection calllog	defpackage/gr4.java
00011	Query data from URI (SMS, CALLLOGS)	sms calllog collection	defpackage/rh2.java
00091	Retrieve data from broadcast	collection	defpackage/gy3.java defpackage/nj0.java
00114	Create a secure socket connection to the proxy address	network command	defpackage/mn0.java
00162	Create InetSocketAddress object and connecting to it	socket	defpackage/ie4.java defpackage/re.java

RULE ID	BEHAVIOUR	LABEL	FILES
00163	Create new Socket and connecting to it	socket	defpackage/ie4.java defpackage/re.java
00191	Get messages in the SMS inbox	sms	defpackage/ub.java
00147	Get the time of current location	collection location	defpackage/ml.java
00075	Get location of the device	collection location	defpackage/ml.java
00115	Get last known location of the device	collection location	defpackage/ml.java
00052	Deletes media specified by a content URI(SMS, CALL_LOG, File, etc.)	sms	com/mardous/booming/data/local/MetadataWriter$write$2.java
00079	Hide the current app's icon	evasion	defpackage/l94.java
00132	Query The ISO country code	telephony collection	defpackage/hi3.java

ABUSED PERMISSIONS

TYPE	MATCHES	PERMISSIONS
Malware Permissions	8/25	android.permission.READ_EXTERNAL_STORAGE, android.permission.WRITE_EXTERNAL_STORAGE, android.permission.WRITE_SETTINGS, android.permission.ACCESS_NETWORK_STATE, android.permission.INTERNET, android.permission.WAKE_LOCK, android.permission.VIBRATE, android.permission.RECEIVE_BOOT_COMPLETED
Other Common Permissions	2/44	android.permission.BLUETOOTH, android.permission.FOREGROUND_SERVICE

Malware Permissions:

Top permissions that are widely abused by known malware.

Other Common Permissions:

Permissions that are commonly abused by known malware.

❗ OFAC SANCTIONED COUNTRIES

This app may communicate with the following OFAC sanctioned list of countries.

DOMAIN	COUNTRY/REGION

🔍 DOMAIN MALWARE CHECK

DOMAIN	STATUS	GEOLOCATION
www.slf4j.org	ok	**IP:** 159.100.250.151 **Country:** Switzerland **Region:** Vaud **City:** Lausanne **Latitude:** 46.515999 **Longitude:** 6.632820 **View:** Google Map
schemas.android.com	ok	No Geolocation information available.
hosted.weblate.org	ok	**IP:** 116.203.108.97 **Country:** Germany **Region:** Bayern **City:** Gunzenhausen **Latitude:** 48.323330 **Longitude:** 11.601220 **View:** Google Map

DOMAIN	STATUS	GEOLOCATION
www.last.fm	ok	**IP:** 146.75.89.188 **Country:** Sweden **Region:** Vastra Gotalands lan **City:** Goeteborg **Latitude:** 57.707161 **Longitude:** 11.966790 **View:** Google Map
www.w3.org	ok	**IP:** 104.18.23.19 **Country:** United States of America **Region:** California **City:** San Francisco **Latitude:** 37.775700 **Longitude:** -122.395203 **View:** Google Map
wwww.last.fm	ok	No Geolocation information available.
www.id3.org	ok	**IP:** 206.189.160.222 **Country:** United States of America **Region:** California **City:** Santa Clara **Latitude:** 37.354111 **Longitude:** -121.955238 **View:** Google Map
google.com	ok	**IP:** 142.251.39.206 **Country:** United States of America **Region:** California **City:** Mountain View **Latitude:** 37.405991 **Longitude:** -122.078514 **View:** Google Map

DOMAIN	STATUS	GEOLOCATION
goo.gle	ok	**IP:** 67.199.248.12 **Country:** United States of America **Region:** New York **City:** New York City **Latitude:** 40.739288 **Longitude:** -73.984955 **View:** Google Map
schemas.microsoft.com	ok	**IP:** 150.171.109.2 **Country:** United States of America **Region:** Washington **City:** Redmond **Latitude:** 47.682899 **Longitude:** -122.120903 **View:** Google Map
s.wikipedia.org	ok	No Geolocation information available.
www.youtube.com	ok	**IP:** 142.251.216.110 **Country:** United States of America **Region:** California **City:** Mountain View **Latitude:** 37.405991 **Longitude:** -122.078514 **View:** Google Map
www.github.com	ok	**IP:** 140.82.121.3 **Country:** United States of America **Region:** California **City:** San Francisco **Latitude:** 37.775700 **Longitude:** -122.395203 **View:** Google Map

DOMAIN	STATUS	GEOLOCATION
t.me	ok	**IP:** 149.154.167.99 **Country:** United Kingdom of Great Britain and Northern Ireland **Region:** England **City:** Lowestoft **Latitude:** 52.475201 **Longitude:** 1.751590 **View:** Google Map
g.co	ok	**IP:** 216.58.223.238 **Country:** United States of America **Region:** California **City:** Mountain View **Latitude:** 37.405991 **Longitude:** -122.078514 **View:** Google Map
www.wikipedia.org	ok	**IP:** 185.15.58.224 **Country:** Netherlands **Region:** Noord-Holland **City:** Amsterdam **Latitude:** 52.374031 **Longitude:** 4.889690 **View:** Google Map
aomedia.org	ok	**IP:** 185.199.110.153 **Country:** United States of America **Region:** Pennsylvania **City:** California **Latitude:** 40.065632 **Longitude:** -79.891708 **View:** Google Map

DOMAIN	STATUS	GEOLOCATION
lrclib.net	ok	**IP:** 65.21.226.122 **Country:** Germany **Region:** Bayern **City:** Gunzenhausen **Latitude:** 48.323330 **Longitude:** 11.601220 **View:** Google Map
developer.android.com	ok	**IP:** 142.251.216.46 **Country:** United States of America **Region:** California **City:** Mountain View **Latitude:** 37.405991 **Longitude:** -122.078514 **View:** Google Map
github.com	ok	**IP:** 140.82.121.3 **Country:** United States of America **Region:** California **City:** San Francisco **Latitude:** 37.775700 **Longitude:** -122.395203 **View:** Google Map
lyrics-api.boidu.dev	ok	No Geolocation information available.
ws.audioscrobbler.com	ok	**IP:** 130.211.19.189 **Country:** United States of America **Region:** Missouri **City:** Kansas City **Latitude:** 39.099731 **Longitude:** -94.578568 **View:** Google Map

DOMAIN	STATUS	GEOLOCATION
ko-fi.com	ok	**IP:** 104.20.38.66 **Country:** United States of America **Region:** California **City:** San Francisco **Latitude:** 37.775700 **Longitude:** -122.395203 **View:** Google Map
developer.apple.com	ok	**IP:** 17.253.65.133 **Country:** United States of America **Region:** New York **City:** New York City **Latitude:** 40.714272 **Longitude:** -74.005966 **View:** Google Map
issuetracker.google.com	ok	**IP:** 192.178.25.110 **Country:** United States of America **Region:** California **City:** Mountain View **Latitude:** 37.405991 **Longitude:** -122.078514 **View:** Google Map
ns.adobe.com	ok	No Geolocation information available.
api.github.com	ok	**IP:** 140.82.121.6 **Country:** United States of America **Region:** California **City:** San Francisco **Latitude:** 37.775700 **Longitude:** -122.395203 **View:** Google Map

DOMAIN	STATUS	GEOLOCATION
musicbrainz.org	ok	**IP:** 142.132.241.153 **Country:** Canada **Region:** Manitoba **City:** Winnipeg **Latitude:** 49.889748 **Longitude:** -97.153961 **View:** Google Map
default.url	ok	No Geolocation information available.
api-lyrics.simpmusic.org	ok	**IP:** 104.21.15.252 **Country:** United States of America **Region:** California **City:** San Francisco **Latitude:** 37.775700 **Longitude:** -122.395203 **View:** Google Map
api.deezer.com	ok	**IP:** 23.1.228.159 **Country:** India **Region:** Telangana **City:** Hyderabad **Latitude:** 17.375280 **Longitude:** 78.474442 **View:** Google Map
www.google.com	ok	**IP:** 142.251.153.119 **Country:** United States of America **Region:** California **City:** Mountain View **Latitude:** 37.405991 **Longitude:** -122.078514 **View:** Google Map

DOMAIN	STATUS	GEOLOCATION
ktor.io	ok	**IP:** 108.139.200.67 **Country:** United States of America **Region:** Washington **City:** Seattle **Latitude:** 47.606209 **Longitude:** -122.332069 **View:** Google Map

EMAILS

EMAIL	FILE
mardous.contact@gmail.com	defpackage/dj5.java

HARDCODED SECRETS

POSSIBLE SECRETS
"lastfm_login_username" : "□□□"
"lastfm_login_password" : "Password"
"lastfm_login_password" : "Contraseña"
"lastfm_login_username" : "Username"
"lastfm_login_password" : "□□"
"lastfm_login_password" : "Şifre"

POSSIBLE SECRETS
c103703e120ae8cc73c9248622f3cd1e
34e4b07b6366c5bb55ebda8b423314fa
49f946663a8deb7054212b8adda248c6
da436f23fb933ba952f6f697a08189e4

SCAN LOGS

Timestamp	Event	Error
2026-05-02 09:27:52	Generating Hashes	OK
2026-05-02 09:27:52	Extracting APK	OK
2026-05-02 09:27:52	Unzipping	OK
2026-05-02 09:27:53	Parsing APK with androguard	OK
2026-05-02 09:27:55	Extracting APK features using aapt/aapt2	OK
2026-05-02 09:27:56	Getting Hardcoded Certificates/Keystores	OK

2026-05-02 09:28:06	Parsing AndroidManifest.xml	OK
2026-05-02 09:28:06	Extracting Manifest Data	OK
2026-05-02 09:28:06	Manifest Analysis Started	OK
2026-05-02 09:28:06	Performing Static Analysis on: Booming Music (com.mardous.booming)	OK
2026-05-02 09:28:09	Fetching Details from Play Store: com.mardous.booming	OK
2026-05-02 09:28:12	Checking for Malware Permissions	OK
2026-05-02 09:28:12	Fetching icon path	OK
2026-05-02 09:28:12	Library Binary Analysis Started	OK
2026-05-02 09:28:12	Analyzing lib/x86_64/libtaglib.so	OK
2026-05-02 09:28:12	Analyzing lib/x86_64/libandroidx.graphics.path.so	OK
2026-05-02 09:28:12	Analyzing lib/x86/libtaglib.so	OK
2026-05-02 09:28:13	Analyzing lib/x86/libandroidx.graphics.path.so	OK

2026-05-02 09:28:13	Analyzing lib/arm64-v8a/libtaglib.so	OK
2026-05-02 09:28:13	Analyzing lib/arm64-v8a/libandroidx.graphics.path.so	OK
2026-05-02 09:28:13	Analyzing lib/armeabi-v7a/libtaglib.so	OK
2026-05-02 09:28:13	Analyzing lib/armeabi-v7a/libandroidx.graphics.path.so	OK
2026-05-02 09:28:13	Analyzing apktool_out/lib/x86_64/libtaglib.so	OK
2026-05-02 09:28:13	Analyzing apktool_out/lib/x86_64/libandroidx.graphics.path.so	OK
2026-05-02 09:28:13	Analyzing apktool_out/lib/x86/libtaglib.so	OK
2026-05-02 09:28:13	Analyzing apktool_out/lib/x86/libandroidx.graphics.path.so	OK
2026-05-02 09:28:13	Analyzing apktool_out/lib/arm64-v8a/libtaglib.so	OK
2026-05-02 09:28:13	Analyzing apktool_out/lib/arm64-v8a/libandroidx.graphics.path.so	OK
2026-05-02 09:28:13	Analyzing apktool_out/lib/armeabi-v7a/libtaglib.so	OK
2026-05-02 09:28:13	Analyzing apktool_out/lib/armeabi-v7a/libandroidx.graphics.path.so	OK

2026-05-02 09:28:13	Reading Code Signing Certificate	OK
2026-05-02 09:28:15	Running APKiD 3.0.0	OK
2026-05-02 09:28:25	Detecting Trackers	OK
2026-05-02 09:28:33	Decompiling APK to Java with JADX	OK
2026-05-02 09:31:04	Converting DEX to Smali	OK
2026-05-02 09:31:04	Code Analysis Started on - java_source	OK
2026-05-02 09:31:17	Android SBOM Analysis Completed	OK
2026-05-02 09:32:03	Android SAST Completed	OK
2026-05-02 09:32:03	Android API Analysis Started	OK
2026-05-02 09:32:26	Android API Analysis Completed	OK
2026-05-02 09:32:26	Android Permission Mapping Started	OK
2026-05-02 09:32:57	Android Permission Mapping Completed	OK

2026-05-02 09:32:58	Android Behaviour Analysis Started	OK
2026-05-02 09:33:39	Android Behaviour Analysis Completed	OK
2026-05-02 09:33:39	Extracting Emails and URLs from Source Code	OK
2026-05-02 09:33:50	Email and URL Extraction Completed	OK
2026-05-02 09:33:50	Extracting String data from APK	OK
2026-05-02 09:33:52	Extracting String data from SO	OK
2026-05-02 09:33:52	Extracting String data from Code	OK
2026-05-02 09:33:52	Extracting String values and entropies from Code	OK
2026-05-02 09:33:56	Performing Malware check on extracted domains	OK
2026-05-02 09:34:33	Saving to Database	OK

Report Generated by - MobSF v4.5.0

Mobile Security Framework (MobSF) is an automated, all-in-one mobile application (Android/iOS/Windows) pen-testing, malware analysis and security assessment framework capable of performing static and dynamic analysis.

© 2026 Mobile Security Framework - MobSF | Ajin Abraham | OpenSecurity.

MOBSF

ANDROID STATIC ANALYSIS REPORT

Money Manager Ex (5.5.5)

File Name:	com.money.manager.ex_1110.apk
Package Name:	com.money.manager.ex
Scan Date:	May 2, 2026, 9:35 a.m.
App Security Score:	49/100 (MEDIUM RISK)
Grade:	B
Trackers Detection:	1/432

FINDINGS SEVERITY

HIGH	MEDIUM	INFO	SECURE	HOTSPOT
2	34	2	1	1

FILE INFORMATION

File Name: com.money.manager.ex_1110.apk
Size: 49.76MB
MD5: 29bbade9794bdf7bf16eee6751c9901b
SHA1: 0f8f5902497db27996bfde211aa5ae16e36a1d91
SHA256: 062b7af53b8ce3143cf4318b1ef9baa2de0208ef9eba69648d9a9656a60ef192

APP INFORMATION

App Name: Money Manager Ex
Package Name: com.money.manager.ex
Main Activity: com.money.manager.ex.home.MainActivity
Target SDK: 36
Min SDK: 29
Max SDK:
Android Version Name: 5.5.5

Android Version Code: 1110

APP COMPONENTS

Activities: 45
Services: 8
Receivers: 18
Providers: 5
Exported Activities: 13
Exported Services: 2
Exported Receivers: 9
Exported Providers: 1

CERTIFICATE INFORMATION

Binary is signed
v1 signature: False
v2 signature: False
v3 signature: True
v4 signature: False
X.509 Subject: C=UK, ST=ORG, L=ORG, O=fdroid.org, OU=FDroid, CN=FDroid
Signature Algorithm: rsassa_pkcs1v15
Valid From: 2019-02-20 11:38:03+00:00
Valid To: 2046-07-08 11:38:03+00:00
Issuer: C=UK, ST=ORG, L=ORG, O=fdroid.org, OU=FDroid, CN=FDroid
Serial Number: 0x66d4a071
Hash Algorithm: sha256
md5: a4ad5ec0d0270855faea143a9a6c0349
sha1: b3a71bead7019ab0c13b5cb7dbd4916ca32105e3
sha256: 5070f673f6a62b6634b0b953b0e2821578efc2f17d05bbf3ebe7bb8b24b15a61
sha512: bb4786611c4edadcd7ff4ef0759ebec209a1a187fa2fa5cfadb714d30b48c6d3fd44f2dcbeff9b2221b4977606907b1a535da0db9e2c95dfff712a37fd499dd8
PublicKey Algorithm: rsa
Bit Size: 2048
Fingerprint: f2e3a64f4730934e526a35c2c0ad4a69a1a062331ac7b0297abba413b6e51f03
Found 1 unique certificates

APPLICATION PERMISSIONS

PERMISSION	STATUS	INFO	DESCRIPTION
android.permission.RECEIVE_SMS	dangerous	receive SMS	Allows application to receive and process SMS messages. Malicious applications may monitor your messages or delete them without showing them to you.
android.permission.INTERNET	normal	full Internet access	Allows an application to create network sockets.
android.permission.ACCESS_NETWORK_STATE	normal	view network status	Allows an application to view the status of all networks.
android.permission.VIBRATE	normal	control vibrator	Allows the application to control the vibrator.
android.permission.RECEIVE_BOOT_COMPLETED	normal	automatically start at boot	Allows an application to start itself as soon as the system has finished booting. This can make it take longer to start the phone and allow the application to slow down the overall phone by always running.
android.permission.USE_BIOMETRIC	normal	allows use of device-supported biometric modalities.	Allows an app to use device supported biometric modalities.
android.permission.WAKE_LOCK	normal	prevent phone from sleeping	Allows an application to prevent the phone from going to sleep.
android.permission.POST_NOTIFICATIONS	dangerous	allows an app to post notifications.	Allows an app to post notifications

PERMISSION	STATUS	INFO	DESCRIPTION
android.permission.FOREGROUND_SERVICE_DATA_SYNC	normal	permits foreground services for data synchronization.	Allows a regular application to use Service.startForeground with the type "dataSync".
android.permission.FOREGROUND_SERVICE	normal	enables regular apps to use Service.startForeground.	Allows a regular application to use Service.startForeground.
android.permission.USE_FINGERPRINT	normal	allow use of fingerprint	This constant was deprecated in API level 28. Applications should request USE_BIOMETRIC instead.
com.money.manager.ex.DYNAMIC_RECEIVER_NOT_EXPORTED_PERMISSION	unknown	Unknown permission	Unknown permission from android reference

APKID ANALYSIS

FILE	DETAILS

FILE	DETAILS
classes.dex	<table><tr><th>FINDINGS</th><th>DETAILS</th></tr><tr><td>yara_issue</td><td>yara issue - dex file recognized by apkid but not yara module</td></tr><tr><td>Anti-VM Code</td><td>Build.FINGERPRINT check Build.MANUFACTURER check network operator name check device ID check</td></tr><tr><td>Compiler</td><td>unknown (please file detection issue!)</td></tr></table>
classes2.dex	<table><tr><th>FINDINGS</th><th>DETAILS</th></tr><tr><td>yara_issue</td><td>yara issue - dex file recognized by apkid but not yara module</td></tr><tr><td>Anti-VM Code</td><td>Build.MANUFACTURER check</td></tr><tr><td>Compiler</td><td>unknown (please file detection issue!)</td></tr></table>
classes3.dex	<table><tr><th>FINDINGS</th><th>DETAILS</th></tr><tr><td>yara_issue</td><td>yara issue - dex file recognized by apkid but not yara module</td></tr><tr><td>Compiler</td><td>unknown (please file detection issue!)</td></tr></table>

BROWSABLE ACTIVITIES

ACTIVITY	INTENT
com.money.manager.ex.home.MainActivity	Schemes: file://, Hosts: *, Mime Types: */*, Path Patterns: .*\\.mmb, .*\\..*\\.mmb, .*\\..*\\..*\\.mmb, .*\\..*\\..*\\..*\\.mmb, .*\\..*\\..*\\..*\\..*\\.mmb, .*\\..*\\..*\\..*\\..*\\..*\\.mmb, .*\\..*\\..*\\..*\\..*\\..*\\..*\\.mmb, .*\\..*\\..*\\..*\\..*\\..*\\..*\\..*\\.mmb, .*\\..*\\..*\\..*\\..*\\..*\\..*\\..*\\..*\\.mmb, .*\\..*\\..*\\..*\\..*\\..*\\..*\\..*\\..*\\..*\\.mmb, .*\\.emb, .*\\..*\\.emb, .*\\..*\\..*\\.emb, .*\\..*\\..*\\..*\\.emb, .*\\..*\\..*\\..*\\..*\\.emb, .*\\..*\\..*\\..*\\..*\\..*\\..*\\.emb, .*\\..*\\..*\\..*\\..*\\..*\\..*\\..*\\.emb, .*\\..*\\..*\\..*\\..*\\..*\\..*\\..*\\..*\\.emb, .*\\..*\\..*\\..*\\..*\\..*\\..*\\..*\\..*\\..*\\.emb,
com.money.manager.ex.settings.SyncPreferencesActivity	Schemes: com.money.manager.ex://,

NETWORK SECURITY

NO	SCOPE	SEVERITY	DESCRIPTION

CERTIFICATE ANALYSIS

HIGH: 0 | WARNING: 0 | INFO: 1

TITLE	SEVERITY	DESCRIPTION
Signed Application	info	Application is signed with a code signing certificate

MANIFEST ANALYSIS

HIGH: **0** | WARNING: **26** | INFO: **0** | SUPPRESSED: **0**

NO	ISSUE	SEVERITY	DESCRIPTION
1	Application Data can be Backed up [android:allowBackup=true]	warning	This flag allows anyone to backup your application data via adb. It allows users who have enabled USB debugging to copy application data off of the device.
2	Broadcast Receiver (com.money.manager.ex.notifications.SmsReceiverTransactions) is Protected by a permission, but the protection level of the permission should be checked. Permission: android.permission.BROADCAST_SMS [android:exported=true]	warning	A Broadcast Receiver is found to be shared with other apps on the device therefore leaving it accessible to any other application on the device. It is protected by a permission which is not defined in the analysed application. As a result, the protection level of the permission should be checked where it is defined. If it is set to normal or dangerous, a malicious application can request and obtain the permission and interact with the component. If it is set to signature, only applications signed with the same certificate can obtain the permission.
3	Broadcast Receiver (com.money.manager.ex.widget.ButtonAddTransactionWidgetProvider) is not Protected. [android:exported=true]	warning	A Broadcast Receiver is found to be shared with other apps on the device therefore leaving it accessible to any other application on the device.
4	Broadcast Receiver (com.money.manager.ex.widget.SummaryWidgetProvider) is not Protected. [android:exported=true]	warning	A Broadcast Receiver is found to be shared with other apps on the device therefore leaving it accessible to any other application on the device.
5	Broadcast Receiver (com.money.manager.ex.widget.AccountBillsWidgetProvider) is not Protected. [android:exported=true]	warning	A Broadcast Receiver is found to be shared with other apps on the device therefore leaving it accessible to any other application on the device.
6	Broadcast Receiver (com.money.manager.ex.sync.SyncSchedulerBroadcastReceiver) is not Protected. [android:exported=true]	warning	A Broadcast Receiver is found to be shared with other apps on the device therefore leaving it accessible to any other application on the device.

NO	ISSUE	SEVERITY	DESCRIPTION
7	Broadcast Receiver (com.money.manager.ex.core.RecurringTransactionBootReceiver) is not Protected. [android:exported=true]	warning	A Broadcast Receiver is found to be shared with other apps on the device therefore leaving it accessible to any other application on the device.
8	Broadcast Receiver (com.money.manager.ex.widget.SingleAccountWidget) is not Protected. [android:exported=true]	warning	A Broadcast Receiver is found to be shared with other apps on the device therefore leaving it accessible to any other application on the device.
9	Activity (com.money.manager.ex.transactions.CheckingTransactionEditActivity) is not Protected. [android:exported=true]	warning	An Activity is found to be shared with other apps on the device therefore leaving it accessible to any other application on the device.
10	Activity (com.money.manager.ex.payee.PayeeActivity) is not Protected. [android:exported=true]	warning	An Activity is found to be shared with other apps on the device therefore leaving it accessible to any other application on the device.
11	Activity (com.money.manager.ex.tag.TagActivity) is not Protected. [android:exported=true]	warning	An Activity is found to be shared with other apps on the device therefore leaving it accessible to any other application on the device.
12	Activity (com.money.manager.ex.account.AccountListActivity) is not Protected. [android:exported=true]	warning	An Activity is found to be shared with other apps on the device therefore leaving it accessible to any other application on the device.
13	Activity (com.money.manager.ex.common.CategoryListActivity) is not Protected. [android:exported=true]	warning	An Activity is found to be shared with other apps on the device therefore leaving it accessible to any other application on the device.
14	Activity (com.money.manager.ex.currency.list.CurrencyListActivity) is not Protected. [android:exported=true]	warning	An Activity is found to be shared with other apps on the device therefore leaving it accessible to any other application on the device.

NO	ISSUE	SEVERITY	DESCRIPTION
15	Activity (com.money.manager.ex.currency.CurrencyEditActivity) is not Protected. [android:exported=true]	warning	An Activity is found to be shared with other apps on the device therefore leaving it accessible to any other application on the device.
16	Activity (com.money.manager.ex.account.AccountEditActivity) is not Protected. [android:exported=true]	warning	An Activity is found to be shared with other apps on the device therefore leaving it accessible to any other application on the device.
17	Activity (com.money.manager.ex.scheduled.ScheduledTransactionEditActivity) is not Protected. [android:exported=true]	warning	An Activity is found to be shared with other apps on the device therefore leaving it accessible to any other application on the device.
18	Activity (com.money.manager.ex.passcode.PasscodeActivity) is not Protected. [android:exported=true]	warning	An Activity is found to be shared with other apps on the device therefore leaving it accessible to any other application on the device.
19	Activity (com.money.manager.ex.settings.SyncPreferencesActivity) is not Protected. [android:exported=true]	warning	An Activity is found to be shared with other apps on the device therefore leaving it accessible to any other application on the device.
20	Activity (com.money.manager.ex.HelpActivity) is not Protected. [android:exported=true]	warning	An Activity is found to be shared with other apps on the device therefore leaving it accessible to any other application on the device.
21	Activity (com.money.manager.ex.widget.SingleAccountWidgetConfigureActivity) is not Protected. [android:exported=true]	warning	An Activity is found to be shared with other apps on the device therefore leaving it accessible to any other application on the device.
22	Content Provider (com.money.manager.ex.MmxContentProvider) is not Protected. [android:exported=true]	warning	A Content Provider is found to be shared with other apps on the device therefore leaving it accessible to any other application on the device.

NO	ISSUE	SEVERITY	DESCRIPTION
23	Service (com.money.manager.ex.sync.adapter.SyncAdapterService) is not Protected. [android:exported=true]	warning	A Service is found to be shared with other apps on the device therefore leaving it accessible to any other application on the device.
24	Service (androidx.work.impl.background.systemjob.SystemJobService) is Protected by a permission, but the protection level of the permission should be checked. Permission: android.permission.BIND_JOB_SERVICE [android:exported=true]	warning	A Service is found to be shared with other apps on the device therefore leaving it accessible to any other application on the device. It is protected by a permission which is not defined in the analysed application. As a result, the protection level of the permission should be checked where it is defined. If it is set to normal or dangerous, a malicious application can request and obtain the permission and interact with the component. If it is set to signature, only applications signed with the same certificate can obtain the permission.
25	Broadcast Receiver (androidx.work.impl.diagnostics.DiagnosticsReceiver) is Protected by a permission, but the protection level of the permission should be checked. Permission: android.permission.DUMP [android:exported=true]	warning	A Broadcast Receiver is found to be shared with other apps on the device therefore leaving it accessible to any other application on the device. It is protected by a permission which is not defined in the analysed application. As a result, the protection level of the permission should be checked where it is defined. If it is set to normal or dangerous, a malicious application can request and obtain the permission and interact with the component. If it is set to signature, only applications signed with the same certificate can obtain the permission.
26	Broadcast Receiver (androidx.profileinstaller.ProfileInstallReceiver) is Protected by a permission, but the protection level of the permission should be checked. Permission: android.permission.DUMP [android:exported=true]	warning	A Broadcast Receiver is found to be shared with other apps on the device therefore leaving it accessible to any other application on the device. It is protected by a permission which is not defined in the analysed application. As a result, the protection level of the permission should be checked where it is defined. If it is set to normal or dangerous, a malicious application can request and obtain the permission and interact with the component. If it is set to signature, only applications signed with the same certificate can obtain the permission.

CODE ANALYSIS

HIGH: 2 | WARNING: 6 | INFO: 2 | SECURE: 1 | SUPPRESSED: 0

NO	ISSUE	SEVERITY	STANDARDS	FILES
1	Files may contain hardcoded sensitive information like usernames, passwords, keys etc.	warning	CWE: CWE-312: Cleartext Storage of Sensitive Information OWASP Top 10: M9: Reverse Engineering OWASP MASVS: MSTG-STORAGE-14	com/amplitude/android/FrustrationAnalyticsUtils.java com/amplitude/android/migration/RemnantDataMigration.java com/amplitude/core/diagnostics/DiagnosticsClientImpl.java com/amplitude/core/utilities/EventsFileManager.java com/amplitude/core/utilities/http/AnalyticsRequest.java com/amplitude/id/FileIdentityStorage.java com/amplitude/id/IdentityConfiguration.java com/money/manager/ex/core/InfoKeys.java com/money/manager/ex/core/Passcode.java com/money/manager/ex/database/PasswordActivity.java com/money/manager/ex/fragment/TipsDialogFragment.java com/money/manager/ex/home/RecentDatabasesProvider.java com/money/manager/ex/passcode/PasscodeActivity.java com/money/manager/ex/widget/SingleAccountWidgetConfigureActivity.java io/reactivex/internal/schedulers/SchedulerPoolFactory.java org/javamoney/moneta/RoundedMoney.java org/javamoney/moneta/RoundedMoneyMonetaryOperatorFactory.java

NO	ISSUE	SEVERITY	STANDARDS	FILES
				org/javamoney/moneta/spi/CompoundRatesProvider.java org/javamoney/moneta/spi/DefaultCashRounding.java org/javamoney/moneta/spi/DefaultRounding.java org/jsoup/helper/W3CDom.java org/jsoup/internal/SharedConstants.java org/jsoup/nodes/DocumentType.java rx/internal/schedulers/NewThreadWorker.java
				com/amplitude/common/android/LogcatLogger.java com/amplitude/common/jvm/ConsoleLogger.java com/caverock/androidsvg/CSSParser.java com/caverock/androidsvg/SVG.java com/caverock/androidsvg/SVGAndroidRenderer.java com/caverock/androidsvg/SVGImageView.java com/caverock/androidsvg/SVGParser.java com/caverock/androidsvg/SimpleAssetResolver.java com/github/mikephil/charting/charts/BarChart.java com/github/mikephil/charting/charts/BarLineChartBase.java com/github/mikephil/charting/charts/Chart.java com/github/mikephil/charting/charts/HorizontalBarChart.java com/github/mikephil/charting/charts/PieRadarChartBase.java com/github/mikephil/charting/components/AxisBase.java com/github/mikephil/charting/data/ChartData.java com/github/mikephil/charting/listener/BarLineChartTouchListener.java

NO	ISSUE	SEVERITY	STANDARDS	FILES
				com/github/mikephil/charting/utils/FileUtils.java com/github/mikephil/charting/utils/Utils.java
2	The App logs information. Sensitive information should never be logged.	info	CWE: CWE-532: Insertion of Sensitive Information into Log File OWASP MASVS: MSTG-STORAGE-3	com/github/pedrovgs/lynx/LynxView.java com/github/pedrovgs/lynx/model/Logcat.java com/mikepenz/aboutlibraries/ui/LibsSupportFragment.java com/mikepenz/aboutlibraries/util/AndroidExtensionsKt.java com/mikepenz/aboutlibraries/util/AndroidParserKt.java com/mikepenz/aboutlibraries/viewmodel/LibsViewModel$listItems$1.java com/mikepenz/fastadapter/FastAdapter.java com/mikepenz/fastadapter/VerboseLogger.java com/mikepenz/fastadapter/listeners/OnBindViewHolderListenerImpl.java com/mikepenz/iconics/Iconics.java com/mikepenz/iconics/IconicsDrawable.java com/mikepenz/iconics/context/ReflectionUtils.java com/mikepenz/iconics/utils/IconicsUtils.java com/money/manager/ex/log/ExceptionHandler.java com/money/manager/ex/servicelayer/RecurringTransactionService.java com/money/manager/ex/view/GestureWebView.java com/pedrogomez/renderers/Renderer.java curtains/internal/WindowManagerSpy.java curtains/internal/WindowSpy.java hirondelle/date4j/Examples.java hirondelle/date4j/ToStringUtil.java it/gmariotti/changelibs/library/parser/XmlParser.java

NO	ISSUE	SEVERITY	STANDARDS	FILES
				it/gmariotti/changelibs/library/view/ChangeLogListView.java it/gmariotti/changelibs/library/view/ChangeLogRecyclerView.java net/zetetic/database/LogcatTarget.java net/zetetic/database/sqlcipher/CloseGuard.java net/zetetic/database/sqlcipher/SQLiteDatabase.java org/greenrobot/eventbus/Logger.java rx/internal/util/IndexedRingBuffer.java rx/internal/util/RxRingBuffer.java rx/plugins/RxJavaHooks.java timber/log/Timber.java
3	IP Address disclosure	warning	CWE: CWE-200: Information Exposure OWASP MASVS: MSTG-CODE-2	com/mikepenz/fontawesome_typeface_library/BuildConfig.java com/mikepenz/mmex_icon_font_typeface_library/MMXIconFont.java
4	App uses SQLite Database and execute raw SQL query. Untrusted user input in raw SQL queries can cause SQL Injection. Also sensitive information should be encrypted and written to the database.	warning	CWE: CWE-89: Improper Neutralization of Special Elements used in an SQL Command ('SQL Injection') OWASP Top 10: M7: Client Code Quality	com/money/manager/ex/database/MmxOpenHelper.java net/zetetic/database/DatabaseUtils.java net/zetetic/database/sqlcipher/SQLiteDatabase.java
5	Debug configuration enabled. Production builds must not be debuggable.	high	CWE: CWE-919: Weaknesses in Mobile Applications OWASP Top 10: M1: Improper Platform Usage OWASP MASVS: MSTG-RESILIENCE-2	com/shamanland/fonticon/BuildConfig.java
6	This App uses SSL certificate pinning to detect or prevent MITM attacks in secure communication channel.	secure	OWASP MASVS: MSTG-NETWORK-4	com/money/manager/ex/investment/prices/FreeCurrencyExchangeRateAPIService.java com/money/manager/ex/investment/yahoofinance/StockPriceRepository.java com/money/manager/ex/investment/yahoofinance/YahooChartDownloaderRetrofit.java

NO	ISSUE	SEVERITY	STANDARDS	FILES
7	App can read/write to External Storage. Any App can read data written to External Storage.	warning	CWE: CWE-276: Incorrect Default Permissions OWASP Top 10: M2: Insecure Data Storage OWASP MASVS: MSTG-STORAGE-2	com/github/mikephil/charting/charts/Chart.java com/github/mikephil/charting/utils/FileUtils.java com/money/manager/ex/core/ExportToCsvFile.java com/money/manager/ex/core/database/DatabaseManager.java
8	The App uses an insecure Random Number Generator.	warning	CWE: CWE-330: Use of Insufficiently Random Values OWASP Top 10: M5: Insufficient Cryptography OWASP MASVS: MSTG-CRYPTO-6	com/amplitude/core/utilities/EventsFileManager.java org/jsoup/helper/DataUtil.java
9	This App copies data to clipboard. Sensitive data should not be copied to clipboard as other applications can access it.	info	OWASP MASVS: MSTG-STORAGE-10	com/money/manager/ex/about/AboutFragment.java
10	App creates temp file. Sensitive information should never be written into a temp file.	warning	CWE: CWE-276: Incorrect Default Permissions OWASP Top 10: M2: Insecure Data Storage OWASP MASVS: MSTG-STORAGE-2	com/money/manager/ex/core/docstorage/FileStorageHelper.java
11	The App uses the encryption mode CBC with PKCS5/PKCS7 padding. This configuration is vulnerable to padding oracle attacks.	high	CWE: CWE-649: Reliance on Obfuscation or Encryption of Security-Relevant Inputs without Integrity Checking OWASP Top 10: M5: Insufficient Cryptography OWASP MASVS: MSTG-CRYPTO-3	com/money/manager/ex/passcode/PasscodeActivity.java

SHARED LIBRARY BINARY ANALYSIS

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
1	x86_64/libsqlcipher.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['__vsnprintf_chk', '__strlen_chk', '__memcpy_chk', '__memset_chk', '__strchr_chk', '__memmove_chk', '__FD_SET_chk', '__read_chk', '__strncpy_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
2	x86/libsqlcipher.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['__vsnprintf_chk', '__strlen_chk', '__memcpy_chk', '__memset_chk', '__strchr_chk', '__memmove_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
3	arm64-v8a/libsqlcipher.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['__vsnprintf_chk', '__strlen_chk', '__memcpy_chk', '__memset_chk', '__strchr_chk', '__memmove_chk', '__FD_SET_chk', '__read_chk', '__strncpy_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
4	armeabi-v7a/libsqlcipher.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['__vsnprintf_chk', '__memcpy_chk', '__strlen_chk', '__memset_chk', '__strchr_chk', '__memmove_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
5	x86_64/libsqlcipher.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['__vsnprintf_chk', '__strlen_chk', '__memcpy_chk', '__memset_chk', '__strchr_chk', '__memmove_chk', '__FD_SET_chk', '__read_chk', '__strncpy_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
6	x86/libsqlcipher.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['__vsnprintf_chk', '__strlen_chk', '__memcpy_chk', '__memset_chk', '__strchr_chk', '__memmove_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
7	arm64-v8a/libsqlcipher.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['__vsnprintf_chk', '__strlen_chk', '__memcpy_chk', '__memset_chk', '__strchr_chk', '__memmove_chk', '__FD_SET_chk', '__read_chk', '__strncpy_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
8	armeabi-v7a/libsqlcipher.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['__vsnprintf_chk', '__memcpy_chk', '__strlen_chk', '__memset_chk', '__strchr_chk', '__memmove_chk']	True info Symbols are stripped.

NIAP ANALYSIS v1.3

NO	IDENTIFIER	REQUIREMENT	FEATURE	DESCRIPTION

BEHAVIOUR ANALYSIS

RULE ID	BEHAVIOUR	LABEL	FILES
00125	Check if the given file path exist	file	com/money/manager/ex/home/MainActivity.java
00014	Read file into a stream and put it into a JSON object	file	com/amplitude/core/diagnostics/DiagnosticsStorage.java com/amplitude/core/utilities/EventsFileManager.java
00022	Open a file from given absolute path of the file	file	com/amplitude/android/migration/DatabaseStorage.java com/amplitude/core/diagnostics/DiagnosticsStorage.java com/amplitude/core/utilities/EventsFileManager.java com/amplitude/id/utilities/PropertiesFile.java com/github/mikephil/charting/charts/Chart.java com/money/manager/ex/core/database/DatabaseManager.java com/money/manager/ex/sync/SyncService.java net/zetetic/database/sqlcipher/SQLiteDatabase.java org/javamoney/moneta/spi/loader/DefaultResourceCache.java org/jsoup/Jsoup.java
00013	Read file and put it into a stream	file	com/amplitude/core/diagnostics/DiagnosticsStorage.java com/amplitude/core/utilities/EventsFileManager.java com/amplitude/id/utilities/PropertiesFile.java com/money/manager/ex/settings/DatabaseSettingsFragment.java com/money/manager/ex/utils/MmxFileUtils.java okio/Okio__JvmOkioKt.java
00005	Get absolute path of file and put it to JSON object	file	com/amplitude/android/migration/DatabaseStorage.java com/amplitude/core/diagnostics/DiagnosticsStorage.java com/amplitude/core/utilities/EventsFileManager.java
00004	Get filename and put it to JSON object	file collection	com/amplitude/core/diagnostics/DiagnosticsStorage.java com/amplitude/core/utilities/EventsFileManager.java

RULE ID	BEHAVIOUR	LABEL	FILES
00091	Retrieve data from broadcast	collection	com/money/manager/ex/notifications/SmsReceiverTransactions.java com/money/manager/ex/transactions/CheckingTransactionEditActivity.java com/money/manager/ex/widget/SingleAccountWidgetConfigureActivity.java
00063	Implicit intent(view a web page, make a phone call, etc.)	control	com/mikepenz/aboutlibraries/ui/item/LibraryItem.java com/mikepenz/aboutlibraries/ui/item/SimpleLibraryItem.java com/money/manager/ex/about/AboutFragment.java com/money/manager/ex/core/docstorage/FileStorageHelper.java com/money/manager/ex/crashreport/CrashReportActivity.java com/money/manager/ex/sync/SyncManager.java com/money/manager/ex/sync/SyncService.java com/money/manager/ex/transactions/AttachmentAdapter.java com/money/manager/ex/transactions/EditTransactionCommonFunctions.java com/money/manager/ex/widget/AccountBillsWidgetProvider.java
00051	Implicit intent(view a web page, make a phone call, etc.) via setData	control	com/money/manager/ex/transactions/AttachmentAdapter.java com/money/manager/ex/widget/AccountBillsWidgetProvider.java
00036	Get resource file from res/raw directory	reflection	com/money/manager/ex/MmxContentProvider.java com/money/manager/ex/widget/AccountBillsWidgetProvider.java
00094	Connect to a URL and read data from it	command network	org/javamoney/moneta/spi/loader/LoadableResource.java
00096	Connect to a URL and set request method	command network	com/amplitude/core/utilities/http/HttpClient.java
00089	Connect to a URL and receive input stream from the server	command network	com/amplitude/core/utilities/http/HttpClient.java
00109	Connect to a URL and get the response code	network command	com/amplitude/core/utilities/http/HttpClient.java
00009	Put data in cursor to JSON object	file	com/amplitude/android/migration/DatabaseStorage.java

RULE ID	BEHAVIOUR	LABEL	FILES
00166	Get SMS message body and retrieve a string from it (possibly PIN / mTAN)	sms pin	com/money/manager/ex/notifications/SmsReceiverTransactions.java
00028	Read file from assets directory	file	com/caverock/androidsvg/SimpleAssetResolver.java
00192	Get messages in the SMS inbox	sms	com/money/manager/ex/core/docstorage/DocFileMetadata.java
00078	Get the network operator name	collection telephony	com/amplitude/common/android/AndroidContextProvider.java
00115	Get last known location of the device	collection location	com/amplitude/common/android/AndroidContextProvider.java
00132	Query The ISO country code	telephony collection	com/amplitude/common/android/AndroidContextProvider.java

ABUSED PERMISSIONS

TYPE	MATCHES	PERMISSIONS
Malware Permissions	6/25	android.permission.RECEIVE_SMS, android.permission.INTERNET, android.permission.ACCESS_NETWORK_STATE, android.permission.VIBRATE, android.permission.RECEIVE_BOOT_COMPLETED, android.permission.WAKE_LOCK
Other Common Permissions	1/44	android.permission.FOREGROUND_SERVICE

Malware Permissions:

Top permissions that are widely abused by known malware.

Other Common Permissions:

Permissions that are commonly abused by known malware.

❗ OFAC SANCTIONED COUNTRIES

This app may communicate with the following OFAC sanctioned list of countries.

DOMAIN	COUNTRY/REGION

🔍 DOMAIN MALWARE CHECK

DOMAIN	STATUS	GEOLOCATION
chart.finance.yahoo.com	ok	No Geolocation information available.
query2.finance.yahoo.com	ok	No Geolocation information available.
www.equalsstr	ok	No Geolocation information available.
www.w3.org	ok	No Geolocation information available.
fontawesome.io	ok	No Geolocation information available.
diagnostics.prod.eu-central-1.amplitude.com	ok	No Geolocation information available.
moneymanagerex.org	ok	No Geolocation information available.
creativecommons.org	ok	No Geolocation information available.
www.moneymanagerex.org	ok	No Geolocation information available.
api2.amplitude.com	ok	No Geolocation information available.

DOMAIN	STATUS	GEOLOCATION
www.google.com	ok	No Geolocation information available.
sr-client-cfg.amplitude.com	ok	No Geolocation information available.
xmlpull.org	ok	No Geolocation information available.
fontawesome.com	ok	No Geolocation information available.
materialdesignicons.com	ok	No Geolocation information available.
api.eu.amplitude.com	ok	No Geolocation information available.
www.paypal.com	ok	No Geolocation information available.
diagnostics.prod.us-west-2.amplitude.com	ok	No Geolocation information available.
xml.org	ok	No Geolocation information available.
twitter.com	ok	No Geolocation information available.
scripts.sil.org	ok	No Geolocation information available.
github.com	ok	No Geolocation information available.
www.gnu.org	ok	No Geolocation information available.
cdn.jsdelivr.net	ok	No Geolocation information available.
design.google.com	ok	No Geolocation information available.
android.moneymanagerex.org	ok	No Geolocation information available.

DOMAIN	STATUS	GEOLOCATION
mikepenz.com	ok	No Geolocation information available.
sr-client-cfg.eu.amplitude.com	ok	No Geolocation information available.
jsoup.org	ok	No Geolocation information available.
www.docs.developers.amplitude.com	ok	No Geolocation information available.

EMAILS

EMAIL	FILE
android@moneymanagerex.org	com/money/manager/ex/Constants.java
moneymanagerex@gmail.com	com/money/manager/ex/about/AboutFragment.java

TRACKERS

TRACKER	CATEGORIES	URL
Amplitude	Profiling, Analytics	https://reports.exodus-privacy.eu.org/trackers/125

HARDCODED SECRETS

POSSIBLE SECRETS
"user" : "Utilizator"
"user" : "Korisnik"
"pref_donate_last_version_key" : "prefdonatelastversioncodekey"
"user" : "User"
"username" : "Brugernavn"
"user" : "Użytkownik"
"user" : "کاربر"
"user" : "Користувач"
"user" : "Uživatel"
"user" : "□□□"
"username" : "Benutzername"
"pref_user_name" : "username"
"user" : "Χρήστης"
"preferences_fingerprint_auth_key" : "Fingerabdruck-Authentifizierungsschlüssel"
"user" : "משתמש"
"user" : "□□□□"

POSSIBLE SECRETS
"donate_bitcoin" : "□□□□□□□□□□□□□□□□"
"username" : "□□□□□"
"library_GoogleMaterialDesignIcons_authorWebsite" : "https://www.google.com/"
"user" : "Пользователь"
"user" : "Användare"
"user" : "Uporabnik"
"library_AndroidIconics_authorWebsite" : "http://mikepenz.com/"
"user" : "Utilizador"
"user" : "■■■■■"
"user" : "Usuário"
"user" : "Tagagamit"
"user" : "მომხმარებელი"
"user" : "صارف"
"user" : "Pengguna"
"user" : "Bruger"
"user" : "Kullanıcı"

POSSIBLE SECRETS
"library_FontAwesome_authorWebsite" : "https://materialdesignicons.com/"
"preferences_fingerprint_auth_key" : "□□□□□□"
"donate_bitcoin" : "□□□□□□□□□□□□"
"user" : "□□"
"user" : "مستخدم"
"user" : "Benutzer"
"enter_password" : "□□□□□□□□"
"username" : "Användarnamn"
"user" : "Uzívatel"
"username" : "□□□□□"
"user" : "Utilisateur"
"user" : "Usuario"
"user" : "Gebruiker"
"user" : "Felhasználó"
"library_fastadapter_authorWebsite" : "http://mikepenz.com/"
"username" : "□□□"

POSSIBLE SECRETS
"username" : "Gebruikersnaam"
"pref_last_version_key" : "preflastversioncodekey"
"user" : "□□□"
"user" : "Utente"
5181942b9ebc31ce68dacb56c16fd79f
16a09e667f3bcc908b2fb1366ea957d3e3adec17512775099da2f590b0667322a
258EAFA5-E914-47DA-95CA-C5AB0DC85B11
ae2044fb577e65ee8bb576ca48a2f06e
1e1fbc10354400d9c3392a89558d693d
6c2a6f30726b3447747559525162665768412370297c5573342324705b

SCAN LOGS

Timestamp	Event	Error
2026-05-02 09:35:47	Generating Hashes	OK

2026-05-02 09:35:47	Extracting APK	OK
2026-05-02 09:35:47	Unzipping	OK
2026-05-02 09:35:48	Parsing APK with androguard	OK
2026-05-02 09:35:49	Extracting APK features using aapt/aapt2	OK
2026-05-02 09:35:50	Getting Hardcoded Certificates/Keystores	OK
2026-05-02 09:36:04	Parsing AndroidManifest.xml	OK
2026-05-02 09:36:04	Extracting Manifest Data	OK
2026-05-02 09:36:04	Manifest Analysis Started	OK
2026-05-02 09:36:04	Performing Static Analysis on: Money Manager Ex (com.money.manager.ex)	OK
2026-05-02 09:36:10	Fetching Details from Play Store: com.money.manager.ex	OK
2026-05-02 09:36:11	Checking for Malware Permissions	OK

2026-05-02 09:36:12	Fetching icon path	OK
2026-05-02 09:36:12	Library Binary Analysis Started	OK
2026-05-02 09:36:12	Analyzing lib/x86_64/libsqlcipher.so	OK
2026-05-02 09:36:12	Analyzing lib/x86/libsqlcipher.so	OK
2026-05-02 09:36:12	Analyzing lib/arm64-v8a/libsqlcipher.so	OK
2026-05-02 09:36:12	Analyzing lib/armeabi-v7a/libsqlcipher.so	OK
2026-05-02 09:36:12	Analyzing apktool_out/lib/x86_64/libsqlcipher.so	OK
2026-05-02 09:36:12	Analyzing apktool_out/lib/x86/libsqlcipher.so	OK
2026-05-02 09:36:12	Analyzing apktool_out/lib/arm64-v8a/libsqlcipher.so	OK
2026-05-02 09:36:13	Analyzing apktool_out/lib/armeabi-v7a/libsqlcipher.so	OK
2026-05-02 09:36:13	Reading Code Signing Certificate	OK

2026-05-02 09:36:15	Running APKiD 3.0.0	OK
2026-05-02 09:36:22	Detecting Trackers	OK
2026-05-02 09:36:28	Decompiling APK to Java with JADX	OK
2026-05-02 09:38:58	Converting DEX to Smali	OK
2026-05-02 09:38:58	Code Analysis Started on - java_source	OK
2026-05-02 09:39:16	Android SBOM Analysis Completed	OK
2026-05-02 09:39:53	Android SAST Completed	OK
2026-05-02 09:39:53	Android API Analysis Started	OK
2026-05-02 09:39:59	Android API Analysis Completed	OK
2026-05-02 09:40:00	Android Permission Mapping Started	OK
2026-05-02 09:40:06	Android Permission Mapping Completed	OK

2026-05-02 09:40:07	Android Behaviour Analysis Started	OK
2026-05-02 09:40:18	Android Behaviour Analysis Completed	OK
2026-05-02 09:40:18	Extracting Emails and URLs from Source Code	OK
2026-05-02 09:40:29	Email and URL Extraction Completed	OK
2026-05-02 09:40:29	Extracting String data from APK	OK
2026-05-02 09:40:30	Extracting String data from SO	OK
2026-05-02 09:40:31	Extracting String data from Code	OK
2026-05-02 09:40:31	Extracting String values and entropies from Code	OK
2026-05-02 09:40:37	Performing Malware check on extracted domains	OK
2026-05-02 09:40:38	Saving to Database	OK

Mobile Security Framework (MobSF) is an automated, all-in-one mobile application (Android/iOS/Windows) pen-testing, malware analysis and security assessment framework capable of performing static and dynamic analysis.

© 2026 Mobile Security Framework - MobSF | Ajin Abraham | OpenSecurity.

MOBSF

ANDROID STATIC ANALYSIS REPORT

app_icon

Piggsy (1.11.1)

File Name:	com.nvllz.piggsy_5.apk
Package Name:	com.nvllz.piggsy
Scan Date:	May 2, 2026, 9:43 a.m.
App Security Score:	52/100 (MEDIUM RISK)
Grade:	B

FINDINGS SEVERITY

HIGH	MEDIUM	INFO	SECURE	HOTSPOT
1	8	2	1	1

FILE INFORMATION

File Name: com.nvllz.piggsy_5.apk
Size: 2.53MB
MD5: 89cb5da9ae85506ee033e67b66325835
SHA1: b0e299b61e30829a1af026d006a1afc75120df21
SHA256: 5a2cde3008a187a20225a6246a02eb4fee983ec4e3ceb128425116f1b17a3676

APP INFORMATION

App Name: Piggsy
Package Name: com.nvllz.piggsy
Main Activity: com.nvllz.piggsy.ui.activities.MainActivity
Target SDK: 36
Min SDK: 24
Max SDK:
Android Version Name: 1.11.1
Android Version Code: 5

APP COMPONENTS

Activities: 8
Services: 3
Receivers: 5
Providers: 1
Exported Activities: 0
Exported Services: 1
Exported Receivers: 2
Exported Providers: 0

CERTIFICATE INFORMATION

Binary is signed
v1 signature: False
v2 signature: True
v3 signature: False
v4 signature: False
X.509 Subject: CN=nvllz
Signature Algorithm: rsassa_pkcs1v15
Valid From: 2025-08-10 19:52:02+00:00
Valid To: 2050-08-04 19:52:02+00:00
Issuer: CN=nvllz
Serial Number: 0x1
Hash Algorithm: sha256
md5: 5171c939c34aa9fe143dbf2c8d93efab
sha1: 5c8cc408d76bbb2e003d52f698be512ab27d458f
sha256: 9242b92c7df80e474b091d6083b273be4912b4aca87e53dae7ffc8530413876e
sha512: d777c42173a8f4949d5f649e1cbc4bdd9500be4fbc207a6a357d918faf6c15c316f234fb65b90d153bfd4c736383472b6f81ad8adfcb8c7345bd2813994ed610
PublicKey Algorithm: rsa
Bit Size: 2048
Fingerprint: 32964a55db0b3b1142b06767921b9d8295f549d26bb089697453beaaae38d393
Found 1 unique certificates

APPLICATION PERMISSIONS

PERMISSION	STATUS	INFO	DESCRIPTION
android.permission.RECEIVE_BOOT_COMPLETED	normal	automatically start at boot	Allows an application to start itself as soon as the system has finished booting. This can make it take longer to start the phone and allow the application to slow down the overall phone by always running.
android.permission.POST_NOTIFICATIONS	dangerous	allows an app to post notifications.	Allows an app to post notifications
android.permission.SCHEDULE_EXACT_ALARM	normal	permits exact alarm scheduling for background work.	Allows an app to use exact alarm scheduling APIs to perform timing sensitive background work.
android.permission.WAKE_LOCK	normal	prevent phone from sleeping	Allows an application to prevent the phone from going to sleep.
android.permission.ACCESS_NETWORK_STATE	normal	view network status	Allows an application to view the status of all networks.
android.permission.FOREGROUND_SERVICE	normal	enables regular apps to use Service.startForeground.	Allows a regular application to use Service.startForeground.
com.nvllz.piggsy.DYNAMIC_RECEIVER_NOT_EXPORTED_PERMISSION	unknown	Unknown permission	Unknown permission from android reference

APKID ANALYSIS

FILE	DETAILS
classes.dex	<table><tr><th>FINDINGS</th><th>DETAILS</th></tr><tr><td>Anti-VM Code</td><td>Build.FINGERPRINT check Build.MANUFACTURER check</td></tr><tr><td>Compiler</td><td>r8</td></tr></table>

NETWORK SECURITY

NO	SCOPE	SEVERITY	DESCRIPTION

CERTIFICATE ANALYSIS

HIGH: 0 | WARNING: 0 | INFO: 1

TITLE	SEVERITY	DESCRIPTION
Signed Application	info	Application is signed with a code signing certificate

MANIFEST ANALYSIS

HIGH: 1 | WARNING: 4 | INFO: 0 | SUPPRESSED: 0

NO	ISSUE	SEVERITY	DESCRIPTION
1	App can be installed on a vulnerable unpatched Android version 7.0, [minSdk=24]	high	This application can be installed on an older version of android that has multiple unfixed vulnerabilities. These devices won't receive reasonable security updates from Google. Support an Android version => 10, API 29 to receive reasonable security updates.
2	Application Data can be Backed up [android:allowBackup=true]	warning	This flag allows anyone to backup your application data via adb. It allows users who have enabled USB debugging to copy application data off of the device.
3	Service (androidx.work.impl.background.systemjob.SystemJobService) is Protected by a permission, but the protection level of the permission should be checked. Permission: android.permission.BIND_JOB_SERVICE [android:exported=true]	warning	A Service is found to be shared with other apps on the device therefore leaving it accessible to any other application on the device. It is protected by a permission which is not defined in the analysed application. As a result, the protection level of the permission should be checked where it is defined. If it is set to normal or dangerous, a malicious application can request and obtain the permission and interact with the component. If it is set to signature, only applications signed with the same certificate can obtain the permission.
4	Broadcast Receiver (androidx.work.impl.diagnostics.DiagnosticsReceiver) is Protected by a permission, but the protection level of the permission should be checked. Permission: android.permission.DUMP [android:exported=true]	warning	A Broadcast Receiver is found to be shared with other apps on the device therefore leaving it accessible to any other application on the device. It is protected by a permission which is not defined in the analysed application. As a result, the protection level of the permission should be checked where it is defined. If it is set to normal or dangerous, a malicious application can request and obtain the permission and interact with the component. If it is set to signature, only applications signed with the same certificate can obtain the permission.
5	Broadcast Receiver (androidx.profileinstaller.ProfileInstallReceiver) is Protected by a permission, but the protection level of the permission should be checked. Permission: android.permission.DUMP [android:exported=true]	warning	A Broadcast Receiver is found to be shared with other apps on the device therefore leaving it accessible to any other application on the device. It is protected by a permission which is not defined in the analysed application. As a result, the protection level of the permission should be checked where it is defined. If it is set to normal or dangerous, a malicious application can request and obtain the permission and interact with the component. If it is set to signature, only applications signed with the same certificate can obtain the permission.

CODE ANALYSIS

HIGH: **0** | WARNING: **3** | INFO: **2** | SECURE: **0** | SUPPRESSED: **0**

NO	ISSUE	SEVERITY	STANDARDS	FILES
				B/b.java B/l.java B0/C.java B0/C0009j.java B0/M.java C0/C0027m.java C0/M.java C0/t.java D/d.java D/e.java D/g.java E/c.java F/b.java F/p.java G/f.java G/g.java G/h.java G/i.java G/j.java I0/c.java K/j.java K0/c.java K0/g.java L/a.java L/c.java L/h.java O/C0032b.java O/C0045o.java O/F.java O/Q.java O/V.java O/k0.java O/l0.java

NO	ISSUE	SEVERITY	STANDARDS	FILES
1	The App logs information. Sensitive information should never be logged.	info	CWE: CWE-532: Insertion of Sensitive Information into Log File OWASP MASVS: MSTG-STORAGE-3	O/o.java O/p0.java O0/d.java T/s.java T0/e.java V/e.java W/a.java Z/g.java Z1/Y.java a/AbstractC0081a.java a1/c.java b0/AbstractC0134d.java com/nvllz/piggsy/receiver/DeadlineReceiver.java com/nvllz/piggsy/ui/activities/BackupActivity.java com/nvllz/piggsy/util/BackupWorker.java f0/ViewOnKeyListenerC0180D.java f0/x.java g/AbstractActivityC0224j.java g/LayoutInflaterFactory2C0203A.java g/p.java g/r.java g/x.java g0/AbstractC0232e.java i0/C0265y.java i0/M.java i0/Y.java i0/d0.java j0/BinderC0302p.java j0/ServiceConnectionC0300n.java j1/d.java k/C0316g.java k/C0317h.java k1/AbstractC0322a.java l/ViewOnKeyListenerC0334g.java

NO	ISSUE	SEVERITY	STANDARDS	FILES
				l/m.java m/AbstractC0351a0.java m/C0359e0.java m/C0385s.java m/C0389u.java m/D0.java m/DialogInterfaceOnClickListenerC0349H.java m/I0.java m/O.java m/P0.java m/e1.java m1/f.java m1/j.java o1/e.java o1/j.java t0/C0488g.java u/c.java u0/C0492a.java w/e.java x/n.java y0/o.java y1/C0532c.java z/AbstractC0535c.java z/C0540h.java z/C0543k.java z/o.java
2	App uses SQLite Database and execute raw SQL query. Untrusted user input in raw SQL queries can cause SQL Injection. Also sensitive information should be encrypted and written to the database.	warning	CWE: CWE-89: Improper Neutralization of Special Elements used in an SQL Command ('SQL Injection') OWASP Top 10: M7: Client Code Quality	B0/M.java com/nvllz/piggsy/ui/activities/HistoryActivity.java t0/C0484c.java u1/C0494b.java v1/f.java y1/C0532c.java

NO	ISSUE	SEVERITY	STANDARDS	FILES
3	The App uses an insecure Random Number Generator.	warning	CWE: CWE-330: Use of Insufficiently Random Values OWASP Top 10: M5: Insufficient Cryptography OWASP MASVS: MSTG-CRYPTO-6	S1/a.java S1/b.java S1/c.java T1/a.java
4	This App copies data to clipboard. Sensitive data should not be copied to clipboard as other applications can access it.	info	OWASP MASVS: MSTG-STORAGE-10	f0/ViewOnCreateContextMenuListenerC0197o.java
5	Files may contain hardcoded sensitive information like usernames, passwords, keys etc.	warning	CWE: CWE-312: Cleartext Storage of Sensitive Information OWASP Top 10: M9: Reverse Engineering OWASP MASVS: MSTG-STORAGE-14	J0/e.java

NIAP ANALYSIS v1.3

NO	IDENTIFIER	REQUIREMENT	FEATURE	DESCRIPTION

BEHAVIOUR ANALYSIS

RULE ID	BEHAVIOUR	LABEL	FILES

RULE ID	BEHAVIOUR	LABEL	FILES
00013	Read file and put it into a stream	file	D/g.java G/h.java G/i.java a/AbstractC0081a.java g0/AbstractC0232e.java g0/C0228a.java g0/h.java
00063	Implicit intent(view a web page, make a phone call, etc.)	control	a/AbstractC0081a.java y1/d.java y1/l.java
00051	Implicit intent(view a web page, make a phone call, etc.) via setData	control	y1/d.java y1/l.java
00022	Open a file from given absolute path of the file	file	C0/C0027m.java C0/r.java
00009	Put data in cursor to JSON object	file	B0/M.java y1/C0532c.java
00004	Get filename and put it to JSON object	file collection	B0/M.java
00010	Read sensitive data(SMS, CALLLOG) and put it into JSON object	sms calllog collection	B0/M.java
00125	Check if the given file path exist	file	B0/M.java
00077	Read sensitive data(SMS, CALLLOG, etc)	collection sms calllog calendar	B0/M.java W/a.java
00147	Get the time of current location	collection location	g/x.java

RULE ID	BEHAVIOUR	LABEL	FILES
00075	Get location of the device	collection location	g/x.java
00115	Get last known location of the device	collection location	g/x.java
00079	Hide the current app's icon	evasion	K0/h.java
00187	Query a URI and check the result	collection sms calllog calendar	W/a.java

ABUSED PERMISSIONS

TYPE	MATCHES	PERMISSIONS
Malware Permissions	3/25	android.permission.RECEIVE_BOOT_COMPLETED, android.permission.WAKE_LOCK, android.permission.ACCESS_NETWORK_STATE
Other Common Permissions	1/44	android.permission.FOREGROUND_SERVICE

Malware Permissions:

Top permissions that are widely abused by known malware.

Other Common Permissions:

Permissions that are commonly abused by known malware.

OFAC SANCTIONED COUNTRIES

This app may communicate with the following OFAC sanctioned list of countries.

DOMAIN	COUNTRY/REGION

DOMAIN MALWARE CHECK

DOMAIN	STATUS	GEOLOCATION
schemas.android.com	ok	No Geolocation information available.
github.com	ok	**IP:** 140.82.121.3 **Country:** United States of America **Region:** California **City:** San Francisco **Latitude:** 37.775700 **Longitude:** -122.395203 **View:** Google Map
developer.android.com	ok	**IP:** 172.217.22.78 **Country:** United States of America **Region:** California **City:** Mountain View **Latitude:** 37.405991 **Longitude:** -122.078514 **View:** Google Map

HARDCODED SECRETS

POSSIBLE SECRETS
"app_author" : "nvllz"
"link_app_author" : "https://github.com/nvllz"
"preference_app_author" : "Author"
149fd8ad55885d3fe3549a37a0163243
a-95ed6082-b8e9-46e8-a73f-ff56f00f5d9d
08b926448d86528e697981ddd30459f7

SCAN LOGS

Timestamp	Event	Error
2026-05-02 09:43:04	Generating Hashes	OK
2026-05-02 09:43:04	Extracting APK	OK
2026-05-02 09:43:04	Unzipping	OK
2026-05-02 09:43:04	Parsing APK with androguard	OK

2026-05-02 09:43:04	Extracting APK features using aapt/aapt2	OK
2026-05-02 09:43:05	Getting Hardcoded Certificates/Keystores	OK
2026-05-02 09:43:12	Parsing AndroidManifest.xml	OK
2026-05-02 09:43:12	Extracting Manifest Data	OK
2026-05-02 09:43:12	Manifest Analysis Started	OK
2026-05-02 09:43:12	Performing Static Analysis on: Piggsy (com.nvllz.piggsy)	OK
2026-05-02 09:43:15	Fetching Details from Play Store: com.nvllz.piggsy	OK
2026-05-02 09:43:16	Checking for Malware Permissions	OK
2026-05-02 09:43:16	Fetching icon path	OK
2026-05-02 09:43:16	Library Binary Analysis Started	OK
2026-05-02 09:43:16	Reading Code Signing Certificate	OK

2026-05-02 09:43:17	Running APKiD 3.0.0	OK
2026-05-02 09:43:20	Detecting Trackers	OK
2026-05-02 09:43:21	Decompiling APK to Java with JADX	OK
2026-05-02 09:43:46	Converting DEX to Smali	OK
2026-05-02 09:43:46	Code Analysis Started on - java_source	OK
2026-05-02 09:43:47	Android SBOM Analysis Completed	OK
2026-05-02 09:43:56	Android SAST Completed	OK
2026-05-02 09:43:56	Android API Analysis Started	OK
2026-05-02 09:43:58	Android API Analysis Completed	OK
2026-05-02 09:43:59	Android Permission Mapping Started	OK
2026-05-02 09:44:01	Android Permission Mapping Completed	OK

2026-05-02 09:44:01	Android Behaviour Analysis Started	OK
2026-05-02 09:44:09	Android Behaviour Analysis Completed	OK
2026-05-02 09:44:09	Extracting Emails and URLs from Source Code	OK
2026-05-02 09:44:11	Email and URL Extraction Completed	OK
2026-05-02 09:44:11	Extracting String data from APK	OK
2026-05-02 09:44:12	Extracting String data from Code	OK
2026-05-02 09:44:12	Extracting String values and entropies from Code	OK
2026-05-02 09:44:12	Performing Malware check on extracted domains	OK
2026-05-02 09:45:19	Saving to Database	OK

Report Generated by - MobSF v4.5.0

Mobile Security Framework (MobSF) is an automated, all-in-one mobile application (Android/iOS/Windows) pen-testing, malware analysis and security assessment framework capable of performing static and dynamic analysis.

© 2026 Mobile Security Framework - MobSF | Ajin Abraham | OpenSecurity.

ANDROID STATIC ANALYSIS REPORT

app_icon

Stepsy (1.6.2)

File Name:	com.nvllz.stepsy_20.apk
Package Name:	com.nvllz.stepsy
Scan Date:	May 2, 2026, 9:46 a.m.

App Security Score: 54/100 (MEDIUM RISK)

Grade: B

FINDINGS SEVERITY

HIGH	MEDIUM	INFO	SECURE	HOTSPOT
0	16	1	1	1

FILE INFORMATION

File Name: com.nvllz.stepsy_20.apk
Size: 3.13MB
MD5: 34ee4b531b6cf56f4e955fbc8e68df20
SHA1: 50c8f9a674151c6b395444a22298d70a055a0b2f
SHA256: 73b15967d647c685b592bc03fc4983bee7f3009d526fd69b2a743bb3dd964429

APP INFORMATION

App Name: Stepsy
Package Name: com.nvllz.stepsy
Main Activity: com.nvllz.stepsy.ui.MainActivity
Target SDK: 35
Min SDK: 26
Max SDK:
Android Version Name: 1.6.2
Android Version Code: 20

APP COMPONENTS

Activities: 9
Services: 6
Receivers: 16
Providers: 1
Exported Activities: 3
Exported Services: 2
Exported Receivers: 7
Exported Providers: 0

CERTIFICATE INFORMATION

Binary is signed
v1 signature: False
v2 signature: True
v3 signature: False
v4 signature: False
X.509 Subject: CN=nvllz
Signature Algorithm: rsassa_pkcs1v15
Valid From: 2025-04-06 16:13:32+00:00
Valid To: 2050-03-31 16:13:32+00:00
Issuer: CN=nvllz
Serial Number: 0x1
Hash Algorithm: sha256
md5: 2546a75ecbaedcbac3ab7195015cd854
sha1: 988a028261359b0ba8c77f701f9ab234428e54a2
sha256: 91e4cd099c31aeaf1bc5ed4029467eb7181d5a7dd893fd98832713ce3be58816

sha512: d73bb4b1fcc74947c897b4f9fc9a92069dbba0702dcb642e0743d91a776d6c8b352512a11c30c7777825741f40a60841737c7111477bd8261580572199ba078a
PublicKey Algorithm: rsa
Bit Size: 2048
Fingerprint: 5c62648c8a8c5940a1317ae36950e7dd7e474714d53a9652268317fdb66b7837
Found 1 unique certificates

APPLICATION PERMISSIONS

PERMISSION	STATUS	INFO	DESCRIPTION
android.permission.ACTIVITY_RECOGNITION	dangerous	allow application to recognize physical activity	Allows an application to recognize physical activity.
android.permission.POST_NOTIFICATIONS	dangerous	allows an app to post notifications.	Allows an app to post notifications
android.permission.RECEIVE_BOOT_COMPLETED	normal	automatically start at boot	Allows an application to start itself as soon as the system has finished booting. This can make it take longer to start the phone and allow the application to slow down the overall phone by always running.
android.permission.FOREGROUND_SERVICE	normal	enables regular apps to use Service.startForeground.	Allows a regular application to use Service.startForeground.
android.permission.FOREGROUND_SERVICE_HEALTH	normal	enables foreground services with health-related functionality.	Allows a regular application to use Service.startForeground with the type "health".
android.permission.REQUEST_IGNORE_BATTERY_OPTIMIZATIONS	normal	permission for using Settings.ACTION_REQUEST_IGNORE_BATTERY_OPTIMIZATIONS.	Permission an application must hold in order to use Settings.ACTION_REQUEST_IGNORE_BATTERY_OPTIMIZATIONS.
android.permission.HIGH_SAMPLING_RATE_SENSORS	normal	Access higher sampling rate sensor data	Allows an app to access sensor data with a sampling rate greater than 200 Hz.
android.permission.WAKE_LOCK	normal	prevent phone from sleeping	Allows an application to prevent the phone from going to sleep.
android.permission.ACCESS_NETWORK_STATE	normal	view network status	Allows an application to view the status of all networks.
com.nvllz.stepsy.DYNAMIC_RECEIVER_NOT_EXPORTED_PERMISSION	unknown	Unknown permission	Unknown permission from android reference

APKID ANALYSIS

FILE	DETAILS
classes.dex	<table><tr><th>FINDINGS</th><th>DETAILS</th></tr><tr><td>Anti-VM Code</td><td>Build.FINGERPRINT check Build.MANUFACTURER check</td></tr><tr><td>Compiler</td><td>r8</td></tr></table>

NETWORK SECURITY

NO	SCOPE	SEVERITY	DESCRIPTION

CERTIFICATE ANALYSIS

HIGH: **0** | WARNING: **0** | INFO: **1**

TITLE	SEVERITY	DESCRIPTION
Signed Application	info	Application is signed with a code signing certificate

MANIFEST ANALYSIS

HIGH: **0** | WARNING: **14** | INFO: **0** | SUPPRESSED: **0**

NO	ISSUE	SEVERITY	DESCRIPTION
1	App can be installed on a vulnerable Android version 8.0, minSdk=26]	warning	This application can be installed on an older version of android that has multiple vulnerabilities. Support an Android version => 10, API 29 to receive reasonable security updates.
2	Application Data can be Backed up [android:allowBackup=true]	warning	This flag allows anyone to backup your application data via adb. It allows users who have enabled USB debugging to copy application data off of the device.
3	Activity (com.nvllz.stepsy.ui.WidgetIconConfigureActivity) is not Protected. [android:exported=true]	warning	An Activity is found to be shared with other apps on the device therefore leaving it accessible to any other application on the device.

NO	ISSUE	SEVERITY	DESCRIPTION
4	Activity (com.nvllz.stepsy.ui.WidgetCompactConfigureActivity) is not Protected. [android:exported=true]	warning	An Activity is found to be shared with other apps on the device therefore leaving it accessible to any other application on the device.
5	Activity (com.nvllz.stepsy.ui.WidgetPlainConfigureActivity) is not Protected. [android:exported=true]	warning	An Activity is found to be shared with other apps on the device therefore leaving it accessible to any other application on the device.
6	Service (com.nvllz.stepsy.service.StepsyTileService) is Protected by a permission, but the protection level of the permission should be checked. Permission: android.permission.BIND_QUICK_SETTINGS_TILE [android:exported=true]	warning	A Service is found to be shared with other apps on the device therefore leaving it accessible to any other application on the device. It is protected by a permission which is not defined in the analysed application. As a result, the protection level of the permission should be checked where it is defined. If it is set to normal or dangerous, a malicious application can request and obtain the permission and interact with the component. If it is set to signature, only applications signed with the same certificate can obtain the permission.
7	Broadcast Receiver (com.nvllz.stepsy.AppUpdateReceiver) is not Protected. [android:exported=true]	warning	A Broadcast Receiver is found to be shared with other apps on the device therefore leaving it accessible to any other application on the device.
8	Broadcast Receiver (com.nvllz.stepsy.ui.WidgetIconProvider) is not Protected. [android:exported=true]	warning	A Broadcast Receiver is found to be shared with other apps on the device therefore leaving it accessible to any other application on the device.
9	Broadcast Receiver (com.nvllz.stepsy.ui.WidgetCompactProvider) is not Protected. [android:exported=true]	warning	A Broadcast Receiver is found to be shared with other apps on the device therefore leaving it accessible to any other application on the device.
10	Broadcast Receiver (com.nvllz.stepsy.ui.WidgetPlainProvider) is not Protected. [android:exported=true]	warning	A Broadcast Receiver is found to be shared with other apps on the device therefore leaving it accessible to any other application on the device.
11	Broadcast Receiver (com.nvllz.stepsy.api.StepsyControlReceiver) is not Protected. [android:exported=true]	warning	A Broadcast Receiver is found to be shared with other apps on the device therefore leaving it accessible to any other application on the device.
12	Service (androidx.work.impl.background.systemjob.SystemJobService) is Protected by a permission, but the protection level of the permission should be checked. Permission: android.permission.BIND_JOB_SERVICE [android:exported=true]	warning	A Service is found to be shared with other apps on the device therefore leaving it accessible to any other application on the device. It is protected by a permission which is not defined in the analysed application. As a result, the protection level of the permission should be checked where it is defined. If it is set to normal or dangerous, a malicious application can request and obtain the permission and interact with the component. If it is set to signature, only applications signed with the same certificate can obtain the permission.
13	Broadcast Receiver (androidx.work.impl.diagnostics.DiagnosticsReceiver) is Protected by a permission, but the protection level of the permission should be checked. Permission: android.permission.DUMP [android:exported=true]	warning	A Broadcast Receiver is found to be shared with other apps on the device therefore leaving it accessible to any other application on the device. It is protected by a permission which is not defined in the analysed application. As a result, the protection level of the permission should be checked where it is defined. If it is set to normal or dangerous, a malicious application can request and obtain the permission and interact with the component. If it is set to signature, only applications signed with the same certificate can obtain the permission.

NO	ISSUE	SEVERITY	DESCRIPTION
14	Broadcast Receiver (androidx.profileinstaller.ProfileInstallReceiver) is Protected by a permission, but the protection level of the permission should be checked. Permission: android.permission.DUMP [android:exported=true]	warning	A Broadcast Receiver is found to be shared with other apps on the device therefore leaving it accessible to any other application on the device. It is protected by a permission which is not defined in the analysed application. As a result, the protection level of the permission should be checked where it is defined. If it is set to normal or dangerous, a malicious application can request and obtain the permission and interact with the component. If it is set to signature, only applications signed with the same certificate can obtain the permission.

CODE ANALYSIS

HIGH: **0** | WARNING: **1** | INFO: **1** | SECURE: **0** | SUPPRESSED: **0**

NO	ISSUE	SEVERITY	STANDARDS	FILES
1	The App logs information. Sensitive information should never be logged.	info	CWE: CWE-532: Insertion of Sensitive Information into Log File OWASP MASVS: MSTG-STORAGE-3	com/github/mikephil/charting/charts/BarChart.java com/github/mikephil/charting/charts/BarLineChartBase.java com/github/mikephil/charting/charts/Chart.java com/github/mikephil/charting/listener/BarLineChartTouchListener.java com/github/mikephil/charting/utils/Utils.java com/nvllz/stepsy/service/MidnightResetReceiver.java com/nvllz/stepsy/service/MotionService$$ExternalSyntheticLambda3.java com/nvllz/stepsy/service/MotionService.java com/nvllz/stepsy/ui/BackupActivity$$ExternalSyntheticLambda8.java com/nvllz/stepsy/ui/BackupActivity$registerLaunchers$3$1$1.java com/nvllz/stepsy/ui/BackupActivity$setupClickListeners$2$1$1.java com/nvllz/stepsy/ui/BackupActivity$setupClickListeners$3$1$1.java com/nvllz/stepsy/ui/BackupActivity.java com/nvllz/stepsy/ui/Chart.java com/nvllz/stepsy/ui/MainActivity.java com/nvllz/stepsy/util/BackupScheduler.java com/nvllz/stepsy/util/BackupWorker$cleanupOldBackups$2.java com/nvllz/stepsy/util/BackupWorker$performBackup$2.java com/nvllz/stepsy/util/BackupWorker.java com/nvllz/stepsy/util/Database.java okio/Okio.java

NO	ISSUE	SEVERITY	STANDARDS	FILES
2	App uses SQLite Database and execute raw SQL query. Untrusted user input in raw SQL queries can cause SQL Injection. Also sensitive information should be encrypted and written to the database.	warning	CWE: CWE-89: Improper Neutralization of Special Elements used in an SQL Command ('SQL Injection') OWASP Top 10: M7: Client Code Quality	com/nvllz/stepsy/util/Database.java

SHARED LIBRARY BINARY ANALYSIS

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
1	x86_64/libdatastore_shared_counter.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
2	x86/libdatastore_shared_counter.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.
3	arm64-v8a/libdatastore_shared_counter.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
4	armeabi-v7a/libdatastore_shared_counter.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.
5	x86_64/libdatastore_shared_counter.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
6	x86/libdatastore_shared_counter.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.
7	arm64-v8a/libdatastore_shared_counter.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
8	armeabi-v7a/libdatastore_shared_counter.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NIAP ANALYSIS v1.3

NO	IDENTIFIER	REQUIREMENT	FEATURE	DESCRIPTION

BEHAVIOUR ANALYSIS

RULE ID	BEHAVIOUR	LABEL	FILES
00091	Retrieve data from broadcast	collection	com/nvllz/stepsy/ui/WidgetCompactConfigureActivity.java com/nvllz/stepsy/ui/WidgetIconConfigureActivity.java com/nvllz/stepsy/ui/WidgetPlainConfigureActivity.java
00013	Read file and put it into a stream	file	com/nvllz/stepsy/ui/BackupActivity$$ExternalSyntheticLambda8.java com/nvllz/stepsy/ui/BackupActivity.java okio/InputStreamSource.java okio/JvmSystemFileSystem.java
00022	Open a file from given absolute path of the file	file	okio/internal/ResourceFileSystem$roots$2.java

RULE ID	BEHAVIOUR	LABEL	FILES
00063	Implicit intent(view a web page, make a phone call, etc.)	control	com/nvllz/stepsy/ui/BackupActivity.java com/nvllz/stepsy/ui/MainActivity.java
00051	Implicit intent(view a web page, make a phone call, etc.) via setData	control	com/nvllz/stepsy/ui/MainActivity.java
00112	Get the date of the calendar event	collection calendar	com/nvllz/stepsy/ui/AchievementsActivity$updateAchievements$results$1.java com/nvllz/stepsy/ui/MainActivity.java

ABUSED PERMISSIONS

TYPE	MATCHES	PERMISSIONS
Malware Permissions	3/25	android.permission.RECEIVE_BOOT_COMPLETED, android.permission.WAKE_LOCK, android.permission.ACCESS_NETWORK_STATE
Other Common Permissions	3/44	android.permission.ACTIVITY_RECOGNITION, android.permission.FOREGROUND_SERVICE, android.permission.REQUEST_IGNORE_BATTERY_OPTIMIZATIONS

Malware Permissions:
Top permissions that are widely abused by known malware.
Other Common Permissions:
Permissions that are commonly abused by known malware.

OFAC SANCTIONED COUNTRIES

This app may communicate with the following OFAC sanctioned list of countries.

DOMAIN	COUNTRY/REGION

DOMAIN MALWARE CHECK

DOMAIN	STATUS	GEOLOCATION

DOMAIN	STATUS	GEOLOCATION
www.gnu.org	ok	**IP:** 209.51.188.116 **Country:** United States of America **Region:** Massachusetts **City:** Boston **Latitude:** 42.358429 **Longitude:** -71.059769 **View:** Google Map
github.com	ok	**IP:** 140.82.121.3 **Country:** United States of America **Region:** California **City:** San Francisco **Latitude:** 37.775700 **Longitude:** -122.395203 **View:** Google Map

HARDCODED SECRETS

POSSIBLE SECRETS
a-95ed6082-b8e9-46e8-a73f-ff56f00f5d9d
1cbd3130fa23b59692c061c594c16cc0
86254750241babac4b8d52996a675549

SCAN LOGS

Timestamp	Event	Error
2026-05-02 09:46:14	Generating Hashes	OK
2026-05-02 09:46:14	Extracting APK	OK

2026-05-02 09:46:14	Unzipping	OK
2026-05-02 09:46:14	Parsing APK with androguard	OK
2026-05-02 09:46:14	Extracting APK features using aapt/aapt2	OK
2026-05-02 09:46:15	Getting Hardcoded Certificates/Keystores	OK
2026-05-02 09:46:20	Parsing AndroidManifest.xml	OK
2026-05-02 09:46:20	Extracting Manifest Data	OK
2026-05-02 09:46:20	Manifest Analysis Started	OK
2026-05-02 09:46:20	Performing Static Analysis on: Stepsy (com.nvllz.stepsy)	OK
2026-05-02 09:46:22	Fetching Details from Play Store: com.nvllz.stepsy	OK
2026-05-02 09:46:23	Checking for Malware Permissions	OK
2026-05-02 09:46:23	Fetching icon path	OK
2026-05-02 09:46:24	Library Binary Analysis Started	OK
2026-05-02 09:46:24	Analyzing lib/x86_64/libdatastore_shared_counter.so	OK
2026-05-02 09:46:24	Analyzing lib/x86/libdatastore_shared_counter.so	OK

2026-05-02 09:46:24	Analyzing lib/arm64-v8a/libdatastore_shared_counter.so	OK
2026-05-02 09:46:24	Analyzing lib/armeabi-v7a/libdatastore_shared_counter.so	OK
2026-05-02 09:46:24	Analyzing apktool_out/lib/x86_64/libdatastore_shared_counter.so	OK
2026-05-02 09:46:24	Analyzing apktool_out/lib/x86/libdatastore_shared_counter.so	OK
2026-05-02 09:46:24	Analyzing apktool_out/lib/arm64-v8a/libdatastore_shared_counter.so	OK
2026-05-02 09:46:24	Analyzing apktool_out/lib/armeabi-v7a/libdatastore_shared_counter.so	OK
2026-05-02 09:46:24	Reading Code Signing Certificate	OK
2026-05-02 09:46:25	Running APKiD 3.0.0	OK
2026-05-02 09:46:29	Detecting Trackers	OK
2026-05-02 09:46:31	Decompiling APK to Java with JADX	OK
2026-05-02 09:47:01	Converting DEX to Smali	OK
2026-05-02 09:47:01	Code Analysis Started on - java_source	OK
2026-05-02 09:47:01	Android SBOM Analysis Completed	OK
2026-05-02 09:47:09	Android SAST Completed	OK

2026-05-02 09:47:09	Android API Analysis Started	OK
2026-05-02 09:47:13	Android API Analysis Completed	OK
2026-05-02 09:47:14	Android Permission Mapping Started	OK
2026-05-02 09:47:18	Android Permission Mapping Completed	OK
2026-05-02 09:47:18	Android Behaviour Analysis Started	OK
2026-05-02 09:47:22	Android Behaviour Analysis Completed	OK
2026-05-02 09:47:22	Extracting Emails and URLs from Source Code	OK
2026-05-02 09:47:23	Email and URL Extraction Completed	OK
2026-05-02 09:47:23	Extracting String data from APK	OK
2026-05-02 09:47:23	Extracting String data from SO	OK
2026-05-02 09:47:23	Extracting String data from Code	OK
2026-05-02 09:47:23	Extracting String values and entropies from Code	OK
2026-05-02 09:47:24	Performing Malware check on extracted domains	OK
2026-05-02 09:47:34	Saving to Database	OK

Report Generated by - MobSF v4.5.0

Mobile Security Framework (MobSF) is an automated, all-in-one mobile application (Android/iOS/Windows) pen-testing, malware analysis and security assessment framework capable of performing static and dynamic analysis.

© 2026 Mobile Security Framework - MobSF | Ajin Abraham | OpenSecurity.

MOBSF

ANDROID STATIC ANALYSIS REPORT

Battery Notification (1.4.7)

File Name:	com.ominous.batterynotification_19.apk
Package Name:	com.ominous.batterynotification
Scan Date:	May 2, 2026, 9:49 a.m.
App Security Score:	53/100 (MEDIUM RISK)
Grade:	B

FINDINGS SEVERITY

HIGH	MEDIUM	INFO	SECURE	HOTSPOT
1	4	2	1	1

FILE INFORMATION

File Name: com.ominous.batterynotification_19.apk
Size: 0.97MB
MD5: 244b77a7f96381846e35c31bfebfe6ca
SHA1: b747555c90fa7005d6d9eb0f16dd4af4a3614e09
SHA256: db1ce76e1b99423c920cadd3f59e4e2f3418f4eca4902d075bbcd68632a66992

APP INFORMATION

App Name: Battery Notification
Package Name: com.ominous.batterynotification
Main Activity: com.ominous.batterynotification.activity.SettingsActivity
Target SDK: 36
Min SDK: 17
Max SDK:
Android Version Name: 1.4.7
Android Version Code: 19

APP COMPONENTS

Activities: 1
Services: 1
Receivers: 2
Providers: 1
Exported Activities: 0
Exported Services: 0
Exported Receivers: 1
Exported Providers: 0

CERTIFICATE INFORMATION

Binary is signed
v1 signature: True
v2 signature: True
v3 signature: True
v4 signature: False
X.509 Subject: C=UK, ST=ORG, L=ORG, O=fdroid.org, OU=FDroid, CN=FDroid
Signature Algorithm: rsassa_pkcs1v15
Valid From: 2022-04-18 17:07:39+00:00
Valid To: 2049-09-03 17:07:39+00:00
Issuer: C=UK, ST=ORG, L=ORG, O=fdroid.org, OU=FDroid, CN=FDroid
Serial Number: 0x7c316da
Hash Algorithm: sha256
md5: 9ba14cc0602595522fdbad5aa1e30092
sha1: cfd58cf425388efd5ae0534d089f5c256a8ee8f1
sha256: bea3e36842f7f655c1ea2893ae621b85a6446c8265c079b48afa758fb1533bdc
sha512: a6cc4439388fac8fc6c7854252fd789aef28268fb1b91f4864d00909839ed31e7b015fff1ec46094e510e7efb96e3ae243888a658a115cc8f5f4b7be3e6e8e97
PublicKey Algorithm: rsa
Bit Size: 2048
Fingerprint: 48c5e5e432494f67768d5b483ee3f1b91fd9b8c6bcbd843a334e80037e4964ec
Found 1 unique certificates

APPLICATION PERMISSIONS

PERMISSION	STATUS	INFO	DESCRIPTION
android.permission.RECEIVE_BOOT_COMPLETED	normal	automatically start at boot	Allows an application to start itself as soon as the system has finished booting. This can make it take longer to start the phone and allow the application to slow down the overall phone by always running.
android.permission.ACCESS_SUPERUSER	unknown	Unknown permission	Unknown permission from android reference
android.permission.POST_NOTIFICATIONS	dangerous	allows an app to post notifications.	Allows an app to post notifications
android.permission.BATTERY_STATS	signature	modify battery statistics	Allows the modification of collected battery statistics. Not for use by common applications.
android.permission.FOREGROUND_SERVICE	normal	enables regular apps to use Service.startForeground.	Allows a regular application to use Service.startForeground.
android.permission.FOREGROUND_SERVICE_SPECIAL_USE	normal	enables special-use foreground services.	Allows a regular application to use Service.startForeground with the type "specialUse".
com.ominous.batterynotification.DYNAMIC_RECEIVER_NOT_EXPORTED_PERMISSION	unknown	Unknown permission	Unknown permission from android reference

APKID ANALYSIS

FILE	DETAILS
classes.dex	<table><tr><th>FINDINGS</th><th>DETAILS</th></tr><tr><td>Compiler</td><td>r8</td></tr></table>

NETWORK SECURITY

NO	SCOPE	SEVERITY	DESCRIPTION

CERTIFICATE ANALYSIS

HIGH: 0 | WARNING: 1 | INFO: 1

TITLE	SEVERITY	DESCRIPTION
Signed Application	info	Application is signed with a code signing certificate
Application vulnerable to Janus Vulnerability	warning	Application is signed with v1 signature scheme, making it vulnerable to Janus vulnerability on Android 5.0-8.0, if signed only with v1 signature scheme. Applications running on Android 5.0-7.0 signed with v1, and v2/v3 scheme is also vulnerable.

MANIFEST ANALYSIS

HIGH: 1 | WARNING: 2 | INFO: 0 | SUPPRESSED: 0

NO	ISSUE	SEVERITY	DESCRIPTION
1	App can be installed on a vulnerable unpatched Android version 4.2-4.2.2, [minSdk=17]	high	This application can be installed on an older version of android that has multiple unfixed vulnerabilities. These devices won't receive reasonable security updates from Google. Support an Android version => 10, API 29 to receive reasonable security updates.
2	Application Data can be Backed up [android:allowBackup=true]	warning	This flag allows anyone to backup your application data via adb. It allows users who have enabled USB debugging to copy application data off of the device.
3	Broadcast Receiver (androidx.profileinstaller.ProfileInstallReceiver) is Protected by a permission, but the protection level of the permission should be checked. Permission: android.permission.DUMP [android:exported=true]	warning	A Broadcast Receiver is found to be shared with other apps on the device therefore leaving it accessible to any other application on the device. It is protected by a permission which is not defined in the analysed application. As a result, the protection level of the permission should be checked where it is defined. If it is set to normal or dangerous, a malicious application can request and obtain the permission and interact with the component. If it is set to signature, only applications signed with the same certificate can obtain the permission.

CODE ANALYSIS

HIGH: 0 | WARNING: 1 | INFO: 2 | SECURE: 0 | SUPPRESSED: 0

NO	ISSUE	SEVERITY	STANDARDS	FILES
				A/b.java B/A.java B/C0008i.java B/C0011l.java B/M.java B/W.java B/X.java

NO	ISSUE	SEVERITY	STANDARDS	FILES
1	The App logs information. Sensitive information should never be logged.	info	CWE: CWE-532: Insertion of Sensitive Information into Log File OWASP MASVS: MSTG-STORAGE-3	B/c0.java B/u0.java E/d.java K/E.java K/x.java L/g.java N/C0035d.java N/Z.java O/e.java R/r.java T/d.java W/a.java com/ominous/batterynotification/receiver/BatteryBroadcastReceiver.java com/ominous/batterynotification/service/BatteryService.java e/j.java e/r.java e/v.java f/AbstractC0094b.java j/h.java j/i.java k/MenuC0117m.java k/ViewOnKeyListenerC0111g.java l/AbstractC0165j0.java l/C0143M.java l/C0171m0.java l/C0173n0.java l/C0177p0.java l/C0183t.java l/D0.java l/DialogInterfaceOnClickListenerC0136F.java l/Q0.java l/S.java l/U0.java l/X.java me/weishu/reflection/BootstrapClass.java r/C0213e.java r/RunnableC0212d.java s/f.java t/AbstractC0224b.java

NO	ISSUE	SEVERITY	STANDARDS	FILES
				u/d.java u/e.java u/f.java
				u/g.java u/h.java u/i.java v/h.java x/d.java
2	The App uses an insecure Random Number Generator.	warning	CWE: CWE-330: Use of Insufficiently Random Values OWASP Top 10: M5: Insufficient Cryptography OWASP MASVS: MSTG-CRYPTO-6	L/h.java e0/a.java e0/b.java e0/c.java f0/a.java
3	This App copies data to clipboard. Sensitive data should not be copied to clipboard as other applications can access it.	info	OWASP MASVS: MSTG-STORAGE-10	K/o.java

NIAP ANALYSIS v1.3

NO	IDENTIFIER	REQUIREMENT	FEATURE	DESCRIPTION

BEHAVIOUR ANALYSIS

RULE ID	BEHAVIOUR	LABEL	FILES

RULE ID	BEHAVIOUR	LABEL	FILES
00013	Read file and put it into a stream	file	L/c.java L/g.java L/m.java u/e.java u/g.java
00191	Get messages in the SMS inbox	sms	l/D0.java
00036	Get resource file from res/raw directory	reflection	l/D0.java
00024	Write file after Base64 decoding	reflection file	com/ominous/batterynotification/application/BatteryNotification.java
00147	Get the time of current location	collection location	e/r.java
00075	Get location of the device	collection location	e/r.java
00115	Get last known location of the device	collection location	e/r.java

ABUSED PERMISSIONS

TYPE	MATCHES	PERMISSIONS
Malware Permissions	1/25	android.permission.RECEIVE_BOOT_COMPLETED
Other Common Permissions	3/44	android.permission.ACCESS_SUPERUSER, android.permission.BATTERY_STATS, android.permission.FOREGROUND_SERVICE

Malware Permissions:

Top permissions that are widely abused by known malware.

Other Common Permissions:

Permissions that are commonly abused by known malware.

! OFAC SANCTIONED COUNTRIES

This app may communicate with the following OFAC sanctioned list of countries.

DOMAIN	COUNTRY/REGION

DOMAIN MALWARE CHECK

DOMAIN	STATUS	GEOLOCATION
schemas.android.com	ok	No Geolocation information available.

PLAYSTORE INFORMATION

Title: Battery Notification

Score: 3.9166667 **Installs:** 10,000+ **Price:** 0 **Android Version Support:** **Category:** Tools **Play Store URL:** com.ominous.batterynotification

Developer Details: Tyler Williamson, Tyler+Williamson, None, https://github.com/TylerWilliamson/BatteryNotification/, tyler.williamson51@gmail.com,

Release Date: Jul 5, 2016 **Privacy Policy:** Privacy link

Description:

Always Free (No IAPs or Ads) and Always Open Source Persistent Notification Includes: • Battery Level (Including Color Indicator for Android 5.0+) • Battery Temperature (in Fahrenheit or Celcius) • Charging State • Battery Health • Charging/Discharging Amperage (for Android 5.0+) • Time Remaining Until Fully Charged

or Discharged (Root/ADB Only for Android 5.0+) Required Permissions • Receive Boot Completed - Used to restart the notification after rebooting the device Optional Permissions • ACCESS_SUPERUSER - Used to give the app the BATTERY_STATS permission • BATTERY_STATS - Used to access the BatteryStats object to get the time remaining until fully charged or discharged • FOREGROUND_SERVICE - Used to keep a service in the foreground to instantly update the notification if the battery information changes Contact the developer at tyler.williamson51@gmail.com View the source code at: https://github.com/TylerWilliamson/BatteryNotification

SCAN LOGS

Timestamp	Event	Error
2026-05-02 09:49:22	Generating Hashes	OK
2026-05-02 09:49:22	Extracting APK	OK
2026-05-02 09:49:22	Unzipping	OK
2026-05-02 09:49:23	Parsing APK with androguard	OK
2026-05-02 09:49:23	Extracting APK features using aapt/aapt2	OK
2026-05-02 09:49:23	Getting Hardcoded Certificates/Keystores	OK
2026-05-02 09:49:27	Parsing AndroidManifest.xml	OK

2026-05-02 09:49:27	Extracting Manifest Data	OK
2026-05-02 09:49:27	Manifest Analysis Started	OK
2026-05-02 09:49:27	Performing Static Analysis on: Battery Notification (com.ominous.batterynotification)	OK
2026-05-02 09:49:31	Fetching Details from Play Store: com.ominous.batterynotification	OK
2026-05-02 09:49:35	Checking for Malware Permissions	OK
2026-05-02 09:49:35	Fetching icon path	OK
2026-05-02 09:49:35	Library Binary Analysis Started	OK
2026-05-02 09:49:35	Reading Code Signing Certificate	OK
2026-05-02 09:49:36	Running APKiD 3.0.0	OK
2026-05-02 09:49:39	Detecting Trackers	OK
2026-05-02 09:49:40	Decompiling APK to Java with JADX	OK

2026-05-02 09:49:57	Converting DEX to Smali	OK
2026-05-02 09:49:57	Code Analysis Started on - java_source	OK
2026-05-02 09:49:57	Android SBOM Analysis Completed	OK
2026-05-02 09:50:02	Android SAST Completed	OK
2026-05-02 09:50:02	Android API Analysis Started	OK
2026-05-02 09:50:03	Android API Analysis Completed	OK
2026-05-02 09:50:04	Android Permission Mapping Started	OK
2026-05-02 09:50:05	Android Permission Mapping Completed	OK
2026-05-02 09:50:05	Android Behaviour Analysis Started	OK
2026-05-02 09:50:08	Android Behaviour Analysis Completed	OK
2026-05-02 09:50:08	Extracting Emails and URLs from Source Code	OK

2026-05-02 09:50:13	Email and URL Extraction Completed	OK
2026-05-02 09:50:13	Extracting String data from APK	OK
2026-05-02 09:50:13	Extracting String data from Code	OK
2026-05-02 09:50:13	Extracting String values and entropies from Code	OK
2026-05-02 09:50:15	Performing Malware check on extracted domains	OK
2026-05-02 09:51:38	Saving to Database	OK

Report Generated by - MobSF v4.5.0

Mobile Security Framework (MobSF) is an automated, all-in-one mobile application (Android/iOS/Windows) pen-testing, malware analysis and security assessment framework capable of performing static and dynamic analysis.

© 2026 Mobile Security Framework - MobSF | Ajin Abraham | OpenSecurity.