

Mitsubishi EVO (Con. rod small end 1.000" or less)

4G63 Evo 4 - 9

Kit Part #	Bore mm / Inch	Over Sizes	Stroke	Rod Lgth.	Comp Ht.	Head cc's	Dome Dish	Gasket Thkness	Deck Clearance	Block Ht.	Comp. Ratio	Pin Part # (included)	Ring # (included)	Gram	Foot Notes
1400H.D. • 9:1cr • Includes .225" wall Tool Steel Pins															
K626M85AP	85.00 / 3.346	Std.	3.465 88	5.906 150	1.378 35	43	-14	.034 0.86	0 0	9.015 229	8.9 8.95 9.0 9.1 9.15 9.2 9.3	S722 22mm	8500XX	334	1
K626M8525AP	85.25 / 3.356	.010											8525XX	345	
K626M855AP	85.50 / 3.366	.020											8550XX	341	
K626M86AP	86.00 / 3.386	.040											8600XX	349	
K626M8625AP	86.25 / 3.396	.050											8625XX		
K626M865AP	86.50 / 3.405	.060											8650XX	356	
K626M87AP	87.00 / 3.425	.080											8700XX	369	
HD2 Asymmetric Skirt • 9.5:1 • Includes .200" wall Pins.															
K666M85AP	85.00 / 3.346	Std.	3.465 88	5.906 150	1.373 34.875	43	-9 -9.3 -9.5 -10.2 -10.8 -11.1 -11.4	.034 .86	.005- 0.18-	9.015 229	9.5	S782 22mm	8500XX	345	1
K666M8525AP	85.25 / 3.356	.010											8525XX	347	
K666M855AP	85.50 / 3.366	.020											8550XX	342	
K666M86AP	86.00 / 3.386	.040											8600XX	353	
K666M865AP	86.50 / 3.405	.060											8650XX	360	
K666M8675AP	86.75 / 3.405	.060											8700XX	363	
K666M87AP	87.00 / 3.425	.080											8700XX		
1400H.D. • E85 Series • 10.5:1cr • Includes .225" wall Tool Steel Pins															
K656M85AP	85.00 / 3.346	Std.	3.465 88	5.905 150	1.378 35	43	-4.5	.034 0.86	0 0	9.015 229	10.49 10.54 10.6 10.72 10.82 10.94	S722 22mm	8500XX	372	1
K656M8525AP	85.25 / 3.356	.010											8525XX		
K656M855AP	85.50 / 3.366	.020											8550XX	380	
K656M86AP	86.00 / 3.386	.040											8600XX		
K656M865AP	86.50 / 3.405	.060											8650XX		
K656M87AP	87.00 / 3.425	.080											8700XX		
HD2 10.5:1 • Asymmetric Skirt • Gas Ported • .225" wall Tool Steel Pins															
K668M85AP	85.00 / 3.346	Std.	3.465 88	5.906 150	1.373 34.875	43	-2.75 -3 -3.25 -3.9 -4.5 -4.75 -5	.034 .86	.005- 0.18-	9.015 229	10.5	S734 22mm	8500XX	333	1
K668M8525AP	85.25 / 3.356	.010											8525XX	336	
K668M855AP	85.50 / 3.366	.020											8550XX	339	
K668M86AP	86.00 / 3.386	.040											8600XX	345	
K668M865AP	86.50 / 3.405	.060											8650XX	348	
K668M8675AP	86.75 / 3.415	.070											8700XX	350	
K668M87AP	87.00 / 3.425	.080											8700XX	352	
NEW! 1400HD Stock Stroke • 156mm Rod • 8:1cr • Includes .225" wall Tool Steel Pins															
K627M85AP	85.00 / 3.346	Std.	3.465 88	6.142 156	1.137 28.875	43	-21	.034 0.86	.011- 0.3-	9.015 229	8.0 8.1 8.17 8.2 8.26 8.3 8.4	S722 22mm	8500XX	292	1
K627M8525AP	85.25 / 3.356	.010											8525XX	294	
K627M855AP	85.50 / 3.366	.020											8550XX	299	
K627M86AP	86.00 / 3.386	.040											8600XX	305	
K627M8625AP	86.25 / 3.396	.050											8625XX	307	
K627M87AP	87.00 / 3.425	.080											8700XX	324	
K627M875AP	87.50 / 3.445	.100											8750XX	331	
NEW! HD2 Asymmetric Skirt • 156mm Rod • 8.4:1cr • Includes .200" wall Pins															
K667M85AP	85.00 / 3.346	Std.	3.465 88	6.142 156	1.137 28.875	43	-17 -17.3 -17.7 -18.4 -19.1 -19.4 -19.8	.034 0.86	.005- 0.18-	9.015 229	8.4	S782 22mm	8500XX	317	1
K667M8525AP	85.25 / 3.356	.010											8525XX	320	
K667M855AP	85.50 / 3.366	.020											8550XX	322	
K667M86AP	86.00 / 3.386	.040											8600XX	331	
K667M865AP	86.50 / 3.405	.060											8650XX	340	
K667M8675AP	86.75 / 3.405	.060											8700XX	341	
K667M87AP	87.00 / 3.425	.080											8700XX	347	
NEW! HD2 Asymmetric Skirt • 156mm Rod • Gas Ported • 9.2:1cr • .225" wall Tool Steel Pins															
K669M85AP	85.00 / 3.346	Std.	3.465 88	6.142 156	1.137 28.875	43	-10 -10.25 -10.5 -11.25 -11.75 -12.25 -12.50	.034 0.86	.005- 0.18-	9.015 229	9.2	S734 22mm	8500XX	311	1
K669M8525AP	85.25 / 3.356	.010											8525XX	315	
K669M855AP	85.50 / 3.366	.020											8550XX	317	
K669M86AP	86.00 / 3.386	.040											8600XX	331	
K669M865AP	86.50 / 3.405	.060											8650XX	332	
K669M8675AP	86.75 / 3.415	.070											8700XX	336	
K669M87AP	87.00 / 3.425	.080											8700XX	340	



FORGED AUTOMOTIVE RACING PISTONS • SPORT COMPACT SERIES

Mitsubishi EVO (Con. rod small end 1.000" or less)

4G63 Evo 4 - 9

Kit Part #	Bore mm / Inch	Over Sizes	Stroke	Rod Lgth.	Comp Ht.	Head cc's	Dome Dish	Gasket Thkness	Deck Clearance	Block Ht.	Comp. Ratio	Pin Part # (included)	Ring # (included)	Gram	Foot Notes
NEW! HD2 Asymmetric Skirt • 94mm Stroker • 153mm Rod • 9.3:1cr • Includes .200" wall Pins															
K667M85AP	85.00 / 3.346	Std.	3.700 94	6.023 153	1.137 28.875	43	-17	.034 0.86	.005- 0.18-	9.015 229	9.3	S782 22mm	8500XX	317	1
K667M8525AP	85.25 / 3.356	.010					-17.3						8525XX	320	
K667M855AP	85.50 / 3.366	.020					-17.7						8550XX	322	
K667M86AP	86.00 / 3.386	.040					-18.4						8600XX	331	
K667M865AP	86.50 / 3.405	.060					-19.1						8650XX	340	
K667M8675AP	86.75 / 3.405	.060					-19.4						8700XX	341	
K667M87AP	87.00 / 3.425	.080					-19.8						8700XX	347	
NEW! HD2 Asymmetric Skirt • 94mm Stroker • 153mm Rod • 10.5:1cr • .225" wall Tool Steel Pins															
K669M85AP	85.00 / 3.346	Std.	3.700 94	6.023 153	1.137 28.875	43	-10	.034 0.86	.005- 0.18-	9.015 229	10.1	S734 22mm	8500XX	311	1
K669M8525AP	85.25 / 3.356	.010					-10.25						8525XX	315	
K669M855AP	85.50 / 3.366	.020					-10.5						8550XX	317	
K669M86AP	86.00 / 3.386	.040					-11.25						8600XX	331	
K669M865AP	86.50 / 3.405	.060					-11.75						8650XX	332	
K669M8675AP	86.75 / 3.415	.070					-12.25						8700XX	336	
K669M87AP	87.00 / 3.425	.080					-12.50						8700XX	340	
NEW! 1400HD 94mm Stroker • 153mm Rod • 8.8:1cr • Includes .225" wall Tool Steel Pins															
K627M85AP	85.00 / 3.346	Std.	3.700 94	6.023 153	1.130 28.7	43	-21	.034 0.86	.011- 0.3-	9.015 229	8.8	S722 22mm	8500XX	292	1
K627M8525AP	85.25 / 3.356	.010											8525XX	294	
K627M855AP	85.50 / 3.366	.020											8550XX	299	
K627M86AP	86.00 / 3.386	.040											8600XX	305	
K627M8625AP	86.25 / 3.396	.050											8625XX	307	
K627M87AP	87.00 / 3.425	.080											8700XX	324	
K627M875AP	87.50 / 3.445	.100											8750XX	331	
1400HD 100mm Stroker • 9:1cr • Includes .225" wall Pins															
K627M85AP	85.00 / 3.346	Std.	3.937 100	5.906 150	1.130 28.7	43	-21	.034 0.86	.011- 0.3-	9.015 229	9.05 9.1 9.15 9.2 9.25 9.4 9.49	S722 22mm	8500XX	292	1
K627M8525AP	85.25 / 3.356	.010											8525XX	294	
K627M855AP	85.50 / 3.366	.020											8550XX	299	
K627M86AP	86.00 / 3.386	.040											8600XX	305	
K627M8625AP	86.25 / 3.396	.050											8625XX	307	
K627M87AP	87.00 / 3.425	.080											8700XX	324	
K627M875AP	87.50 / 3.445	.100											8750XX	331	
HD2 Asymmetric Skirt • 100mm Stroker • 9.5:1cr • Includes .200" wall Pins															
K667M85AP	85.00 / 3.346	Std.	3.937 100	5.906 150	1.137 28.875	43	-17	.034 0.86	.005- 0.18-	9.015 229	9.5	S782 22mm	8500XX	317	1
K667M8525AP	85.25 / 3.356	.010					-17.3						8525XX	320	
K667M855AP	85.50 / 3.366	.020					-17.7						8550XX	322	
K667M86AP	86.00 / 3.386	.040					-18.4						8600XX	331	
K667M865AP	86.50 / 3.405	.060					-19.1						8650XX	340	
K667M8675AP	86.75 / 3.405	.060					-19.4						8700XX	341	
K667M87AP	87.00 / 3.425	.080					-19.8						8700XX	347	
HD2 Asymmetric Skirt • 100mm Stroker • 10.5:1 • Gas Ported • .225" wall Tool Steel Pins															
K669M85AP	85.00 / 3.346	Std.	3.937 100	5.906 150	1.137 28.875	43	-10	.034 0.86	.005- 0.18-	9.015 229	10.5	S734 22mm	8500XX	311	1
K669M8525AP	85.25 / 3.356	.010					-10.25						8525XX	315	
K669M855AP	85.50 / 3.366	.020					-10.5						8550XX	317	
K669M86AP	86.00 / 3.386	.040					-11.25						8600XX	331	
K669M865AP	86.50 / 3.405	.060					-11.75						8650XX	332	
K669M8675AP	86.75 / 3.415	.070					-12.25						8700XX	336	
K669M87AP	87.00 / 3.425	.080					-12.50						8700XX	340	
4G64 Evo 4 - 9															
1400HD 100mm Stroker • 9:1cr • Includes .225" wall Tool Steel Pins															
K627M865AP	86.50 / 3.405	Std.	3.937 100	6.142 156	1.130 28.7	43	-21	.034 0.86	.011- 0.3-	9.251 235	9.25 9.4 9.49	S722 22mm	8650XX	292	1
K627M87AP	87.00 / 3.425	.010											8700XX	294	
K627M875AP	87.50 / 3.445	.040											8750XX	299	
HD2 Asymmetric Skirt • 100mm Stroker • 10.5:1cr • Gas Ported • .225" wall Tool Steel Pins															
K669M865AP	86.50 / 3.405	Std.	3.937 100	6.142 156	1.137 28.875	43	-11.75	.034 0.86	.005- 0.18-	9.251 235	10.5	S734 22mm	8650XX	311	1
K669M8675AP	86.75 / 3.415	.010					-12.25						8700XX	315	
K669M87AP	87.00 / 3.425	.020					-12.50						8750XX	317	

Foot Notes (far right column)

1 - Most Wiseco Pistons have offset pins. (Pins must be offset, same as OEM, for quietest operation).

3 - Optional pin upgrade available. See page 98 for info.



Mitsubishi EVO

4G64 with 4G63 DSM head

K548M865AP	86.50 / 3.405	Std.	3.937	5.906	1.378	43	-17	.042	0	9.251	9.8	S710	8650XX	353	1
K548M87AP	87.00 / 3.425	.020	100	150	35			1.1	0	235	9.9	22mm	8700XX	360	

Includes .200" wall pin

K626M865AP	86.50 / 3.405	Std.	3.937	5.906	1.378	43	-14	.042	0	9.251	10.3	S722	8650XX	356	1
K626M87AP	87.00 / 3.425	.020	100	150	35			1.1	0	235	10.4	22mm	8700XX		

Includes .225" wall tool steel pin

HD2 Asymmetric Skirt • EVO 4G64 • Includes .200" wall Pins.

K666M865AP	86.50 / 3.405	Std.	3.937	5.906	1.373	43	-10.8	.042	.0035	9.251	10.7	S782	8650XX	360	1
K666M8675AP	86.75 / 3.415	.010	100	150	34.875		-11.1	1.1	0.09	235		22mm	8700XX	363	
K666M87AP	87.00 / 3.425	.020					-11.4						8700XX		

HD2 Asymmetric Skirt • Gas Ported • .225" wall tool steel Pins.

K668M865AP	86.50 / 3.405	Std.	3.937	5.906	1.373	43	-4.5	.042	.0035	9.251	11.8	S734	8650XX	348	1
K668M8675AP	86.75 / 3.415	.010	100	150	34.875		-4.75	1.1	0.09	235		22mm	8700XX	350	
K668M87AP	87.00 / 3.425	.020					-5						8700XX	352	

Optional K1 Rod for 4G63, 2nd Generation Series: Part # 032CJ17150

Optional K1 4G63 Crank * 4340 Billet

Part # 032BCJ880 88mm Stroke

Part # 032BCJ940 94mm Stroke (For Stroker Custom Piston only)

Part # 032BCJ100 100mm Stroke

All have: 7-Bolt Flanges * 4G63 Main & Rod Journals * 31 lbs.

Evo 10

Kit Part #	Bore mm / Inch	Over Sizes	Stroke	Rod Lgth.	Comp Ht.	Head cc's	Dome Dish	Gasket Thkness	Deck Clearance	Block Ht.	Comp. Ratio	Pin Part # (included)	Ring # (included)	Gram	Foot Notes
4B11T Evo X 2008+															
K636M86	86.00 / 3.386	Std.									9.2		8600XX	371	
K636M865	86.50 / 3.405	.020	3.386	5.659	1.309	49	-4.5	.048	0	8.661	9.3	S752	8650XX	379	1
K636M87	87.00 / 3.425	.040	86	143.75	33.25			1.2	0	220	9.4	23mm	8700XX	382	
K636M88	88.00 / 3.464	.080									9.6		8800XX	395	

Optional K1 Rod for Mitsubishi Evo 10 4B11T: Part # 032CK21144

420A

420A Eclipse 2.0L 16V DOHC 1995-02 (Same as Neon DOHC engine)

K580M875	87.50 / 3.445	Std.	3.268	5.472	1.236	52	-5	.040	.004-	8.346	8.8	S624	8750XX	331	1, 3
K580M88	88.00 / 3.464	.020	83	139	31.4			1	0.1-	212	8.9	21mm	8800XX	339	
K580M885	88.50 / 3.484	.040									9.0		8850XX	347	
K581M875	87.50 / 3.445	Std.	3.268	5.472	1.236	52	5	.040	.004-	8.346	10.3	S624	8750XX	334	1, 3
K581M88	88.00 / 3.464	.020	83	139	31.4			1	0.1-	212	10.4	21mm	8800XX	341	
K581M885	88.50 / 3.484	.040									10.5		8850XX	349	

4G54B Starion Conquest TSI 2.5L 16V 1984-89

K555M92	92.00 / 3.622	.031	3.858	6.535	1.390	73.5	-17	.052	.028-	9.882	7.2	S625	9200XX	382	1, 3
K555M925	92.50 / 3.642	.051	98	166	35.3			1.3	0.7-	251	7.3	22mm	9250XX	396	

NEW! 4G93 & 4G94

4G93 1.8L 1997-02 Mirage / Lancer

K683M815AP	81.50 / 3.209	.020	3.504	5.250	1.190	47	-2.5 FT	.042	.027-	8.219	8.9	S622	8150XX		1, 3
K683M82AP	82.00 / 3.228	.040	89	133.25	30.25			1.07	.68-	208.75	9.0	19mm	8200XX		

Optional K1 Rod for Mitsubishi 4G93: Part # 032CN12133

4G94 2.0L 2002-05 Lancer

K683M815AP	81.50 / 3.209	Std.	3.770	6.023	1.190	49	-2.5 FT	.042	.036-	9.134	9.06	S622	8150XX		1, 3
K683M82AP	82.00 / 3.228	.020	95.8	153	30.25			1.07	0.91	231	9.15	19mm	8200XX		

Optional K1 Rod for Mitsubishi 4G94: Part # 032CM12153

6G72T 3.0L 24V 3000GT

K570M915	91.50 / 3.602	.015	2.991	5.548	1.250	48	-14	.050	.019-	8.313	7.8	S625	9150XX	343	1, 3
K570M92	92.00 / 3.622	.035	76	140.9	31.75			1.27	0.48-	211.15	7.85	22mm	9200XX	355	
K570M925	92.50 / 3.642	.055									7.9		9250XX	362	



FORGED AUTOMOTIVE RACING PISTONS • SPORT COMPACT SERIES

Nissan

Kit Part #	Bore mm / Inch	Over Sizes	Stroke	Rod Lgth.	Comp Ht.	Head cc's	Dome Dish	Gasket Thkness	Deck Clearnce	Block Ht.	Comp. Ratio	Pin Part # (included)	Ring # (included)	Gram	Foot Notes
CA18DET 1.8L 16V (Oil Squirters may require modification)															
K630M83	83.00 / 3.268	Std.									8.38		8300XX	303	
K630M835	83.50 / 3.289	.020	3.291	5.231	1.171	51	0 FT	.059	.014-	8.061	8.46	S641	8350XX	309	1, Q
K630M84	84.00 / 3.307	.040	83.6	132.87	29.75			1.5	0.36-	204.75	8.55	20mm	8400XX	312	
Optional K1 Rod for CA16DE/CA18DE: Part # 033CO14133															
FJ20															
K574M895	89.50 / 3.524	.020	3.504	5.512	1.267	49.5	-16.7				8.0:1	S625	8950XX	383	1, 3
K574M90	90.00 / 3.543	.040	80	140	32.18							22mm	9000XX	386	
SR20DE & SR20DET 180SX/200SX 2.0L 16V															
K556M86AP	86.00 / 3.386	Std.									9.0		8600XX	328	
K556M8625AP	86.25 / 3.396	.010	3.386	5.364	1.260	45	-12	.036	0	8.317	9.0	S625	8625XX	330	1,2,3
K556M865AP	86.50 / 3.405	.020	86	136.25	32			0.91	0	211.25	9.1	22mm	8650XX		
K556M87AP	87.00 / 3.425	.040									9.2		8700XX	345	
K557M86	86.00 / 3.386	Std.									10.9		8600XX	330	
K557M865	86.50 / 3.405	.020	3.386	5.364	1.260	45	0 FT	.036	0	8.317	11.0	S625	8650XX	336	1,2,3
K557M87	87.00 / 3.425	.040	86	136.25	32			0.91	0	211.25	11.1	22mm	8700XX	344	
KE233M87	87.00 / 3.425	.040	3.386	5.364	1.260	45	4	.036	0	8.317	12.0:1	S618	8700XX	330	1,2,E
			86	136.25	32			0.91	0	211.25		22mm			
SR20 & SR20DET 92mm Stroker															
K655M86	86.00 / 3.386	Std.									8.9		8600XX	316	
K655M865	86.50 / 3.405	.020	3.622	5.364	1.140	45	-17	0.036	.002-	8.317	9.0	S751	8650XX	321	1,2,3
K655M87	87.00 / 3.425	.040	92	136.25	28.95			0.91	0.051	211.25	9.0	22mm	8700XX	327	
K655M89	89.00 / 3.504	.120									9.4		8900XX	350	
Optional K1 Rod for SR20 Bushed: Part # 033CS17136															
Optional K1 Crank for SR20 Crank: Part # 032ECS920 (Strokers only)															
KA24DE 240SX 2.4L 16V 1991-98															
K586M89AP	89.00 / 3.504	Std.									8.9		8900XX	352	
K586M895AP	89.50 / 3.524	.020	3.780	6.496	1.336	46	-22	.045	.003-	9.724	9.0	S624	8950XX	358	1, 3
K586M90AP	90.00 / 3.543	.040	96	165	33.94			1.1	0.08-	247	9.0	21mm	9000XX	363	
K586M905AP	90.50 / 3.563	.060									9.1		9050XX	370	
K587M89	89.00 / 3.504	Std.									10.5		8900XX	360	
K587M895	89.50 / 3.524	.020	3.780	6.496	1.336	46	-9	.045	.003-	9.724	10.6	S624	8950XX	364	1, 3
K587M90	90.00 / 3.543	.040	96	165	33.94			1.1	0.08-	247	10.7	21mm	9000XX	369	
K587M905	90.50 / 3.563	.060									10.8		9050XX	374	
Optional K1 Rod for KA24: Part # 033CP16165															



QR25DE Sentra 2.5L 16V

K670M8900AP	89.00 / 3.504	Std.									8.4		8900XX		
K670M8950AP	89.50 / 3.524	.020	3.937	5.630	1.260	55	-19.5	.040	.020-	8.878	8.47	S623	8950XX		1, 3
K670M9000AP	90.00 / 3.543	.040	100	143	32			1.0	0.50-	225.5	8.55	20mm	9000XX		
K671M8900AP	89.00 / 3.504	Std.	3.937	5.630	1.260	55	-1.8	.040	.020-	8.878	10.36	S623	8900XX		1, 3
K671M8950AP	89.50 / 3.524	.020	100	143	32			1.0	0.50-	225.5	10.46	20mm	8950XX		
Optional K1 Rod for QR25: Part # 033CQ14143															
RB25DET Skyline 2.5L 24V															
K578M8625AP	86.25 / 3.396	.010									8.39		8625XX		
K578M865AP	86.50 / 3.405	.020	2.823	4.783	1.240	66.5	14	.040	.013+	7.421	8.43	S624	8650XX	401	1,2,3
K578M87AP	87.00 / 3.425	.040	71.7	121.5	31.5			1.0	0.33+	188.5	8.52	21mm	8700XX	406	

Foot Notes (far right column)

- 1 - Most Wiseco Pistons have offset pins. (Pins must be offset, same as OEM, for quietest operation).
 - 2 - Due to compression height that may protrude above the deck, it is recommended that a 1.00mm thick head gasket is used.
 - 3 - Optional pin upgrade available. See page 98 for info.
- E - With valve pockets online K557M Series.
Q - Oil Squirter modification required.



Nissan

Kit Part #	Bore mm / Inch	Over Sizes	Stroke	Rod Lgth.	Comp Ht.	Head cc's	Dome Dish	Gasket Thickness	Deck Clearance	Block Ht.	Comp. Ratio	Pin Part # (included)	Ring # (included)	Gram	Foot Notes
RB26DETT Skyline 2.6L 24V															
K591M86AP	86.00 / 3.386	Std.									8.1		8600XX	334	
K591M8625AP	86.25 / 3.396	.010									8.14		8625XX		
K591M865AP	86.50 / 3.405	.020	2.901	4.783	1.181	66.5	14	.045	.006-	7.421	8.18	S624	8650XX	348	1, 3
K591M87AP	87.00 / 3.425	.040	73.68	121.5	30			1.1	0.15-	188.5	8.26	21mm	8700XX	348	
K591M8725AP	87.25 / 3.435	.050									8.31		8725XX		
K591M875AP	87.50 / 3.445	.060									8.35		8750XX	360	
Optional K1 Rod for RB25 / RB26: Part # 033CR16122															
VG30DETT 300ZX 3.0L 24V 1990-96															
K549M87AP	87.00 / 3.425	Std.											8700XX	325	
K549M8725AP	87.25 / 3.435	.010	3.270	6.071	1.260	49.5	-9	.045	.005-	8.971	8.5-8.9	S625	8725XX	330	1, 3
K549M875AP	87.50 / 3.445	.020	83	154	32			1.2	0.12-	227.86		22mm	8750XX	335	
K549M88AP	88.00 / 3.464	.040											8800XX	344	
VQ35DE 3.5L 24V V6 • 350Z Maxima, Altima, and Infiniti G35 2004-06															
K605M955AP	95.50 / 3.760	Std.	3.205	5.676	1.168	57	-10	.024	.024-	8.464	8.8	S625	9550XX	354	1, 3
K605M96AP	96.00 / 3.780	.020	81.4	144.2	29.67			0.6	0.6-	215		22mm	9600XX	360	
K606M955	95.50 / 3.760	Std.	3.205	5.676	1.168	57	7	.024	.024-	8.464	11.0	S625	9550XX	375	1, 3
K606M96	96.00 / 3.780	.020	81.4	144.2	29.67			0.6	0.6-	215		22mm	9600XX	379	
Optional K1 Rod for Nissan VQ-35: Part # 033CV17144															
VQ37 3.7L 24V V6 • VHR, G37, 370Z															
K643M955	95.50 / 3.760	Std.	3.385	5.886	1.198		-15.5				9.0	S710	9550XS	365	1
K643M96	96.00 / 3.780	.020	86	149.5	29.95							22mm	9600XS	372	
Optional K1 Rod for Nissan VQ37 VHR: Part # 033CW17150															
VR38DETT 3.8L 24V V6 • Nissan GTR															
HD2 Asymmetric Skirt • 9.5:1cr • Gas Ported • Includes .225" wall tool steel pins															
K681M955AP	95.50 / 3.760	Std.	88.4	165	1.35	64.2	-1.8	.030	-.020	9.606	9.5	S789	9550XX		1
K681M9558AP	95.58 / 3.763	+.003"										23mm	9550XX	446	
NEW! HD2 Asymmetric Skirt • 10:1cr • Gas Ported • Includes .225" wall tool steel pins															
NEW	95.50 / 3.760	Std.	88.4	165	1.35	64.2	-1.8	.030	-.020	9.606	10.0	S789	9550XX		1
	95.58 / 3.763	+.003"										23mm	9550XX		
HD2 Asymmetric Skirt • 9.5:1cr • Stroker • Gas Ported • Includes .225" wall tool steel pins															
K680M955AP	95.50 / 3.760	Std.	94.4	165	1.232	64.2	-6.3	.030	-.020	9.606	9.5	S789	9550XX		1
K680M9558AP	95.58 / 3.763	+.003"										23mm	9550XX	432	

