

# Chevrolet • Small Block

## 350 23° Blower / Turbo Dish

Pistons designed for high performance street / drag race

- Designed for forced induction
- ArmorGlide® Skirt Coating
- 2618 High Strength Alloy
- .150" wall pins & Spirolox®
- .280" Top Ring Land Thickness
- Valve Pockets: Int. .280" / Exh .200"
- C/R @ 0 deck with .040" gasket
- Pin upgrade recommended over 700HP
- Anti-detonation & pressure seal grooves
- Pin fitting



Kit Part #	Bore	Comp. Ht.	Stroke	Rod	0 Deck at	Std. Deck Ht.	Avg. Wt.	Volume	Compression Ratio At:				Pin Part # (Included)	Std. Tension Rings 1/16, 1/16, 3/16 (sold separately)	Skirt Type
									58cc	62cc	66cc	70cc			
K0066A3	4.030	1.250	3.480	6.000	8.990	9.025		-20.0cc	9.4	8.9	8.4	8.2	S643 .927 x 2.250	W100F8-4030-5	Strutted
K0066A35	4.035						W100F8-4030-5								
K0066A4	4.040						W100F8-4040-5								
K0066A6	4.060						W100F8-4060-5								
K0067A3	4.030	1.125	3.750	6.000	9.000	9.025	427	-29.0cc	9.2	8.7	8.2	8.0	S643 .927 x 2.250	W100F8-4030-5	Strutted
K0067A35	4.035						W100F8-4030-5								
K0067A4	4.040						419							W100F8-4040-5	
K0067A6	4.060						427							W100F8-4060-5	
• .250" Top Ring Land Thickness on 1.062" Comp. height															
K0068A3	4.030	1.062	3.875	6.000	9.000	9.025		-32.0cc	9.2	8.7	8.3	8.1	S643 .927 x 2.250	W100F8-4030-5	Strutted
K0068A35	4.035						W100F8-4030-5								
K0068A4	4.040						W100F8-4040-5								
K0068A6	4.060						W100F8-4060-5								
• .260" Top Ring Land Thickness on 1.000" Comp. height															
K0069A3	4.030	1.000	4.000	6.000	9.000	9.025		-36.0cc	9.2	8.7	8.3	8.1	S643 .927 x 2.250	W100F8-4030-5	Strutted
K0069A35	4.035						W100F8-4030-5								
K0069A4	4.040						W100F8-4040-5								
K0069A6	4.060						W100F8-4060-5								

## 360 Sprint Car • Brodix® 11X ASCS Head

Piston designed for 360 Sprint Car or Street/Strip use

- Lateral Gas Ports
- ArmorGlide® Skirt Coating
- 2618 High Strength Alloy
- C/R @ 0 deck with .040" gasket
- Pin fitting
- Valve Pockets: Int. .320/ Exh .220
- Contoured Dome & Valve Pockets
- Anti-detonation & pressure seal grooves
- .155" wall chamfered pins & round wire locks



Kit Part #	Bore	Comp. Ht.	Stroke	Rod	0 Deck at	Std. Deck Ht.	Avg. Wt.	Volume	Compression Ratio At:				Pin Part # (Included)	Std. Tension Rings 1.2, 1.2, 3.0mm (Included)	Skirt Type
									58cc	62cc	66cc	70cc			
K0138X2	4.020	1.250	3.480	6.000	8.990	9.025		15cc	15.2	14.2	13.1	12.5	S795 .927 x 2.750	4022GFX	Slab Sided
K0138X3	4.030													4032GFX	
K0138X35	4.035													4037GFX	
K0138X4	4.040													4042GFX	
K0138X6	4.060													4062GFX	
K0139X2	4.020	1.225	3.550	6.000	9.000	9.025		15cc	15.5	14.5	13.3	12.7	S795 .927 x 2.750	4022GFX	Slab Sided
K0139X3	4.030													4032GFX	
K0139X35	4.035													4037GFX	
K0139X4	4.040													4042GFX	
K0139X6	4.060													4062GFX	

## Chevrolet • Small Block

### 350 23° Hollow Dome • Strutted High Strength • "Lil Quick 16"

Piston designed for four barrel, circle track or Street/Strip use

- Lateral Gas Ports
- ArmorGlide® Skirt Coating
- 2618 High Strength Alloy
- .150" wall pins & Spirolox®
- Pin Fitting
- .240" Top Ring Land Thickness
- Valve Pockets: Int. .310" Exh. .235"
- C/R @ 0 deck with .040" gasket
- Anti-detonation & pressure seal grooves
- Pin upgrade recommended over 700HP



Kit Part #	Bore	Comp. Ht.	Stroke	Rod	0 Deck at	Std. Deck Ht.	Avg. Wt.	Volume	Compression Ratio At:				Pin Part # (Included)	Low Tension Rings .043, .043, 3.0mm (sold separately)	Skirt Type
									58cc	62cc	66cc	70cc			
K0127B3	4.030	1.550	3.480	5.700	8.990	9.025	525	13.5cc	15.2	14.2	13.3	12.5	S424 .927 x 2.500	WG7708-4030-5	Strutted
K0127B35	4.035						527							WG7708-4030-5	
K0127B4	4.040						529							WG7708-4040-5	
K0127B6	4.060						536							WG7708-4060-5	
K0128B3	4.030	1.250	3.480	6.000	9.000	9.025	473	13.5cc	15.2	14.2	13.3	12.5	S424 .927 x 2.500	WG7708-4030-5	Strutted
K0128B35	4.035						478							WG7708-4030-5	
K0128B4	4.040						480							WG7708-4040-5	
K0128B6	4.060						486							WG7708-4060-5	
K0129B3	4.030	1.125	3.480	6.125	8.990	9.025	450	13.5cc	15.2	14.2	13.3	12.5	S424 .927 x 2.500	WG7708-4030-5	Strutted
K0129B35	4.035						455							WG7708-4030-5	
K0129B4	4.040						458							WG7708-4040-5	
K0129B6	4.060						462							WG7708-4060-5	
K0130B3	4.030	1.062	3.875	6.000	9.000	9.025	441	13.5cc	16.7	15.6	14.6	13.8	S424 .927 x 2.500	WG7708-4030-5	Strutted
K0130B35	4.035						443							WG7708-4030-5	
K0130B4	4.040						445							WG7708-4040-5	
K0130B6	4.060						451							WG7708-4060-5	

### 400 23° Blower / Turbo Dish

Pistons designed for high performance street / drag race

- .150" wall pins & Spirolox®
- ArmorGlide® Skirt Coating
- 2618 High Strength Alloy
- Designed for Forced Induction
- Pin upgrade recommended over 700HP
- Anti-detonation & pressure seal grooves
- C/R @ 0 deck with .040" gasket
- Valve Pockets Int .280" Exh .200"
- Pin Fitting

Kit Part #	Bore	Comp. Ht.	Stroke	Rod	0 Deck at	Std. Deck Ht.	Avg. Wt.	Volume	Compression Ratio At:				Pin Part # (Included)	Std. Tension Rings 1/16, 1/16, 3/16 (sold separately)	Skirt Type
									58cc	64cc	70cc	74cc			
K0070A125	4.125	1.125	3.750	6.000	9.000	9.025		-32.0cc	9.4	8.9	8.5	8.2	S424 .927 x 2.500	W100F8-4125-5	Strutted
K0070A155	4.155						476							W100F8-4155-5	
K0070A165	4.165													W100F8-4165-5	
K0071A125	4.125	1.062	3.875	6.000	9.000	9.025		-36.0cc	9.4	8.9	8.5	8.2	S424 .927 x 2.500	W100F8-4125-5	Strutted
K0071A155	4.155						427							W100F8-4155-5	
K0071A165	4.165													W100F8-4165-5	
• .220" Top Ring Land Thickness on 1.000" CH															
K0072A125	4.125	1.000	4.000	6.000	9.000	9.025		-38.0cc	9.5	9.0	8.6	8.3	S424 .927 x 2.500	W100F8-4125-5	Strutted
K0072A155	4.155													W100F8-4155-5	
K0072A165	4.165													W100F8-4165-5	

# Chevrolet • Small Block

**410 Sprint Car • All Pro® 13° / Brodix® GB2000 / Dart® 13°**

*Piston designed for circle track or Street/Strip use*

- Lateral Gas Ports
- ArmorGlide® Skirt Coating
- 2618 High Strength Alloy
- .260" Top Ring Land Thickness
- Valve Pockets Int .300" Exh .240"
- Chamfered Pins & Round Wire Locks
- Anti-detonation & pressure seal grooves
- C/R @ 0 deck with .040" gasket
- Dedicated Left & Right Hand Forgings
- Pin Fitting



Kit Part #	Bore	Comp. Ht.	Stroke	Rod	0 Deck at	Std. Deck Ht.	Avg. Wt.	Volume	Compression Ratio At:				Pin Part # (Included)	Low Tension Rings 1.2, 1.2, 3.0mm (sold separately)	Skirt Type
									48cc	52cc	58cc	62cc			
K0140XS	4.125	1.250	3.800	5.850	9.000	9.025		-2cc	15.2	14.3	13.1	12.3	S795 .927 x 2.750	4127GFX	Slab Sided
K0140X05	4.130						469							4127GFX	
K0140X1	4.135						472							4137GFX	
K0140X15	4.140													4137GFX	
K0140X2	4.145													4147GFX	
K0140X3	4.155													4158GFX	
K0141XS	4.125	1.100	3.800	6.000	9.000	9.025		-2cc	15.3	14.4	13.4	12.6	S795 .927 x 2.750	4127GFX	Slab Sided
K0141X05	4.130													4127GFX	
K0141X1	4.135						438							4137GFX	
K0141X15	4.140													4137GFX	
K0141X2	4.145													4147GFX	
K0141X3	4.155						443							4158GFX	



## Chevrolet • Small Block

### 400 18° Solid Dome • Strutted High Strength • "Lil Quick 16"

Pistons designed for high performance street / drag race

- Lateral Gas Ports
- ArmorGlide® Skirt Coating
- 2618 High Strength Alloy
- Radiused Valve Pockets
- CNC Race-ready Domes
- Pockets: Int. .290" / Exh. .260"
- Anti-detonation & pressure seal grooves
- C/R @ 0 deck with .040" gasket
- .150" Tapered Wall Tool Steel Pins & Spirolox®
- Pin Fitting



Kit Part #	Bore	Comp. Ht.	Stroke	Rod	0 Deck at	Std. Deck Ht.	Avg. Wt.	Volume	Compression Ratio At:				Pin Part # (Included)	Low Tension Rings .043, .043, 3.0mm (sold separately)	Skirt Type
									45cc	52cc	54cc	65cc			
K0031BS	4.125	1.120	3.750	6.000	8.995	9.025	476	3cc solid	15.5	13.9	13.5	11.7	S699 .927 x 2.500	WG7708-4125-5	Strutted
K0031B05	4.130													WG7708-4125-5	
K0031B1	4.135						476							WG7708-4135-5	
K0031B15	4.140													WG7708-4135-5	
K0031B2	4.145													WG7708-4145-5	
K0031B3	4.155						484							WG7708-4155-5	
K0031B4	4.165						486							WG7708-4165-5	
K0031B6	4.185	1.062	3.875	6.000	9.000	9.025	492	3cc solid	16.2	14.6	14.1	12.3	S699 .927 x 2.500	WG7708-4185-5	Strutted
K0030BS	4.125						457							WG7708-4125-5	
K0030B05	4.130						460							WG7708-4125-5	
K0030B1	4.135						462							WG7708-4135-5	
K0030B15	4.140						465							WG7708-4135-5	
K0030B2	4.145						467							WG7708-4145-5	
K0030B3	4.155						468							WG7708-4155-5	
K0030B4	4.165	1.000	4.000	6.000	9.000	9.025	470	3cc solid	16.7	15.0	14.6	12.6	S699 .927 x 2.500	WG7708-4165-5	Strutted
K0030B6	4.185						474							WG7708-4185-5	
K0029BS	4.125						443							WG7708-4125-5	
K0029B05	4.130													WG7708-4125-5	
K0029B1	4.135						448							WG7708-4135-5	
K0029B15	4.140													WG7708-4135-5	
K0029B2	4.145						446							WG7708-4145-5	
K0029B3	4.155	1.000	4.000	6.000	9.000	9.025	452	3cc solid	16.7	15.0	14.6	12.6	S699 .927 x 2.500	WG7708-4155-5	Strutted
K0029B4	4.165						453							WG7708-4165-5	
K0029B6	4.185						458							WG7708-4185-5	





# Chevrolet • Small Block

## 400 23° Hollow Dome • Strutted High Strength • "Lil Quick 16"

Pistons designed for high performance street / drag race

- Lateral Gas Ports
- ArmorGlide® Skirt Coating
- 2618 High Strength Alloy
- Radiused Valve Pockets
- Pockets: Int. .325" / Exh. .250" (except K0033 .310" Int.)
- Anti-detonation & pressure seal grooves
- .150" Wall Pins & Spirolox®
- Pin upgrade recommended over 700HP
- CNC Race-ready Domes
- C/R @ 0 deck with .040" gasket
- Pin Fitting

Kit Part #	Bore	Comp. Ht.	Stroke	Rod	0 Deck at	Std. Deck Ht.	Avg. Wt.	Volume	Compression Ratio At:				Pin Part # (Included)	Low Tension Rings .043, .043, 3.0mm (sold separately)	Skirt Type
									58cc	62cc	67cc	76cc			
K0033BS	4.125						499							WG7708-4125-5	
K0033B05	4.130						500							WG7708-4125-5	
K0033B15	4.140													WG7708-4135-5	
K0033B2	4.145	1.120	3.750	6.000	8.995	9.025		13.5cc	14.8	14.0	13.0	11.6	S424 .927 x 2.500	WG7708-4135-5	Strutted
K0033B3	4.155						507							WG7708-4155-5	
K0033B4	4.165						508							WG7708-4165-5	
K0033B6	4.185						514							WG7708-4185-5	
K0034BS	4.125						477							WG7708-4125-5	
K0034B05	4.130													WG7708-4125-5	
K0034B15	4.140													WG7708-4135-5	
K0034B2	4.145	1.060	3.875	6.000	8.998	9.025		12.0cc	15.1	14.2	13.3	11.9	S424 .927 x 2.500	WG7708-4135-5	Strutted
K0034B3	4.155						485							WG7708-4155-5	
K0034B4	4.165						469							WG7708-4165-5	
K0034B6	4.185						475							WG7708-4185-5	
K0032BS	4.125						458							WG7708-4125-5	
K0032B05	4.130													WG7708-4125-5	
K0032B15	4.140													WG7708-4135-5	
K0032B2	4.145	1.000	4.000	6.000	9.000	9.025		10.0cc	15.2	14.3	13.4	12.0	S424 .927 x 2.500	WG7708-4135-5	Strutted
K0032B3	4.155						465							WG7708-4155-5	
K0032B4	4.165						469							WG7708-4165-5	
K0032B6	4.185						475							WG7708-4185-5	

