DECK 1 OF 10 · FRC JAVA CRASH COURSE

Your first robot program

A command-based Java program, built from WPILib’s template

WPILib 2026 · Java · Command-based

OVERVIEW

What this deck covers

One small program: hold a button and a motor spins. It starts from WPILib's Command Robot template, the base for every project in these decks.

- How WPILib and command-based code fit together.
- A new project from the Command Robot template.
- A first binding, tested in the simulator with no robot.
- One subsystem and one motor, running on a robot.

WPILIB

Your code and WPILib run on the roboRIO



“The standard software library provided for teams to write code for their FRC robots.”

COMMAND-BASED

The parts of a command-based program

WPILib builds the pattern around two core abstractions: **commands** and **subsystems**.

Command

An action the robot can take. It runs when scheduled, until interrupted or finished.

Subsystem

Robot hardware that operates together. Only one command can use it at a time.

Trigger

An event, such as a button press. Binding a command to it schedules that command.

CommandScheduler

The WPILib class that runs commands. Scheduling a command adds it to the running list.

COMMAND-BASED

Command-based code declares what should happen

Checking the button every loop

```
if (condition.get()) {
  if (!pressed) {
    piston.set(
        DoubleSolenoid.Value.kForward);
    pressed = true;
  }
} else {
  pressed = false;
}
```


Declaring it once

```
new Trigger(condition::get)
    .onTrue(Commands.runOnce(
        () -> piston.set(
            DoubleSolenoid.Value.kForward)));
```


WPILib docs: What Is “Command-Based” Programming?

CONTROL THEORY

The scheduler reads, decides and acts every 20 ms



The four steps are WPILib's Scheduler Run Sequence. Step 2 reads the buttons and starts bound commands. Step 3 runs every scheduled command.

WPILib docs: The Command Scheduler

PROJECT

Creating a project from the Command Robot template

In **2026 WPILib VS Code**, press Ctrl+Shift+P, type WPILib and choose **Create a new project**. Fill in the form, click **Generate Project**, open the project, and click **Yes I trust the authors**.



Screenshot: WPILib documentation, CC BY 4.0.

1. **Project type:** Template
2. **Language:** Java
3. **Project base:** Command Robot
4. **Base folder:** any folder outside OneDrive
5. **Project name:** your choice
6. **Create a new folder:** leave it ticked
7. **Team number:** your team's number
8. **Enable Desktop Support:** tick it

PROJECT

The files in a command-based project

In src/main/java/frc/robot	What it is for	In this deck
Main.java	The main robot application	WPILib says not to touch it
Robot.java	Main control flow, and the scheduler call	No changes
RobotContainer.java	Holds subsystems, commands and button bindings	Both programs go here
Constants.java	Globally accessible constants	The motor ID and speed
subsystems/	Your subsystem classes	RollerSubsystem
commands/	Your command classes	Not needed in this deck

WPILib docs: Structuring a Command-Based Robot Project

FIRST PROGRAM

Java terms used in this deck

Term	What it is	Example in the template
class	A named block of code, usually one per file	RobotContainer
field	A value that a class keeps	m_driverController
method	A named action, called with parentheses	configureBindings()
import	Tells a file where to find a class	import …button.Trigger;
lambda	Code passed to a method, to run later	() -> { }

FIRST PROGRAM

One binding in RobotContainer

RobotContainer.java

```
private void configureBindings() {
  // Schedule `ExampleCommand` when `exampleCondition` changes to `true`
  new Trigger(m_exampleSubsystem::exampleCondition)
      .onTrue(new ExampleCommand(m_exampleSubsystem));

  // Schedule `exampleMethodCommand` when the Xbox controller's B button is pressed,
  // cancelling on release.
  m_driverController.b().whileTrue(m_exampleSubsystem.exampleMethodCommand());


  // Print a message when the A button is pressed.
  m_driverController.a()
      .onTrue(Commands.print("Hello, robot"));
}
```

Add import edu.wpi.first.wpilibj2.command.Commands; at the top of the file. .a() is a Trigger for the A button, and onTrue schedules the command once per press.

FIRST PROGRAM

Running the program in the simulator

Run WPILib: Simulate Robot Code, keep **Sim GUI** selected and press **Ok**.



Screenshot: WPILib documentation, CC BY 4.0. Robot State now also has a Disconnected row.

3 **System Joysticks**
Drag **Keyboard 0** from this window.

6 **Joysticks**
Drop it on Joystick[0], which is port 0.

1 **Robot State**
Click **Teleoperated**.

Z **The Z key**
Click the simulator window, then press Z. Keyboard 0 sends button 1, the A button, and Hello, robot prints in the VS Code terminal.

COMMON MISTAKE

The build fails with cannot find symbol

What you see	error: cannot find symbol, pointing at Commands, then BUILD FAILED.
Why it happens	Java only knows a class if the file imports it, and this file has no import for Commands.
The fix	Add the import at the top of the file. The first error names the file and the line.

```
RobotContainer.java:37: error: cannot find symbol
        .onTrue(Commands.print("Hello, robot"));
                ^
  symbol:   variable Commands
```

EXERCISE

Print from two buttons


1. Add the import and the binding, then run WPILib: Simulate Robot Code.
2. Drag **Keyboard 0** onto Joystick[0] and click **Teleoperated**.
3. Press **Z** and read the message in the VS Code terminal.
4. Close the simulator. Add a binding on .x() with a different message.
5. Run it again. On Keyboard 0, the **C** key is the X button.

Done when: Z and C print two different messages.

ONE MOTOR

REVLib: the vendor library for a SPARK MAX

A vendor dependency is how a vendor adds its library to a robot project. WPILib does not include code for the SPARK MAX.



WPILib documentation, CC BY 4.0. Versions shown are older.

1. **Open the Dependency Manager**
   Click the WPILib logo in the activity bar, on the left of VS Code.

2. **Find REVLib**
   Scroll down the Available Dependencies list.

3. **Click Install**
   The library's file is copied into this project's vendordeps folder.

4. **Click back in the editor**
   VS Code builds the project when the panel loses focus.

BEST PRACTICE

Give every number a name in Constants

> **Put CAN IDs and speeds in Constants.java, not in the middle of the code.**

The template includes this class for robot-wide constants. Add this inside it, and set kMotorId to the CAN ID of your SPARK MAX.

```
public static class RollerConstants {
  // The feeder roller on the 2026 KitBot. Must match REV Hardware Client 2.
  public static final int kMotorId = 6;

  // Output from -1 to 1. 0.3 is 30% of battery voltage.
  public static final double kSpeed = 0.3;
}
```

ONE MOTOR

A subsystem with one motor

subsystems/RollerSubsystem.java

```java
import static frc.robot.Constants.RollerConstants.*;
import com.revrobotics.spark.SparkLowLevel.MotorType;
import com.revrobotics.spark.SparkMax;
import edu.wpi.first.wpilibj2.command.Command;
import edu.wpi.first.wpilibj2.command.SubsystemBase;

1 public class RollerSubsystem extends SubsystemBase {
2   private final SparkMax m_motor =
2       new SparkMax(kMotorId, MotorType.kBrushed);

3   public Command spinCommand() {
      return startEnd(
4         () -> m_motor.set(kSpeed),
4         () -> m_motor.set(0));
    }
  }
```

1. **SubsystemBase**
   WPILib's recommended base class. It registers the subsystem with the scheduler.

2. **Private hardware**
   Only this class can use the motor. A CIM is kBrushed.

3. **A command factory**
   A method that returns a command. WPILib ends these names in Command.

4. **startEnd**
   First lambda when scheduled, second when canceled.

ONE MOTOR

Binding the motor to the A button

RobotContainer.java

```
import frc.robot.subsystems.RollerSubsystem;

// The robot's subsystems and commands are defined here...
private final ExampleSubsystem m_exampleSubsystem = new ExampleSubsystem();
private final RollerSubsystem m_roller = new RollerSubsystem();

private void configureBindings() {
  // The template's two bindings stay here.

  m_driverController.a()
      .whileTrue(m_roller.spinCommand());
}
```

This replaces the Hello, robot line. whileTrue schedules the command on press and cancels it on release.

ONE MOTOR

Three trigger bindings from WPILib

Binding	When the button is pressed	When it is released
onTrue	Schedules the command	Nothing: the command runs until it ends
whileTrue	Schedules the command	Cancels the command
toggleOnTrue	Schedules it, or cancels it if running	Nothing

Commands.print ends by itself, so onTrue suits it. A startEnd command never ends by itself, so it needs whileTrue.

EXERCISE


Add the motor to the program

1. Install **REVLib** from the Dependency Manager.
2. Add RollerConstants inside Constants, with your SPARK MAX's CAN ID.
3. Right-click the subsystems folder, choose **Create a new class/command**, then **Subsystem**. Name it RollerSubsystem.
4. Keep its package line, and replace the rest with the subsystem code.
5. Add the field and the whileTrue binding, then run WPILib: Build Robot Code.

Done when: the terminal shows BUILD SUCCESSFUL.

CONTROL THEORY

The program reads the button once every 20 ms



1. **Press**
   Pressed at 33 ms. The 40 ms loop sets the output to 0.3.

2. **Release**
   Released at 93 ms. The 100 ms loop sets it to 0.

3. **Sample time**
   A change waits for the next loop, up to 20 ms.

4. **Open loop**
   The code sets an output. Nothing measures the roller.

WPILib docs: The Command Scheduler

ON THE ROBOT

Deploying the program to the roboRIO

1. **Turn the robot on**
   Stay clear of moving parts from now on.

2. **Connect the laptop to the roboRIO**
   USB or Ethernet.

3. **Plug the controller into the laptop**

4. **Run WPILib: Deploy Robot Code**
   It builds if needed, then sends the program.

5. **Look for BUILD SUCCESSFUL**
   Keep the robot on until then.




Building and deploying

docs.wpilib.org: Building and Deploying Robot Code

ON THE ROBOT

Running the robot from Driver Station



Screenshot: WPILib documentation, CC BY 4.0. The lights are red here because no robot is connected.

FRC Driver Station
Open it, and enter your team number on the Setup tab (gear icon).

Three green lights
Communications, Robot Code and Joysticks.

1 Robot Mode
Choose **TeleOperated**.

2 Enable, Disable
Enter disables. Space is the emergency stop.

EXERCISE

Spin the motor

1. Deploy the program, open Driver Station and get three green lights.
2. Stand clear of the motor and anything it drives.
3. Choose **TeleOperated**, say “enabling” out loud, then click **Enable**.
4. Hold **A**, then release it.
5. Press Enter to disable.

Done when: the motor spins only while A is held.

RECAP

What this deck covered

- WPILib, commands, subsystems, triggers and the CommandScheduler.
- A project from the Command Robot template, and the files in it.
- A binding tested in the simulator.
- A subsystem with one motor, using a vendor library.
- Deploying the program and running it from Driver Station.

Next: Deck 2 uses the same parts to drive the KitBot from a gamepad.

REFERENCE

Official docs



Create a project

docs.wpilib.org: Zero to Robot, Step 4



What is command-based

docs.wpilib.org: Command-Based Programming



Binding to triggers

docs.wpilib.org: Binding Commands to Triggers



Running the program

docs.wpilib.org: Running your Test Program