



Incident report analysis

Instructions

As you continue through this course, you may use this template to record your findings after completing an activity or to take notes on what you've learned about a specific tool or concept. You can also use this chart as a way to practice applying the NIST framework to different situations you encounter.

Summary	The company experienced a DDoS attack, which compromised the internal network for two hours until it was resolved. During the attack, network services suddenly stopped responding due to an incoming flood of ICMP packets. Normal internal network traffic could not access any network resources. The team responded by blocking incoming ICMP packets, stopping all non-critical network services offline, and restoring critical network services.
Identify	The cybersecurity team investigated the security event. They found that a malicious actor had sent a flood of ICMP pings into the company's network through an unconfigured firewall.
Protect	The security team implemented a new firewall rule to limit the rate of incoming packets and an IDS/IPS system to filter out some ICMP traffic based on suspicious characteristics.
Detect	The Team Configured source ip address verification on firewall to check for spoofed IP addresses on incoming ICMP packets and implemented network monitoring software to detect abnormal traffic patterns.
Respond	In response to future security incidents, the cybersecurity team will promptly contain and isolate compromised systems to minimize further impact on the

	network. Their next priority will be to restore essential systems and services that may have been disrupted. Following recovery efforts, the team will conduct a thorough review of network logs to identify any unusual or suspicious activity. Finally, all incidents will be documented and reported to senior management, and when necessary, communicated to the appropriate legal or regulatory authorities.
Recover	To recover from an ICMP flooding DDoS attack, the first step is to restore network services so they operate normally again. Moving forward, future ICMP flood attempts can be prevented by configuring the firewall to block them. During the recovery process, non-essential services should be temporarily shut down to reduce unnecessary internal traffic. Priority should then be given to bringing critical systems and services back online. Once the attack traffic has subsided, the remaining non-essential services can be safely reactivated.

Reflections/Notes: