Beyond Hallucination Detection: Measuring Consequential Uncertainty in LLM-Generated Code

Michael Jaquith
Independent Researcher
michael.j.jaquith@gmail.com

April 2026

Abstract

Large language models generate code that looks uniformly confident. A correct call to `stripe.PaymentIntent.create()` and a deprecated call to `stripe.Charge.create()` are emitted with the same surface tone, even when the underlying token distribution is a near-50/50 split (probability 0.52 vs. 0.47). Code-generation uncertainty is primarily *intra-generational*: visible in the token distribution at generation time, invisible once tokens are committed. Multi-sample methods, which detect inter-generational inconsistency, therefore produce almost no signal on code tasks.

We introduce ε, a per-token normalized Shannon entropy computed from the top-k log-probabilities returned by the generation API, aggregated over the semantic tokens of a function via AST filtering and max-pooling. ε is designed as a *recall-maximizing filter*, not a detector. On a 30-prompt calibration benchmark across GPT-4o, GPT-4o-mini, GPT-4-turbo, and DeepSeek V3, ε at the FLAGGED threshold ($\varepsilon \geq 0.30$) achieves recall = 1.00 on true failures with precision = 0.272. The black-box multi-sample baseline UQLM detects 5% of version-split API failures (with 0% false positives on simple logic prompts), versus ε's 85% detection at 50% false-positive rate on GPT-4o; a `min_logprob` baseline achieves 45–55% where ε achieves 70–85%.

The low stage-1 precision is the design. We pair the filter with a parallel LLM review loop that reclassifies each flagged entry as CLEARED or CONFIRMED. On 201 production and scenario entries across three models, a variant that injects model-specific learned false-positive patterns into the reviewer clears 68.7% of flagged entries with zero late false positives, lifting end-to-end precision above 94% (Wilson lower bound, $n = 57$). The contribution is the system: a filter that misses nothing, paired with a reviewer that keeps up with machine-speed code generation.

1 Introduction

A model asked to charge a credit card might emit `stripe.Charge.create(...)` — deprecated since 2019 — or `stripe.PaymentIntent.create(...)`, the current API. Both arrive in the developer's editor with the same syntactic fluency, the same confident indentation, and no visible marker distinguishing a well-chosen call from one the model guessed at. At the method-selector token, the two choices split the probability mass near 50/50 (0.52 vs. 0.47); the output exposes none of this. Failures of AI code generation cluster at exactly these points: version-split APIs, renamed SDK methods, signature changes between library releases. The model is uncertain; the output is not.

Intra- versus inter-generational uncertainty. Existing uncertainty-quantification methods for LLMs are overwhelmingly *inter-generational*: they sample the same prompt multiple times

and measure disagreement across completions [9, 3]. This works when the model's uncertainty surfaces as instability across re-rolls — factual questions, open-ended reasoning. Code is not such a task. A model with a 0.52 prior on the deprecated `Charge` API samples that branch nearly every time; once the early tokens commit, the rest of the function is forced by context. The uncertainty exists, but it lives *inside a single generation*, in the token distribution at each decoding step, not *across* generations. We call this the *intra- versus inter-generational* distinction. It is the conceptual foundation of this paper: UQLM, the closest published tool for LLM uncertainty quantification, achieves 5% detection on our benchmark where ε achieves 85% (§5).

ε: a recall-maximizing filter. We introduce ε (epsilon), a per-token normalized Shannon entropy over the top-k log-probabilities returned during generation. After AST-based filtering to keep only semantically meaningful tokens (attribute accesses, keyword arguments, import targets — not whitespace, comments, or cosmetic identifiers), we aggregate via max-pooling to obtain a single score per function. ε is not a detector — it identifies where the model was uncertain at decoding time. At a threshold of $\varepsilon \geq 0.30$ it catches 100% of true failures on our benchmark, at the cost of roughly 73% false alarms.

The two-stage system. A 27%-precision filter is not meant to be used in isolation. Stage 2 is a parallel LLM review loop: every flagged entry is dispatched, in parallel, to a reviewer model that returns CLEARED or CONFIRMED. At current API prices this costs fractions of a cent per entry and completes in seconds. ε has perfect recall but poor precision; the reviewer has good precision but would be too expensive per line. Filter plus reviewer gives a system with near-100% end-to-end precision while missing nothing the filter catches. AI-assisted developers now write code several times faster than they can review it; a parallel review system scales with generation speed and moves review off the developer's critical path.

Contributions.

1. The intra/inter-generational distinction, with empirical confirmation: 5% vs. 85% detection for UQLM vs. ε on the same benchmark.
2. ε: an AST-filtered, max-aggregated token-level entropy score, with a three-type uncertainty taxonomy (cosmetic, consequential, implementation-approach) that motivates the filter design.
3. A two-stage filter-plus-review architecture, with a context-accumulation variant, evaluated on 201 entries across three models (GPT-4o, GPT-4o-mini, DeepSeek V3): near-100% end-to-end precision at 100% recall. Scenario and calibration evaluation additionally covers GPT-4-turbo (four models total).

Implementation and benchmark are at `https://github.com/michaeljaquith/epsilon-code`.

2 Related Work

2.1 LLM Uncertainty Quantification

Semantic entropy. Kuhn et al. [9] introduce semantic entropy as a method for detecting hallucinations in free-form text generation. Multiple responses to the same prompt are generated and clustered by semantic equivalence (via natural language inference); high entropy across clusters indicates uncertainty. The method is principled and effective for factual question answering, where model uncertainty produces cross-generation variance. As we show in Section 5, this variance is not

present for code generation API decisions: models generate the same (potentially wrong) API call across all samples.

UQLM. The UQLM library [3] provides open-source implementations of multiple uncertainty scoring methods for LLM outputs, including semantic negentropy, semantic clustering, and conformal prediction wrappers. It is the closest published tool to our work and serves as our primary baseline. Our direct comparison (Section 5) shows 5% detection rate (1 of 20 high-uncertainty prompts) compared to 85% for ε.

Conformal prediction for LLMs. Quach et al. [10] and Angelopoulos et al. [1] apply conformal prediction to construct prediction sets with coverage guarantees over LLM outputs. The approach is statistically rigorous but produces set-valued predictions over outputs rather than within-generation token-level signals. It also requires a calibration dataset and does not provide the localization (which token, which line, which function) that makes ε actionable for code review.

Token-level calibration. Kadavath et al. [8] show that LLMs are reasonably well-calibrated at the token level: stated confidence correlates with accuracy. Varshney et al. [11] use token-level log-probabilities for selective generation, abstaining when confidence is low. Our work extends this line by identifying *which* tokens carry meaningful uncertainty in code — specifically, by filtering out cosmetic naming decisions that dominate naive entropy measurements. Uncertainty propagation through multi-stage ML pipelines is well-studied in adjacent domains [7]; the ε primitive is designed to support analogous propagation in code generation pipelines, deferred to future work.

Code generation uncertainty and self-consistency. Concurrent approaches to code generation quality estimation include test-based ranking (CodeT [4] generates tests and ranks candidate solutions by pass rate) and repeated-sampling self-consistency (AlphaCode-style approaches use pass@k as an implicit uncertainty proxy). These methods are inter-generational by construction: they require multiple independent samples and aggregate across them. They are therefore subject to the same structural limitation as UQLM for the problem we study — a model that consistently generates the same API version across samples will produce consistent test outcomes regardless of whether the API version is correct. Our approach is complementary: it operates within a single generation and is zero-overhead.

2.2 Code Generation Quality

Recent work on evaluating LLM code generation quality focuses primarily on functional correctness via execution-based benchmarks (HumanEval [5], MBPP [2], SWE-bench [6]). These benchmarks measure whether generated code passes test cases, not whether the model was confident in its decisions. A model that passes all tests with low ε is reliable; a model that passes all tests with high ε on specific API decisions may be one dependency update away from failure.

To our knowledge, no prior work treats within-generation token-level uncertainty as a first-class signal for code generation risk. The closest work is in automated program repair, where uncertainty has been used to rank repair candidates [12], but this operates post-generation and does not address the intra-generation measurement problem we identify.

3 ε: Definition and Construction

3.1 Per-token entropy

For each generated token t, the API returns top-k candidates with log-probabilities $\ell_1, \ldots, \ell_k$. Let $p_j = \exp(\ell_j)/\sum_j \exp(\ell_j)$ be the renormalized distribution. Define

$$\varepsilon_t \;=\; -\frac{1}{\log k}\sum_{j=1}^{k} p_j \log p_j \;\in\; [0,1]. \tag{1}$$

Normalization by $\log k$ maps a one-hot distribution to 0 and a uniform distribution to 1. We use $k = 5$ (the OpenAI cap), which covers the dominant mass for code tokens; tails beyond top-5 are negligible for the binary flag decision. The name is deliberate: in numerical analysis, ε denotes a small perturbation that propagates through a computation — a high-ε token is such a perturbation at a specific decision point.

3.2 Three types of code-generation uncertainty

Empirical analysis of our calibration benchmark reveals three categorically distinct types of token-level uncertainty in generated code.

Type 1 — Cosmetic (naming). Uncertainty about what to *call* something (`sort_list` vs. `sort_numbers`). ε reaches 0.7–0.9, but any choice is correct. Dominates LOW prompts: the top flag on 9 of 10 LOW prompts was a function or parameter name on the first line.

Type 2 — Consequential (API/library decisions). Uncertainty about which *API or library* to use. Example: `stripe.Charge.create()` (prob. 0.52) vs. `stripe.PaymentIntent.create()` (prob. 0.47), $\varepsilon = 0.73$ at the attribute token. This is the target signal.

Type 3 — Implementation-approach. Uncertainty among multiple correct algorithms (recursive vs. iterative Fibonacci, for-loop vs. comprehension). The residual false-positive floor on simple utility prompts.

Only Type 2 correlates with functional failure. Type 1 is removable by AST filtering; Type 3 reflects real decoder uncertainty on correct code and constitutes the irreducible false-positive floor.

3.3 AST filtering

We eliminate Type 1 via the generated code's AST. After stripping markdown fences and parsing with Python's `ast`, we identify *declaration positions* — source ranges where the model is choosing a name rather than an API. **Filtered:** function/method names, parameter names (`ast.arg`), local variable names (`ast.Name` in `Store`). **Retained:** import targets, attribute accesses, keywords, type annotations. Token-to-declaration matching uses range overlap (BPE introduces a leading space); a pure-identifier guard prevents over-filtering of delimiter-prefixed tokens such as `(db`.

3.4 Aggregation: max vs. mean

We aggregate with $\varepsilon_{\text{file}} = \max\{\varepsilon_t : t \text{ retained}, \varepsilon_t > \delta\}$, $\delta = 0.30$. The compound alternative $1 - \prod(1 - \varepsilon_t)$ converges to 1.0 for any non-trivial function. Across all 90 runs of the benchmark (3×30), max and mean produced identical fire/no-fire decisions at every threshold; we prefer max because it localizes uncertainty to a specific actionable token.

Type	Label	Source	ε fires?	Risk
1	Cosmetic	Naming choices (`sort_list` vs `sort_numbers`)	Yes (0.7–0.9)	None
Filter: AST declaration filter removes this uncertainty before scoring.				
2	Consequential	API/library decisions (`Charge` vs `PaymentIntent`)	Yes (0.5–0.9)	**High**
Note: Target signal — this is what the system is designed to catch.				
3	Implementation	Algorithm structure (recursive vs. iterative)	Yes (0.3–0.7)	None
Note: Irreducible FP floor; rare in production API-integration code.				

Table 1: The three-type uncertainty taxonomy. Type 2 is the target signal; Type 1 is removed by AST filtering; Type 3 is the irreducible false-positive floor.

Configuration	LOW FP rate
Naive token entropy (no filtering)	90%
+ Whitespace / comment filtering	90%
+ System prompt naming conventions	60%
+ AST declaration filtering	60%
+ Fence-format stripping	50%
Residual (Type 3 only)	50%

Table 2: Successive filtering stages on 10 LOW prompts. Naming-convention prompt and AST filter are partially overlapping; without the prompt, AST filtering alone drops FP from 90% to 70%. Residual 50% is Type 3, rare in production API-integration code.

3.5 Thresholds and tiers

Three tiers: COMPLETE ($\varepsilon < 0.30$), FLAGGED ($0.30 \leq \varepsilon < 0.95$), PAUSED ($\varepsilon \geq 0.95$). An earlier version of this system used a four-tier scheme that split FLAGGED and PAUSED at 0.65, but both tiers triggered identical system behavior — routing to the same parallel reviewer — so we merged them. PAUSED is now reserved for genuinely extreme uncertainty ($\varepsilon \geq 0.95$). Whether PAUSED actually holds code delivery until the review completes, or simply runs the review loop like FLAGGED, is a deliberate design choice left to the implementer; this paper notes the possibility but does not prescribe it. These are UX signals, not calibrated probabilities — the FLAGGED empirical failure rate is $\sim 27\%$ (§4); PAUSED fires rarely enough in our evaluation that its failure rate is a small-sample estimate. The load-bearing boundary is the binary COMPLETE vs. FLAGGED+: everything FLAGGED+ is forwarded to the stage-2 reviewer. In our qualitative scenarios A–D across four models, no HIGH prompt crossed the PAUSED threshold; PAUSED is a design boundary that exists but was not exercised on the scenarios in this work.

3.6 Adaptive ensemble

The production implementation refines tier placement within FLAGGED+ using a rolling mean-ε baseline and a top-1 logprob check; neither affects the binary FLAGGED+ gate. Conformal calibration is left to future work.

4 Evaluation

4.1 Qualitative scenarios

Five scenarios exercise distinct failure modes. Scenarios A–D are run across four models (GPT-4o-2024-08-06, GPT-4o-mini, GPT-4-turbo, DeepSeek V3) with `logprobs=True, top_logprobs=5`, temperature = 0, and a system prompt specifying concise naming conventions. Scenario E is evaluated on GPT-4o across 16 independent runs.

		ε (tier)			
	Scenario	GPT-4o	GPT-4o-mini	GPT-4-turbo	DeepSeek V3
A	Stripe deprecation	0.878 F	0.665 F	0.680 F	0.775 F
B	OpenAI SDK v0 vs v1	0.560 F	0.487 F	0.678 F	0.646 F
C	SQLAlchemy 1.x vs 2.0	0.907 F	**0.000** C	0.911 F	0.925 F
D	FastAPI async/sync	0.505 F	0.506 F	0.774 F	0.679 F

Table 3: Scenarios A–D across four models. F = FLAGGED ($0.30 \leq \varepsilon < 0.95$); C = COMPLETE ($\varepsilon < 0.30$). All 15 of 16 cells are FLAGGED; the lone miss is GPT-4o-mini on SQLAlchemy, where the model committed to one version with no hesitation ($\varepsilon = 0.000$) — a genuine false negative. No HIGH prompt crossed the PAUSED threshold ($\varepsilon \geq 0.95$) in this sweep.

A — Deprecated API (Stripe). *"Charge a customer's card for $50."* GPT-4o: $\varepsilon = 0.878$, FLAGGED. The peak token is the method selector after `stripe`: `.Ch` (`Charge`, prob. 0.52) vs. `.Payment` (`PaymentIntent`, prob. 0.47). Both paths are in the training data; neither is definitively preferred. All four models flag.

B — Confident wrongness (OpenAI SDK). *"Call GPT-4 and return the response text."* GPT-4o: $\varepsilon = 0.560$, FLAGGED. The model generated v0 (`openai.ChatCompletion.create(...)`) confidently; v0 raises `AttributeError` on SDK ≥ 1.0. ε fired not on the API call — the model was certain at that token — but on surrounding parameter design. FLAGGED routes the function to the review loop; the reviewer, examining the full function, surfaces the deprecated call. This is indirect detection: ε flagged adjacent uncertainty, not the failing token itself. All four models flag.

C — Syntax split (SQLAlchemy). *"Query all active users."* GPT-4o: $\varepsilon = 0.907$, FLAGGED, near the top of the FLAGGED range — the model is highly uncertain which SQLAlchemy version to target. GPT-4-turbo and DeepSeek V3 produce similarly high ε (0.911, 0.925). GPT-4o-mini, however, produces $\varepsilon = 0.000$ (COMPLETE): it commits to one version with no visible hesitation. This is a genuine false negative — the same prompt that surfaces uncertainty in three models of four generates confidently-chosen output in the fourth. The cross-model contrast is the interesting finding: intra-generational signal exists only when the model itself is uncertain, and training-data convergence on one branch silently removes it.

D — Compatibility mismatch (FastAPI async/sync). *"FastAPI endpoint that fetches weather from an external API."* GPT-4o: $\varepsilon = 0.505$, FLAGGED (solidly mid-range); GPT-4-turbo is highest at 0.774. The model generated `async def` with `requests.get()` inside — two individually defensible decisions that combine into a silent bug (blocks the event loop). The cross-decision mismatch is not directly what ε measures: ε sees token-level uncertainty, which in this scenario fires

on surrounding choices (URL and key handling) rather than on the async/sync combination itself. A mismatch post-processor, run on already-flagged functions, can surface the combination explicitly — arguing for cross-decision consistency checks as a complement to ε. The practical outcome is unchanged: the function is FLAGGED and reaches the reviewer.

E — Multi-function module. Six auth functions with four interdependent decisions (password hash, JWT, SQLAlchemy, datetime). FLAGGED on all 16 runs, $\varepsilon \in [0.69, 0.92]$ (none crossed PAUSED). Library choices varied across runs (passlib, bcrypt, PyJWT, python-jose, mixed), but each run looked internally confident. Early functions $\varepsilon = 0.40$–0.58; later functions frequently $\varepsilon = 0.000$ — an *uncertainty collapse* after initial commitment. The first function is the high-risk window.



Figure 1: Scenarios A–E (GPT-4o) summarised by failure class and peak ε. All five clear the FLAGGED threshold; none crosses the PAUSED threshold ($\varepsilon \geq 0.95$). The scalar urgency signal within FLAGGED still varies across scenarios.

4.2 Scenario E limitation: joint-prompt uncertainty collapse

Scenario E's detection success holds when the six functions are generated independently. When generated in a *single* prompt with "use a consistent library," ε collapses across all six functions — not just the later ones. The joint signature list plus the consistency instruction resolves the library choice before decoding starts, leaving nothing for ε to observe (Table 4, GPT-4o-mini).

Function	GPT-4o-mini Combined	GPT-4o-mini Per-fn	DeepSeek V3 Combined	DeepSeek V3 Per-fn
`register_user`	0.579	0.627	0.424	0.864
`login`	0.820	0.872	0.518	0.972
`verify_token`	0.606	0.911	0.372	0.735
`refresh_token`	0.414	0.711	0.503	0.957
`request_password_reset`	**0.295**	0.788	0.764	0.760
`reset_password`	0.394	0.728	0.419	0.878

Table 4: Combined generation reduces per-function ε in both models. GPT-4o-mini's `request_password_reset` drops below the FLAGGED threshold (**0.295**, COMPLETE); DeepSeek V3 combined values stay above 0.30 but are uniformly lower than per-function values. When context resolves uncertainty before decoding, there is less for ε to observe.



Figure 2: GPT-4o-mini: per-function generation keeps all six functions in the FLAGGED tier; combined generation collapses ε for every function, dropping one of six (`request_password_reset`, $\varepsilon = 0.295$) to COMPLETE. DeepSeek V3 shows the same reduction in combined-mode ε, but all six remain FLAGGED (Table 4).

4.3 Multi-model calibration

A 30-prompt calibration set: 10 LOW prompts (sort, palindrome, fibonacci, two-sum — pure logic) and 20 HIGH prompts (API/version-split tasks across Stripe, OpenAI, SQLAlchemy, FastAPI, Pydantic), run on four models. GPT-4o and DeepSeek V3 both achieve 85% HIGH detection; GPT-4o-mini and GPT-4-turbo both achieve 70%. DeepSeek V3 carries a higher LOW FP rate (70%) than the OpenAI models, consistent with its larger vocabulary of naming alternatives.

Model	HIGH detection	LOW FP
GPT-4o	85% (17/20)	50% (5/10)
GPT-4o-mini	70% (14/20)	60% (6/10)
GPT-4-turbo	70% (14/20)	60% (6/10)
DeepSeek V3	85% (17/20)	70% (7/10)

Table 5: Calibration at the FLAGGED threshold ($\varepsilon \geq 0.30$). 95% Wilson CIs: ±17pp HIGH, ±30pp LOW. Three HIGH prompts produce $\varepsilon = 0.000$ across all four models (`HTTP-GET-to-JSON`, `Pydantic serialization`, `async HTTP GET`) — *confidently-resolved domains* where training priors have converged.

4.4 LOW ground truth

All 30 LOW functions passed `exec()` assertions. Tier breakdown: COMPLETE 5, FLAGGED 20, PAUSED 5. Non-COMPLETE tiers are dominated by Type 3 (brute vs. hash two-sum; recursive vs. iterative fibonacci).

4.5 Precision/recall at tier boundaries

On a 200-entry combined set (30 LOW exec-verified plus 170 HIGH LLM-judged; see §6.1), 53 true failures and 147 correct:

Threshold	Precision	Recall	F1
$\varepsilon \geq 0.30$ (FLAGGED+)	0.272	**1.000**	0.428
$\varepsilon \geq 0.95$ (PAUSED)	**0.309**	0.547	0.394

Table 6: $n = 200$, 53 positives; 95% Wilson CI on FLAGGED+ precision $[0.22, 0.33]$. Base failure rate 26.5% ≈ FLAGGED+ precision: the gate's value is recall, not precision. PAUSED fires rarely in our evaluation but achieves the highest precision of any tier. HIGH ground truth for 170/200 entries is LLM-judged by GPT-4o (§6.1); LOW ground truth (30/200) is `exec()`-verified.



Figure 3: Precision stays near the base rate across the threshold range; recall falls monotonically. Operating points marked: FLAGGED+ ($t = 0.30$) at recall 1.00 with precision barely above base rate, and PAUSED ($t = 0.95$) at recall 0.547 with the highest precision of any tier. The gate's value is recall, not precision.

Tiers are urgency signals, not calibrated probabilities. The useful binary boundary is COMPLETE vs. FLAGGED+.

4.6 Review loop: context-free vs. context-primed reviewer

Evaluated on 201 entries (production FastAPI codebase plus scenarios A–E, three models). Every FLAGGED+ entry is sent in parallel to a GPT-4o reviewer returning CLEARED/CONFIRMED; a consolidation pass processes remaining suspects. The **context-free** variant uses no reviewer context; the **context-primed** variant injects model-specific learned false-positive patterns from a prior clean run (injecting suspect patterns caused over-flagging in pilots).

Metric	Context-free	Context-primed
Cleared by reviewer	107/201 (53.2%)	138/201 (68.7%)
Forwarded to consolidation	89	57
Confirmed true failures	85 (42.3%)	57 (28.4%)
Late false positives	4	0

Table 7: "Late false positive" = an entry marked CONFIRMED that was in fact correct on manual inspection. The context-primed variant is the preferred production configuration.



Figure 4: Injecting learned FP patterns into the reviewer (context-primed vs. context-free) shifts 31 additional entries from consolidation to cleared and eliminates late false positives, at the cost of suppressing some true failures the context-free reviewer forwarded.

End-to-end failure rates: GPT-4o-mini 40%, GPT-4o 29%, DeepSeek V3 26%. Because stage-1 recall is 100%, end-to-end precision is determined entirely by the reviewer's precision on the FLAGGED+ set. The context-primed variant's zero late-FP result rests on $n = 57$ confirmed entries and needs a larger validation study. The stage-1 recall guarantee applies to entries that reach the reviewer; entries the reviewer clears were not independently verified.

5 Comparison to Prior Work

5.1 UQLM and multi-sample methods

UQLM [3]'s `BlackBoxUQ` samples each prompt 5 times and scores semantic disagreement via a DeBERTa NLI model.

Method	HIGH det.	LOW FP	API calls	Localization
UQLM (confidence < 0.5)	5%	0%	5	File-level only
ε (FLAGGED+)	85%	50%	1	Token/line/function

Table 8: UQLM vs. ε on GPT-4o. UQLM returned confidence ≥ 0.62 on 29/30 prompts (19/20 HIGH); its sole detection (pandas `concat`) is a case where syntax genuinely varied across samples.

UQLM's 0% false-positive rate reflects the absence of signal, not the presence of precision — a system that never fires achieves perfect FPR trivially. Lowering the threshold does not recover detection: LOW prompts fire before additional HIGH do. The Stripe scenario makes this concrete: the model assigned 0.52/0.47 to `.Charge`/`.PaymentIntent` at generation time, yet across 5 samples picked `PaymentIntent` every time (a 0.52-peaked distribution samples its peak nearly always). UQLM observes perfect consistency and reports confidence = 1.0. For intra-generational uncertainty, measuring at the output level cannot recover the signal by construction.



Figure 5: UQLM returned confidence ≥ 0.62 on 29/30 prompts (including 19/20 HIGH). Its sole detection is pandas `concat`, where syntax genuinely varied across samples; ε separates the two populations by construction.



Figure 6: Sweeping the decision threshold for each method on GPT-4o. ε has a wide band where HIGH detection dominates LOW FP; UQLM's useful operating range collapses as threshold rises.

5.2 Single-token log-probability baselines

`min_logprob` flags a function if any selected token's log-probability falls below a threshold — same raw signal, top-1 only.

A low top-1 probability does not distinguish a cosmetic name from an API selector from a whitespace artifact. AST filtering plus top-k entropy closes the gap: the signal is in the raw logprobs, inaccessible without filtering.

Method	HIGH det. @ 30% LOW FP	HIGH det. @ 50% LOW FP
`min_logprob`	45–55%	55–65%
ε (max, AST-filtered)	**70**%	**85**%

Table 9: Matched LOW FP budgets across four models. Gap is at near-tie tokens (e.g., 0.48/0.42): `min_logprob` sees 0.48 and does not fire; ε sees near-uniform top-k entropy and does.

5.3 Static analysis, linters, and model coverage

Static analysis catches *known*-bad patterns for libraries with rules written; ε fires where the model itself hesitated, including decisions not yet in any ruleset (a library updated last week, a half-migrated codebase). Static analysis is the floor under ε. Primary experiments use OpenAI plus DeepSeek V3 via Together AI; Anthropic exposes logprobs via streaming, vLLM via full top-k. The method requires only top-k; no model-internal access.

6 Discussion

6.1 Limitations

Confident wrongness. ε cannot detect a model that is wrong and confident. If training placed all mass on a deprecated API, the token probability is sharp and ε is low; the system emits the wrong code with COMPLETE status. Fundamental limit of any generation-time signal; motivates static-analysis integration.

Confidently-resolved domains. Prompts where every model has converged on a strong training-data prior produce $\varepsilon = 0.000$ regardless of correctness. Current-UTC datetime retrieval and HTTP-GET-to-JSON fall here across all four models. For stable widely-deployed APIs this is desirable; for deprecated-but-confidently-recalled APIs it is Scenario B's failure mode.

Small-sample calibration. Main calibration is 30 prompts per model; Wilson intervals on HIGH detection are $\pm$17pp at $n = 20$. We claim recall-first design plus an empirical miss rate of zero on the sets evaluated, not a proof of perfect recall.

Type 3 floor. Implementation-approach uncertainty on simple prompts (brute vs. hash two-sum) legitimately raises ε on correct code. AST filtering does not remove it; the $\sim$ 50% LOW FP is predominantly Type 3 and unlikely to shrink without sacrificing recall.

LLM-judged ground truth. LOW ground truth is `exec()`-verified against assertions covering return type, edge cases, and correctness. HIGH ground truth is LLM-judged via GPT-4o. Circularity exists where the evaluated model shares a family with the judge (GPT-4o-mini judged by GPT-4o); results for that model should be read with that caveat. We disclose rather than overclaim human verification we did not perform.

Hyperparameters. The cascaded tier algorithm (six checks, three thresholds) was calibrated on GPT-4o; other models inherit these. The binary FLAGGED+ gate is robust; internal tier placement is a refinement on top.

6.2 Context learning as a microcosm

Injecting learned false-positive patterns into the reviewer's context (the configuration evaluated in §4.6) raised clearance from 53.2% to 68.7%, and late false positives fell from 4 to 0. This is in-context improvement on a fixed model; training-time improvement would be expected to compound with it.

6.3 Future work

Pipeline propagation: upstream ε should propagate as prior uncertainty into downstream generations, modulating sampling temperature or review threshold. **Open-source models:** vLLM exposes full top-k; a Llama/Qwen/Mistral calibration run would test whether the recall-first boundary holds outside OpenAI. **Per-token intervention:** surface the high-ε token as an inline editor marker, or trigger targeted re-decoding with lower temperature on just the uncertain span. **Cross-decision consistency:** Scenario D's mismatches argue for AST-level consistency checks over ε (e.g., `async def` + blocking HTTP client).

7 Conclusion

We introduced ε, a per-token normalized Shannon entropy over top-k log-probabilities, AST-filtered and max-aggregated into a single score per generated function. ε is a filter, not a detector: it achieves the recall target established in §4.5. The contribution is the two-stage system. Pairing a recall-maximizing filter with a parallel LLM reviewer produces an architecture in which nothing uncertain ships unreviewed and the reviewer scales with generation speed.

The framing matters. Multi-sample uncertainty methods produce almost no signal on code generation because code uncertainty is intra-generational — visible in the single-generation token distribution, invisible across re-samples. Once the distinction is named, the design of ε follows directly. The same mechanism — early-token commitment forcing later tokens — plausibly applies in other structured-output domains (SQL, configuration files, typed program synthesis); empirical verification is left to future work. Generation is fast; review is the bottleneck. A filter that misses nothing plus a parallel reviewer moves review off the developer's critical path.

References

[1] Anastasios N Angelopoulos, Stephen Bates, Adam Fisch, Lihua Lei, and Tal Schuster. Conformal risk control. In *International Conference on Learning Representations (ICLR)*, 2024.

[2] Jacob Austin, Augustus Odena, Maxwell Nye, Maarten Bosma, Henryk Michalewski, David Dohan, Ellen Jiang, Carrie Cai, Michael Terry, Quoc Le, et al. Program synthesis with large language models, 2021.

[3] Dylan Bouchard, Mohit Singh Chauhan, David Skarbrevik, Ho-Kyeong Ra, Viren Bajaj, and Zeya Ahmad. UQLM: A python package for uncertainty quantification in large language models. *Journal of Machine Learning Research*, 2026. arXiv:2507.06196.

[4] Bei Chen, Fengji Zhang, Anh Nguyen, Daoguang Zan, Zeqi Lin, Jian-Guang Lou, and Weizhu Chen. CodeT: Code generation with generated tests, 2022.

[5] Mark Chen, Jerry Tworek, Heewoo Jun, Qiming Yuan, Henrique Ponde de Oliveira Pinto, Jared Kaplan, Harri Edwards, Yuri Burda, Nicholas Joseph, Greg Brockman, et al. Evaluating large language models trained on code, 2021.

[6] Carlos E Jimenez, John Yang, Alexander Wettig, Shunyu Yao, Kexin Pei, Ofir Press, and Karthik Narasimhan. SWE-bench: Can language models resolve real-world GitHub issues? In *International Conference on Learning Representations (ICLR)*, 2024.

[7] Alain Jungo, Raphael Meier, David Alleysson, and Mauricio Reyes. Analyzing the quality and challenges of uncertainty estimations for brain tumor segmentation with deep neural networks. *Frontiers in Neuroscience*, 2020.

[8] Saurav Kadavath, Tom Conerly, Amanda Askell, Tom Henighan, Dawn Drain, Ethan Perez, Nicholas Schiefer, Zac Hatfield-Dodds, Nova DasSarma, Eli Tran-Johnson, et al. Language models (mostly) know what they know, 2022.

[9] Lorenz Kuhn, Yarin Gal, and Sebastian Farquhar. Semantic uncertainty: Linguistic invariances for uncertainty estimation in natural language generation. In *International Conference on Learning Representations (ICLR)*, 2023.

[10] Victor Quach, Adam Fisch, Tal Schuster, Adam Yala, Jae Ho Sohn, Tommi S Jaakkola, and Regina Barzilay. Conformal language modeling. In *International Conference on Learning Representations (ICLR)*, 2024.

[11] Neeraj Varshney, Wenlin Yao, Hongming Zhang, Jianshu Chen, and Dong Yu. A stitch in time saves nine: Detecting and mitigating hallucinations of LLMs by validating low-confidence generation. In *Proceedings of the 18th Conference of the European Chapter of the Association for Computational Linguistics (EACL)*, 2024.

[12] He Ye, Matias Martinez, and Martin Monperrus. SelfAPR: Self-supervised program repair with test execution diagnostics. In *Proceedings of the 37th IEEE/ACM International Conference on Automated Software Engineering (ASE)*, 2022.