Internal Air Transport Certification

AFLCMC/EZFC (ATTLA)
2145 Monahan Way
WPAFB, OH 45433-7017
https://intelshare.intelink.gov/sites/attla/

Date: 23 July 2026
Item Nomenclature: AAR ISU Containers, 56000 series
File Number: 99.05.14 Rev 1
Superseded Certification Date: 29 October 2014

New Information Summary: This certification supersedes file numbers 99.05.14.01 and 99.05.14.02.

Item Description: The subject items are identified to be models in the AAR 56000 series of ISU containers. All models have a base size of 108" W x 88" L. Height varies by model.

All variants (as denoted by letter suffix configurations EO, KC, KCA, etc.) of the base models listed in Table 1 are approved.

AAR 56000 series ISU containers with installed equipment, or otherwise modified, are not covered by this certification.

ISU-60	ISU-72.5
ISU-60.5	ISU-80
ISU-70	ISU-90

Table 1: Approved Base Models

Conditions of Certification:

Some container variants are intended for certain aircraft but not for others due to their geometry. Refer to manufacturer's technical manual and individual container placards for correct application and orientation.

1. **Maximum Weight for Air Transport:**

   a. Gross Weight: 12,000 lbs or as noted on the applicable data plate.

2. **Item Preparation:**

   a. All hazardous materials (to include fuel level, batteries, etc.) must be prepared and certified for airlift in accordance with TM 38-250/AFMAN 24-604. Do not consider this air transport certification as approval for hazardous materials. Authorization for airlifting hazardous material is the responsibility of AFMC/A4RT email: AFMC.A4RT.Workflow@us.af.mil.

3. **Loading Instructions:**

   a. The ISUs can be loaded using general loading procedures as listed in the respective aircraft cargo loading manual.

   b. Individual roller limits as contained in the applicable aircraft TO 1C-XXX-9 shall apply to the internal cargo load. Maximum load per quadrant is 2,500 lbs.

c. C-130: any container which is not an “I”-suffixed container must be positioned forward or aft of the wheel well area to maintain aisleway restrictions. “I” suffixed containers (e.g. ISU-90I) are not restricted when oriented to provide adequate aisleway.

d. Depending upon the host aircraft, the container doors may be oriented in any direction. However, the doors must be closed and latched in order to achieve the required restraint. The container will be loaded to allow in-flight inspection and access to the contents, as needed.

Required Distribution:

1. Shipper shall give a copy of this certification to the ATOC representative when the item is presented for airlift. This memo shall be part of the official cargo manifest documentation package and shall be briefed to the aircraft loadmaster prior to loading the ISUs.

2. AMC/A3V & AMC/A4T

3. ARTRANS TEA

Point of Contact: MSgt Josh Herrier, at joshua.herrier@us.af.mil or ATTLA@us.af.mil, DSN 323-634-3178 or Commercial (385) 634-3178. Refer to file number 99.05.14 Rev 1 to reference this item.

Eric Treadwell
Digitally signed by TREADWELL.ERIC.B.1241966042
Date: 2026.07.23 09:12:27 -04'00'

Reviewed by: ERIC TREADWELL
Senior Aerial Delivery Engineer
Air Transportability Test Loading Activity (ATTLA)

KEIL.DEKEN.L.1256605402
Digitally signed by KEIL.DEKEN.L.1256605402
Date: 2026.07.23 09:16:39 -04'00'

Approved by: DEKEN L. KEIL
Chief, Air Transportability Test Loading Activity (ATTLA)