

WHENEVER I LEARN A
NEW SKILL I CONCOCT
ELABORATE FANTASY
SCENARIOS WHERE IT
LETS ME SAVE THE DAY.

OH NO! THE KILLER
MUST HAVE FOLLOWED
HER ON VACATION!



BUT TO FIND THEM WE'D HAVE TO SEARCH
THROUGH 200 MB OF EMAILS LOOKING FOR
SOMETHING FORMATTED LIKE AN ADDRESS!



IT'S HOPELESS!

EVERYBODY STAND BACK.



I KNOW REGULAR
EXPRESSIONS.



CS 1671/2071

Human Language Technologies

Session 2: Text normalization

Michael Miller Yoder

January 13, 2025

About Norah (TA)

- **2nd year PhD student at Pitt.**
- **Office Hours:**
 - By appointment.
 - Email: nia135@pitt.edu
 - Location TBD

Hacking 4 Humanity hackathon

- Tech and policy hackathon
- Last year, a team from here at SCI won 1st in the technology track and was invited to Harrisburg to present their projects to First Lady Lori Shapiro and members of Governor Shapiro's staff
- More information at www.hacking4humanity.online/



Overview: Text normalization

- Course logistics
- Basic terminology
- Regular expressions
- Text normalization

Course logistics

- Reading for today was Jurafsky & Martin sections 2-2.3, 2.5-2.7
- Assignments and quizzes are generally due Thu nights in this course
- [Homework 1](#) has been released. Is **due Jan 23**
- Please remind me of your name before asking or answering a question (just this class session)

NLP terminology: words and corpora

How many words in this phrase?

they lay back on the San Francisco grass and looked at the stars and their

- How many?
 - 15 tokens (or 14 if you count "San Francisco" as one)
 - 13 types (or 12) (or 11?)
- **Type**: a unique word in the vocabulary
- **Token**: an instance of a word type in running text
- **Lemma**: same stem, part of speech, rough word sense
 - **cat** and **cats** = same lemma
- **Wordform**: the full inflected surface form
 - **cat** and **cats** = different wordforms

How many words in a corpus?

Corpus: a (machine-readable) collection of texts

N = number of tokens

V = vocabulary = set of types, $|V|$ is size of vocabulary

	Tokens = N	Types = $ V $
Switchboard phone conversations	2.4 million	20 thousand
Shakespeare	884,000	31 thousand
COCA	440 million	2 million
Google N-grams	1 trillion	13+ million

Corpora vary along dimensions like

- Texts don't appear out of nowhere!
- **Language:** 7097 languages in the world
- **Variety**, like African American Language varieties.
 - AAE Twitter posts might include forms like "*iont*" (*I don't*)
- **Code switching**, e.g., Spanish/English, Hindi/English:

Por primera vez veo a @username actually being helpful! It was beautiful:)

[For the first time I get to see @username actually being helpful! it was beautiful:]


dost tha or ra- hega ... dont worry ... but dherya rakhe

["he was and will remain a friend ... don't worry ... but have faith"]
- **Genre:** newswire, fiction, scientific articles, Wikipedia
- **Author Demographics:** writer's age, gender, ethnicity, SES
- Corpus datasheets [Bender & Friedman 2018, Gebru+ 2020] ask about this information

JupyterHub setup

Set up Python virtual environment


1. Log in to jupyter.crc.pitt.edu
2. Go to this [nbgitpuller link](#)
 - This should pull a folder (cs1671_jupyterhub) into your JupyterLab
3. Open a terminal



Set up Python virtual environment


In a terminal, run

```
conda env create -p conda_env --file environment.yml
```



Open Jupyter Notebook for Session 2

1. Double-click `session2_text_normalization.ipynb` on the left panel to open the notebook
2. Click the top right to change the kernel
3. Select **Python** `[conda_env:conda_env]` as your kernel
4. You're ready to go!



Regular expressions (regex)

Regular expressions

- A formal language for specifying text strings
- How can we search for any of these?
 - woodchuck
 - woodchucks
 - Woodchuck
 - Woodchucks



Regular expressions: Disjunctions (OR)

- Letters inside square brackets []


Pattern	Matches
[wW]oodchuck	Woodchuck, woodchuck
[1234567890]	Any digit

- Ranges [A-Z] [a-z] [0-9]
- Negations [^A-Z]
 - Carat means negation only when first in []
- Sequence disjunctions with pipe |
 - **groundhog|woodchuck**



Regular expression wildcards: *+.

Pattern	Matches	
oo*h	0 or more of previous char	<u>oh</u> <u>ooh</u> <u>oooh</u> <u>ooooh</u>
o+h	1 or more of previous char	<u>oh</u> <u>ooh</u> <u>oooh</u> <u>ooooh</u>
beg.n	Any char	<u>begin</u> <u>begun</u> <u>begun</u> <u>beg3n</u>



Stephen C Kleene

Regular expression example

- Find all instances of the word “the” in a text.

the

- Misses capitalized examples

[tT]he

- Incorrectly returns "other" or "theology"

[^a-zA-Z][tT]he[^a-zA-Z]

Errors

The process we just went through was based on fixing two kinds of errors:

1. Matching strings that we should not have matched (there, then, other)

False positives (Type I errors)

2. Not matching things that we should have matched (The)

False negatives (Type II errors)

Simple Application: ELIZA

- Early NLP system that imitated a Rogerian psychotherapist [Weizenbaum 1966]
- Uses pattern matching to match phrases

“I need X”

- and translates them into, e.g.

“What would it mean to you if you got X?”

Simple Application: ELIZA

Men are all alike.

IN WHAT WAY

They're always bugging us about something or other.

CAN YOU THINK OF A SPECIFIC EXAMPLE

Well, my boyfriend made me come here.

YOUR BOYFRIEND MADE YOU COME HERE

He says I'm depressed much of the time.

I AM SORRY TO HEAR YOU ARE DEPRESSED

How ELIZA works

. * I'M (depressed|sad) . * → I AM SORRY TO HEAR YOU ARE \1

. * all . * → IN WHAT WAY?

. * always . * → CAN YOU THINK OF A SPECIFIC EXAMPLE?/

Regular expressions summary

- Regular expressions play a surprisingly large role in NLP
 - Sophisticated sequences of regular expressions are often the first model for any text processing text
- For hard tasks, we use machine learning classifiers
 - But regular expressions are still used for pre-processing, or used to extract features for the classifiers

Implementation: regular expressions

- Remove undesired text from Airbnb listing data

Text normalization (preprocessing)

Every NLP task requires text normalization

- Tokenizing (separating) words
- Normalizing word formats

Case folding (lowercasing)

- Applications like IR: reduce all letters to lowercase
 - Since users tend to use lowercase
 - Possible exception: upper case in mid-sentence?
 - e.g., *General Motors*
 - *Fed* vs. *fed*
 - *SAIL* vs. *sail*
- For sentiment analysis, MT, information extraction
 - Case is helpful (*US* versus *us* is important)



Implementation: lowercasing

- Lowercase your Airbnb listing data

Stopword removal

- Do we want to keep "function words" like *the, of, and, I, you*, etc?
- Sometimes **no** (information retrieval)
- Sometimes **yes** (authorship attribution)

Implementation: remove stopwords

- Remove stopwords from your Airbnb listing data

Tokenization

Space-based tokenization

- A very simple way to tokenize
- For languages that use space characters between words
 - Arabic, Cyrillic, Greek, Latin, etc., based writing systems
- Segment off a token between instances of spaces

Issues in Tokenization

- Can't just blindly remove punctuation:
 - m.p.h., Ph.D., AT&T, cap'n
 - prices (\$45.55)
 - dates (01/02/06)
 - URLs (<http://www.pitt.edu>)
 - hashtags ([#nlproc](#))
 - email addresses (someone@cs.colorado.edu)
- Clitic: a word that doesn't stand on its own
 - "are" in [we're](#), French "je" in [j'ai](#), "le" in [l'honneur](#)
- When should multiword expressions (MWE) be words?
 - [New York](#), [rock 'n' roll](#)

Regex-based tokenization

```
>>> text = 'That U.S.A. poster-print costs $12.40...'
>>> pattern = r'''(?x)      # set flag to allow verbose regexps
...     ([A-Z]\.)+          # abbreviations, e.g. U.S.A.
...     | \w+(-\w+)*         # words with optional internal hyphens
...     | \$?\d+(\.\d+)?%?    # currency and percentages, e.g. $12.40, 82%
...     | \.\.\.            # ellipsis
...     | [][.,;'"?():_-']  # these are separate tokens; includes ], [
...     '''
>>> nltk.regex.tokenize(text, pattern)
['That', 'U.S.A.', 'poster-print', 'costs', '$12.40', '...']
```

- NLTK [Bird+ 2009] provides regex and ML models for tokenization (like punkt tokenizer)
- spaCy, other packages provide good tokenization

Implementation: word tokenization

- Tokenize your Airbnb listing data with the NLTK package

Tokenization in languages without spaces between words

- Many languages (like Chinese, Japanese, Thai) don't use spaces to separate words!
- How do we decide where the token boundaries should be?

Word tokenization in Chinese

- Chinese words are composed of characters called "**hanzi**" (or sometimes just "**zi**")
- Each one represents a meaning unit called a morpheme
- Each word has on average 2.4 of them.
- But deciding what counts as a word is complex and not agreed upon.

How to do word tokenization in Chinese?

姚明进入总决赛 “Yao Ming reaches the finals”

3 words?

姚明 进入 总决赛

YaoMing reaches finals

5 words?

姚 明 进入 总 决赛

Yao Ming reaches overall finals

7 characters? (don't use words at all):

姚 明 进 入 总 决 赛

Yao Ming enter enter overall decision game

Word tokenization / segmentation

- In Chinese NLP it's common to just treat each character (zi) as a token.
 - So the **segmentation** step is very simple
- In other languages (like Thai and Japanese), more complex word segmentation is required, usually using machine learning

Lemmatization and stemming

Lemmatization

Represent words as their **lemma**: their shared root, dictionary headword form:

- *am, are, is* → *be*
- *car, cars, car's, cars'* → *car*
- Spanish **quiero** ('I want'), **quieres** ('you want')
→ **querer** 'want'
- *He is reading detective stories*
→ *He be read detective story*

Lemmatization is done by Morphological Parsing

- Morphemes: small meaningful units that make up words
 - **Roots**: The core meaning-bearing units
 - **Affixes**: Parts that adhere to roots

un-think-able; kitten-s

- Affixes can add grammatical meaning (inflections, 2nd column) or modify semantic meaning (derivations, 3rd column)

<root>	<root>ing	<root>er
run	running	runner
think	thinking	thinker
program	programming	programmer
kill	killing	killer

Lemmatization is done by Morphological Parsing

- *cats* into two morphemes *cat* and *s*
- Spanish *amaren* ('if in the future they would love') into morpheme *amar* 'to love' + morphological features *3PL* + *future subjunctive*.

Dealing with complex morphology is necessary for many languages

- e.g., the Turkish word:

Uygarlastiramadiklarimizdanmissinizcasina

'(behaving) as if you are among those whom we could not civilize'

Uygar 'civilized' + las 'become'

+ tir 'cause' + ama 'not able'

+ dik 'past' + lar 'plural'

+ imiz '1pl' + dan 'abl'

+ mis 'past' + siniz '2pl' + casina 'as if'

Stemming

- Reduce terms to stems, chopping off affixes crudely

This was not the map we found in
Billy Bones's chest, but an
accurate copy, complete in all
things-names and heights and
soundings-with



Thi wa not the map we found in
Billi Bone s chest but an accur
copi complet in all thing name
and height and sound with

ATIONAL → ATE (e.g., relational → relate)


ING → € if stem contains vowel (e.g., motoring → motor)

SSES → SS (e.g., grasses → grass)

Implementation: stemming

- Stem the tokens in your Airbnb listing data



Saving your work



Ending your session

Be sure to save your work before ending the session

1. Select **File > Hub Control Panel**
2. Click **Stop My Server**



Conclusion: Text normalization

- Regular expressions match flexible sequences of characters and allow substitution of groups of characters
- Stopwords are function words like “the”, “a”, “and”, “of”, etc that are often ignored in NLP applications
- Tokenization: splitting texts into sequences of words
 - Subword tokenization finds tokens based on frequencies of sequences of characters in data
- Lemmatization: normalizing words to their dictionary roots
- Stemming: chopping off affixes of words to reduce them to stems

Subword tokenization & BPE

Another option for text tokenization

- Use the data to tell us how to tokenize.
- **Subword tokenization** (because tokens can be parts of words as well as whole words)
- Many modern neural NLP systems (like BERT) use this to handle unknown words
- 2 parts:
 - A token learner that takes a raw training corpus and induces a vocabulary (a set of tokens).
 - A token segmenter that takes a raw test sentence and tokenizes it according to that vocabulary

Byte Pair Encoding [BPE, Sennrich+ 2016] token learner

Let vocabulary be the set of all individual characters

= {A, B, C, D,..., a, b, c, d....}

Repeat:

- Choose the two symbols that are most frequently adjacent in the training corpus (say 'A', 'B')
- Add a new merged symbol 'AB' to the vocabulary
- Replace every adjacent 'A' 'B' in the corpus with 'AB'.

Until k merges have been done.

BPE token learner

Original (very fascinating 🤖) corpus:

low low low low low lowest lowest newer newer newer newer newer
newer wider wider wider new new

Split on whitespace, add end-of-word tokens _

corpus

```
5   l o w  _  
2   l o w e s t  _  
6   n e w e r  _  
3   w i d e r  _  
2   n e w  _
```

vocabulary

_, d, e, i, l, n, o, r, s, t, w

BPE token learner

- Merge **e r** to **er**

corpus

5 l o w _
2 l o w e s t _
6 n e w er _
3 w i d er _
2 n e w _

vocabulary

_, d, e, i, l, n, o, r, s, t, w, er

- Merge **er _** to **er_**
- Merge **n e** to **ne**

BPE token learner

The next merges are:

Merge	Current Vocabulary
(ne, w)	—, d, e, i, l, n, o, r, s, t, w, er, er—, ne, new
(l, o)	—, d, e, i, l, n, o, r, s, t, w, er, er—, ne, new, lo
(lo, w)	—, d, e, i, l, n, o, r, s, t, w, er, er—, ne, new, lo, low
(new, er—)	—, d, e, i, l, n, o, r, s, t, w, er, er—, ne, new, lo, low, newer—
(low, —)	—, d, e, i, l, n, o, r, s, t, w, er, er—, ne, new, lo, low, newer—, low—

BPE token segmenter algorithm

- On the test data, run each merge learned from the training data:
 - Greedily, in the order we learned them
- So merge every `e r` to `er`, then merge `er _` to `er_`, etc.
- Result:
 - Test set "n e w e r _" would be tokenized as a full word
 - Test set "l o w e r _" would be two tokens: "low er_"

Questions?