

GraphQL API Documentation

Endpoint: `http://localhost:3002/graphql`

Development playground/introspection is enabled outside production.

Authentication

Protected resolvers require:

```
{ "Authorization": "Bearer <token>" }
```

By default, `login` starts an OTP session. For load tests or local scenarios where login should be phone-number only, set:

```
DISABLE_OTP=true
```

With `DISABLE_OTP=true`, this login input returns a JWT directly:

```
{ "input": { "phoneNumber": "+6281234567892" } }
```

Auth Mutations

`login`

```
mutation Login($input: LoginInput!) {  
  login(input: $input) {  
    token  
    sessionId  
    expires  
    user { id fullName phoneNumber role isVerifiedTenant unitNumber }  
  }  
}
```

Variables:

```
{ "input": { "phoneNumber": "+6281234567892" } }
```

Default OTP response contains `sessionId` and `expires`. When `DISABLE_OTP=true`, response contains `token` and `user`.

verifyOtp

```
mutation VerifyOtp($input: OTPInput!) {  
  verifyOtp(input: $input) {  
    token  
    user { id fullName phoneNumber role isVerifiedTenant unitNumber }  
  }  
}
```

Variables:

```
{  
  "input": {  
    "sessionId": "8f1f2f20-5a28-4a61-a54b-4a17e09cfa40",  
    "otp": "1234"  
  }  
}
```

resendOtp

```
mutation ResendOtp($input: ResendOTPInput!) {  
  resendOtp(input: $input) {  
    phoneNumber  
    sessionId  
    expires  
  }  
}
```

Variables:

```
{ "input": { "sessionId": "8f1f2f20-5a28-4a61-a54b-4a17e09cfa40" } }
```

Queries

me

Protected.

```
query GetMe {  
  me { id fullName phoneNumber role isVerifiedTenant unitNumber }  
}
```

facilities

Public. Returns active facilities.

```
query GetFacilities {  
  facilities { id name description pricePerHour openTime closeTime isActive  
}  
}
```

facility

Public.

```
query GetFacility($id: Int!) {  
  facility(id: $id) { id name description pricePerHour openTime closeTime  
    isActive }  
}
```

Variables: { "id": 1 }

availableSlots

Public.

```
query GetAvailableSlots($input: SlotAvailabilityInput!) {  
  availableSlots(input: $input) {  
    facilityId  
    date  
    slots { startTime endTime isAvailable }  
  }  
}
```

Variables:

```
{ "input": { "facilityId": 1, "date": "2026-01-22" } }
```

bookings

Admin or super admin only.

```
query GetBookings {  
  bookings {  
    id bookingDate startTime endTime status totalPrice  
    user { id fullName }  
  }  
}
```

```
    facility { id name }
  }
}
```

booking

Protected.

```
query GetBooking($id: Int!) {
  booking(id: $id) {
    id bookingDate startTime endTime status totalPrice
    user { id fullName phoneNumber role }
    facility { id name pricePerHour }
  }
}
```

Variables: { "id": 301 }

userBookings

Protected. Uses optimized nested loading with DataLoader.

```
query GetUserBookings($userId: Int!, $limit: Int!, $offset: Int!) {
  userBookings(userId: $userId, limit: $limit, offset: $offset) {
    id bookingDate startTime endTime status totalPrice
    user { id fullName phoneNumber role }
    facility { id name pricePerHour openTime closeTime }
  }
}
```

Variables: { "userId": 3, "limit": 10, "offset": 0 }

userBookingsGeneric

Protected. Returns the same shape as `userBookings`, but uses the plain query path for comparison tests.

```
query GetUserBookingsGeneric($userId: Int!, $limit: Int!, $offset: Int!) {
  userBookingsGeneric(userId: $userId, limit: $limit, offset: $offset) {
    id bookingDate startTime endTime status totalPrice
    user { id fullName phoneNumber role }
    facility { id name pricePerHour }
  }
}
```

userDashboard

Protected.

```
query GetUserDashboard($userId: Int!, $limit: Int!, $offset: Int!) {  
  userDashboard(userId: $userId, limit: $limit, offset: $offset) {  
    user { id fullName phoneNumber role isVerifiedTenant unitNumber }  
    bookings {  
      id bookingDate startTime endTime status totalPrice  
      facility { id name pricePerHour }  
    }  
    bookingCountToday  
    upcomingBookings  
    totalSpent  
  }  
}
```

Variables: { "userId": 3, "limit": 10, "offset": 0 }

users

Admin or super admin only.

```
query GetUsers {  
  users { id fullName phoneNumber role isVerifiedTenant unitNumber }  
}
```

user

Protected.

```
query GetUser($id: Int!) {  
  user(id: $id) { id fullName phoneNumber role isVerifiedTenant unitNumber }  
}
```

Variables: { "id": 3 }

Domain Mutations

createBooking

Protected.

```
mutation CreateBooking($input: CreateBookingInput!) {  
  createBooking(input: $input) {  
    id bookingDate startTime endTime status totalPrice  
    user { fullName }  
  }  
}
```

```
    facility { name }  
  }  
}
```

Variables:

```
{  
  "input": {  
    "userId": 3,  
    "facilityId": 1,  
    "bookingDate": "2026-01-22",  
    "startTime": "14:00:00",  
    "endTime": "15:00:00"  
  }  
}
```

confirmBooking

Protected.

```
mutation ConfirmBooking($id: Int!) {  
  confirmBooking(id: $id) { id status }  
}
```

Variables: { "id": 301 }

cancelBooking

Protected.

```
mutation CancelBooking($id: Int!) {  
  cancelBooking(id: $id) { id status }  
}
```

Variables: { "id": 301 }

deleteBooking

Admin or super admin only. Permanently deletes a booking.

```
mutation DeleteBooking($id: Int!) {  
  deleteBooking(id: $id)  
}
```

Variables: { "id": 301 }

createFacility

Admin or super admin only.

```
mutation CreateFacility($input: CreateFacilityInput!) {  
  createFacility(input: $input) {  
    id name description pricePerHour openTime closeTime isActive  
  }  
}
```

Variables:

```
{  
  "input": {  
    "name": "Swimming Pool",  
    "description": "Olympic-size indoor pool",  
    "pricePerHour": 75000,  
    "openTime": "06:00:00",  
    "closeTime": "21:00:00",  
    "isActive": true  
  }  
}
```

updateFacility

Admin or super admin only.

```
mutation UpdateFacility($id: Int!, $input: UpdateFacilityInput!) {  
  updateFacility(id: $id, input: $input) {  
    id name pricePerHour isActive  
  }  
}
```

Variables: { "id": 1, "input": { "pricePerHour": 80000, "isActive": false } }

deleteFacility

Admin or super admin only.

```
mutation DeleteFacility($id: Int!) {  
  deleteFacility(id: $id)  
}
```

Variables: { "id": 1 }

createUser

Admin or super admin only.

```
mutation CreateUser($input: CreateUserInput!) {  
  createUser(input: $input) {  
    id fullName phoneNumber role isVerifiedTenant unitNumber  
  }  
}
```

Variables:

```
{  
  "input": {  
    "fullName": "Siti Rahayu",  
    "phoneNumber": "+6289876543210",  
    "role": "tenant",  
    "isVerifiedTenant": true,  
    "unitNumber": "0802"  
  }  
}
```

updateUser

Admin or super admin only.

```
mutation UpdateUser($id: Int!, $input: UpdateUserInput!) {  
  updateUser(id: $id, input: $input) {  
    id fullName role isVerifiedTenant unitNumber  
  }  
}
```

Variables: { "id": 3, "input": { "isVerifiedTenant": true, "unitNumber": "1203" } }

deleteUser

Admin or super admin only.

```
mutation DeleteUser($id: Int!) {  
  deleteUser(id: $id)  
}
```

Variables: { "id": 3 }

Error Handling

```
{
  "errors": [
    {
      "message": "Validation failed",
      "extensions": {
        "code": "VALIDATION_ERROR",
        "statusCode": 400,
        "fields": {
          "phoneNumber": "Phone number must contain only digits and
optional + prefix"
        }
      }
    }
  ]
}
```

Common codes: `UNAUTHENTICATED`, `FORBIDDEN`, `NOT_FOUND`, `VALIDATION_ERROR`, `BOOKING_CONFLICT`, `BOOKING_LIMIT_EXCEEDED`, `INVALID_TIME_SLOT`, `FACILITY_CLOSED`, `CONFLICT`, `INTERNAL_SERVER_ERROR`.