

INPUT

“How did Q3 engineering spend compare to the finance budget?”

role from verified JWT · never from the request body

01 · PLAN

State manager

Splits the prompt into one gathering task per department. The output schema is a closed set built per request, so an invented department fails validation before any code runs.

gemini-3.5-flash · Vertex AI · Google ADK

02 · GATHER

Gatherer fleet

One agent per department, fanned out concurrently under a configurable cap. Globs, gates, reads, then assesses each file for relevance.

gemini-3.5-flash · parallel

03 · SYNTHESISE

Synthesiser

Compiles one answer in Obsidian-flavoured markdown with inline `[[dept/path]]` citations back to the files it actually used.

gemini-3.5-flash

04 · REJECT

Veto checker

Adversarial. Receives the full source text, not just the citations, and tries to reject unsupported claims and citations that do not resolve. Vetoes carry revision notes.

Claude · structured verdict · operator allowlist

05 · DRAW

Map

Departments, cited files, and every denied file drawn dashed and locked. One graph builder feeds the live canvas and a self-contained offline page.

canvas · streamed over SSE

▼ EVERY FILE, BEFORE IT IS OPENED ▼

THE GATE

non-bypassable · fails closed · in front of the read, not behind the answer

01 Path check

Decided on the path. A file you may not read is never opened, so its contents cannot reach a prompt.

02 Two configs agree

permissions.yaml AND environment.yaml must both grant it. Disagreement denies.

03 Spawn re-check

Every file a gatherer returns is re-checked centrally against the trusted role.

04 Containment

Traversal, absolute paths and escaping symlinks rejected. Cloud keys checked against the bucket prefix.

05 Provenance

The path must be a file the department actually holds, so an invented path cannot wear a real department's name.

read(role, dept, path) <=> G_perm(role,dept) AND G_env(role,dept) AND contained(path,dept) AND exists(path,dept)

SOURCES

One gate, any backend

A cloud object passes exactly the same gate as a local file. For GCS the department name is the bucket prefix and the prefix is the containment root.

- local filesystem
- Google Cloud Storage
- Google Drive
- denied · drawn, not dropped

EVIDENCE

Proving it, not just doing it

Access ledger · append-only record of every decision at both gates, pinned to the caller

Citation coverage · integrity, grounding and usage, computed with no model call

Role comparison · one prompt under two roles, downward only

SURFACE

Backend and client

FastAPI + SSE · the run streams file by file; cancel is authorised against the JWT

JWT auth · pbkdf2-sha256 credentials, per-IP login rate limiting

Replay · a recorded run plays back with zero API calls, pinned to the recording's role