Evolutionary Computation

Lab 1: Greedy heuristics

Michał Pokładowski 160278
Oskar Prusinowski 160290

October 2026

1 Problem description

We have a set of n nodes. Each node j has a position on a plane and a cost c_j. We have to choose exactly $k = \lceil n/2 \rceil$ nodes and connect them into a cycle (a Hamiltonian cycle over the chosen nodes). The goal is to make the length of the cycle plus the costs of the chosen nodes as small as possible. If a solution is the list of nodes $\pi = (\pi_1, \ldots, \pi_k)$, the objective is

$$f(\pi) \;=\; \sum_{i=1}^{k} d_{\pi_i \pi_{i+1}} \;+\; \sum_{i=1}^{k} c_{\pi_i}, \qquad \pi_{k+1} \equiv \pi_1,$$

where d_{ij} is the Euclidean distance between nodes i and j, rounded to the nearest integer. So we have to decide two things: *which* nodes to visit and *in what order*.

Both instances, TSPA and TSPB, have 200 nodes, so every solution has 100 nodes. We compute the distance matrix once, right after reading an instance. The algorithms use only this matrix and the node costs, not the coordinates.

2 Implemented algorithms

As the assignment says, "nearest" does not just mean the shortest edge. In every step the greedy methods choose the option that increases the objective the least, so they look at the extra distance *and* at the cost of the new node. If two options are equally good, we take the node with the lower index, so each greedy method always gives the same result for the same starting node.

When node j is inserted between two neighbouring nodes a and b, we add the edges $a \to j$ and $j \to b$, remove the edge $a \to b$ and pay the cost of j, so the objective grows by

$$\Delta(a, j, b) \;=\; d_{aj} + d_{jb} - d_{ab} + c_j.$$

Algorithm 1 Random solution

1: $P \leftarrow$ random permutation of V
2: **return** the first k nodes of P

Algorithm 2 Nearest neighbour, adding nodes only at the end of the path

Require: starting node s
1: $P \leftarrow (s)$
2: **while** $|P| < k$ **do**
3: $\quad \ell \leftarrow$ last node of P
4: $\quad j^* \leftarrow \arg\min_{j \notin P} \left(d_{\ell j} + c_j\right)$
5: $\quad$ append j^* to P
6: **return** P ▷ the last node connects back to the first

Algorithm 3 Nearest neighbour, adding nodes at any position of the path

Require: starting node s
$P \leftarrow (s)$ ▷ an open path $(p_1, \ldots, p_m)$
while $|P| < k$ **do**
  for all $j \notin P$ **do**
    ▷ cost of each place where j can go
    at the beginning: $d_{jp_1} + c_j$
    at the end: $d_{p_m j} + c_j$
    between p_i and p_{i+1}, $i = 1, \ldots, m-1$: $\Delta(p_i, j, p_{i+1})$
  insert the node j^* at the cheapest place found for any j
return P ▷ the last node connects back to the first

Algorithm 4 Greedy cycle

Require: starting node s
$j' \leftarrow \arg\min_{j \neq s} \left(d_{sj} + c_j\right)$ ▷ the "nearest" node
$C \leftarrow (s, j')$ ▷ an incomplete cycle $s \to j' \to s$
while $|C| < k$ **do**
  $(j^*, (a^*, b^*)) \leftarrow \arg\min_{j \notin C,\, (a,b) \in E(C)} \Delta(a, j, b)$
  $E(C)$: all edges of the cycle, also the one from the last node back to the first
  insert j^* between a^* and b^*
return C

Algorithms 3 and 4 differ in one thing. Algorithm 3 builds an open path and ignores the edge back to the start until the very end. Algorithm 4 keeps a closed cycle from the beginning, so this edge counts in every step like any other edge. Both need $O(k^2 n)$ time per solution; Algorithm 2 needs $O(kn)$.

3 Computational experiment

We ran each greedy method 200 times, once from every node as the starting node, and we generated 200 random solutions (with a fixed seed). 200 solutions take about 0.2 s for Algorithms 3 and 4 and about 10 ms for Algorithm 2. Table 1 shows the objective values; the best average and the best minimum for each instance are in bold. Table 2 shows the median for the greedy methods and what their average objective is made of.

Table 1: Objective function values over 200 solutions per method.

	TSPA			TSPB		
Method	avg	min	max	avg	min	max
Random	261 928	236 759	289 659	205 907	174 617	233 796
NN (end only)	87 477	84 362	90 075	**59 397**	56 007	63 166
NN (any position)	74 347	**72 328**	77 022	59 476	**52 915**	66 164
Greedy cycle	**73 797**	72 590	75 281	59 709	53 016	63 736

Table 2: Greedy methods: median objective, and average cycle length, node costs and closing edge (part of the length).

	TSPA				TSPB			
Method	median	length	costs	closing	median	length	costs	closing
NN (end only)	87 594	33 642	53 835	1 452	59 589	26 882	32 515	1 651
NN (any position)	74 278	23 072	51 276	1 576	60 254	18 678	40 798	2 031
Greedy cycle	73 744	22 309	51 489	233	59 167	17 935	41 774	194

4 Best solutions

Figures 1 and 2 show the best solution of each method. The colour and the size of a node show its cost; nodes that are not in the solution are faded. The red dashed line is the edge from the last node of the list back to the first.




Figure 1: Best solutions for instance TSPA.




Figure 2: Best solutions for instance TSPB.

Best solutions as lists of node indices (starting from 0)

TSPA, Random `46, 44, 47, 50, 168, 133, 112, 167, 91, 43, 5, 83, 184, 197, 9, 79, 24, 1, 75, 34, 51, 76, 192, 141, 163, 166, 196, 130, 84, 80, 182, 41, 118, 187, 15, 54, 22, 99, 120, 140, 148, 158, 121, 78, 52, 106, 90, 188, 63, 89, 97, 161, 174, 66, 139, 190, 65, 64, 164, 144, 38, 86, 55, 4, 16, 156, 105, 191, 162, 18, 33, 21, 19, 6, 42, 0, 67, 87, 117, 185, 74, 153, 109, 194, 138, 177, 157, 176, 81, 3, 49, 127, 126, 100, 69, 11, 131, 147, 125, 2`

TSPA, NN (end only) 54, 9, 33, 36, 177, 67, 144, 53, 135, 58, 134, 176, 174, 106, 89, 107, 57, 182, 151, 93, 50, 3, 1, 164, 178, 29, 136, 186, 184, 47, 159, 130, 153, 78, 88, 193, 170, 146, 75, 64, 150, 42, 113, 43, 85, 142, 8, 131, 84, 158, 192, 181, 114, 141, 180, 132, 76, 80, 48, 31, 63, 149, 168, 97, 127, 187, 30, 123, 152, 108, 60, 116, 49, 11, 119, 160, 83, 90, 51, 16, 35, 87, 45, 140, 52, 179, 185, 28, 102, 156, 157, 71, 91, 38, 100, 4, 112, 139, 115, 5

TSPA, NN (any position) 104, 129, 69, 127, 97, 168, 116, 149, 63, 11, 49, 160, 83, 123, 100, 152, 108, 60, 31, 48, 80, 91, 157, 71, 4, 76, 132, 180, 28, 102, 185, 35, 156, 51, 16, 67, 144, 140, 53, 179, 52, 177, 36, 33, 9, 54, 131, 174, 8, 164, 186, 136, 163, 29, 101, 178, 1, 169, 3, 50, 147, 47, 93, 106, 42, 89, 113, 130, 159, 146, 170, 153, 193, 78, 88, 107, 64, 57, 182, 151, 150, 176, 72, 134, 84, 58, 158, 192, 181, 114, 135, 73, 45, 87, 141, 187, 30, 189, 2, 171

TSPA, Greedy cycle 31, 116, 149, 168, 63, 11, 49, 60, 108, 152, 100, 90, 123, 83, 160, 97, 127, 69, 171, 2, 189, 30, 187, 141, 87, 45, 73, 135, 114, 181, 192, 158, 58, 84, 134, 72, 176, 150, 151, 182, 57, 64, 107, 88, 78, 193, 153, 170, 146, 159, 130, 113, 89, 42, 106, 93, 47, 147, 50, 3, 169, 1, 178, 101, 29, 163, 136, 186, 164, 142, 8, 174, 131, 54, 9, 33, 36, 177, 52, 179, 53, 140, 144, 67, 16, 51, 156, 35, 185, 102, 28, 180, 132, 76, 4, 71, 157, 91, 80, 48

TSPB, Random 111, 70, 192, 14, 22, 141, 29, 197, 163, 181, 82, 99, 25, 176, 16, 116, 60, 134, 104, 161, 40, 120, 66, 196, 155, 103, 64, 130, 183, 57, 3, 94, 80, 117, 38, 140, 49, 32, 174, 37, 166, 119, 41, 69, 65, 102, 46, 93, 186, 154, 198, 36, 1, 54, 106, 87, 107, 72, 0, 17, 171, 97, 114, 71, 27, 59, 165, 199, 4, 10, 179, 2, 124, 191, 149, 62, 51, 33, 113, 148, 84, 145, 132, 67, 160, 42, 48, 8, 177, 101, 61, 81, 152, 19, 121, 77, 50, 92, 133, 195

TSPB, NN (end only) 32, 89, 57, 76, 54, 127, 129, 90, 153, 20, 14, 2, 110, 118, 56, 114, 196, 10, 148, 143, 78, 192, 162, 104, 185, 184, 3, 151, 69, 172, 133, 120, 96, 121, 198, 48, 72, 46, 86, 117, 160, 136, 8, 21, 154, 140, 47, 170, 125, 177, 6, 132, 29, 197, 175, 134, 45, 60, 40, 71, 155, 97, 115, 180, 65, 28, 149, 145, 158, 116, 147, 42, 50, 130, 30, 183, 38, 64, 85, 59, 167, 51, 87, 179, 82, 88, 171, 99, 67, 24, 34, 181, 152, 73, 98, 27, 135, 75, 79, 156

TSPB, NN (any position) 110, 2, 14, 20, 74, 153, 182, 52, 90, 129, 127, 80, 54, 192, 162, 104, 76, 185, 57, 89, 86, 46, 72, 3, 184, 173, 151, 122, 117, 8, 160, 69, 172, 136, 133, 120, 156, 43, 48, 96, 198, 121, 130, 191, 50, 42, 147, 116, 37, 146, 13, 149, 28, 145, 65, 158, 177, 125, 26, 170, 197, 36, 132, 29, 6, 180, 115, 155, 71, 175, 134, 45, 157, 60, 40, 141, 97, 154, 140, 47, 38, 21, 176, 30, 183, 189, 168, 64, 59, 85, 51, 73, 167, 152, 34, 24, 181, 179, 87, 82

TSPB, Greedy cycle 49, 64, 33, 40, 60, 71, 155, 141, 157, 45, 134, 175, 62, 36, 197, 29, 132, 178, 103, 6, 180, 115, 170, 177, 125, 26, 97, 140, 154, 47, 38, 21, 176, 30, 183, 191, 130, 63, 121, 198, 96, 48, 89, 156, 120, 133, 136, 172, 160, 69, 8, 117, 72, 46, 86, 184, 3, 173, 122, 151, 98, 111, 27, 135, 76, 185, 57, 104, 162, 54, 192, 127, 52, 182, 153, 20, 74, 2, 14, 90, 129, 80, 150, 84, 66, 67, 31, 24, 34, 152, 181, 88, 179, 87, 82, 73, 167, 51, 59, 85

Verification with the solution checker

We checked all best solutions with the solution checker spreadsheet. We pasted each list of nodes into the checker, recalculated it and compared its result with ours (Table 3). All values are the same. We also checked every solution from the experiment: each one has exactly k different nodes.

Table 3: Best solutions: our objective value and the value from the checker.

	TSPA		TSPB	
Method	reported	checker	reported	checker
Random	236759	236759	174617	174617
NN (end only)	84362	84362	56007	56007
NN (any position)	72328	72328	52915	52915
Greedy cycle	72590	72590	53016	53016

5 Source code

The code is available at `https://github.com/michaelo-ponteski/evolutionary-computation/tree/lab1`. It is written in Rust. Code that later labs will also use (reading instances, distance matrix, objective function, heuristics) is in `common/`, the experiment for this lab is in `lab1/`, and the Python scripts for the plots and the checker are in `scripts/`.

6 Conclusions

- All greedy methods are much better than random solutions. The average drops from about 262 000 to 74 000-87 000 on TSPA and from about 206 000 to about 59 500 on TSPB. A big part of this comes from choosing cheap nodes: in the best greedy solutions on TSPA a chosen node costs about 510 on average, while the average over all nodes is 971.
- On TSPA, inserting nodes anywhere helps a lot: both insertion methods are about 15 % better on average than adding nodes only at the end. Greedy cycle has the best average and the best worst case, and nearest neighbour (any position) found the best single solution, but on average they differ by less than 1 %.
- On TSPB the averages of the three greedy methods are almost the same (59 397-59 709), but for different reasons (Table 2). Nearest neighbour (end only) makes 44-50 % longer cycles (26 882 vs. 17 935-18 678), but it chooses much cheaper nodes (32 515 vs. 40 798-41 774). On this instance the two effects almost cancel out. We think the reason is simple geometry: to add a far, cheap node at the end of a path we pay its distance once, but to insert it into the cycle we pay about twice as much, because we have to go there and come back. So the insertion methods prefer more expensive nodes that are close. On TSPA the node costs of the three methods are similar (51 276-53 835), so the shorter cycles win.
- On TSPB the order by average is not reliable. By median, greedy cycle is the best (59 167) and nearest neighbour (any position) is the worst (60 254). Nearest neighbour (any position) also has the widest range of results (52 915 to 66 164): a few very good solutions, including the best one of all methods, pull its average down, while a few weaker solutions pull up the average of greedy cycle.
- The edge back to the start explains much of this range. Nearest neighbour (any position) ignores this edge while building the path, so the two ends of the path can end up far apart. On average this edge is 2 031 long on TSPB and 1 576 on TSPA, and in its best TSPB solution it is the longest edge of the cycle (1 850). In greedy cycle it is a normal edge (194 and 233 on average), because in every step it can be split like any other edge.
- Node costs are 56-70 % of the objective of the best greedy solutions (for example 51 020 of 72 590 for the best greedy cycle on TSPA), so choosing the right nodes matters at least as much as their order. The greedy methods never change a node once it is chosen, so methods that can swap chosen and unchosen nodes could improve these solutions a lot.