

Function argument passing

Michael Nowak

Texas A&M University

Acknowledgement: Lecture slides based on those created by Bjarne Stroustrup for use with his textbook

Overview

Introduction

Passing arguments by value

Passing arguments by reference

- Using references to avoid copies

- Using references to “return” multiple values

Passing arguments by constant reference

Aside: reading declarations

Guidance for passing arguments

Functions that return a value

- How values are returned

- Never return a reference or pointer to a local variable

References

Overview

Introduction

Passing arguments by value

Passing arguments by reference

- Using references to avoid copies

- Using references to “return” multiple values

Passing arguments by constant reference

Aside: reading declarations

Guidance for passing arguments

Functions that return a value

- How values are returned

- Never return a reference or pointer to a local variable

References

Introduction

- ▶ Each time a function is called, its parameters are defined and initialized by the arguments passed in the function call

Introduction

- ▶ Each time a function is called, its parameters are defined and initialized by the arguments passed in the function call
- ▶ The semantics of argument passing are identical to the semantics of initialization

Introduction

- ▶ Each time a function is called, its parameters are defined and initialized by the arguments passed in the function call
- ▶ The semantics of argument passing are identical to the semantics of initialization
 - ▶ Parameter initialization/binding works the same way as variable/reference initialization

Introduction

- ▶ Each time a function is called, its parameters are defined and initialized by the arguments passed in the function call
- ▶ The semantics of argument passing are identical to the semantics of initialization
 - ▶ Parameter initialization/binding works the same way as variable/reference initialization
 - ▶ When the parameter is an object, we say that the argument is **passed by value** because a value is copied into that object for initialization

Introduction

- ▶ Each time a function is called, its parameters are defined and initialized by the arguments passed in the function call
- ▶ The semantics of argument passing are identical to the semantics of initialization
 - ▶ Parameter initialization/binding works the same way as variable/reference initialization
 - ▶ When the parameter is an object, we say that the argument is **passed by value** because a value is copied into that object for initialization
 - ▶ When a parameter is a reference, we say that the argument is **passed by reference** because the parameter binds to the object being passed; the parameter becomes an **alias** for the object to which it is bound

Introduction

- ▶ Each time a function is called, its parameters are defined and initialized by the arguments passed in the function call
- ▶ The semantics of argument passing are identical to the semantics of initialization
 - ▶ Parameter initialization/binding works the same way as variable/reference initialization
 - ▶ When the parameter is an object, we say that the argument is **passed by value** because a value is copied into that object for initialization
 - ▶ When a parameter is a reference, we say that the argument is **passed by reference** because the parameter binds to the object being passed; the parameter becomes an **alias** for the object to which it is bound
 - ▶ Argument types are checked during compilation and implicit type conversions take place when necessary

Overview

Introduction

Passing arguments by value

Passing arguments by reference

- Using references to avoid copies

- Using references to “return” multiple values

Passing arguments by constant reference

Aside: reading declarations

Guidance for passing arguments

Functions that return a value

- How values are returned

- Never return a reference or pointer to a local variable

References

Passing arguments by value

- ▶ When we initialize a variable, the value of the initializer is copied into the object that the name refers; consider that:

Passing arguments by value

- ▶ When we initialize a variable, the value of the initializer is copied into the object that the name refers; consider that:

```
int i = 7;  
int ii = i; // ii value is a copy of the value in i  
i = 11 // value stored in i is 11; value in ii is left  
unchanged
```

Passing arguments by value

- ▶ When we initialize a variable, the value of the initializer is copied into the object that the name refers; consider that:

```
int i = 7;  
int ii = i; // ii value is a copy of the value in i  
i = 11 // value stored in i is 11; value in ii is left  
unchanged
```

i

7

(0x7fff5952233c)

ii

11

(0x7fff59522338)

Passing arguments by value

- ▶ The semantics of argument passing are identical to the semantics of initialization

Passing arguments by value

- ▶ The semantics of argument passing are identical to the semantics of initialization
- ▶ Passing an argument by value works the exact same way as initializing a variable with some value

Passing arguments by value

- ▶ The semantics of argument passing are identical to the semantics of initialization
- ▶ Passing an argument by value works the exact same way as initializing a variable with some value
 - ▶ Changes that the function makes to the parameter will *never* be reflected in the object (i.e., argument) used to initialize that parameter: we're merely working with a copy of the argument

Overview

Introduction

Passing arguments by value

Passing arguments by reference

- Using references to avoid copies

- Using references to “return” multiple values

Passing arguments by constant reference

Aside: reading declarations

Guidance for passing arguments

Functions that return a value

- How values are returned

- Never return a reference or pointer to a local variable

References

Passing arguments by reference

- ▶ When defining a reference to an object, we bind that reference to its initializer

Passing arguments by reference

- ▶ When defining a reference to an object, we bind that reference to its initializer

```
int i = 7;  
int &ii = i; // ii a reference to i  
ii = 11 // value stored in i is now 11
```

Passing arguments by reference

- When defining a reference to an object, we bind that reference to its initializer

```
int i = 7;  
int &ii = i; // ii a reference to i  
ii = 11 // value stored in i is now 11
```

Passing arguments by reference

- ▶ The semantics of argument passing are identical to the semantics of initialization

Passing arguments by reference

- ▶ The semantics of argument passing are identical to the semantics of initialization
- ▶ Passing an argument by reference works the exact same way as binding a reference to a named object for which it is initialized

Passing arguments by reference

- ▶ The semantics of argument passing are identical to the semantics of initialization
- ▶ Passing an argument by reference works the exact same way as binding a reference to a named object for which it is initialized
 - ▶ Changes that the function “makes” on a reference parameter will *always* be reflected in the object bound to that reference

Passing arguments by reference

- ▶ The semantics of argument passing are identical to the semantics of initialization
- ▶ Passing an argument by reference works the exact same way as binding a reference to a named object for which it is initialized
 - ▶ Changes that the function “makes” on a reference parameter will *always* be reflected in the object bound to that reference
 - ▶ The reference parameter is simply another name for the object for which it is initialized

Overview

Introduction

Passing arguments by value

Passing arguments by reference

- Using references to avoid copies

- Using references to “return” multiple values

Passing arguments by constant reference

Aside: reading declarations

Guidance for passing arguments

Functions that return a value

- How values are returned

- Never return a reference or pointer to a local variable

References

Using references to avoid copies

- ▶ Some objects in our program can become very large

Using references to avoid copies

- ▶ Some objects in our program can become very large
 - ▶ Passing such objects by reference avoids the overhead of copying very large arguments

Using references to avoid copies

- ▶ Some objects in our program can become very large
 - ▶ Passing such objects by reference avoids the overhead of copying very large arguments
- ▶ Some objects (such as the IO types) cannot be copied

Using references to avoid copies

- ▶ Some objects in our program can become very large
 - ▶ Passing such objects by reference avoids the overhead of copying very large arguments
- ▶ Some objects (such as the IO types) cannot be copied
 - ▶ Passing such objects by reference allows our functions to operate on objects that cannot be copied

Overview

Introduction

Passing arguments by value

Passing arguments by reference

- Using references to avoid copies

- Using references to “return” multiple values

Passing arguments by constant reference

Aside: reading declarations

Guidance for passing arguments

Functions that return a value

- How values are returned

- Never return a reference or pointer to a local variable

References

Using references to “return” multiple values

- ▶ A function can only return a single object (value)

Using references to “return” multiple values

- ▶ A function can only return a single object (value)
- ▶ Sometimes, we would like to “return” multiple objects to the caller

Using references to “return” multiple values

- ▶ A function can only return a single object (value)
- ▶ Sometimes, we would like to “return” multiple objects to the caller
 - ▶ We could create a user-defined type that contains those objects

Using references to “return” multiple values

- ▶ A function can only return a single object (value)
- ▶ Sometimes, we would like to “return” multiple objects to the caller
 - ▶ We could create a user-defined type that contains those objects
 - ▶ An easier solution is to pass-by-reference additional arguments that can be used to house the values that we'd like to return

Overview

Introduction

Passing arguments by value

Passing arguments by reference

- Using references to avoid copies

- Using references to “return” multiple values

Passing arguments by constant reference

Aside: reading declarations

Guidance for passing arguments

Functions that return a value

- How values are returned

- Never return a reference or pointer to a local variable

References

Passing arguments by constant reference

- ▶ Passing arguments by “plain vanilla” references should generally be avoided (unless you have reason to use them)

Passing arguments by constant reference

- ▶ Passing arguments by “plain vanilla” references should generally be avoided (unless you have reason to use them)
 - ▶ They can lead to obscure bugs when you forget which arguments can be changed

Passing arguments by constant reference

- ▶ Passing arguments by “plain vanilla” references should generally be avoided (unless you have reason to use them)
 - ▶ They can lead to obscure bugs when you forget which arguments can be changed
- ▶ You should use `reference to const` when you are passing large objects and would like the benefits of pass-by-reference, but do not need to modify the arguments

Passing arguments by constant reference

- ▶ Passing arguments by “plain vanilla” references should generally be avoided (unless you have reason to use them)
 - ▶ They can lead to obscure bugs when you forget which arguments can be changed
- ▶ You should use `reference to const` when you are passing large objects and would like the benefits of pass-by-reference, but do not need to modify the arguments
 - ▶ We can use the non-type specifier `const` in a `declaration` to tell the compiler that the object being referenced should be constant (and thus not be changed):

Passing arguments by constant reference

- ▶ Passing arguments by “plain vanilla” references should generally be avoided (unless you have reason to use them)
 - ▶ They can lead to obscure bugs when you forget which arguments can be changed
- ▶ You should use `reference to const` when you are passing large objects and would like the benefits of pass-by-reference, but do not need to modify the arguments
 - ▶ We can use the non-type specifier `const` in a `declaration` to tell the compiler that the object being referenced should be constant (and thus not be changed):

```
const int &i = j;
```


Overview

Introduction

Passing arguments by value

Passing arguments by reference

- Using references to avoid copies

- Using references to “return” multiple values

Passing arguments by constant reference

Aside: reading declarations

Guidance for passing arguments

Functions that return a value

- How values are returned

- Never return a reference or pointer to a local variable

References

Aside: reading declarations

- It is often helpful to read declarations from the right-to-left to figure out what we've got going on in a declaration

Aside: reading declarations

- ▶ It is often helpful to read declarations from the right-to-left to figure out what we've got going on in a declaration
- ▶ I'll frequently declare a constant reference by writing the alternative (but equivalent) declaration `int const &i = j;`

Aside: reading declarations

- ▶ It is often helpful to read declarations from the right-to-left to figure out what we've got going on in a declaration
- ▶ I'll frequently declare a constant reference by writing the alternative (but equivalent) declaration `int const &i = j;`
- ▶ Reading from right-to-left, it is certain that *i is a reference to a constant int*

Aside: reading declarations

- ▶ It is often helpful to read declarations from the right-to-left to figure out what we've got going on in a declaration
- ▶ I'll frequently declare a constant reference by writing the alternative (but equivalent) declaration `int const &i = j;`
- ▶ Reading from right-to-left, it is certain that *i is a reference to a constant int*
- ▶ In the following code, what is `pr`?

```
int i = 7;  
int const*p = &i;  
int const*&pr = p;
```

Aside: reading declarations

- ▶ It is often helpful to read declarations from the right-to-left to figure out what we've got going on in a declaration
- ▶ I'll frequently declare a constant reference by writing the alternative (but equivalent) declaration `int const &i = j;`
- ▶ Reading from right-to-left, it is certain that *i is a reference to a constant int*
- ▶ In the following code, what is `pr`?

```
int i = 7;  
int const*p = &i;  
int const*&pr = p;
```

- ▶ What happens if we write the statement `*pr = 11;` in our program?

Overview

Introduction

Passing arguments by value

Passing arguments by reference

- Using references to avoid copies

- Using references to “return” multiple values

Passing arguments by constant reference

Aside: reading declarations

Guidance for passing arguments

Functions that return a value

- How values are returned

- Never return a reference or pointer to a local variable

References

Guidance for passing arguments

- ▶ Use pass-by-value for small objects, such as the primitive built-in types
 - ▶ Using pass-by-reference to a small object is a bit slower than copying that object

Guidance for passing arguments

- ▶ Use pass-by-value for small objects, such as the primitive built-in types
 - ▶ Using pass-by-reference to a small object is a bit slower than copying that object
 - ▶ If you think of a reference as a constant pointer (value cannot be changed) that automatically dereferences itself when it is used, the reason becomes clear

Guidance for passing arguments

- ▶ Use pass-by-value for small objects, such as the primitive built-in types
 - ▶ Using pass-by-reference to a small object is a bit slower than copying that object
 - ▶ If you think of a reference as a constant pointer (value cannot be changed) that automatically dereferences itself when it is used, the reason becomes clear
 - ▶ Such indirection would require us to look-up the address of the object being referenced and then look up the object residing at that address

Guidance for passing arguments

- ▶ Use pass-by-value for small objects, such as the primitive built-in types
 - ▶ Using pass-by-reference to a small object is a bit slower than copying that object
 - ▶ If you think of a reference as a constant pointer (value cannot be changed) that automatically dereferences itself when it is used, the reason becomes clear
 - ▶ Such indirection would require us to look-up the address of the object being referenced and then look up the object residing at that address
- ▶ Use pass-by-const-reference for large objects, such as vectors

Guidance for passing arguments

- ▶ Use pass-by-value for small objects, such as the primitive built-in types
 - ▶ Using pass-by-reference to a small object is a bit slower than copying that object
 - ▶ If you think of a reference as a constant pointer (value cannot be changed) that automatically dereferences itself when it is used, the reason becomes clear
 - ▶ Such indirection would require us to look-up the address of the object being referenced and then look up the object residing at that address
- ▶ Use pass-by-const-reference for large objects, such as vectors
- ▶ Use pass-by-reference *only when you have to*
 - ▶ Favor returning a result rather than modifying an object through a reference argument

Overview

Introduction

Passing arguments by value

Passing arguments by reference

- Using references to avoid copies

- Using references to “return” multiple values

Passing arguments by constant reference

Aside: reading declarations

Guidance for passing arguments

Functions that return a value

- How values are returned

- Never return a reference or pointer to a local variable

References

Functions that return a value

- ▶ Every function with a return type other than `void` must return a value

Functions that return a value

- ▶ Every function with a return type other than `void` must return a value
- ▶ The value that the function returns must match the return type or be compatible with the return type

Overview

Introduction

Passing arguments by value

Passing arguments by reference

- Using references to avoid copies

- Using references to “return” multiple values

Passing arguments by constant reference

Aside: reading declarations

Guidance for passing arguments

Functions that return a value

- How values are returned

- Never return a reference or pointer to a local variable

References

How values are returned

- ▶ The value to be returned is used to initialize a temporary variable at the call site
 - ▶ The type of this variable is that of the return type

How values are returned

- ▶ The value to be returned is used to initialize a temporary variable at the call site
 - ▶ The type of this variable is that of the return type
- ▶ This temporary is the result of the function call

How values are returned

- ▶ The value to be returned is used to initialize a temporary variable at the call site
 - ▶ The type of this variable is that of the return type
- ▶ This temporary is the result of the function call
- ▶ The semantics used for initializing the temporary are identical to the semantics of initialization

Overview

Introduction

Passing arguments by value

Passing arguments by reference

- Using references to avoid copies

- Using references to “return” multiple values

Passing arguments by constant reference

Aside: reading declarations

Guidance for passing arguments

Functions that return a value

- How values are returned

- Never return a reference or pointer to a local variable

References

Never return a reference or pointer to a local variable

- ▶ Why not?
- ▶ Think about this... with respect to an automatic variable's lifetime...

Overview

Introduction

Passing arguments by value

Passing arguments by reference

- Using references to avoid copies

- Using references to “return” multiple values

Passing arguments by constant reference

Aside: reading declarations

Guidance for passing arguments

Functions that return a value

- How values are returned

- Never return a reference or pointer to a local variable

References

References

- ▶ Lippman, B., Lajoie, Josee, & Moo, B. E. (2016). *C++ primer* (5th ed.). Addison-Wesley.
- ▶ Stroustrup, B. (2014). *Programming: principles and practice using C++* (2nd ed.). Addison-Wesley.