

Customizing I/O

Michael Nowak

Texas A&M University

Acknowledgement: Lecture slides based on those created by Bjarne Stroustrup for use with his textbook

Notes

Overview

Output formats

Formatting output

Integer output

Floating-point output

defaultfloat format

scientific format

fixed format

Output fields

Field width

Field fill

Field adjustment

Line-oriented input

Type vs. line

Mixing formatted input with line-oriented input - be careful

Prefer formatted input

Character-oriented input

Character classification functions

References

Notes

Observation

- ▶ As programmers we prefer **regularity** and **simplicity**
 - ▶ But, our job is to meet people's expectations
- ▶ People are very fussy/particular/picky about the way their output looks
 - ▶ They often have good reasons to be
 - ▶ Convention/tradition rules
 - ▶ What does 110 mean?
 - ▶ What does 123,456 mean?
 - ▶ What does (123) mean?
- ▶ The world (of output formats) is far more particular than you could possibly imagine

Notes

Overview

Output formats

Formatting output

Integer output

Floating-point output

defaultfloat format

scientific format

fixed format

Output fields

Field width

Field fill

Field adjustment

Line-oriented input

Type vs. line

Mixing formatted input with line-oriented input - be careful

Prefer formatted input

Character-oriented input

Character classification functions

References

Notes

Output formats

- ▶ Integer values
 - ▶ 1234 (decimal)
 - ▶ 2322 (octal)
 - ▶ 4d2 (hexadecimal)
- ▶ Floating-point values
 - ▶ 1234.57 (general)
 - ▶ 1.2345678e+03 (scientific)
 - ▶ 1234.567890 (fixed)
- ▶ Precision (for floating-point values)
 - ▶ 1234.57 (precision 6)
 - ▶ 1234.6 (precision 5)
- ▶ Fields
 - ▶ |12| (default for l followed by 12 followed by l)
 - ▶ l 12l (12 in a field of 4 characters)

Notes

Overview

Output formats

Formatting output

Integer output

Floating-point output

defaultfloat format

scientific format

fixed format

Output fields

Field width

Field fill

Field adjustment

Line-oriented input

Type vs. line

Mixing formatted input with line-oriented input - be careful

Prefer formatted input

Character-oriented input

Character classification functions

References

Notes

Formatting output

- ▶ Output formatting is controlled by a set of flags and integer values for a given stream
 - ▶ Integral output
 - ▶ Floating-point output
 - ▶ Output fields
 - ▶ Field adjustment
- ▶ Manipulators
 - ▶ Manipulators allow us to manipulate the state of a stream; they are inserted between the objects being read or written
 - ▶ Most manipulators are sticky : they are set and permanent until changed

```
#include<iomanip>
```

Notes

Overview

- Output formats
- Formatting output
 - Integer output
 - Floating-point output
 - defaultfloat format
 - scientific format
 - fixed format
- Output fields
 - Field width
 - Field fill
 - Field adjustment
- Line-oriented input
 - Type vs. line
 - Mixing formatted input with line-oriented input - be careful
 - Prefer formatted input
- Character-oriented input
 - Character classification functions
- References

Notes

Integer output

- ▶ Decimal (base-10)
 - ▶ Manipulator: `std::dec` (sticky)
`cout << dec << 1234; → 1234`
- ▶ Octal (base-8)
 - ▶ Manipulator: `std::oct` (sticky)
`cout << oct << 1234; → 2322`
- ▶ Hexadecimal (base-16)
 - ▶ Manipulator: `std::hex` (sticky)
`cout << hex << 1234; → 4d2`
- ▶ Showbase
 - ▶ Manipulator: `std::showbase` (sticky)
`cout << showbase << oct << 1234; → 02322`
`cout << showbase << hex << 1234; → 0x4d2`
- ▶ Noshowbase
 - ▶ Manipulator: `std::noshowbase` (sticky)

Notes

Integer output ex1

```
// simple test:
cout << dec << 1234 << "\t(decimal)\n"
    << hex << 1234 << "\t(hexadecimal)\n"
    << oct << 1234 << "\t(octal)\n";

// results:
1234      (decimal)
4d2       (hexadecimal)
2322      (octal)
```

Notes

Integer output ex2

```
// simple test:
cout << 1234 << '\t'
    << hex << 1234 << '\t'
    << oct << 1234 << '\n';
cout << 1234 << '\n';

// results:
1234      4d2      2322
2322
```

Notes

Integer output ex3

```
// simple test:
cout << 1234 << '\t'
    << hex << 1234 << '\t'
    << oct << 1234 << endl;
cout << showbase << dec;
cout << 1234 << '\t'
    << hex << 1234 << '\t'
    << oct << 1234 << '\n';

// results:
1234      4d2 2322
1234      0x4d2 02322
```

Notes

Overview

- Output formats
 - Formatting output**
 - Integer output
 - Floating-point output**
 - defaultfloat format
 - scientific format
 - fixed format
 - Output fields
 - Field width
 - Field fill
 - Field adjustment
 - Line-oriented input
 - Type vs. line
 - Mixing formatted input with line-oriented input - be careful
 - Prefer formatted input
 - Character-oriented input
 - Character classification functions
 - References

Notes

Floating-point output

- ▶ Floating-point output formatting is controlled by its **format** and **precision**
- ▶ The floating-point value being output is rounded to give the best approximation that can be printed given the specified **precision** in the chosen **format**
- ▶ The default **precision** is six digits

Notes

Overview

- Output formats
 - Formatting output**
 - Integer output
 - Floating-point output**
 - defaultfloat format
 - scientific format
 - fixed format
 - Output fields
 - Field width
 - Field fill
 - Field adjustment
 - Line-oriented input
 - Type vs. line
 - Mixing formatted input with line-oriented input - be careful
 - Prefer formatted input
 - Character-oriented input
 - Character classification functions
 - References

Notes

defaultfloat format

- ▶ The `defaultfloat` format lets the implementation choose the format (`fixed` or `scientific`) that presents a value in the style that best preserves the value in the specified `precision`
- ▶ For `defaultfloat`, `precision` specifies the maximum number of digits
 - ▶ We can specify the precision using the `setprecision()` manipulator (sticky)
- ▶ `cout << defaultfloat << 1234.567; → 1234.57`
- ▶ `cout << defaultfloat << 1234567.0; → 1.23457e+006`

Notes

Overview

Output formats

Formatting output

Integer output

Floating-point output

`defaultfloat` format

`scientific` format

`fixed` format

Output fields

Field width

Field fill

Field adjustment

Line-oriented input

Type vs. line

Mixing formatted input with line-oriented input - be careful

Prefer formatted input

Character-oriented input

Character classification functions

References

Notes

scientific format

- ▶ The `scientific` format presents a value with one digit before a decimal point followed by an exponent
- ▶ The `precision` is the number n of digits after the decimal point
- ▶ `cout << scientific << 1234.56789; → 1.234568e+03`
- ▶ `cout << scientific << setprecision(3) << 1234.56789; → 1.235e+03`

Notes

Overview

- Output formats
 - Formatting output
 - Integer output
 - Floating-point output
 - defaultfloat format
 - scientific format
 - fixed format
 - Output fields
 - Field width
 - Field fill
 - Field adjustment
 - Line-oriented input
 - Type vs. line
 - Mixing formatted input with line-oriented input - be careful
 - Prefer formatted input
 - Character-oriented input
 - Character classification functions
 - References

Notes

fixed format

- ▶ The `fixed` format presents a floating-point value as an integer followed by a decimal point and a fractional part
- ▶ The `precision` is the number of digits after the decimal point
- ▶ `cout << fixed << 1234.56789` → `1234.567890`
- ▶ `cout << fixed << setprecision(3) << 1234.56789` → `1234.568`

Notes

Overview

- Output formats
 - Formatting output
 - Integer output
 - Floating-point output
 - defaultfloat format
 - scientific format
 - fixed format
 - Output fields
 - Field width
 - Field fill
 - Field adjustment
 - Line-oriented input
 - Type vs. line
 - Mixing formatted input with line-oriented input - be careful
 - Prefer formatted input
 - Character-oriented input
 - Character classification functions
 - References

Notes

Output fields

- Frequently, we would like to fill a specific number of character spaces on an output line with text
 - E.g., we want exactly n -characters and not fewer (and more only if the text does not fit)
- We can specify a field width, and a character to be used if padding is needed, for a value being output

Notes

Overview

Output formats

Formatting output

Integer output

Floating-point output

defaultfloat format

scientific format

fixed format

Output fields

Field width

Field fill

Field adjustment

Line-oriented input

Type vs. line

Mixing formatted input with line-oriented input - be careful

Prefer formatted input

Character-oriented input

Character classification functions

References

Notes

Field width

- We can specify the minimum number of characters to be used in an output field
 - Manipulator: `std::setw()` (not-sticky)
 - By default, the text is right-aligned in the output field
- ```
cout << setw(4) << 1; → 1
cout << setw(8) << "Michael"; → Michael
```

### Notes

---

---

---

---

---

---

---



## Overview

- Output formats
- Formatting output
  - Integer output
  - Floating-point output
    - defaultfloat format
    - scientific format
    - fixed format
- Output fields**
  - Field width
  - Field fill**
  - Field adjustment
- Line-oriented input
  - Type vs. line
  - Mixing formatted input with line-oriented input - be careful
  - Prefer formatted input
- Character-oriented input
  - Character classification functions
- References

## Notes

---

---

---

---

---

---

---

## Field fill

- We can specify the “padding” or “filler” character of an output field
- Manipulator: `std::setfill()` (sticky)  
`cout << setw(4) << setfill('*') << 1; → ***1`

## Notes

---

---

---

---

---

---

---

## Overview

- Output formats
- Formatting output
  - Integer output
  - Floating-point output
    - defaultfloat format
    - scientific format
    - fixed format
- Output fields**
  - Field width
  - Field fill
  - Field adjustment**
- Line-oriented input
  - Type vs. line
  - Mixing formatted input with line-oriented input - be careful
  - Prefer formatted input
- Character-oriented input
  - Character classification functions
- References

## Notes

---

---

---

---

---

---

---

## Field adjustment

- We can adjust characters within a field
  - **right** (non-sticky) adjustment (default), which right-aligns the characters within a field

```
cout << setw(4) << 1; → 1111
```
  - **left** (non-sticky) adjustment, which left-aligns the characters within a field

```
cout << setw(4) << << setfill('*') << right << 1;
→ 1***
```
  - **internal** (non-sticky) adjustment, which places fill characters between the sign and the value

```
cout << setw(4) << << setfill('.') << internal <<
-1; → -.1
```

### Notes

---

---

---

---

---

---

---

## Overview

Output formats  
Formatting output  
Integer output  
Floating-point output  
    defaultfloat format  
    scientific format  
    fixed format  
Output fields  
Field width  
Field fill  
Field adjustment  
**Line-oriented input**  
Type vs. line  
Mixing formatted input with line-oriented input - be careful  
Prefer formatted input  
Character-oriented input  
    Character classification functions  
References

### Notes

---

---

---

---

---

---

---

## Overview

Output formats  
Formatting output  
Integer output  
Floating-point output  
    defaultfloat format  
    scientific format  
    fixed format  
Output fields  
Field width  
Field fill  
Field adjustment  
**Line-oriented input**  
Type vs. line  
Mixing formatted input with line-oriented input - be careful  
Prefer formatted input  
Character-oriented input  
    Character classification functions  
References

### Notes

---

---

---

---

---

---

---

## Type vs. line

### ► Read a string:

```
string name;
cin >> name;
// input: Bjarne Stroustrup
cout << name << endl;
// output: Bjarne
```

### ► Read a line:

```
string name;
getline(cin,name);
// input: Bjarne Stroustrup
cout << name << endl;
// output: Bjarne Stroustrup
/* now what? */
/* maybe... */
istringstream ss(name);
ss >> first_name;
ss >> second_name;
```

## Notes

---

---

---

---

---

---

## Overview

Output formats

Formatting output

Integer output

Floating-point output

defaultfloat format

scientific format

fixed format

Output fields

Field width

Field fill

Field adjustment

Line-oriented input

Type vs. line

Mixing formatted input with line-oriented input - be careful

Prefer formatted input

Character-oriented input

Character classification functions

References

## Notes

---

---

---

---

---

---

## Mixing formatted input with line-oriented input - be careful

```
int yob; string name;
cin >> yob;
// input: 1950
getline(cin,name);
cout << yob << '\t' << name << endl;
Output: 1950
```

- (cin) reads formatted input and delimits on white-spaces
- This means that there is still a linefeed left-over in the input buffer from the character return when I entered 1950  
[Return]
- It is that character return that is read by `getline(cin,name)`
- Meaning that `getline` does not block for data from standard input

## Notes

---

---

---

---

---

---

Overview

- Output formats
- Formatting output
  - Integer output
  - Floating-point output
    - defaultfloat format
    - scientific format
    - fixed format

- Output fields
  - Field width
  - Field fill
  - Field adjustment

- Line-oriented input
  - Type vs. line
  - Mixing formatted input with line-oriented input - be careful
- Prefer formatted input

- Character-oriented input
  - Character classification functions
- References

Notes

---

---

---

---

---

---

---

Prefer formatted input

- Prefer formatted input >> to line-oriented input `getline()`
  - i.e. avoid line-oriented input when you can
- People often use `getline()` because they see no alternative
  - But it easily gets messy
  - When trying to use `getline()`, you often end up
    - using >> to parse the line from a `stringstream`
    - using `get()` to read individual characters

Notes

---

---

---

---

---

---

---

Overview

- Output formats
- Formatting output
  - Integer output
  - Floating-point output
    - defaultfloat format
    - scientific format
    - fixed format

- Output fields
  - Field width
  - Field fill
  - Field adjustment

- Line-oriented input
  - Type vs. line
  - Mixing formatted input with line-oriented input - be careful
  - Prefer formatted input

- Character-oriented input
  - Character classification functions
- References

Notes

---

---

---

---

---

---

---

## Character-oriented input

- You can also read individual characters:

```
for (char ch; cin >> ch;)
{
 if (isalpha(ch)) {
 // do something
 }
}

for (char ch; cin.get(ch);)
{
 characters
 if (isspace(ch)) {
 // do something
 } else if (isalpha(ch)) {
 // do something else
 }
}
```

### Notes

---

---

---

---

---

---

---

## Overview

Output formats

Formatting output

Integer output

Floating-point output

defaultfloat format

scientific format

fixed format

Output fields

Field width

Field fill

Field adjustment

Line-oriented input

Type vs. line

Mixing formatted input with line-oriented input - be careful

Prefer formatted input

Character-oriented input

Character classification functions

References

### Notes

---

---

---

---

---

---

---

## Character classification functions

- If you use character-oriented input, you often need one or more of these (from header `<cctype>`):
  - `isspace(c)`
    - is `c` whitespace (' ', '\t', '\n', etc.)?
  - `isalpha(c)`
    - is `c` a letter ('a'..'z', 'A'..'Z')? note: not '\_'
  - `isdigit(c)`
    - is `c` a decimal digit ('0'..'9')?
  - `isupper(c)`
    - is `c` an upper case letter ('A'..'Z')?
  - `islower(c)`
    - is `c` a lower case letter ('a'..'z')?
  - `isalnum(c)`
    - is `c` a letter or a decimal digit ('a'..'z', 'A'..'Z', '0'..'9')?

### Notes

---

---

---

---

---

---

---

## Overview

Output formats

Formatting output

Integer output

Floating-point output

defaultfloat format

scientific format

fixed format

Output fields

Field width

Field fill

Field adjustment

Line-oriented input

Type vs. line

Mixing formatted input with line-oriented input - be careful

Prefer formatted input

Character-oriented input

Character classification functions

References

Notes

## References

- Lippman, B., Lajoie, Josee, & Moo, B. E. (2016). *C++ primer* (5th ed.). Addison-Wesley.
- Stroustrup, B. (2014). *Programming: principles and practice using C++* (2nd ed.). Addison-Wesley.

Notes

Notes