

# I/O streams

Michael Nowak

Texas A&M University

Acknowledgement: Lecture slides based on those created by Bjarne Stroustrup for use with his textbook

# Overview

- Introduction

- Input & output

- The stream model

  - ostream

  - istream

  - Reading and writing

    - Reading from character streams

- The I/O classes

  - Relationship among I/O types

- File I/O

  - General model

  - General process

  - File streams

  - Using file stream objects

    - Opening a file for reading

    - Opening a file for writing (discard contents)

    - Opening a file for writing (append to existing contents)

    - Reading a file

- I/O error handling

  - Stream state flags

  - Stream state functions

  - Validating input with stream state

- References

# Overview

## Introduction

### Input & output

### The stream model

- ostream

- istream

### Reading and writing

- Reading from character streams

## The I/O classes

### Relationship among I/O types

## File I/O

### General model

### General process

### File streams

### Using file stream objects

- Opening a file for reading

- Opening a file for writing (discard contents)

- Opening a file for writing (append to existing contents)

- Reading a file

## I/O error handling

### Stream state flags

### Stream state functions

### Validating input with stream state

## References

# Introduction

- ▶ The C++ language does not deal directly with input and output

# Introduction

- ▶ The C++ language does not deal directly with input and output
- ▶ The C++ language's `standard library` provides a family of `types` that provide the I/O facilities
  - ▶ For instance, we have had to `#include<iostream>` to use the `objects`
    - ▶ `std::cin` to read from `standard input`
    - ▶ `std::cout` to write to `standard output`

# Introduction

- ▶ The C++ language does not deal directly with input and output
- ▶ The C++ language's `standard library` provides a family of `types` that provide the I/O facilities
  - ▶ For instance, we have had to `#include<iostream>` to use the `objects`
    - ▶ `std::cin` to read from `standard input`
    - ▶ `std::cout` to write to `standard output`

# Introduction

- ▶ The C++ language does not deal directly with input and output
- ▶ The C++ language's `standard library` provides a family of `types` that provide the I/O facilities
  - ▶ For instance, we have had to `#include<iostream>` to use the `objects`
    - ▶ `std::cin` to read from `standard input`
    - ▶ `std::cout` to write to `standard output`
  - ▶ For most programs, limiting I/O to the console window is insufficient

# Introduction

- ▶ The C++ language does not deal directly with input and output
- ▶ The C++ language's `standard library` provides a family of `types` that provide the I/O facilities
  - ▶ For instance, we have had to `#include<iostream>` to use the `objects`
    - ▶ `std::cin` to read from `standard input`
    - ▶ `std::cout` to write to `standard output`
  - ▶ For most programs, limiting I/O to the console window is insufficient
- ▶ The `standard library` provides different kinds of I/O types to support different kinds of I/O processing



# Overview

Introduction

**Input & output**

The stream model

ostream

istream

Reading and writing

Reading from character streams

The I/O classes

Relationship among I/O types

File I/O

General model

General process

File streams

Using file stream objects

Opening a file for reading

Opening a file for writing (discard contents)

Opening a file for writing (append to existing contents)

Reading a file

I/O error handling

Stream state flags



Stream state functions

Validating input with stream state


References

# Input & output

**data source:**



**data destination:**



# Overview

Introduction

Input & output

The stream model

ostream

istream

Reading and writing

Reading from character streams

The I/O classes

Relationship among I/O types

File I/O

General model

General process

File streams

Using file stream objects

Opening a file for reading

Opening a file for writing (discard contents)

Opening a file for writing (append to existing contents)

Reading a file

I/O error handling

Stream state flags

Stream state functions

Validating input with stream state

References

# The stream model

- ▶ A `stream` is a programming language construct that provides you with a character-based interface to I/O devices

# The stream model

- ▶ A **stream** is a programming language construct that provides you with a character-based interface to I/O devices
- ▶ A common metaphor is a “stream of water”: data is provided or consumed in a single-pass

# The stream model

- ▶ A `stream` is a programming language construct that provides you with a character-based interface to I/O devices
- ▶ A common metaphor is a “stream of water”: data is provided or consumed in a single-pass
  - ▶ Character data provided to a program from standard input flows through the `input stream` precisely once

# The stream model

- ▶ A **stream** is a programming language construct that provides you with a character-based interface to I/O devices
- ▶ A common metaphor is a “stream of water”: data is provided or consumed in a single-pass
  - ▶ Character data provided to a program from standard input flows through the **input stream** precisely once
  - ▶ Character data sent to standard output flows through the output stream to the console window precisely once

# The stream model

- ▶ A `stream` is a programming language construct that provides you with a character-based interface to I/O devices
- ▶ A common metaphor is a “stream of water”: data is provided or consumed in a single-pass
  - ▶ Character data provided to a program from standard input flows through the `input stream` precisely once
  - ▶ Character data sent to standard output flows through the output stream to the console window precisely once
  - ▶ In both cases, the `stream` is nothing but a series of characters; its serial nature means that it can be traversed only once



# The stream model

- ▶ A `stream` is a programming language construct that provides you with a character-based interface to I/O devices
- ▶ A common metaphor is a “stream of water”: data is provided or consumed in a single-pass
  - ▶ Character data provided to a program from standard input flows through the `input stream` precisely once
  - ▶ Character data sent to standard output flows through the output stream to the console window precisely once
  - ▶ In both cases, the `stream` is nothing but a series of characters; its serial nature means that it can be traversed only once
  - ▶ You may have heard of buffered I/O; a `stream buffer` houses a fixed amount of extracted stream data

# Overview

- Introduction

- Input & output

- The stream model**

  - ostream**

  - istream

  - Reading and writing

    - Reading from character streams

- The I/O classes

  - Relationship among I/O types

- File I/O

  - General model

  - General process

  - File streams

  - Using file stream objects

    - Opening a file for reading

    - Opening a file for writing (discard contents)

    - Opening a file for writing (append to existing contents)

    - Reading a file

- I/O error handling


  - Stream state flags

  - Stream state functions

  - Validating input with stream state

- References

## ostreams



- ▶ An `ostream` turns values of various types into character sequences
- ▶ sends those characters somewhere
- ▶ `std::cout` is an `ostream` typed object that provides character sequences to standard output

# Overview

- Introduction

- Input & output

- The stream model**

  - ostream

  - istream**

  - Reading and writing

    - Reading from character streams

- The I/O classes

  - Relationship among I/O types

- File I/O

  - General model

  - General process

  - File streams

  - Using file stream objects

    - Opening a file for reading

    - Opening a file for writing (discard contents)

    - Opening a file for writing (append to existing contents)

    - Reading a file

- I/O error handling


  - Stream state flags

  - Stream state functions

  - Validating input with stream state

- References

# istream



- ▶ An `istream` turns character sequences into values of various types
- ▶ gets those characters from somewhere
- ▶ `std::cin` is an `istream` typed object that consumes character sequences from standard input

# Overview

Introduction

Input & output

**The stream model**

ostream

istream

**Reading and writing**

Reading from character streams

**The I/O classes**

Relationship among I/O types

**File I/O**

General model

General process

File streams

Using file stream objects

Opening a file for reading

Opening a file for writing (discard contents)

Opening a file for writing (append to existing contents)

Reading a file

**I/O error handling**

Stream state flags

Stream state functions

Validating input with stream state

References

# Reading and writing

- ▶ Reading and writing of typed entities

# Reading and writing

- ▶ Reading and writing of typed entities
  - ▶ << (output) and >> (input) plus other operations



# Reading and writing

- ▶ Reading and writing of typed entities
  - ▶ << (output) and >> (input) plus other operations
  - ▶ Type safe

# Reading and writing

- ▶ Reading and writing of typed entities
  - ▶ << (output) and >> (input) plus other operations
  - ▶ Type safe
  - ▶ Formatted

# Reading and writing

- ▶ Reading and writing of typed entities
  - ▶ << (output) and >> (input) plus other operations
  - ▶ Type safe
  - ▶ Formatted
  - ▶ Typically stored (entered, printed, etc.) as text
    - ▶ But not necessarily (e.g., binary streams)

# Reading from character streams

- ▶ Suppose we enter  $3*4+8$  to standard input

# Reading from character streams

- ▶ Suppose we enter  $3*4+8$  to standard input
- ▶ This would be represented as a stream of characters as the data flowed from the keyboard to our program

# Reading from character streams

- ▶ Suppose we enter `3*4+8` to standard input
- ▶ This would be represented as a stream of characters as the data flowed from the keyboard to our program
- ▶ We would specify how we would like to consume these five characters using an `istream` in our program

# Reading from character streams

- ▶ Suppose we enter `3*4+8` to standard input
- ▶ This would be represented as a stream of characters as the data flowed from the keyboard to our program
- ▶ We would specify how we would like to consume these five characters using an `istream` in our program
  - ▶ We could read the input into an `std::string`

# Reading from character streams

- ▶ Suppose we enter `3*4+8` to standard input
- ▶ This would be represented as a stream of characters as the data flowed from the keyboard to our program
- ▶ We would specify how we would like to consume these five characters using an `istream` in our program
  - ▶ We could read the input into an `std::string`
  - ▶ We could read the number `3`, followed by the character `*`, etc.



# Reading from character streams

- ▶ Suppose we enter `3*4+8` to standard input
- ▶ This would be represented as a stream of characters as the data flowed from the keyboard to our program
- ▶ We would specify how we would like to consume these five characters using an `istream` in our program
  - ▶ We could read the input into an `std::string`
  - ▶ We could read the number `3`, followed by the character `*`, etc.
- ▶ It is completely up to us what type we would like to convert the characters into  
(as long as the character sequence is valid for the desired type)

# Overview

- Introduction

- Input & output

- The stream model

  - ostream

  - istream

  - Reading and writing

    - Reading from character streams

- The I/O classes

  - Relationship among I/O types

- File I/O

  - General model

  - General process

  - File streams

  - Using file stream objects

    - Opening a file for reading

    - Opening a file for writing (discard contents)

    - Opening a file for writing (append to existing contents)

    - Reading a file

- I/O error handling

  - Stream state flags

  - Stream state functions

  - Validating input with stream state

- References

# The I/O classes

Header	Type
<code>iostream</code>	<code>istream</code> reads from a <code>stream</code>
<code>iostream</code>	<code>ostream</code> writes to a <code>stream</code>
<code>iostream</code>	<code>iostream</code> reads and writes a <code>stream</code>
<code>fstream</code>	<code>ifstream</code> reads from a <code>file</code>
<code>fstream</code>	<code>ofstream</code> writes a <code>file</code>
<code>fstream</code>	<code>fstream</code> reads and writes a <code>file</code>
<code>sstream</code>	<code>istringstream</code> reads from a <code>string</code>
<code>sstream</code>	<code>ostringstream</code> writes a <code>string</code>
<code>sstream</code>	<code>stringstream</code> reads and writes a <code>string</code>

- ▶ The above classes are provided to us by the standard library and allow for different kinds of I/O processing
  - ▶ To support languages that use wide characters, the library also provides a set of types and objects for `wchar_t` data

# Overview

- Introduction

- Input & output

- The stream model

  - ostream

  - istream

  - Reading and writing

    - Reading from character streams

- The I/O classes

  - Relationship among I/O types

- File I/O

  - General model

  - General process

  - File streams

  - Using file stream objects

    - Opening a file for reading

    - Opening a file for writing (discard contents)

    - Opening a file for writing (append to existing contents)

    - Reading a file

- I/O error handling

  - Stream state flags

  - Stream state functions

  - Validating input with stream state

- References

# Relationship among I/O types

- ▶ A stream can be attached to any I/O or storage device

# Relationship among I/O types

- ▶ A stream can be attached to any I/O or storage device
- ▶ The standard library lets us ignore the differences among different types of streams through the use of common operations

# Relationship among I/O types

- ▶ A stream can be attached to any I/O or storage device
- ▶ The standard library lets us ignore the differences among different types of streams through the use of common operations
  - ▶ We can use `>>` to read data irrespective of whether we are reading from the console window, a disk file, or a string

# Relationship among I/O types

- ▶ A stream can be attached to any I/O or storage device
- ▶ The standard library lets us ignore the differences among different types of streams through the use of common operations
  - ▶ We can use `>>` to read data irrespective of whether we're reading from the console window, a disk file, or a string
  - ▶ Likewise, we can use `<<` to write data irrespective of whether we're writing to the console window, a disk file, or a string



# Relationship among I/O types

- ▶ The standard library lets us ignore the differences among different types of streams by using `inheritance`

# Relationship among I/O types

- ▶ The standard library lets us ignore the differences among different types of streams by using `inheritance`
  - ▶ `ifstream` and `istream` inherit functionality from `istream`

# Relationship among I/O types

- ▶ The standard library lets us ignore the differences among different types of streams by using `inheritance`
  - ▶ `ifstream` and `istreamstream` inherit functionality from `istream`
  - ▶ This means that the features of `istream` are made available to `ifstream` and `istreamstream`

# Relationship among I/O types

- ▶ The standard library lets us ignore the differences among different types of streams by using `inheritance`
  - ▶ `ifstream` and `istreamstream` inherit functionality from `istream`
  - ▶ This means that the features of `istream` are made available to `ifstream` and `istreamstream`
  - ▶ So we can use objects of these types in the same manner that we've used `std::cin`

# Relationship among I/O types

- ▶ The standard library lets us ignore the differences among different types of streams by using `inheritance`
  - ▶ `ifstream` and `istreamstream` inherit functionality from `istream`
  - ▶ This means that the features of `istream` are made available to `ifstream` and `istreamstream`
  - ▶ So we can use objects of these types in the same manner that we've used `std::cin`
  - ▶ Similarly, `ofstream` and `ostreamstream` inherit from `ostream`

# Relationship among I/O types

- ▶ The standard library lets us ignore the differences among different types of streams by using `inheritance`
  - ▶ `ifstream` and `istreamstream` inherit functionality from `istream`
  - ▶ This means that the features of `istream` are made available to `ifstream` and `istreamstream`
  - ▶ So we can use objects of these types in the same manner that we've used `std::cin`
  - ▶ Similarly, `ofstream` and `ostreamstream` inherit from `ostream`
  - ▶ So we can use objects of these types in the same manner that we've used `std::cout`

# Overview

- Introduction

- Input & output

- The stream model

  - ostream

  - istream

  - Reading and writing

    - Reading from character streams

- The I/O classes

  - Relationship among I/O types

- File I/O

  - General model

  - General process

  - File streams

  - Using file stream objects

    - Opening a file for reading

    - Opening a file for writing (discard contents)

    - Opening a file for writing (append to existing contents)

    - Reading a file

- I/O error handling

  - Stream state flags

  - Stream state functions

  - Validating input with stream state

- References

# Files

- ▶ We turn our computers off and on
  - ▶ The contents of main memory are `volatile`



# Files

- ▶ We turn our computers off and on
  - ▶ The contents of main memory are `volatile`
- ▶ We like to keep our data
  - ▶ We keep what we want to preserve on disks and similar permanent storage

# Files

- ▶ We turn our computers off and on
  - ▶ The contents of main memory are `volatile`
- ▶ We like to keep our data
  - ▶ We keep what we want to preserve on disks and similar permanent storage
- ▶ A file is a sequence of bytes stored in permanent storage
  - ▶ A file has a name
  - ▶ The data on a file has a format

# Files

- ▶ We turn our computers off and on
  - ▶ The contents of main memory are `volatile`
- ▶ We like to keep our data
  - ▶ We keep what we want to preserve on disks and similar permanent storage
- ▶ A file is a sequence of bytes stored in permanent storage
  - ▶ A file has a name
  - ▶ The data on a file has a format
- ▶ We can read/write a file if we know its name and format

# A file



- At the fundamental level, a file is a sequence of bytes numbered from 0 upwards

# A file



- ▶ At the fundamental level, a file is a sequence of bytes numbered from 0 upwards
- ▶ Other notions can be supplied by programs that interpret a “file format”

# A file



- ▶ At the fundamental level, a file is a sequence of bytes numbered from 0 upwards
- ▶ Other notions can be supplied by programs that interpret a “file format”
  - ▶ For example, the 6 bytes (characters) “123.45” might be interpreted as the floating-point number 123.45

# Overview

- Introduction

- Input & output

- The stream model

  - ostream

  - istream

  - Reading and writing

    - Reading from character streams

- The I/O classes

  - Relationship among I/O types

## File I/O

  - General model

  - General process

  - File streams

  - Using file stream objects

    - Opening a file for reading

    - Opening a file for writing (discard contents)

    - Opening a file for writing (append to existing contents)

    - Reading a file

- I/O error handling


  - Stream state flags

  - Stream state functions

  - Validating input with stream state

- References

# General model





# Overview

Introduction

Input & output

The stream model

ostream

istream

Reading and writing

Reading from character streams

The I/O classes

Relationship among I/O types

**File I/O**

General model

**General process**

File streams

Using file stream objects

Opening a file for reading

Opening a file for writing (discard contents)

Opening a file for writing (append to existing contents)

Reading a file

I/O error handling

Stream state flags

Stream state functions

Validating input with stream state

References

# General process

- ▶ To read a file, we must:

# General process

- ▶ To read a file, we must:
  - ▶ know its name

# General process

- ▶ To read a file, we must:
  - ▶ know its name
  - ▶ open it for reading

# General process

- ▶ To read a file, we must:
  - ▶ know its name
  - ▶ open it for reading
  - ▶ ensure that it opened successfully

# General process

- ▶ To read a file, we must:
  - ▶ know its name
  - ▶ open it for reading
  - ▶ ensure that it opened successfully
  - ▶ read it

# General process

- ▶ To read a file, we must:
  - ▶ know its name
  - ▶ open it for reading
  - ▶ ensure that it opened successfully
  - ▶ read it
  - ▶ close it

# General process

- ▶ To read a file, we must:
  - ▶ know its name
  - ▶ open it for reading
  - ▶ ensure that it opened successfully
  - ▶ read it
  - ▶ close it

- ▶ To write a file, we must:



# General process

- ▶ To read a file, we must:
  - ▶ know its name
  - ▶ open it for reading
  - ▶ ensure that it opened successfully
  - ▶ read it
  - ▶ close it

- ▶ To write a file, we must:
  - ▶ know its name

# General process

- ▶ To read a file, we must:
  - ▶ know its name
  - ▶ open it for reading
  - ▶ ensure that it opened successfully
  - ▶ read it
  - ▶ close it
- ▶ To write a file, we must:
  - ▶ know its name
  - ▶ open it for writing
    - or create a new file with that name

# General process

- ▶ To read a file, we must:

- ▶ know its name
- ▶ open it for reading
- ▶ ensure that it opened successfully
- ▶ read it
- ▶ close it

- ▶ To write a file, we must:

- ▶ know its name
- ▶ open it for writing
  - or create a new file with that name
- ▶ ensure that it opened successfully
- ▶ write to it

# General process

- ▶ To read a file, we must:

- ▶ know its name
- ▶ open it for reading
- ▶ ensure that it opened successfully
- ▶ read it
- ▶ close it

- ▶ To write a file, we must:

- ▶ know its name
- ▶ open it for writing
  - or create a new file with that name
- ▶ ensure that it opened successfully
- ▶ write to it
- ▶ close it

# Overview

- Introduction

- Input & output

- The stream model

  - ostream

  - istream

  - Reading and writing

    - Reading from character streams

- The I/O classes

  - Relationship among I/O types

## File I/O

  - General model

  - General process

### File streams

  - Using file stream objects

    - Opening a file for reading

    - Opening a file for writing (discard contents)

    - Opening a file for writing (append to existing contents)

    - Reading a file

- I/O error handling

  - Stream state flags

  - Stream state functions

  - Validating input with stream state

- References

# File streams

Header	Type
<code>fstream</code>	<code>ifstream</code> reads from a file
<code>fstream</code>	<code>ofstream</code> writes a file
<code>fstream</code>	<code>fstream</code> reads and writes a file

- These types provide the same operations as those we have used on with `std::cin` and `std::cout`

# Overview

- Introduction

- Input & output

- The stream model

  - ostream

  - istream

  - Reading and writing

    - Reading from character streams

- The I/O classes

  - Relationship among I/O types

## File I/O

  - General model

  - General process

  - File streams

  - Using file stream objects**

    - Opening a file for reading

    - Opening a file for writing (discard contents)

    - Opening a file for writing (append to existing contents)

    - Reading a file

- I/O error handling

  - Stream state flags

  - Stream state functions

  - Validating input with stream state

- References

# Using file stream objects

- ▶ When we want to read or write a file, we declare a `fstream` object and initialize it with the file name we d like to open



# Using file stream objects

- ▶ When we want to read or write a file, we declare a `fstream` object and initialize it with the file name we d like to open
  - ▶ When we initialize the `fstream` object with a file name, that file is opened implicitly
    - ▶ When an `fstream` object is created, `open` is called automatically

# Using file stream objects

- ▶ When we want to read or write a file, we declare a `fstream` object and initialize it with the file name we d like to open
  - ▶ When we initialize the `fstream` object with a file name, that file is opened implicitly
    - ▶ When an `fstream` object is created, `open` is called automatically
  - ▶ `// construct an ifstream and open ifile`  
`ifstream in{ifile};`

# Using file stream objects

- ▶ When we want to read or write a file, we declare a `fstream` object and initialize it with the file name we d like to open
  - ▶ When we initialize the `fstream` object with a file name, that file is opened implicitly
    - ▶ When an `fstream` object is created, `open` is called automatically
  - ▶ `// construct an ifstream and open ifile`  
`ifstream in{ifile};`
  - ▶ `// construct an ofstream and open ofile`  
`ofstream out{ofile};`

# Using file stream objects

- ▶ When we want to read or write a file, we declare a `fstream` object and initialize it with the file name we'd like to open
  - ▶ When we initialize the `fstream` object with a file name, that file is opened implicitly
    - ▶ When an `fstream` object is created, `open` is called automatically
  - ▶ `// construct an ifstream and open ifile`  
`ifstream in{ifile};`
  - ▶ `// construct an ofstream and open ofile`  
`ofstream out{ofile};`
  - ▶ When the `fstream` object's lifetime ends, the `fstream` will implicitly close the file
    - ▶ When an `fstream` object is destroyed, `close` is called automatically

# Opening a file for reading

```
// ...  
  
cout << "Please enter input file name: ";  
string iname;  
cin >> iname;  
  
ifstream ist {iname};  
// ifstream is "aninput stream from a " file  
// defining an ifstream with a name string  
// opens the file of that name for reading  
  
if (!ist) throw runtime_error("'cant open input file");  
  
// ...
```

## Opening a file for writing (discard contents)

```
// ...  
  
cout << "Please enter name of output file : ";  
string oname;  
cin >> oname;  
  
ofstream ofs {oname};  
// ofstream is an "output stream from a "file"  
// defining an ofstream with a name string  
// opens the file with that name for writing  
// the contents of the file are discarded  
  
if (!ofs) throw runtime_error("'"cant open output file");  
  
// ...
```

# Opening a file for writing (append to existing contents)

```
// ...  
  
cout << "Please enter name of output file : ";  
string oname;  
cin >> oname;  
  
ofstream ofs {oname, ofstream::app};  
// ofstream is an "output stream from a "file"  
// defining an ofstream with a name string  
// opens the file with that name for writing  
// the contents of the file are preserved  
  
if (!ofs) throw runtime_error("'cant open output file");  
  
// ...
```

# Reading a file

- ▶ Suppose a file contains a sequence of pairs representing hours and temperature readings

0 60.7

1 60.6

2 60.3

3 59.22

- ▶ The hours are in the range

0, ..., 23

- ▶ No further format is assumed
- ▶ Termination
  - ▶ Reaching the end of file terminates the read
  - ▶ Anything unexpected in the file terminates the read



# Reading a file

```
vector<int> hours;  
vector<double> temps;  
  
std::string iname = "temperatures.dat"  
ifstream ist {iname};  
if (!ist) throw runtime_error("'cant_open_input_file");  
  
int hour;  
double temperature;  
while (ist >> hour >> temperature)    // read  
{  
    // check  
    if (hour < 0 || 23 < hour) error("hour_out_of_range");  
    hours.push_back(hour); // store  
    temps.push_back(temperature); // store  
}
```

# Overview

- Introduction

- Input & output

- The stream model

  - ostream

  - istream

  - Reading and writing

    - Reading from character streams

- The I/O classes

  - Relationship among I/O types

- File I/O

  - General model

  - General process

  - File streams

  - Using file stream objects

    - Opening a file for reading

    - Opening a file for writing (discard contents)

    - Opening a file for writing (append to existing contents)

    - Reading a file

- I/O error handling**

  - Stream state flags

  - Stream state functions

  - Validating input with stream state

- References

# I/O error handling

- Sources of errors:

# I/O error handling

- ▶ Sources of errors:
  - ▶ Human mistakes

# I/O error handling

- ▶ Sources of errors:
  - ▶ Human mistakes
  - ▶ Files that fail to meet specifications

# I/O error handling

- ▶ Sources of errors:
  - ▶ Human mistakes
  - ▶ Files that fail to meet specifications
  - ▶ Specifications that fail to match reality

# I/O error handling

- ▶ Sources of errors:
  - ▶ Human mistakes
  - ▶ Files that fail to meet specifications
  - ▶ Specifications that fail to match reality
  - ▶ Programmer errors

# I/O error handling

- ▶ Sources of errors:
  - ▶ Human mistakes
  - ▶ Files that fail to meet specifications
  - ▶ Specifications that fail to match reality
  - ▶ Programmer errors
  - ▶ etc.



# I/O error handling

- ▶ Sources of errors:
  - ▶ Human mistakes
  - ▶ Files that fail to meet specifications
  - ▶ Specifications that fail to match reality
  - ▶ Programmer errors
  - ▶ etc.
- ▶ Some errors will be recoverable; others will be beyond the scope of a program to correct

# I/O error handling

- ▶ Sources of errors:
  - ▶ Human mistakes
  - ▶ Files that fail to meet specifications
  - ▶ Specifications that fail to match reality
  - ▶ Programmer errors
  - ▶ etc.
- ▶ Some errors will be recoverable; others will be beyond the scope of a program to correct
- ▶ The I/O stream types define flags and functions that allow us to interrogate and manipulate the condition state of a stream

# I/O error handling

- ▶ Sources of errors:
  - ▶ Human mistakes
  - ▶ Files that fail to meet specifications
  - ▶ Specifications that fail to match reality
  - ▶ Programmer errors
  - ▶ etc.
- ▶ Some errors will be recoverable; others will be beyond the scope of a program to correct
- ▶ The I/O stream types define flags and functions that allow us to interrogate and manipulate the condition state of a stream
  - ▶ We can use a stream as a condition, e.x., `if (cin)`, to ask whether that stream is valid

# I/O error handling

- ▶ Sources of errors:
  - ▶ Human mistakes
  - ▶ Files that fail to meet specifications
  - ▶ Specifications that fail to match reality
  - ▶ Programmer errors
  - ▶ etc.
- ▶ Some errors will be recoverable; others will be beyond the scope of a program to correct
- ▶ The I/O stream types define flags and functions that allow us to interrogate and manipulate the condition state of a stream
  - ▶ We can use a stream as a condition, e.x., `if (cin)`, to ask whether that stream is valid
  - ▶ If the condition evaluates `false`, we know we have a situation, but we re not sure why the stream is invalid (just yet)

# Overview

Introduction

Input & output

The stream model

ostream

istream

Reading and writing

Reading from character streams

The I/O classes

Relationship among I/O types

File I/O

General model

General process

File streams

Using file stream objects

Opening a file for reading

Opening a file for writing (discard contents)

Opening a file for writing (append to existing contents)

Reading a file

**I/O error handling**

Stream state flags

Stream state functions

Validating input with stream state

References

# Stream state flags

- ▶ The I/O stream types each provide a collection of bits (typed `iostate`) that are used to convey information about the state of a stream; different bit pattern are used to express different kinds of I/O conditions

Flag	Meaning
<code>goodbit</code>	Set when the stream is not in an error state
<code>badbit</code>	Set when an unrecoverable failure has occurred
<code>failbit</code>	Set when a recoverable error has occurred
<code>eofbit</code>	Set when the stream has hit end-of-file

# Stream state flags

- ▶ Each I/O stream type has an `rdstate` function that returns an `iostate` value corresponding to the current state of a stream

# Stream state flags

- ▶ Each I/O stream type has an `rdstate` function that returns an `iosstate` value corresponding to the current state of a stream
- ▶ We could check whether the `failbit` is set for `cin` by writing:

```
if ((cin.rdstate() & std::ios::failbit) != 0)
    /* failbit set, do something to recover */
```



# Stream state flags

- ▶ Each I/O stream type has an `rdstate` function that returns an `iosstate` value corresponding to the current state of a stream
- ▶ We could check whether the `failbit` is set for `cin` by writing:

```
if ((cin.rdstate() & std::ios::failbit) != 0)
    /* failbit set, do something to recover */
```

- ▶ Similarly, we could check whether the `failbit` is set for an `ifstream` named `ifs` by writing:

```
if ((ifs.rdstate() & std::ifstream::failbit) != 0)
    /* failbit set, do something to recover */
```

# Stream state flags

- ▶ Each I/O stream type has an `rdstate` function that returns an `iosstate` value corresponding to the current state of a stream
- ▶ We could check whether the `failbit` is set for `cin` by writing:

```
if ((cin.rdstate() & std::ios::failbit) != 0)
    /* failbit set, do something to recover */
```

- ▶ Similarly, we could check whether the `failbit` is set for an `ifstream` named `ifs` by writing:

```
if ((ifs.rdstate() & std::ifstream::failbit) != 0)
    /* failbit set, do something to recover */
```

- ▶ Lucky for us, there is an easier way to check the current state of a respective stream

# Overview

Introduction

Input & output

The stream model

ostream

istream

Reading and writing

Reading from character streams

The I/O classes

Relationship among I/O types

File I/O

General model

General process

File streams

Using file stream objects

Opening a file for reading

Opening a file for writing (discard contents)

Opening a file for writing (append to existing contents)

Reading a file

**I/O error handling**

Stream state flags

**Stream state functions**

Validating input with stream state

References

# Stream state functions

- The I/O stream types have functions that can be used to interrogate the state of a stream

	Flag			
Function	goodbit	badbit	failbit	eofbit
good()	✓			
bad()		✓		
fail()		✓	✓	
eof()				✓

# Overview

- Introduction

- Input & output

- The stream model

  - ostream

  - istream

  - Reading and writing

    - Reading from character streams

- The I/O classes

  - Relationship among I/O types

- File I/O

  - General model

  - General process

  - File streams

  - Using file stream objects

    - Opening a file for reading

    - Opening a file for writing (discard contents)

    - Opening a file for writing (append to existing contents)

    - Reading a file

- I/O error handling

  - Stream state flags

  - Stream state functions

  - Validating input with stream state

- References

# Validating input with stream state

```
string prompt = "Enter an integer: ";
cout << prompt;

int i;
cin >> i;

while (!cin.good())    // goodbit NOT set
{
    if (cin.bad()) { // badbit set
        /* do something */
    } else if (cin.eof()) { // eofbit set
        /* do something else */
    } else { // failbit set
        cout << "Invalid input!" << endl;
        cin.clear();
        cin.ignore(numeric_limits<streamsize>::max(), '\n');
        cout << prompt;
        cin >> i;
    }
}
/* do something with valid input */
```

# Validating input with stream state

- ▶ `cin.clear();`
  - ▶ Resets all conditional values of `cin` to valid state
  - ▶ Does not affect the `buffered input`
- ▶ `cin.ignore(numeric_limits<streamsize>::max(),  
'\n');`
  - ▶ Ignore contents in the buffer
    - ▶ First argument is the max number of characters to ignore
    - ▶ Second argument is a character that, when observed in the stream, tells us to stop ignoring characters

# Overview

- Introduction

- Input & output

- The stream model

  - ostream

  - istream

  - Reading and writing

    - Reading from character streams

- The I/O classes

  - Relationship among I/O types

- File I/O

  - General model

  - General process

  - File streams

  - Using file stream objects

    - Opening a file for reading

    - Opening a file for writing (discard contents)

    - Opening a file for writing (append to existing contents)

    - Reading a file

- I/O error handling

  - Stream state flags

  - Stream state functions

  - Validating input with stream state

- References



# References

- ▶ Lippman, B., Lajoie, Josee, & Moo, B. E. (2016). *C++ primer* (5th ed.). Addison-Wesley.
- ▶ Stroustrup, B. (2014). *Programming: principles and practice using C++* (2nd ed.). Addison-Wesley.