

Michael Nowak

Texas A&M University

Overview

MyArray

Removing an item from MyArray

Overview

MyArray

Removing an item from MyArray

MyArray

```
1  #ifndef MYARRAY_H
2  #define MYARRAY_H
3  struct MyArray {
4      int *arr = nullptr;
5      int capacity = 0; // no elements can store
6      int size = 0; // no elements currently held
7  };
8  #endif
```

Overview

MyArray

Removing an item from MyArray

Removing an item from `MyArray`

```
1  #include "removeValue.h"
2  void removeValue(MyArray &mya, int val)
3  {
4      int noRemoved = 0;
5      for (int i = 0, j = 0; i < mya.size; ++i) {
6          if (mya.arr[i] != val) {
7              mya.arr[j] = mya.arr[i]; j += 1;
8          } else {
9              noRemoved += 1;
10         }
11     }
12     mya.size -= noRemoved;
13 }
```

Removing an item from `MyArray`

```
1  #include <iostream>
2  #include "MyArray.h"
3  #include "removeValue.h"
4
5  using namespace std;
6
7  int main()
8  {
9      MyArray array {new int[4], 4, 0};
10
11     for (int i = 0; i < array.capacity; ++i) {
12         array.arr[i] = i % 2; array.size += 1;
13     }
14
15     removeValue(array, 1);
16
17     return 0;
18 }
```

Removing an item from `MyArray`

```
1  #include <iostream>
2  #include "MyArray.h"
3  #include "removeValue.h"
4
5  using namespace std;
6
7  int main()
8  {
9      MyArray array {new int[4], 4, 0};
10
11     for (int i = 0; i < array.capacity; ++i) {
12         array.arr[i] = i % 2; array.size += 1;
13     }
14
15     removeValue(array, 1);
16
17     return 0;
18 }
```


Removing an item from `MyArray`

```
1  #include <iostream>
2  #include "MyArray.h"
3  #include "removeValue.h"
4
5  using namespace std;
6
7  int main()
8  {
9      MyArray array {new int[4], 4, 0};
10
11     for (int i = 0; i < array.capacity; ++i) {
12         array.arr[i] = i % 2; array.size += 1;
13     }
14
15     removeValue(array, 1);
16
17     return 0;
18 }
```

Removing an item from `MyArray`

```
1  #include <iostream>
2  #include "MyArray.h"
3  #include "removeValue.h"
4
5  using namespace std;
6
7  int main()
8  {
9      MyArray array {new int[4], 4, 0};
10
11      for (int i = 0; i < array.capacity; ++i) {
12          array.arr[i] = i % 2; array.size += 1;
13      }
14
15      removeValue(array, 1);
16
17      return 0;
18  }
```

Removing an item from `MyArray`

```
1  #include <iostream>
2  #include "MyArray.h"
3  #include "removeValue.h"
4
5  using namespace std;
6
7  int main()
8  {
9      MyArray array {new int[4], 4, 0};
10
11     for (int i = 0; i < array.capacity; ++i) {
12         array.arr[i] = i % 2; array.size += 1;
13     }
14
15     removeValue(array, 1);
16
17     return 0;
18 }
```

Removing an item from `MyArray`

```
1  #include <iostream>
2  #include "MyArray.h"
3  #include "removeValue.h"
4
5  using namespace std;
6
7  int main()
8  {
9      MyArray array {new int[4], 4, 0};
10
11      for (int i = 0; i < array.capacity; ++i) {
12          array.arr[i] = i % 2; array.size += 1;
13      }
14
15      removeValue(array, 1);
16
17      return 0;
18  }
```

Removing an item from `MyArray`

```
1  #include <iostream>
2  #include "MyArray.h"
3  #include "removeValue.h"
4
5  using namespace std;
6
7  int main()
8  {
9      MyArray array {new int[4], 4, 0};
10
11     for (int i = 0; i < array.capacity; ++i) {
12         array.arr[i] = i % 2; array.size += 1;
13     }
14
15     removeValue(array, 1);
16
17     return 0;
18 }
```

Removing an item from `MyArray`

```
1  #include <iostream>
2  #include "MyArray.h"
3  #include "removeValue.h"
4
5  using namespace std;
6
7  int main()
8  {
9      MyArray array {new int[4], 4, 0};
10
11      for (int i = 0; i < array.capacity; ++i) {
12          array.arr[i] = i % 2; array.size += 1;
13      }
14
15      removeValue(array, 1);
16
17      return 0;
18  }
```

Removing an item from `MyArray`

```
1  #include <iostream>
2  #include "MyArray.h"
3  #include "removeValue.h"
4
5  using namespace std;
6
7  int main()
8  {
9      MyArray array {new int[4], 4, 0};
10
11     for (int i = 0; i < array.capacity; ++i) {
12         array.arr[i] = i % 2; array.size += 1;
13     }
14
15     removeValue(array, 1);
16
17     return 0;
18 }
```

Removing an item from `MyArray`

```
1  #include <iostream>
2  #include "MyArray.h"
3  #include "removeValue.h"
4
5  using namespace std;
6
7  int main()
8  {
9      MyArray array {new int[4], 4, 0};
10
11      for (int i = 0; i < array.capacity; ++i) {
12          array.arr[i] = i % 2; array.size += 1;
13      }
14
15      removeValue(array, 1);
16
17      return 0;
18  }
```


Removing an item from `MyArray`

```
1  #include <iostream>
2  #include "MyArray.h"
3  #include "removeValue.h"
4
5  using namespace std;
6
7  int main()
8  {
9      MyArray array {new int[4], 4, 0};
10
11     for (int i = 0; i < array.capacity; ++i) {
12         array.arr[i] = i % 2; array.size += 1;
13     }
14
15     removeValue(array, 1);
16
17     return 0;
18 }
```

Removing an item from `MyArray`

```
1  #include <iostream>
2  #include "MyArray.h"
3  #include "removeValue.h"
4
5  using namespace std;
6
7  int main()
8  {
9      MyArray array {new int[4], 4, 0};
10
11     for (int i = 0; i < array.capacity; ++i) {
12         array.arr[i] = i % 2; array.size += 1;
13     }
14
15     removeValue(array, 1);
16
17     return 0;
18 }
```

Removing an item from `MyArray`

```
1  #include "removeValue.h"
2  void removeValue(MyArray &mya, int val)
3  {
4      int noRemoved = 0;
5      for (int i = 0, j = 0; i < mya.size; ++i) {
6          if (mya.arr[i] != val) {
7              mya.arr[j] = mya.arr[i]; j += 1;
8          } else {
9              noRemoved += 1;
10         }
11     }
12     mya.size -= noRemoved;
13 }
```

Removing an item from `MyArray`

```
1  #include "removeValue.h"
2  void removeValue(MyArray &mya, int val)
3  {
4      int noRemoved = 0;
5      for (int i = 0, j = 0; i < mya.size; ++i) {
6          if (mya.arr[i] != val) {
7              mya.arr[j] = mya.arr[i]; j += 1;
8          } else {
9              noRemoved += 1;
10         }
11     }
12     mya.size -= noRemoved;
13 }
```

Removing an item from `MyArray`

```
1  #include "removeValue.h"
2  void removeValue(MyArray &mya, int val)
3  {
4      int noRemoved = 0;
5      for (int i = 0, j = 0; i < mya.size; ++i) {
6          if (mya.arr[i] != val) {
7              mya.arr[j] = mya.arr[i]; j += 1;
8          } else {
9              noRemoved += 1;
10         }
11     }
12     mya.size -= noRemoved;
13 }
```

Removing an item from `MyArray`

```
1  #include "removeValue.h"
2  void removeValue(MyArray &mya, int val)
3  {
4      int noRemoved = 0;
5      for (int i = 0, j = 0; i < mya.size; ++i) {
6          if (mya.arr[i] != val) {
7              mya.arr[j] = mya.arr[i]; j += 1;
8          } else {
9              noRemoved += 1;
10         }
11     }
12     mya.size -= noRemoved;
13 }
```

Removing an item from `MyArray`

```
1  #include "removeValue.h"
2  void removeValue(MyArray &mya, int val)
3  {
4      int noRemoved = 0;
5      for (int i = 0, j = 0; i < mya.size; ++i) {
6          if (mya.arr[i] != val) {
7              mya.arr[j] = mya.arr[i]; j += 1;
8          } else {
9              noRemoved += 1;
10         }
11     }
12     mya.size -= noRemoved;
13 }
```

Removing an item from `MyArray`

```
1  #include "removeValue.h"
2  void removeValue(MyArray &mya, int val)
3  {
4      int noRemoved = 0;
5      for (int i = 0, j = 0; i < mya.size; ++i) {
6          if (mya.arr[i] != val) {
7              mya.arr[j] = mya.arr[i]; j += 1;
8          } else {
9              noRemoved += 1;
10         }
11     }
12     mya.size -= noRemoved;
13 }
```


Removing an item from `MyArray`

```
1  #include "removeValue.h"
2  void removeValue(MyArray &mya, int val)
3  {
4      int noRemoved = 0;
5      for (int i = 0, j = 0; i < mya.size; ++i) {
6          if (mya.arr[i] != val) {
7              mya.arr[j] = mya.arr[i]; j += 1;
8          } else {
9              noRemoved += 1;
10         }
11     }
12     mya.size -= noRemoved;
13 }
```

Removing an item from `MyArray`

```
1  #include "removeValue.h"
2  void removeValue(MyArray &mya, int val)
3  {
4      int noRemoved = 0;
5      for (int i = 0, j = 0; i < mya.size; ++i) {
6          if (mya.arr[i] != val) {
7              mya.arr[j] = mya.arr[i]; j += 1;
8          } else {
9              noRemoved += 1;
10         }
11     }
12     mya.size -= noRemoved;
13 }
```

Removing an item from `MyArray`

```
1  #include "removeValue.h"
2  void removeValue(MyArray &mya, int val)
3  {
4      int noRemoved = 0;
5      for (int i = 0, j = 0; i < mya.size; ++i) {
6          if (mya.arr[i] != val) {
7              mya.arr[j] = mya.arr[i]; j += 1;
8          } else {
9              noRemoved += 1;
10         }
11     }
12     mya.size -= noRemoved;
13 }
```

Removing an item from `MyArray`

```
1  #include "removeValue.h"
2  void removeValue(MyArray &mya, int val)
3  {
4      int noRemoved = 0;
5      for (int i = 0, j = 0; i < mya.size; ++i) {
6          if (mya.arr[i] != val) {
7              mya.arr[j] = mya.arr[i]; j += 1;
8          } else {
9              noRemoved += 1;
10         }
11     }
12     mya.size -= noRemoved;
13 }
```

Removing an item from `MyArray`

```
1  #include "removeValue.h"
2  void removeValue(MyArray &mya, int val)
3  {
4      int noRemoved = 0;
5      for (int i = 0, j = 0; i < mya.size; ++i) {
6          if (mya.arr[i] != val) {
7              mya.arr[j] = mya.arr[i]; j += 1;
8          } else {
9              noRemoved += 1;
10         }
11     }
12     mya.size -= noRemoved;
13 }
```

Removing an item from `MyArray`

```
1  #include "removeValue.h"
2  void removeValue(MyArray &mya, int val)
3  {
4      int noRemoved = 0;
5      for (int i = 0, j = 0; i < mya.size; ++i) {
6          if (mya.arr[i] != val) {
7              mya.arr[j] = mya.arr[i]; j += 1;
8          } else {
9              noRemoved += 1;
10             }
11     }
12     mya.size -= noRemoved;
13 }
```

Removing an item from `MyArray`

```
1  #include "removeValue.h"
2  void removeValue(MyArray &mya, int val)
3  {
4      int noRemoved = 0;
5      for (int i = 0, j = 0; i < mya.size; ++i) {
6          if (mya.arr[i] != val) {
7              mya.arr[j] = mya.arr[i]; j += 1;
8          } else {
9              noRemoved += 1;
10         }
11     }
12     mya.size -= noRemoved;
13 }
```

Removing an item from `MyArray`

```
1  #include "removeValue.h"
2  void removeValue(MyArray &mya, int val)
3  {
4      int noRemoved = 0;
5      for (int i = 0, j = 0; i < mya.size; ++i) {
6          if (mya.arr[i] != val) {
7              mya.arr[j] = mya.arr[i]; j += 1;
8          } else {
9              noRemoved += 1;
10         }
11     }
12     mya.size -= noRemoved;
13 }
```


Removing an item from `MyArray`

```
1  #include "removeValue.h"
2  void removeValue(MyArray &mya, int val)
3  {
4      int noRemoved = 0;
5      for (int i = 0, j = 0; i < mya.size; ++i) {
6          if (mya.arr[i] != val) {
7              mya.arr[j] = mya.arr[i]; j += 1;
8          } else {
9              noRemoved += 1;
10         }
11     }
12     mya.size -= noRemoved;
13 }
```

Removing an item from `MyArray`

```
1  #include <iostream>
2  #include "MyArray.h"
3  #include "removeValue.h"
4
5  using namespace std;
6
7  int main()
8  {
9      MyArray array {new int[4], 4, 0};
10
11     for (int i = 0; i < array.capacity; ++i) {
12         array.arr[i] = i % 2; array.size += 1;
13     }
14
15     removeValue(array, 1);
16
17     return 0;
18 }
```

Removing an item from `MyArray`

```
1  #include <iostream>
2  #include "MyArray.h"
3  #include "removeValue.h"
4
5  using namespace std;
6
7  int main()
8  {
9      MyArray array {new int[4], 4, 0};
10
11     for (int i = 0; i < array.capacity; ++i) {
12         array.arr[i] = i % 2; array.size += 1;
13     }
14
15     removeValue(array, 1);
16
17     return 0;
18 }
```