

Software and errors

Michael Nowak

Texas A&M University

Acknowledgement: Some lecture slides based on those created by Bjarne Stroustrup for use with his textbook

Notes

Overview

- Software
 - Nature of programming
 - Machine language
 - Assembly language
 - Higher-level languages
 - C++ Compilation
- Errors
 - Sources of errors
 - Your program
 - Kinds of errors
- Compile-time errors
 - Syntax errors
 - Type errors
- Link-time errors
- Run-time errors
 - Detected by the computer
 - Detected by a library
 - Detected by user-code
 - Local
 - Non-local
- Logic errors
- References

Notes

Overview

- Software
 - Nature of programming
 - Machine language
 - Assembly language
 - Higher-level languages
 - C++ Compilation
- Errors
 - Sources of errors
 - Your program
 - Kinds of errors
- Compile-time errors
 - Syntax errors
 - Type errors
- Link-time errors
- Run-time errors
 - Detected by the computer
 - Detected by a library
 - Detected by user-code
 - Local
 - Non-local
- Logic errors
- References

Notes

Software

- ▶ Software are the programs that run on the hardware
- ▶ Like hardware, can be seen as having multiple components:
 - ▶ The *BIOS (basic input/output system)* is the base layer that provides computer initial instructions for what to do when powered on
 - ▶ *Operating system* is responsible for controlling the operations of the machine, how the user interacts with it, reading/writing files to disk, and loading and starting other programs
 - ▶ *Application and utility programs* are those that the user runs, such as your email client or web browser

Notes

Overview

Software

Nature of programming

Machine language

Assembly language

Higher-level languages

C++ Compilation

Errors

Sources of errors

Your program

Kinds of errors

Compile-time errors

Syntax errors

Type errors

Link-time errors

Run-time errors

Detected by the computer

Detected by a library

Detected by user-code

Local

Non-local

Logic errors

References

Notes

Nature of programming

- ▶ Every piece of software is written by a programmer, but
 - ▶ what is programming, and
 - ▶ how do we do it?
- ▶ At the fundamental level, during each cycle, the computer loads an instruction and executes it

Notes

Overview

- Software
 - Nature of programming
 - Machine language
 - Assembly language
 - Higher-level languages
 - C++
 - Compilation
 - Errors
 - Sources of errors
 - Your program
 - Kinds of errors
 - Compile-time errors
 - Syntax errors
 - Type errors
 - Link-time errors
 - Run-time errors
 - Detected by the computer
 - Detected by a library
 - Detected by user-code
 - Local
 - Non-local
 - Logic errors
 - References

Notes

Machine language

- Each instruction is encoded as a binary sequence of numbers; the language of these instructions is known as *machine language*
- For instance, using the MIPS machine language, we could write the equation `wage = rate * hours` as:

```
100011 00000 00010 0000000000000000 # Load rate, register 2
100011 00001 00011 0000000000000000 # Load hours, register 3
000000 00010 00011 00100 00000 011000 # Multiply registers 2 and 3;
                                         store the result in register 4
101011 00100 00101 0000000000000000 # Store value of register 4
```

Notes

Overview

- Software
 - Nature of programming
 - Machine language
 - Assembly language
 - Higher-level languages
 - C++
 - Compilation
 - Errors
 - Sources of errors
 - Your program
 - Kinds of errors
 - Compile-time errors
 - Syntax errors
 - Type errors
 - Link-time errors
 - Run-time errors
 - Detected by the computer
 - Detected by a library
 - Detected by user-code
 - Local
 - Non-local
 - Logic errors
 - References

Notes

Assembly language

- ▶ Assembly language has an assembly instruction for each machine language instruction
- ▶ Unlike machine language, assembly language is entered as mnemonics (i.e., words) that describe what they do
- ▶ For instance, we could write the equation `wage = rate * hours` as:

```
lw    $s0, $s2, 0
lw    $s1, $s3, 0
mult  $s2, $s3, $s4
sw    $s4, $s5, 0
```

- ▶ In order for the assembly language to be understood by the computer, we use an *assembler* to translate from assembly language to machine language

Notes

Overview

- Software
 - Nature of programming
 - Machine language
 - Assembly language
 - Higher-level languages
- C++
 - Compilation
- Errors
 - Sources of errors
 - Your program
 - Kinds of errors
- Compile-time errors
 - Syntax errors
 - Type errors
- Link-time errors
- Run-time errors
 - Detected by the computer
 - Detected by a library
 - Detected by user-code
 - Local
 - Non-local
- Logic errors
- References

Notes

Higher-level languages

- ▶ It is hard for a programmer to express ideas in machine language and assembly language
- ▶ Higher-level languages use more complete mnemonics and allow more complex organization of ideas
- ▶ In C++, provided that `wage` had been *declared*, and `rate` and `hours` had been *defined*, we could simply write the following *statement* in our program:

```
wage = rate * hours;
```

Notes

Overview


Software
Nature of programming
Machine language
Assembly language
Higher-level languages

C++ Compilation

Errors
Sources of errors
Your program
Kinds of errors
Compile-time errors
Syntax errors
Type errors
Link-time errors
Run-time errors
Detected by the computer
Detected by a library
Detected by user-code
Local
Non-local
Logic errors
References

Notes

C++ Compilation Processes



Notes

Overview

Software
Nature of programming
Machine language
Assembly language
Higher-level languages

C++ Compilation

Errors
Sources of errors
Your program
Kinds of errors
Compile-time errors
Syntax errors
Type errors
Link-time errors
Run-time errors
Detected by the computer
Detected by a library
Detected by user-code
Local
Non-local
Logic errors
References

Notes

Errors

- ▶ When we write programs, errors are natural and unavoidable; the question is, how do we deal with them?
 - ▶ Organize software to minimize errors
 - ▶ Eliminate most of the errors we made anyway
 - ▶ Debugging
 - ▶ Testing

“My guess is that avoiding, finding, and correcting errors is 95% or more of the effort for serious software development.”
– Bjarne Stroustrup

Notes

Overview

Software
Nature of programming
Machine language
Assembly language
Higher-level languages
C++ Compilation
Errors
Sources of errors
Your program
Kinds of errors
Compile-time errors
Syntax errors
Type errors
Link-time errors
Run-time errors
Detected by the computer
Detected by a library
Detected by user-code
Local
Non-local
Logic errors
References

Notes

Sources of errors

- ▶ Poor specification
 - ▶ “What s this suppose to do?”
- ▶ Incomplete programs
 - ▶ “but I ll get around to it... tomorrow...”
- ▶ Unexpected arguments to functions
 - ▶ “but `sqrt()` isn t suppose to be called with `-1` as its argument”
- ▶ Unexpected input
 - ▶ “but the user was suppose to input an integer”
- ▶ Code that simply doesn t do what it was supposed to do
 - ▶ “so fix it...”

Notes

Overview

- Software
 - Nature of programming
 - Machine language
 - Assembly language
 - Higher-level languages
 - C++ Compilation
- Errors
 - Sources of errors
 - Your program**
 - Kinds of errors
- Compile-time errors
 - Syntax errors
 - Type errors
- Link-time errors
- Run-time errors
 - Detected by the computer
 - Detected by a library
 - Detected by user-code
 - Local
 - Non-local
- Logic errors
- References

Notes

Your program

- ▶ Should produce the desired results for all legal inputs
- ▶ Should give reasonable error messages for all illegal inputs
- ▶ Need not worry about misbehaving hardware
- ▶ Need not worry about misbehaving system software
- ▶ Is allowed to terminate after finding an error

Notes

Overview

- Software
 - Nature of programming
 - Machine language
 - Assembly language
 - Higher-level languages
 - C++ Compilation
- Errors
 - Sources of errors
 - Your program
 - Kinds of errors**
- Compile-time errors
 - Syntax errors
 - Type errors
- Link-time errors
- Run-time errors
 - Detected by the computer
 - Detected by a library
 - Detected by user-code
 - Local
 - Non-local
- Logic errors
- References

Notes

Kinds of errors

- Compile-time errors Errors found by the compiler
- ▶ Syntax errors
 - ▶ Type errors
- Link-time errors Errors found by the linker when it is trying to combine object files into an executable program
- Run-time errors Errors found by checks made during a running program; that is, errors detected by
- ▶ the computer (hardware and/or the operating system)
 - ▶ by a library (e.g., the standard library)
 - ▶ by user code
- Logic errors Errors found by the programmer looking for the causes of erroneous results

Notes

Overview

- Software
- Nature of programming
 - Machine language
 - Assembly language
 - Higher-level languages
 - C++
 - Compilation
 - Errors
 - Sources of errors
 - Your program
 - Kinds of errors
 - Compile-time errors
 - Syntax errors
 - Type errors
 - Link-time errors
 - Run-time errors
 - Detected by the computer
 - Detected by a library
 - Detected by user-code
 - Local
 - Non-local
 - Logic errors
 - References

Notes

Overview

- Software
- Nature of programming
 - Machine language
 - Assembly language
 - Higher-level languages
 - C++
 - Compilation
 - Errors
 - Sources of errors
 - Your program
 - Kinds of errors
 - Compile-time errors
 - Syntax errors
 - Type errors
 - Link-time errors
 - Run-time errors
 - Detected by the computer
 - Detected by a library
 - Detected by user-code
 - Local
 - Non-local
 - Logic errors
 - References

Notes

Compile-time errors : Syntax errors

Notes

```
#include <iostream>
#include <vector>
#include <string>
using namespace std;

int main ( ) {
    string first_name = "Michael";
    string last_name = "Nowak";
    string full_name = first_name + ' ' + last_name;
    cout << full_name << endl

    return 0;
}
```

Overview

- Software
 - Nature of programming
 - Machine language
 - Assembly language
 - Higher-level languages
 - C++ Compilation
- Errors
 - Sources of errors
 - Your program
 - Kinds of errors
 - Compile-time errors
 - Syntax errors
 - Type errors
 - Link-time errors
 - Run-time errors
 - Detected by the computer
 - Detected by a library
 - Detected by user-code
 - Local
 - Non-local
 - Logic errors
 - References

Notes

Compile-time errors : Type errors

Notes

```
#include <iostream>
#include <vector>
#include <string>
using namespace std;

int main ( ) {
    string first_name = "Michael";
    string last_name = "Nowak";

    string sub_name = first_name - last_name;
    cout << sub_name;

    return 0;
}
```

Overview

- Software
 - Nature of programming
 - Machine language
 - Assembly language
 - Higher-level languages
- C++
 - Compilation
- Errors
 - Sources of errors
 - Your program
 - Kinds of errors
- Compile-time errors
 - Syntax errors
 - Type errors
- Link-time errors
- Run-time errors
 - Detected by the computer
 - Detected by a library
 - Detected by user-code
 - Local
 - Non-local
- Logic errors
- References

Notes

Link-time errors

```
#include <iostream>
#include <vector>
#include <string>
using namespace std;

/*      declaration , for an undefined symbol
*/
string make_full_name (string f, string l);

int main ( ) {
    string first_name = "Michael";
    string last_name = "Nowak";
    string full_name = make_full_name(first_name , last_name);

    return 0;
}
```

```
Desktop/LX_Errors-Exceptions/code
% g++ LinkTimeErrors1.cpp
Undefined symbols for architecture x86_64:
  "make_full_name(std::__cxx11::basic_string<char, std::cha
ar_traits<char>, std::allocator<char>>, std::__cxx11::bas
ic_string<char, std::char_traits<char>, std::allocator<cha
r>>>)", referenced from:
      _main in ccvmp09.o
ld: symbol(s) not found for architecture x86_64
collect2: error: ld returned 1 exit status
```

Notes

Overview

- Software
 - Nature of programming
 - Machine language
 - Assembly language
 - Higher-level languages
- C++
 - Compilation
- Errors
 - Sources of errors
 - Your program
 - Kinds of errors
- Compile-time errors
 - Syntax errors
 - Type errors
- Link-time errors
- Run-time errors
 - Detected by the computer
 - Detected by a library
 - Detected by user-code
 - Local
 - Non-local
- Logic errors
- References

Notes

Overview

- Software
 - Nature of programming
 - Machine language
 - Assembly language
 - Higher-level languages
- C++
 - Compilation
- Errors
 - Sources of errors
 - Your program
 - Kinds of errors
 - Compile-time errors
 - Syntax errors
 - Type errors
 - Link-time errors
- Run-time errors
 - Detected by the computer
 - Detected by a library
 - Detected by user-code
 - Local
 - Non-local
 - Logic errors
- References

Notes

Run-time errors : detected by the computer

Notes

```
#include <iostream>
#include <vector>
using namespace std;

int main ( ) {

    int x = -1;
    int y = 0;
    /*      divide by zero
    */
    int z = x / y;
    cout << z;

    return 0;
}
```

Desktop/LX_Errors-Exceptions/code
% g++ RunTimeErrors1.cpp

Desktop/LX_Errors-Exceptions/code
% ./a.out
[1] 46493 floating point exception ./a.out

Overview

- Software
 - Nature of programming
 - Machine language
 - Assembly language
 - Higher-level languages
- C++
 - Compilation
- Errors
 - Sources of errors
 - Your program
 - Kinds of errors
 - Compile-time errors
 - Syntax errors
 - Type errors
 - Link-time errors
- Run-time errors
 - Detected by the computer
 - Detected by a library
 - Detected by user-code
 - Local
 - Non-local
 - Logic errors
- References

Notes

Run-time errors : detected by a library

Notes

```
#include <iostream>
#include <vector>
using namespace std;

int main ( ) {
    vector<int> v(10);
    /*
     * when we are at v.size(), we are out of
     * v's range of elements
     */
    for (int i = 0 ; i <= v.size() ; ++i)
        cout << v.at(i) << ' ';

    return 0;
}
```

```
Desktop/LX_Errors-Exceptions/code
% g++ RunTimeErrors2.cpp

Desktop/LX_Errors-Exceptions/code
% ./a.out
terminate called after throwing an instance of 'std::out_of_range'
what(): vector::_M_range_check: __n (which is 10) >= th
is->size() (which is 10)
0 0 0 0 0 0 0 0 0 0 [1] 50620 abort ./a.out
```

Overview

- Software
 - Nature of programming
 - Machine language
 - Assembly language
 - Higher-level languages
 - C++ Compilation
- Errors
 - Sources of errors
 - Your program
 - Kinds of errors
- Compile-time errors
 - Syntax errors
 - Type errors
- Link-time errors
- Run-time errors
 - Detected by the computer
 - Detected by a library
 - Detected by user-code
 - Local
 - Non-local
- Logic errors
- References

Notes

Run-time errors : detected by user-code

Notes

- We can find errors through various checks made during a running program...

Overview

- Software
 - Nature of programming
 - Machine language
 - Assembly language
 - Higher-level languages
- C++
 - Compilation
- Errors
 - Sources of errors
 - Your program
 - Kinds of errors
- Compile-time errors
 - Syntax errors
 - Type errors
- Link-time errors
- Run-time errors**
 - Detected by the computer
 - Detected by a library
 - Detected by user-code**
 - Local
 - Non-local
- Logic errors
- References

Notes

Local run-time errors

Notes

```
► Easy to do for local run-time errors
  ► int i;
    std::cin >> i;
    if (i < 0)
      return 1;
```

Overview

- Software
 - Nature of programming
 - Machine language
 - Assembly language
 - Higher-level languages
- C++
 - Compilation
- Errors
 - Sources of errors
 - Your program
 - Kinds of errors
- Compile-time errors
 - Syntax errors
 - Type errors
- Link-time errors
- Run-time errors**
 - Detected by the computer
 - Detected by a library
 - Detected by user-code**
 - Local
 - Non-local
- Logic errors
- References

Notes

Non-local run-time errors

- How can we handle non-local errors during run-time?

```
// necessary #includes...
```

```
int area (int length, int width) { return length * width; }
int framed_area (int x, int y) { return area(x-2, y-2); }
```

```
int main ( ) {
    int x = -1;
    int y = 2;
    int z = 4;
    // ...
    int area1 = area(x, y);
    int area2 = framed_area(1, z);
    int area3 = framed_area(y, z);
    double ratio = double(area1)/area3;
    return 0;
}
```

- Need some means of error reporting... will discuss this shortly

Notes

Overview

Software

Nature of programming

Machine language

Assembly language

Higher-level languages

C++ Compilation

Errors

Sources of errors

Your program

Kinds of errors

Compile-time errors

Syntax errors

Type errors

Link-time errors

Run-time errors

Detected by the computer

Detected by a library

Detected by user-code

Local

Non-local

Logic errors

References

Notes

Logic errors

```
#include <iostream>
#include <vector>
#include <string>
using namespace std;
```

```
int main ( ) {
```

```
    vector<double> temps { -16.5, -23.2, -24.0, -25.7, -26.1, -18.6, -9.7, -2.4,
        7.5, 12.6, 23.8, 25.3, 28.0, 34.8, 36.7, 41.5, 40.3, 42.6, 39.7, 35.4,
        12.6, 6.5, -3.7, -14.3};
```

```
    double sum = 0;
    double high_temp = 0;
    double low_temp = 0;
```

```
    for (double t : temps) {
        if (t > high_temp) high_temp = t;
        if (t < low_temp) low_temp = t;
        sum += t;
    }
```

```
    double avg_temp = sum/temps.size();
    for (int i = 1 ; i <= temps.size() ; ++ i) {
        cout << temps.at(i-1) << 't';
        if (i % 4 == 0) cout << endl;
```

```
    }
    cout << endl;
    cout << "High temperature:u" << high_temp << endl;
    cout << "Low temperature:u" << low_temp << endl;
    cout << "Average temperature:u" << avg_temp << endl;
```

```
}
```

```
Desktop/LX_Errors-Exceptions/code
% g++ LogicErrors1.cpp
```

```
Desktop/LX_Errors-Exceptions/code
% ./a.out
```

```
-16.5 -23.2 -24 -25.7
-26.1 -18.6 -9.7 -2.4
7.5 12.6 23.8 25.3
28 34.8 36.7 41.5
40.3 42.6 39.7 35.4
12.6 6.5 -3.7 -14.3
```

```
High temperature: 42.6
Low temperature: -26.1
Average temperature: 9.29583
```

Notes

References

- ▶ Lippman, B., Lajoie, Josee, & Moo, B. E. (2016). *C++ primer* (5th ed.). Addison-Wesley.
- ▶ Stroustrup, B. (2014). *Programming: principles and practice using C++* (2nd ed.). Addison-Wesley.

Notes

Notes

Notes
