

ExNEWTON_1_HuangSo

Reproduce the explicit 2×2 examples (Examples 2.5–2.7) from:

L. Huang and W. So, "On left eigenvalues of a quaternionic matrix," *Linear Algebra and its Applications* 323 (2001) 105–116. DOI: 10.1016/S0024-3795(00)00246-9

The shipped script `examples/ExNEWTON_1_HuangSo.m` builds the matrices using MATLAB built-in quaternion class and runs `checkNEWTON` plus the sphere utilities for Example 2.7.

Requirements

```
hasQuat = true;
try
    quaternion(0,0,0,0);
catch
    hasQuat = false;
end
if ~hasQuat
    disp('This toolbox requires MATLAB''s built-in quaternion class
(quaternion(w,x,y,z)).');
    disp('Examples in this page are skipped.');
```

```
    return;
end

if exist('leigqNEWTON','file') ~= 2
    thisFile = mfilename('fullpath');
    if ~isempty(thisFile)
        rootGuess = fileparts(fileparts(fileparts(thisFile))); % .../docs/source ->
toolbox root
        if exist(fullfile(rootGuess,'leigqNEWTON.m'),'file')
            addpath(rootGuess);
        end
    end
end

if exist('leigqNEWTON','file') ~= 2
    error('leigqNEWTON not found on the MATLAB path. Add the toolbox root folder.');
```

```
end
```

Run the shipped script

```
root = fileparts(which('leigqNEWTON'));
ex = fullfile(root,'examples','ExNEWTON_1_HuangSo.m');
if exist(ex,'file')
    run(ex);
else
    error('Example not found: %s', ex);
end
```

=====

EXAMPLE 2.5

A25 =

$$\begin{array}{cc} 0 + 0i + 0j + 0k & 1 + 1i + 0j + 0k \\ 1 - 1i + 0j + 0k & 0 + 0i + 0j + 0k \end{array}$$

Expected left eigenvalues (paper) =

$$\begin{array}{cccc} 1.4142 + & 0i + & 0j + & 0k \\ -1.4142 + & 0i + & 0j + & 0k \end{array}$$

=== checkNEWTON ===

Matrix: 2x2 quaternion

Lambdas: 2 (computed). Vectors: 2 columns (computed).

Certificate/residual summary (median | max):

resMin abs: 9.70e-13 | 1.94e-12 resMin rel: 2.84e-13 | 5.68e-13
resPair abs: 9.71e-13 | 1.94e-12 resPair rel: 2.84e-13 | 5.68e-13

Per-eigenvalue residuals:

#	lambda (cleaned/rounded)	resMin(abs/rel)	resPair(abs/rel)
1	1.414 +0i +2.192e-12j +1.168e-12k	1.94e-12/ 5.68e-13	1.94e-12/ 5.68e-13
2	-1.414 +0i +0j +0k	1.47e-16/ 4.31e-17	4.56e-16/ 1.34e-16

Interestingness:

Standard: Kdistinct = n = 2.

Sphere check: not run. Use checkNEWTON(..., 'SphereCheck', 'on') to force.

Outputs:

out : main struct (out.lambda, out.v, out.resMinAbs, out.resPairAbs, ...).
cases{1} : simple case struct with fields A, lamAll, lamSamples, sph, info (sphere tooling style).
S : summary struct (n, Ktot, Kdistinct, spheresFound, ...).
Nearest distances to the reference set (in 4D):
lambda[1] ~ ref[1], dist = 2.603e-12, lambda = 1.4142 + 0i + 2.1921e-12j + 1.168e-12k
lambda[2] ~ ref[2], dist = 0.000e+00, lambda = -1.4142 + 0i + 0j + 0k

EXAMPLE 2.6

A26 =

$$\begin{array}{cc} 0 + 0i + 0j + 0k & 0 + 1i + 0j + 0k \\ 0 + 0i + 1j + 0k & 1 + 0i + 0j + 0k \end{array}$$

Expected left eigenvalues (paper) =

$$\begin{array}{c} 0.5 + 0.5i + 0.5j - 0.5k \\ 0.5 - 0.5i - 0.5j - 0.5k \end{array}$$

=== checkNEWTON ===

Matrix: 2x2 quaternion

Lambdas: 2 (computed). Vectors: 2 columns (computed).

Certificate/residual summary (median | max):

resMin abs: 1.34e-11 | 2.68e-11 resMin rel: 4.91e-12 | 9.81e-12
resPair abs: 1.34e-11 | 2.68e-11 resPair rel: 4.91e-12 | 9.81e-12

Per-eigenvalue residuals:

#	lambda (cleaned/rounded)	resMin(abs/rel)	resPair(abs/rel)
1	0.5 +0.5i +0.5j -0.5k	2.68e-11/ 9.81e-12	2.68e-11/ 9.81e-12
2	0.5 -0.5i -0.5j -0.5k	6.31e-17/ 2.31e-17	3.16e-16/ 1.15e-16

Interestingness:

Standard: Kdistinct = n = 2.

Sphere check: not run. Use checkNEWTON(..., 'SphereCheck', 'on') to force.

Outputs:

out : main struct (out.lambda, out.v, out.resMinAbs, out.resPairAbs, ...).
cases{1} : simple case struct with fields A, lamAll, lamSamples, sph, info (sphere tooling style).
S : summary struct (n, Ktot, Kdistinct, spheresFound, ...).
Nearest distances to the reference set (in 4D):
lambda[1] ~ ref[1], dist = 3.721e-11, lambda = 0.5 + 0.5i + 0.5j - 0.5k

```
lambda[2] ~ ref[2], dist = 3.331e-16, lambda = 0.5 - 0.5i - 0.5j - 0.5k
```

EXAMPLE 2.7

```
A27 =
```

```
2 + 0i + 0j + 0k    0 + 1i + 0j + 0k
0 - 1i + 0j + 0k    2 + 0i + 0j + 0k
```

```
Paper claim: sigma_l(A27) is infinite (a sphere family).
```

```
=== checkNEWTON ===
```

```
Matrix: 2x2 quaternion
```

```
Lambdas: 2 (computed). Vectors: 2 columns (computed).
```

```
Certificate/residual summary (median | max):
```

```
resMin abs: 1.11e-11 | 1.89e-11    resMin rel: 2.25e-12 | 3.84e-12
resPair abs: 1.11e-11 | 1.89e-11    resPair rel: 2.25e-12 | 3.84e-12
```

```
Per-eigenvalue residuals:
```

#	lambda (cleaned/rounded)	resMin(abs/rel)	resPair(abs/rel)
1	1.526 +1.848e-11i -0.01666j +0.8802k	1.89e-11/ 3.84e-12	1.89e-11/ 3.84e-12
2	1.672 +3.249e-12i -0.6181j +0.7145k	3.33e-12/ 6.55e-13	3.33e-12/ 6.55e-13

```
Interestingness:
```

```
Standard: Kdistinct = n = 2.
```

```
Sphere check: not run. Use checkNEWTON(...,'SphereCheck','on') to force.
```

```
Outputs:
```

```
out          : main struct (out.lambda, out.v, out.resMinAbs, out.resPairAbs, ...).
cases{1}     : simple case struct with fields A, lamAll, lamSamples, sph, info (sphere tooling style).
S            : summary struct (n, Ktot, Kdistinct, spheresFound,...).
```

```
=== leigqNEWTON_sphere_sample: collecting samples (n=2, targetDistinct=20) ===
```

```
run 1 | Seed=1 | addedDistinct 2 | totalDistinct 2 | counted 2
run 2 | Seed=2 | addedDistinct 2 | totalDistinct 4 | counted 4
run 3 | Seed=3 | addedDistinct 2 | totalDistinct 6 | counted 6
run 4 | Seed=4 | addedDistinct 2 | totalDistinct 8 | counted 8
run 5 | Seed=5 | addedDistinct 2 | totalDistinct 10 | counted 10
run 6 | Seed=6 | addedDistinct 2 | totalDistinct 12 | counted 12
run 7 | Seed=7 | addedDistinct 2 | totalDistinct 14 | counted 14
run 8 | Seed=8 | addedDistinct 2 | totalDistinct 16 | counted 16
run 9 | Seed=9 | addedDistinct 2 | totalDistinct 18 | counted 18
run 10 | Seed=10 | addedDistinct 2 | totalDistinct 20 | counted 20
```

```
Please note: The refinement may take about ten minutes.
```

```
=== leigqNEWTON_sphere_refine: idx=NaN, seed=NaN, origin= ===
```

```
Ktot=20, Kdistinct=20, spheres=1
```

```
Initial residuals: lamAll med=1.91e-15 max=1.89e-11 | lamSamples med=1.91e-15 max=1.89e-11
```

What to look for

- Example 2.5 and 2.6: two isolated left eigenvalues, agreement with the paper.
- Example 2.7: an infinite left spectrum (sphere family). The script runs `leigqNEWTON_sphere_sample` and then `leigqNEWTON_sphere_validate` (which calls `leigqNEWTON_sphere_refine` in the public release) and prints the fitted sphere model sphere model and a confidence report. Validation is a lengthy process and may take up to 10 minutes.

See also

```
doc_SphereHunting, leigqNEWTON_sphere_sample, leigqNEWTON_sphere_refine, checkNEWTON
```