Copyright 1986-2022 Xilinx, Inc. All Rights Reserved. Copyright 2022-2024 Advanced Micro Devices, Inc. All Rights Reserved.

| Tool Version : Vivado v.2024.1 (win64) Build 5076996 Wed May 22 18:37:14 MDT 2024
| Date : Thu Oct 1 00:19:39 2026
| Host : MICHALADENND5D2 running 64-bit major release (build 9200)
| Command : report_utilization -file lab3_top_utilization_synth.rpt -pb lab3_top_utilization_synth.pb
| Design : lab3_top
| Device : xc7a100tcsg324-1
| Speed File : -1
| Design State : Synthesized

Utilization Design Information

Table of Contents
---
1. Slice Logic
1.1 Summary of Registers by Type
2. Memory
3. DSP
4. IO and GT Specific
5. Clocking
6. Specific Feature
7. Primitives
8. Black Boxes
9. Instantiated Netlists

1. Slice Logic

Site Type	Used	Fixed	Prohibited	Available	Util%
Slice LUTs*	88	0	0	63400	0.14
LUT as Logic	88	0	0	63400	0.14
LUT as Memory	0	0	0	19000	0.00
Slice Registers	89	0	0	126800	0.07
Register as Flip Flop	89	0	0	126800	0.07
Register as Latch	0	0	0	126800	0.00
F7 Muxes	4	0	0	31700	0.01
F8 Muxes	0	0	0	15850	0.00

* Warning! The Final LUT count, after physical optimizations and full implementation, is typically lower. Run opt_design after synthesis, if not already completed, for a more realistic count.
Warning! LUT value is adjusted to account for LUT combining.
Warning! For any ECO changes, please run place_design if there are unplaced instances

1.1 Summary of Registers by Type

Total	Clock Enable	Synchronous	Asynchronous
0	_	-	-
0	_	-	Set
0	_	-	Reset
0	_	Set	-
0	_	Reset	-
0	Yes	-	-
0	Yes	-	Set
89	Yes	-	Reset
0	Yes	Set	-
0	Yes	Reset	-

2. Memory

Site Type	Used	Fixed	Prohibited	Available	Util%
Block RAM Tile	0	0	0	135	0.00
RAMB36/FIFO*	0	0	0	135	0.00
RAMB18	0	0	0	270	0.00

* Note: Each Block RAM Tile only has one FIFO logic available and therefore can accommodate only one FIFO36E1 or one FIFO18E1. However, if a FIFO18E1 occupies a Block RAM Tile, that tile can still accommodate a RAMB18E1

3. DSP

Site Type	Used	Fixed	Prohibited	Available	Util%
DSPs	0	0	0	240	0.00

4. IO and GT Specific

Site Type	Used	Fixed	Prohibited	Available	Util%
Bonded IOB	50	0	0	210	23.81
Bonded IPADs	0	0	0	2	0.00
PHY_CONTROL	0	0	0	6	0.00
PHASER_REF	0	0	0	6	0.00

OUT_FIFO	0	0	0	24	0.00
IN_FIFO	0	0	0	24	0.00
IDELAYCTRL	0	0	0	6	0.00
IBUFDS	0	0	0	202	0.00
PHASER_OUT/PHASER_OUT_PHY	0	0	0	24	0.00
PHASER_IN/PHASER_IN_PHY	0	0	0	24	0.00
IDELAYE2/IDELAYE2_FINEDELAY	0	0	0	300	0.00
ILOGIC	0	0	0	210	0.00
OLOGIC	0	0	0	210	0.00

5. Clocking

Site Type	Used	Fixed	Prohibited	Available	Util%
BUFGCTRL	2	0	0	32	6.25
BUFIO	0	0	0	24	0.00
MMCME2_ADV	0	0	0	6	0.00
PLLE2_ADV	0	0	0	6	0.00
BUFMRCE	0	0	0	12	0.00
BUFHCE	0	0	0	96	0.00
BUFR	0	0	0	24	0.00

6. Specific Feature

Site Type	Used	Fixed	Prohibited	Available	Util%
BSCANE2	0	0	0	4	0.00
CAPTUREE2	0	0	0	1	0.00
DNA_PORT	0	0	0	1	0.00
EFUSE_USR	0	0	0	1	0.00
FRAME_ECCE2	0	0	0	1	0.00
ICAPE2	0	0	0	2	0.00
PCIE_2_1	0	0	0	1	0.00
STARTUPE2	0	0	0	1	0.00
XADC	0	0	0	1	0.00

7. Primitives

Ref Name	Used	Functional Category
FDCE	89	Flop & Latch
LUT2	61	LUT
OBUF	32	IO
IBUF	18	IO
LUT6	14	LUT
CARRY4	14	CarryLogic
LUT4	13	LUT
LUT3	11	LUT
MUXF7	4	MuxFx
BUFG	2	Clock
LUT1	1	LUT

8. Black Boxes

Ref Name	Used

9. Instantiated Netlists

Ref Name	Used