Deep reinforcement learning

Michal CHOVANEC, PhD.

April 2018

Faculty of Management Science and Informatics

Problem definition

- learn to play game with unknow rules
- input : state and reward
- output : action and total score
- $Q(s, a)$: learn Q function

agent never sees required value (required action)



Storing Q values

- table
- linear combination of basis function (handmade features)
- Kenerva's sparse encoding
- neural network

problems

- state correlations
- nonstationary Q values
- convergence to optimal strategy

Neural network approximator - deep reinforcement learning



64 32 2



Speed up learning



common feed forward neural network



stacked autoencoder + feed forward neural network

Arcade game experiment



	FNN sparse	FNN no sparse	AE+FNN sparse	AE+FNN no sparse
unsupervised iterations	0	0	100000	100000
supervised iterations	200000	200000	200000	200000
iterations per slice	0	0	50000	50000
learning rate	0.0005	0.0005	0.0005	0.0005
init weight range	0.1	0.1	0.1	0.1
dropout	0	0	0	0
lambda	0.00000001	0	0.00000001	0

Results



Average training progress comparison

	average score	best score	worst score	average best action probability [%
FNN sparse weights	957.31	978.3	927.31	94.04
FNN nosparse weights	951.5	959.3	942.644	95.95
AE+FNN sparse weights	763.58	942.97	618.66	88.16
AE+FNN no sparse weights	737.78	884.98	618.99	87.19

Snake game experiment



FNN score progress comparison



AE+FNN score progress comparison

Q&A

https://github.com/michalnand/robotics
https://github.com/michalnand/machine_learning

michal.nand@gmail.com