

dpcReport: web server and software suite for unified analysis of digital PCRs and digital assays

Michał Burdukiewicz¹, Jim Huggett², Alexandra Whale², Piotr Sobczyk³, Paweł Mackiewicz¹, Andrej-Nikolai Spiess³, Peter Schierack⁵, and Stefan Rödiger⁵

¹University of Wrocław, Department of Genomics,

²Molecular and Cell Biology Team, LGC, Teddington, United Kingdom,

³Wrocław University of Science and Technology, Faculty of Pure and Applied Mathematics,

⁴University Medical Center Hamburg-Eppendorf, Hamburg, Germany,

⁵Brandenburg University of Technology Cottbus-Senftenberg, Institute of Biotechnology

Outline

dPCR software


Aim

Methods

Reproducibility


dPCR software

dPCR-related publications



Number of publications with words "digital PCR" or "dPCR" in the title/abstract.

dPCR-related publications



541 expected publications in 2017.

Vendor-provided dPCR software

Graphical user interfaces:

- QuantaSoft™ (Biorad),
- OpenArray® Digital PCR Software (Thermo Fisher),
- Digital PCR Analysis software (Fluidigm).

Vendor-provided dPCR software

Graphical user interfaces:

- QuantaSoft™ (Biorad),
- OpenArray® Digital PCR Software (Thermo Fisher),
- Digital PCR Analysis software (Fluidigm).

Closed-source software tied only to the vendor-specific data format.

Scripts and smaller tools tied to very specific task:

- **Mathematica** (Strain et al., 2013),
- **MS EXCEL** (Dobnik et al., 2015),
- **R** (Dreo et al., 2014; Trypsteen et al., 2015; Dorazio and Hunter, 2015; Vynck et al., 2016).

R: a software environment and a programming language (R Core Team, 2016), extensively used in bioinformatics and biostatistics.

Web servers (limited to published web servers):

- definetherain (Jones et al., 2014),
- ddpcr (Attali et al., 2016) (also the **R** package),

Aim

Existing software	Desired software
closed-source (vendors), open-source (scientific)	open-source
partially reproducible	fully reproducible
tied to a specific platform	multi-platform
solving a specific problem	focused on common tasks
scattered	integrated

Create framework for dPCR data analysis:

Create framework for dPCR data analysis:

- tailored for the most common tasks,

Create framework for dPCR data analysis:

- tailored for the most common tasks,
- universal,

Create framework for dPCR data analysis:

- tailored for the most common tasks,
- universal,
- unified,

Create framework for dPCR data analysis:

- tailored for the most common tasks,
- universal,
- unified,
- reproducible.

Methods

Multiple comparison

Uniformly most powerful test

Confidence intervals

Array quality control

Reproducibility

Scientific software must support reproducibility, otherwise it is not scientific.

A report should contain enough information to allow the full reproduction of the conducted analysis.

Table of Contents

- [dpcReport](#)
 - [Data summary table](#)
 - [Explanation](#)
 - [Data summary scatter charts](#)
 - [Scatter chart](#)
 - [Compare runs](#)
 - [Compare digital PCR experiments](#)
 - [The mean number of template molecules per partition](#)
- [R code](#)
- [R Session](#)

dpcReport

Report generated on 2017-03-27 07:12:26 using [dpcR](#) R package.

Detected input file: 20130918_Dilution_log10.csv.

md5 checksum of the input file: 6bf3306199dd7af439d1c8acd08e23c1

The input was modified manually in dpcReport application.

File format: QX100.

Data summary table

Run	Experiment name	Replicate ID	Assay	Method	λ	λ (lower CI)	λ (upper CI)	Concentration	Concentration (lower CI)	Concentration (upper CI)	k	n
ABS1.A09.gDNA + P 10 ⁴	ABS1	A09.gDNA + P 10 ⁴	ileS	dube	0.07	0.07	0.08	970.44	0.08	0.09	936	13346
ABS1.A09.gDNA + P 10 ⁴	ABS1	A09.gDNA + P 10 ⁴	ileS	bhat	0.07	0.07	0.08	970.44	0.08	0.09	936	13346
ABS1.B09.gDNA	ABS1	B09.gDNA	ileS	bhat	0.07	0.07	0.08	1171.87	0.11	0.12	1140	11000

Date and time

Table of Contents

- [dpcReport](#)
 - [Data summary table](#)
 - [Explanation](#)
 - [Data summary scatter charts](#)
 - [Scatter chart](#)
 - [Compare runs](#)
 - [Compare digital PCR experiments](#)
 - [The mean number of template molecules per partition](#)
- [R code](#)
- [R Session](#)

dpcReport

Report generated on 2017-03-27 07:12:26 using [dpcR](#) R package.

Detected input file: 20130918_Dilution_log10.csv.

md5 checksum of the input file: 6bf3306199dd7af439d1c8acd08e23c1

The input was modified manually in dpcReport application.

File format: QX100.

Data summary table

Run	Experiment name	Replicate ID	Assay	Method	λ	λ (lower CI)	λ (upper CI)	Concentration	Concentration (lower CI)	Concentration (upper CI)	k	n
ABS1.A09.gDNA + P 10 ⁴	ABS1	A09.gDNA + P 10 ⁴	ileS	dube	0.07	0.07	0.08	970.44	0.08	0.09	936	13346
ABS1.A09.gDNA + P 10 ⁴	ABS1	A09.gDNA + P 10 ⁴	ileS	bhat	0.07	0.07	0.08	970.44	0.08	0.09	936	13346
ABS1.B09.gDNA	ABS1	B09.gDNA	ileS	bhat	0.07	0.07	0.08	1171.87	0.11	0.12	1140	11688

Input file name

Table of Contents

- [dpcReport](#)
 - [Data summary table](#)
 - [Explanation](#)
 - [Data summary scatter charts](#)
 - [Scatter chart](#)
 - [Compare runs](#)
 - [Compare digital PCR experiments](#)
 - [The mean number of template molecules per partition](#)
- [R code](#)
- [R Session](#)

dpcReport

Report generated on 2017-03-27 07:12:26 using [dpcR](#) R package.

Detected input file: 20130918_Dilution_log10.csv.

md5 checksum of the input file: 6bf3306199dd7af439d1c8acd08e23c1

The input was modified manually in dpcReport application.

File format: QX100.

Data summary table

Run	Experiment name	Replicate ID	Assay	Method	λ	λ (lower CI)	λ (upper CI)	Concentration	Concentration (lower CI)	Concentration (upper CI)	k	n
ABS1.A09.gDNA + P 10 ⁴	ABS1	A09.gDNA + P 10 ⁴	ileS	dube	0.07	0.07	0.08	970.44	0.08	0.09	936	13346
ABS1.A09.gDNA + P 10 ⁴	ABS1	A09.gDNA + P 10 ⁴	ileS	bhat	0.07	0.07	0.08	970.44	0.08	0.09	936	13346
ABS1.B09.gDNA	ABS1	B09.gDNA	ileS	bhat	0.07	0.07	0.08	1171.87	0.11	0.12	1140	11688

Input file checksum

Table of Contents

- [dpcReport](#)
 - [Data summary table](#)
 - [Explanation](#)
 - [Data summary scatter charts](#)
 - [Scatter chart](#)
 - [Compare runs](#)
 - [Compare digital PCR experiments](#)
 - [The mean number of template molecules per partition](#)
- [R code](#)
- [R Session](#)

dpcReport

Report generated on 2017-03-27 07:12:26 using [dpcR](#) R package.

Detected input file: 20130918_Dilution_log10.csv.

md5 checksum of the input file: 6bf3306199dd7af439d1c8acd08e23c1

The input was modified manually in dpcReport application.

File format: QX100.

Data summary table

Run	Experiment name	Replicate ID	Assay	Method	λ	λ (lower CI)	λ (upper CI)	Concentration	Concentration (lower CI)	Concentration (upper CI)	k	n
ABS1.A09.gDNA + P 10 ⁴	ABS1	A09.gDNA + P 10 ⁴	ileS	dube	0.07	0.07	0.08	970.44	0.08	0.09	936	13346
ABS1.A09.gDNA + P 10 ⁴	ABS1	A09.gDNA + P 10 ⁴	ileS	bhat	0.07	0.07	0.08	970.44	0.08	0.09	936	13346
ABS1.B09.gDNA	ABS1	B09.gDNA	ileS	bhat	0.07	0.07	0.08	1171.07	0.08	0.10	1110	11000

Changes in case of the manual alteration of the input file.

Manual alterations inside dpcReport

Table of Contents

- [dpcReport](#)
 - [Data summary table](#)
 - [Explanation](#)
 - [Data summary scatter charts](#)
 - [Scatter chart](#)
 - [Compare runs](#)
 - [Compare digital PCR experiments](#)
 - [The mean number of template molecules per partition](#)
- [R code](#)
- [R Session](#)

dpcReport

Report generated on 2017-03-27 07:12:26 using [dpcR](#) R package.

Detected input file: 20130918_Dilution_log10.csv.

md5 checksum of the input file: 6bf3306199dd7af439d1c8acd08e23c1

The input was modified manually in dpcReport application.

File format: QX100.

Data summary table

Run	Experiment name	Replicate ID	Assay	Method	λ	λ (lower CI)	λ (upper CI)	Concentration	Concentration (lower CI)	Concentration (upper CI)	k	n
ABS1.A09.gDNA + P 10 ⁴	ABS1	A09.gDNA + P 10 ⁴	ileS	dube	0.07	0.07	0.08	970.44	0.08	0.09	936	13346
ABS1.A09.gDNA + P 10 ⁴	ABS1	A09.gDNA + P 10 ⁴	ileS	bhat	0.07	0.07	0.08	970.44	0.08	0.09	936	13346
ABS1.B09.gDNA	ABS1	B09.gDNA	ileS	bhat	0.07	0.07	0.08	970.44	0.08	0.09	936	13346

R Session

```
## R version 3.3.3 (2017-03-06)
## Platform: x86_64-pc-linux-gnu (64-bit)
## Running under: Ubuntu 14.04.5 LTS
##
## locale:
## [1] LC_CTYPE=pl_PL.UTF-8      LC_NUMERIC=C
## [3] LC_TIME=pl_PL.UTF-8      LC_COLLATE=pl_PL.UTF-8
## [5] LC_MONETARY=pl_PL.UTF-8  LC_MESSAGES=pl_PL.UTF-8
## [7] LC_PAPER=pl_PL.UTF-8     LC_NAME=C
## [9] LC_ADDRESS=C             LC_TELEPHONE=C
## [11] LC_MEASUREMENT=pl_PL.UTF-8 LC_IDENTIFICATION=C
##
## attached base packages:
## [1] stats      graphics  grDevices  utils      datasets  methods   base
##
## other attached packages:
## [1] xtable_1.8-2      knitr_1.15.1      digest_0.6.12
## [4] dplyr_0.5.0       DT_0.2            ggplot2_2.2.1
## [7] rhandsontable_0.3.4 shinythemes_1.1.1 shiny_1.0.0
## [10] dpcR_0.4
##
## loaded via a namespace (and not attached):
## [1] jsonlite_1.2      binom_1.1-1      splines_3.3.3
## [4] assertthat_0.1    highr_0.6        Rfit_0.23.0
## [7] chipPCR_0.0.8-11  yaml_2.1.14      outliers_0.14
## [10] robustbase_0.92-7 lattice_0.20-34  quantreg_5.29
## [13] quadprog_1.5-5    polyclip_1.5-6   colorspace_1.3-1
## [16] sandwich_2.3-4    htmltools_0.3.5  httpuv_1.3.3
## [19] Matrix_1.2-8      plyr_1.8.4       SparseM_1.74
## [22] mvtnorm_1.0-5     ptw_1.9-11       scales_0.4.1
## [25] tensor_1.5        pracma_1.9.5     MatrixModels_0.4-1
## [28] tibble_1.2        mgcv_1.8-16      TH.data_1.0-7
## [31] dgof_1.2          lazyeval_0.2.0   survival_2.40-1
## [34] magrittr_1.5      readxl_0.1.1     mime_0.5
## [37] deldir_0.1-12     evaluate_0.10    nlme_3.1-131
```

Reproducibility of the workflow

An analysis conducted in a GUI-based software, as *dpcReport*, is more challenging to reproduce.

dpcReport exports all steps of the analysis, including parameters adjusted manually by the user, in form of the **R** code that recreates the whole workflow.

Reproducibility of the workflow

R code

The R code below may be used to recreate reported results.

```
# Load packages
library(dpcR)
# if you do not have dpcR package, install it from GitHub:
# devtools::install_github("michbur/dpcR")
library(ggplot2) # ggplot2 library for nice plots
# Define theme for plots
cool_theme <- theme(plot.background=element_rect(fill = "transparent", colour = "transparent"),
panel.grid.major = element_line(colour="lightgrey", linetype = "dashed"), panel.background =
element_rect(fill = "white", colour = "black"), legend.background = element_rect(fill="NA"),
legend.position = "bottom", axis.text = element_text(size = 14), axis.title.x = element_text(size=17,
vjust = -0.1), axis.title.y = element_text(size = 17, vjust = 1), strip.text = element_text(size = 17,
face = "bold"), strip.background = element_rect(fill = "#9ecae1", colour = "black"), legend.text =
element_text(size=14), legend.title = element_text(size = 17), plot.title = element_text(size = 22),
legend.key = element_rect(fill = "white", colour = "black", linetype = "dashed", size = 0.5))
# Read and adjust data
# The input file is assumed to be in the current R working directory
input_data <- read_dpcr("20130918_Dilution_log10.csv", format = "QX100")

#####
# Print only table from summary.dpcr function
summary(input_data, print = FALSE)[["summary"]]

#####
# Prepare data for plots
plot_data <- summary(input_data, print = FALSE)[["summary"]]
plot_data <- plot_data[plot_data[["method"]] == "dube", ]
ggplot(plot_data, aes(x = experiment, y = lambda, ymax = lambda.up, ymin = lambda.low)) + geom_point(size
= 4, alpha = 0.6, shape = 2, colour = "blue") + cool_theme + geom_boxplot(outlier.colour = NA, fill =
adjustcolor("lightgrey", alpha.f = 0.25), shape = 15) + ggtitle(paste0("Experiment boxplot\nCI method: ",
```

dpcReport is the integrated environment for the analysis of dPCR data.

Web server: `www.smorfland.uni.wroc.pl/shiny/dpcReport`

R package (including your local instance of dpcReport):

`www.github.com/michbur/dpcR`

This research was partially funded by the KNOW Consortium Wrocław Center for Biotechnology, National Science Center (2015/17/N/NZ2/01845) and COST action "Harmonising standardisation strategies to increase efficiency and competitiveness of European life-science research".

- Jim Hugget and Alexandra Whale.
- Stefan Rödiger.

References

- Attali, D., Bidshahri, R., Haynes, C., and Bryan, J. (2016). Ddpcr: An R package and web application for analysis of droplet digital PCR data. *F1000Research*, 5:1411.
- Dobnik, D., Spilsberg, B., Bogožalec Košir, A., Holst-Jensen, A., and Žel, J. (2015). Multiplex Quantification of 12 European Union Authorized Genetically Modified Maize Lines with Droplet Digital Polymerase Chain Reaction. *Analytical Chemistry*, 87(16):8218–8226.

- Dorazio, R. M. and Hunter, M. E. (2015). Statistical Models for the Analysis and Design of Digital Polymerase Chain Reaction (dPCR) Experiments. *Analytical Chemistry*, 87(21):10886–10893.
- Dreo, T., Pirc, M., Ramšak, Ž., Pavšič, J., Milavec, M., Žel, J., and Gruden, K. (2014). Optimising droplet digital PCR analysis approaches for detection and quantification of bacteria: A case study of fire blight and potato brown rot. *Analytical and Bioanalytical Chemistry*, 406(26):6513–6528.

References III

- Jones, M., Williams, J., Gärtner, K., Phillips, R., Hurst, J., and Frater, J. (2014). Low copy target detection by Droplet Digital PCR through application of a novel open access bioinformatic pipeline, 'definetherain'. *Journal of Virological Methods*, 202(100):46–53.
- R Core Team (2016). *R: A Language and Environment for Statistical Computing*. R Foundation for Statistical Computing, Vienna, Austria.
- Strain, M. C., Lada, S. M., Luong, T., Rought, S. E., Gianella, S., Terry, V. H., Spina, C. A., Woelk, C. H., and Richman, D. D. (2013). Highly precise measurement of HIV DNA by droplet digital PCR. *PloS one*, 8(4):e55943.

References IV

- Trypsteen, W., Vynck, M., De Neve, J., Bonczkowski, P., Kiselina, M., Malatinkova, E., Vervisch, K., Thas, O., Vandekerckhove, L., and De Spiegelaere, W. (2015). ddpcRquant: Threshold determination for single channel droplet digital PCR experiments. *Analytical and Bioanalytical Chemistry*, 407(19):5827–5834.
- Vynck, M., Vandesompele, J., Nijs, N., Menten, B., De Ganck, A., and Thas, O. (2016). Flexible analysis of digital PCR experiments using generalized linear mixed models. *Biomolecular Detection and Quantification*, 9:1–13.