

Benefits of Electric Road System with charging from below technology to battery electric vehicles

Wasim Shoman¹, Sten Karlsson¹, Sonia Yeh¹

¹ *Department of Space, Earth and Environment Chalmers University of Technology, 412 96 Gothenburg, Sweden, wasim.shoman@chalmers.se*

Summary

This study uses the detailed driving patterns of 412 Swedish drivers in Western Sweden to model the benefits of implementing an Electric Road System (ERS) that is also usable by private passenger EVs. ERS transfers electricity to vehicles dynamically on-road while driving and is being considered as one of the few possible solutions to electrify long-haul trucks. The charging from below, either conductive or inductive, although less well established, has the advantage of also making possible charging of electric passenger cars. This research examines the benefits of charging passenger Battery Electric Vehicles (BEVs) on ERS in Sweden. This technology would increase the utilization of ERS infrastructure and possibly lead to significant cost savings in BEVs by enabling smaller batteries. We examine different ERS placement scenarios, charging options and percentage of BEV penetration. Our results show that the required battery capacity to meet all driving needs drops by 76% and the expected gross savings of using smaller batteries range between 0.17 and 6.5 M€/ERS km for a total of 2900-9300 M€. The economic net benefit is heavily dependent on the percentage of cars switching to BEV and ERS placement and less on the ERS charging rate.

Introduction

Electrifying freight, particularly the long-haul trucks whose growth and greenhouse gas (GHG) emissions that have grown rapidly over the past few decades, has few viable options. Charging From Below (CFB) on Electric Road System (ERS), either conductive or inductive, although less well established, has the advantage of providing charging to passenger battery electric vehicles (BEVs). Overhead line technology, on the other hand, serves only heavy vehicles and buses. The expected ERS infrastructure cost using overhead conductive lines is about 1 M€/ km [1], while it ranges between 0.4-2.7 M€/km for rail and inductive technologies [2, 3, 4]. The difference between the two options might be huge in some cases. However, selecting a technology that benefits more vehicle types is attractive, especially when the benefits are large. For instance, the charging of passenger cars along the road would

increase the utilization of ERS infrastructure and electric vehicles and therefore strengthen their economic standing. A second advantage is that it may enable smaller batteries in battery electric vehicles (BEV), or increase the electric drive fraction and utilization of the already reasonable small battery in Plug-in Hybrid Electric Vehicles (PHEV). For passenger cars, CFB on ERS could be an alternative to fast-charging stations, especially for longer trips.

Therefore, there is a crucial societal choice to be made for infrastructure for possible electric roads: either the more established overhead technique servicing only the heavy traffic and busses or utilize CFB to include passenger vehicles. To make a deliberate and good choice good assessment is needed. For that purpose, several ERS assessments including BEVs have been conducted earlier on the effect on the BEV charging and battery size due to ERS, such as [5, 6, 7, 8]. However, they were based on some general assumptions only. Thus, to our knowledge, there has not been any research on the effects and implications of BEV charging on ERS based on real driving of individual vehicles. This work will contribute to the assessment of BEVs in the CFB alternatives based on individual real car movement patterns.

Primarily, this research aims to investigate specifically the BEV contribution to the viability of CFB on ERS based on individual real movement patterns for representative passenger cars in Sweden. The research identifies benefits to passenger BEVs by assessing possible reduction in battery capacity while meeting all driving needs. The research also examines the cost savings of reduced battery capacities with ERS.

Methodology

The research inspects the expected BEV usage of ERS by modelling individual driving patterns. The research utilizes GPS loggings for 412 cars with data loggings for 30 days or more. They are extracted from the Swedish car movement database [9] measured between 2010-2012. The database contains the use of cars representative in car size and fuel types in Western Sweden, which is a representative part for all Sweden in urban and rural areas, city and household size, and population density. The loggings are filtered and projected on the road network. To explore the full potential benefits of ERS, BEVs are assumed to be charged (besides on ERS) at home or overnight only. Single trips are therefore regrouped to represent a “Daily Driving” (DD) with a full battery charge at the start of driving. A temporal approach is followed to group the trips: trips are grouped if the parking time in between does not exceed 1) 10 hours or 2) 8 hours if the parking time includes 03:00 am. That results in a reduction in the number of trips to be 20,411 DDs, associated with increasing the average DD

duration and distance. The resulted histograms for both average travel time and traveled distance for each car are shown in Figure 1. The figure shows the different driving patterns for all 412 modelled cars. The means for both average travel time and distance are 63 minutes and 54 km, respectively.




Figure 1 Histograms for the A) average travel time and B) travelled distance of representative driving days (DDs).

For simplicity, all BEVs are assumed to use 0.18 kWh/km independent of for instance road conditions and traffic, load and weather. This corresponds to the average energy use in a larger Swedish EV trial using VW e-Golf.

Sweden has a total road network of 601259 km (Vasttrafik). Of that, the European (E) and National (N) roads have total lengths of 12743 km and 12333 km, respectively. In this research, ERS is assumed to be installed on the Swedish European (E) and National (N) roads, both of which represent 4% of the total road network in Sweden. Six ERS cases that include different lengths and traffic distributions are investigated: all E roads alone, all N roads alone, and also 25%, 50%, 75% and 100% of road lengths of both E and N roads, prioritized by traffic volume (Figure 2). The study, also, inspects three different charging rate options while using ERS: 1.0, 1.5 and 2.0 times the assumed BEV specific energy use of 0.18 kWh/km.




Figure 2 (A) Swedish European (E), (B) national (N) roads, and (C-F) 100%, 75%, 50% and 25% shares of E and N roads together, prioritized by traffic volume.

The research examines E-roads because it is discussed mostly for ERS in other researches [2], and compares it with N roads results. Knowing that E roads and N roads are almost equal in lengths, the traffic shares on each road type is different (Figure 3). E roads only cover about 65% of both E and N traffic shares, while N roads only cover a little bit over 35%. On the other hand, 25% and 50% of both E and N road lengths, cover more than 81% and 95%, respectively, of traffic share on both road types (Figure 3).




Figure 3 Traffic volume (%) by road length (%) of E, N, and E & N roads.

Results and Discussion

ERS utilization

For all modeled cars, the study identified “Charging Distances” (CDs) as the distance of driving at roads equipped with ERS. Using that, the study identified ERS shares for each ERS placement case as CD to Distance of DD. Distributions for ERS shares grouped by each modelled car are shown in Figure 4. Obviously, applying ERS to more road lengths increases the coverage rate. However, even though both E and N roads have equal lengths, their ERS shares are very different (Figure 4.E and Figure 4.F). More specifically, using 50% traffic-selected lengths of both E and N roads results in higher coverage of ERS distance compared with 100% E or 100% N only (Figure 4.C), which shows the importance of considering both the lengths and traffic while placing ERS.




Figure 4 Distributions for ERS share using A) 100% E&N, B) 75% E&N, C) 50% E&N, D) 25% of E& N, E) E roads only and F) N roads only as ERS.

Effects of battery size

With a small battery, not all DDs can be fulfilled. When no ERS is assumed, utilizing battery capacities of 10, 15, 30 and 85 kWh, leaves 31%, 19%, 5.6% and 0.34%, respectively, of the DD distances not completed (Figure 5). On the other hand, the analysis shows that for all considered ERS placements of 100%, 75%, 50% and 25% of both E and N roads, E roads alone and N roads alone ERS shares are 34.9%, 31.6%, 28.5%, 24.6%, 24.6% and 11.3%, respectively. These percentages illustrate that ERS shares are relatively small compared to travelled distances of DD. However, with ERS, the not-completed distances of DD drop significantly with utilized battery capacity (Figure 5). For instance, using 100% of both E and N as ERS, a 10-kWh battery fulfills more than 96% of DD distances. On the other hand, using only 25% of E and N as ERS, a 30-kWh battery could complete more than 99.5% of DD distances. We can also note that the resulting non-completed DD differs slightly between the three considered charging options (Figure 5).




Figure 5 Not-completed share of DD distances for different ERS scenarios A)-F) and different battery sizes (x-axis).

Possible reduction in battery capacity

The battery is still considered the most expensive component in an EV. Reduction in its capacity will decrease EV's prices, thus influence more people to buy them [10]. However, reducing battery capacities alone means impacting driving behaviors resulting in less driving distances and less BEV use.

The study investigates the required battery capacity to fulfill all DDs. Kernel density estimators for all considered cases are shown in Figure 6. The figure clearly indicates the reduction in the required battery capacity to cover DDs. Using 100% of both E and N, the mean necessary capacity is reduced from 49 kWh to almost 12 kWh, a reduction of 76 % of battery capacity (Figure 6.A). Likewise, for using 25% of both E and N, the reduction in battery capacity is 62%. Ultimately, implementing ERS to BEV reduces the need for larger batteries to fulfill DDs with minimum impact on current driving behaviors.




Figure 6 Simulated required battery capacity to cover all DDs.

ERS savings

Several studies have forecasted the ERS infrastructure cost. However, the uncertainty in the infrastructure cost of ERS at present is still large for many reasons, including that ERS is still an immature technology under development. For rail, inductive and conductive technologies, the estimates vary between 0.4 and 2.7 M €/km, including the components both for the electric road infrastructure in both directions and the electricity system network to the road [2, 3, 11, 4]. Maintenance costs are estimated to 1–2.5% of the initial infrastructure investment cost [6, 3].

The ERS infrastructure cost can be compared to the possible savings in BEV battery capacity costs. The price of lithium-ion batteries used in BEV dropped from 300 \$/kWh in 2015 [10, 12, 13] to as low as 190-250 \$/kWh in 2017-2019 [14, 8, 15, 16], and is expected to reach a range of 100- 160 \$/kWh in 2025-2030 [13, 8]. We investigate the cost of savings, resulting from reducing the mean capacities (Figure 6) with a predicted battery cost of 120 \$/kWh (~106 €₂₀₁₉/kWh) in all identified ERS cases. This calculation is also dependent on the share of passenger cars switching to BEVs. There is currently a total of 4.9 million private vehicles in Sweden.

The analysis suggests that the savings for a km of ERS through reduced battery size range between 0.17-6.5 M€/ERS km. Different variables (i.e. ERS placement, BEV share of cars and charging rate) affect the estimated benefits from ERS differently. The economic net benefit is heavily dependent on the percentage of cars switching to BEV and ERS placement and less on the ERS charging rate. Sweden will benefit the most of ERS on 25% (traffic-wise) of both E and N with a charging rate of 2×0.18 kWh/km, which will cost between 1000-6500 M€. Depending on the participating BEV share, the gains in reducing battery capacity ranges between 3900 and 15800 M€, resulting in gross savings of 2900-9300 M€. In most considered cases, ERS infrastructure cost is less than its expected benefits.

Conclusion

The research utilizes real detailed driving patterns to investigate the benefits to BEVs from using ERS with technology that allows charging from below. For that, the research exploits GPS loggings of a representative group of cars found in Sweden. The research also proposes different ERS placements scenarios, percentage of cars switching to BEV and ERS charging rates. The research summarizes its results as following. First, the research shows the importance of considering both the lengths of segments covered with ERS and traffic of segments to assure successful coverage of ERS to daily driving. Second, considering battery capacities of 10, 15, 30 and 85 kWh, ERS could reduce the not-completed DD significantly. Small battery capacities of 10 kWh complete 96% of DD distances with 100% of both E and N as ERS. The required number of cars with 85 kWh battery capacities are also reduced significantly. Third, the study illustrates that with ERS the required battery capacity to meet all needed driving could drop up to 76% with an average battery capacity of only 12 kWh. Fourth, the considered ERS charging rates slightly impact the reduction in battery capacities and completed DD. On the other hand, the percentage of cars switching to BEV and ERS placement cases impact both the reduction in battery capacities and completed DD with ERS significantly. Finally, considering the gains in reducing battery capacity ranges between 3900 and 15800 M€, resulting in gross savings of 2900-9300 M€.

Acknowledgments

We acknowledge the support for this research by the Area of Advance Energy, Chalmers University of Technology, Sweden and Mistra Carbon Exit financed by Mistra, the Swedish Foundation for Strategic Environmental Research.

References

- [1] P. Ranch, "Elektriska vägar-elektrifiering av tunga vägtransporter," Grontmij, Stockholm, 2010.
- [2] M. Taljegard, "Large-scale implementation of electric road system, Electrification of Road Transportation - Implications for the Electricity," *Thesis for the Degree of Doctor of Philosophy*, 2019.
- [3] O. Olsson, "'Slide-in Electric Road System: Conductive project report" in phase 1," Viktoria Swedish ICT, 2013.
- [4] G. Asplund, "Elways," 2017. [Online]. Available: <http://elways.se/?lang=en/>. [Accessed 30 12 2019].
- [5] D. Connolly, "eRoads: A comparison between oil, battery electric vehicles, and electric roads for Danish road transport in terms of energy, emissions, and cost," Aalborg Universitet, Aalborg, Denmark, 2016.
- [6] E. A. S. K. F. & P. J. Boer, "Zero emissions trucks: An overview of state-of-the-art technologies and their potential.," German Aerospace Center, Stuttgart, Germany, 2013.
- [7] M. Wilson, "Feasibility study - powering electric vehicles on England's major roads," Transport Research Laboratory , 2015.
- [8] R. Schmich, Ralf, G. Wagner, T. Hörpel, P. & Martin and Winter, "Performance and cost of materials for lithium-based rechargeable automotive batteries," *Nature Energy*, vol. 3, p. 267–278, 2018.
- [9] S. Karlsson, "The Swedish Car Movement Data Project Final Report.," Chalmers University of Technology, Gothenburg, Sweden, 2013.
- [10] G. Berckmans, M. Maarten, S. Jelle, O. Noshin, V. Lieselot and i. V. M. Joer, "Cost Projection of State of the Art Lithium-Ion Batteries for Electric Vehicles Up to 2030," *energies*, vol. 10, no. 1314, 2017.

- [11] TRL, “Feasibility Study - Powering Electric Vehicles on England's Major Roads,” Transport Research Laboratory, 2015.
- [12] D. Chung, E. Elgqvist and S. Santhanagopalan, “Automotive Lithium-ion Cell Manufacturing: Regional Cost Structures and Supply Chain Considerations,” Clean Energy Manufacturing Analysis Center (CEMAC), Golden,, 2016.
- [13] B. Nykvist and M. Nilsson, “Rapidly falling costs of battery packs for electric vehicles,” *Nature Climate Change*, vol. 5, p. 329–332, 2015.
- [14] w. e. c. WEC, “Energy Storage Monitor Latest trends in energy storage | 2019,” Future energy leaders, 2019.
- [15] O. H. A. G. A. e. a. Schmidt, “he future cost of electrical energy storage based on experience rates,” *Nature Energy*, vol. 2, 2017.
- [16] V. V. P. B. J. A. V. F. V. K. a. B. H. Mongird K, “Energy Storage Technology and Cost Characterization Report,” prepared for the U.S. Department of Energy’s Water Power Technologies Office by Pacific Northwest National Laboratory, Richland, Washington, 2019.