

# Starting with Erlang

## Sequential Programming in Erlang (Overview)

Walter Cazzola

Dipartimento di Informatica  
Università degli Studi di Milano  
e-mail: cazzola@di.unimi.it  
twitter: @w\_cazzola



# Erlang Overview

Erlang is concurrency oriented, i.e., the process is the basic of every computation.

Erlang adopts the actor's model for concurrency with

- asynchronous message exchange;
- non shared memory

Erlang is a dynamically typed functional language.

Erlang supports distribution, fault tolerance and hot-swapping (dynamic SW updating).



# Erlang

## A Few of History

|98| — the Ericsson CS Lab has been founded.

|98|-|986

- a lot of work to decide which paradigm would be better to use in the telecommunication domain
- conclusions: doesn't exist the perfect paradigm but several characteristics should be mixed.

1987 Erlang is born

- the name is after the Danish mathematician Agner Krarup Erlang but could also mean **Ericsson** language.

|987-|99|

- the JAM ("Joe's Abstract Machine") virtual machine (inspired by the Prolog WAM) has been implemented (in C);
- in 1998 it has been replaced by BEAM ("Bogdan/Björn's Erlang Abstract Machine").

1996 — Open Telecom Platform (OTP) has been released.

998

- Ericsson stops to develop Erlang but not to use it
- Erlang becomes open source
  - since 2006 the BEAM supports multi-core processors.

30+ Years



## My First Erlang Program

### Again a Factorial!!!

```
-module(fact).  
-export([fact/1]).  
  
fact(0) -> 1;  
fact(N) -> N*fact(N-1).
```

The program must be run through the BEAM shell

```
[12:56]cazzola@mangog:~/lp/erlang-erl [async-threads:1] [jit]
Erlang/OTP 24 [erts-12.3.2.6] [source] [64-bit] [smp:16:16]
Eschell V12.3.2.6 (abort with ^G)
1> c(fact).
{ok,fact}
2> fact:fact(7).
5040
3> fact:fact(100).
9332621544394415268169923885626670049071596826438162146859296389521759999322991560894146
```

Alternatively it could be run as a script via escript or through native compilation via HiPE.





## Sequential Erlang Overview

### Numbers and Atoms

Starting with Erlang

Walter Cazzola

Erlang

a few of history characteristics

Sequential Erlang

BEAM

datatypes

pattern matching

functions

swords

comprehensions

References

```
1> 10.
10
2> 16#FF.
255
3> $A.
65
4> -12.35e-2.
-0.1235
```

- b#val is used to store the number "val" in base "b";
- \$char is used for ascii values.

```
1> cazzola@di.unimi.it.
'cazzola@di.unimi.it'
2> 'Walter Cazzola'.
'Walter Cazzola'
3> 'Walter'M
'WalterM'
3> Cazzola'.
'Walter\nCazzola'
```

- atoms start with lowercase letter but can contain any character
- if quoted they can start by uppercase letters.



Slide 5 of 12



## Sequential Erlang Overview

### Tuples and Lists

Starting with Erlang

Walter Cazzola

Erlang

a few of history characteristics

Sequential Erlang

BEAM

datatypes

pattern matching

functions

swords

comprehensions

References

```
1> {123, "walter", cazzola}.
{123, "walter", cazzola}
2> {}.
{}
3> {abc, {'Walter', 'Cazzola'}, 3.14}.
{abc, {'Walter', 'Cazzola'}, 3.14}
4> {{1, 2}, 3}=={1, {2, 3}}.
false
```

- used to store a fixed number of items;
- tuples of any size, type and complexity are allowed.

```
1> [].
[]
2> [1][].
[1]
3> [1][2]].
[1, 2]
4> [{1,2}, ok, []].
[{1, 2}, ok, []]
5> length([1, 2], ok, []).
3
6> [{1, 2}, ok, []] == [{1, 2}, ok, []].
true
7> A=[$w, $a, $l, $t, $e, $r], B[$c, $a, $z, $z, $o, $l, $a].
"Cazzola"
8> A++ "++B.
"Walter Cazzola"
9> A--B.
"Wter"
```

- used to store a variable number of items;
- lists are dynamically sized.



Slide 6 of 12



## Sequential Erlang Overview

### Assignments & Pattern Matching

Starting with Erlang

Walter Cazzola

Erlang

a few of history characteristics

Sequential Erlang

BEAM

datatypes

pattern matching

functions

swords

comprehensions

References

```
1> A = 1.
1
2> A = 2.
** exception error: no match of right hand side value 2
```

- are just name bindings to values and **cannot** be modified;
- start with an uppercase letter and \_ is an anonymous variable.
- the bindings are created via pattern matching.

```
3> [B|L]=[a,b,c].
[a, b, c]
4> {A,B,L}.
{1, a, [b, c]}
5> {X, X} = {B, B}.
{a, a}
6> {Y, Y} = {X, b}.
** exception error: no match of right hand side value {a, b}
7> 1=A.
1
8> 1=Z.
* 1: variable 'Z' is unbound
9> {A1, _, [B1|_], {B1}} = {abc, 23, [22,x], {22}}.
{abc, 23, [22, x], {22}}
10> A1.
abc
11> B1.
22
```

Slide 7 of 12



## Sequential Erlang Overview

### Functions & Modules

Starting with Erlang

Walter Cazzola

Erlang

a few of history characteristics

Sequential Erlang

BEAM

datatypes

pattern matching

functions

swords

comprehensions

References

```
name(pattern1, pattern2, ..., patternn) [when guard] -> body ;
name(pattern1, pattern2, ..., patternn) [when guard2] -> body2 ;
...
name(patternk1, patternk2, ..., patternkn) [when guardk] -> bodyk .
```

- clauses are scanned sequentially until a match is found;
- when a match is found all the variables in the head become bound;

```
-module(ex_module).
-export([double/1]).
```

```
double(X) -> times(X, 2).
times(X, N) -> X * N.
```

- double can be called from outside the module, times is local to the module;
- double/1 means the function double with one argument (note that double/1 and double/2 are two different functions).



Slide 8 of 12



## Sequential Erlang Overview

### Guard Sequences

Starting with Erlang  
Walter Cazzola

Erlang  
a few of history  
characteristics  
Sequential Erlang  
BEAM  
datatypes  
pattern matching  
functions  
guards  
comprehensions  
References

Each clause in function definition can be guarded by a **guard sequence**.


- a guard is a sequence  $G_1, G_2, \dots, G_n$  of **guard expressions**;
- a guard expression is a subset of Erlang expressions to guarantee to be free of side-effects;
- a guard sequence is true when all the guard expressions evaluate to true

Valid guard expression are:

- the atom true and other constants;
- calls to some built-in functions (BIFs);
- arithmetic and boolean expressions; and
- short-circuit expressions (**andalso**/**orelse**).

Permitted BIFs are:

is_atom/1	is_binary/1	is_bitstring/1	is_float/1	is_function/2
is_function/1	is_integer/1	is_list/1	is_number/1	is_pid/1
is_port/1	is_record/2	is_record/3	is_reference/1	is_tuple/1
abs/1	bit_size/1	byte_size/1	element/2	float/1
hd/1	length/1	node/0	round/1	tuple_size/1
self/1	size/1	tl/1	trunc/1	



Slide 9 of 12



## Sequential Erlang Overview

### Map, Filter ≠ Reduce

Starting with Erlang  
Walter Cazzola

Erlang  
a few of history  
characteristics  
Sequential Erlang  
BEAM  
datatypes  
pattern matching  
functions  
guards  
comprehensions  
References

```
-module(mfr).
-export([map/2,filter/2,reduce/2]).

map(_, []) -> [];
map(F, [H|TL]) -> [F(H)|map(F,TL)].

filter(_, []) -> [];
filter(P, [H|TL]) -> filter(P(H), P, H, TL).
filter(true, P, H, L) -> [H|filter(P, L)];
filter(false, P, _, L) -> filter(P, L).

reduce(F, [H|TL]) -> reduce(F, H, TL).
reduce(_, Q, []) -> Q;
reduce(F, Q, [H|TL]) -> reduce(F, F(Q,H), TL).
```

```
1> mfr:map(fun(X) -> X*X end, [1,2,3,4,5,6,7]).
[1, 4, 9, 16, 25, 36, 49]
2> mfr:filter(fun(X) -> (X rem 2)==0 end, [1,2,3,4,5,6,7]).
[2, 4, 6]
3> mfr:reduce(fun(X,Y) -> X+Y end, [1,2,3,4,5,6,7]).
28
```

They are available in the module lists.



Slide 10 of 12



## Sequential Erlang Overview

### List Comprehensions

Starting with Erlang  
Walter Cazzola

Erlang  
a few of history  
characteristics  
Sequential Erlang  
BEAM  
datatypes  
pattern matching  
functions  
guards  
comprehensions  
References

$[X | \text{Qualifier}_1, \dots, \text{Qualifier}_n]$

$X$  is an expression, each qualifier is a generator or a filter

- generators are in the form **Pattern** <- **ListExpr** where **ListExpr** evaluates to a list;
- filters are either predicates or boolean expressions.

```
-module(sort).
-export([qsort/2]).

qsort(_, []) -> [];
qsort(P, [Pivot|TL]) ->
  qsort(P, [X||X<-TL, P(X,Pivot)]) ++ [Pivot] ++ qsort(P, [X||X<-TL, not P(X,Pivot)]).
```

```
-module(prime).
-export([primes/1]).

primes(N) when N>1 -> [X|| X<- lists:seq(2,N),
  (length([Y || Y<- lists:seq(2, trunc(math:sqrt(X))), (X rem Y) == 0]) == 0)];
primes(_) -> [].
```

```
1> sort:qsort(fun(X, Y) -> X<Y end, [13, 1, -1, 8, 9, 0, 3.14]).
[-1, 0, 1, 3.14, 8, 9, 13]
2> sort:qsort(fun(X, Y) -> X>Y end, [13, 1, -1, 8, 9, 0, 3.14]).
[13, 9, 8, 3.14, 1, 0, -1]
3> prime:primes(100).
[2,3,5,7,11,13,17,19,23,29,31,37,41,43,47,53,59,61,67,71,73,79,83,89,97]
```

Slide 11 of 12



## References

Starting with Erlang  
Walter Cazzola

Erlang  
a few of history  
characteristics  
Sequential Erlang  
BEAM  
datatypes  
pattern matching  
functions  
guards  
comprehensions  
References

- Gul Agha.  
*Actors: A Model of Concurrent Computation in Distributed Systems*.  
MIT Press, Cambridge, 1986.
- Joe Armstrong.  
*Programming Erlang: Software for a Concurrent World*.  
The Pragmatic Bookshelf, fifth edition, 2007.
- Francesco Cesarini and Simon J. Thompson.  
*Erlang Programming: A Concurrent Approach to Software Development*.  
O'Reilly, June 2009.



Slide 12 of 12