



## Domain Specific Languages Part 2: Parser Combinators

Walter Cazzola

Dipartimento di Informatica  
Università degli Studi di Milano  
e-mail: cazzola@di.unimi.it  
twitter: @w\_cazzola



## Domain Specific Languages (DSLs) Parser Combinators: Introduction

A **parser combinator** is

- a high-order function accepting several parsers as input and returning a new parser;
- a parser is a function accepting strings as input and returning some structure, e.g., a parse tree


Parser combinators enable a recursive descent parsing strategy.

The basic idea

- parser combinators are building blocks for parsers that can be combined together
- a combinator framework eases to combine parsers to deal with sequential and alternative cases, repetition, optional terms, etc ...

Case study: the paycheck program, e.g.,

```
paycheck for employee "Buck Trends" is salary for 2 weeks minus deductions for {
  federal income tax      is 25. percent of gross,
  state income tax        is  5. percent of gross,
  insurance premiums      are 500. in gross currency,
  retirement fund contributions are 10. percent of gross
}
```



## Domain Specific Languages (DSLs) Case Study: the DSL Grammar.

```
paycheck      = empl • gross • deduct
empl          = paycheck • for • employee • employeeName
gross         = is • salary • for • duration
deduct        = minus • deductions • for • { • deductItems • }
employeeName  = "• name • , • name • "
name          = ...
duration      = decimalNumber • weeksDays
weeksDays     = week | weeks | day | days
deductItems   = deductItem { • , • deductItem • } | ε
deductItem    = deductKind • deductAmount
deductKind    = tax | insurance | retirement
tax           = fedState • income • tax
fedState      = federal | state
insurance     = insurance • premiums
retirement   = retirement • fund • contributions
deductAmount  = percentage | amount
percentage    = toBe • doubleNumber • percent • of • gross
amount        = toBe • doubleNumber • in • gross • currency
toBe          = is | are
decimalNumber = ...
doubleNumber  = ...
```

nonterminals   terminals   alternatives   sequences   repetitions




## Domain Specific Languages (DSLs) Payroll DSL: A First Parser Combinator Version.

```
package payroll.pcdsl

import scala.util.parsing.combinator._
import payroll._
import payroll.Type2Money._

class PayrollParserCombinatorsV1 extends JavaTokenParsers {
  def paycheck = empl ~ gross ~ deduct
  def empl = "paycheck" -> "for" -> "employee" -> employeeName
  def gross = "is" -> "salary" -> "for" -> duration
  def deduct = "minus" -> "deductions" -> "for" -> "{" ~ deductItems ~> "}"
  def employeeName = stringLiteral // stringLiteral from JavaTokenParsers
  def duration = decimalNumber ~ weeksDays // decimalNumber from JavaTokenParsers
  def weeksDays = "weeks" | "week" | "days" | "day"
  def deductItems = repsep(deductItem, ",")
  def deductItem = deductKind -> deductAmount
  def deductKind = tax | insurance | retirement
  def tax = fedState ~> "income" ~> "tax"
  def fedState = "federal" | "state"
  def insurance = "insurance" -> "premiums"
  def retirement = "retirement" -> "fund" -> "contributions"
  def deductAmount = percentage | amount
  def percentage = toBe -> doubleNumber ~> "percent" ~> "of" ~> "gross"
  def amount = toBe -> doubleNumber ~> "in" ~> "gross" ~> "currency"
  def toBe = "is" | "are"
  def doubleNumber = floatingPointNumber // floatingPointNumber from JavaTokenParsers
}
```





## Domain Specific Languages (DSLs)

### Some Combinators

Domain Specific Languages

Walter Cazzola

DSLs

parser  
combinator  
DSL grammar  
a simple parser  
parsers  
"seventies"

References

#### Sequential Composition

- ~ is used when the results produced by the productions on the left and right of the ~ should be retained for further processing

```
def paycheck = empl ~ gross ~ deduct
```

- > is used when the result for the productions to the left is no longer needed

```
def empl = "paycheck" -> "for" -> "employee" -> employeeName
```

- <- is used when the result for the productions to the right is no longer needed

```
def tax = fedState <- "income" <- "tax"
```

#### Alternative Composition

- | expresses when two parsers are in alternative

```
def weekdays = "weeks" | "week" | "days" | "day"
```

#### Repetitive Composition

- rep/repsep match zero or more repetitions

```
def deduct = "minus" -> "deductions" -> "for" -> "{" -> repsep(deductItem, ",") <- "}"
```

There is an **opt** method for optional terms not used.



Slide 5 of 14



## Domain Specific Languages (DSLs)

### Parsing

Domain Specific Languages

Walter Cazzola

DSLs


parser  
combinator  
DSL grammar  
a simple parser  
parsers  
"seventies"

References

#### To use the defined parser

```
val p = new PayrollParserCombinatorsV1
p.parseAll(p.paycheck, input) match {
  case p.Success(r, _) => ...
  case x => ...
}
```

- parseAll is defined in a parent class it receives a parser (an invocation to paycheck in our case) and the input string to parse;
- if the parsing process is successful the result is an instance of p.**Success**[+T] a case class declared in the **Parsers** trait;
- the p prefix indicates that p.**Success** is a path-dependent type and permits to distinguish the result from two different parsers;
- the **Success** instance has two fields, the first is the result of the parse (of type **T**), the second is the remaining input to parse (normally empty);
- if the parse fails, the return instance is either a p.**Failure** or p.**Error**; both are derived from p.**NoSuccess** and contains fields for an error message and the unconsumed input at the point of failure.



Slide 6 of 14



## Domain Specific Languages (DSLs)

### Parsing (Cont'd)

Domain Specific Languages

Walter Cazzola

DSLs

parser  
combinator  
DSL grammar  
a simple parser  
parsers  
"seventies"

References

#### Do you know which types have the parsers and the result?

```
scala> import scala.util.parsing.combinator._
scala> import payroll.pcdsl._
scala> val p = new PayrollParserCombinatorsV1
scala> p.empl
res0: p.Parser[String] = Parser (->)
scala> p.weeksDays
res2: p.Parser[String] = Parser (|)
scala> p.paycheck
res3: p.Parser[p.~[p.~[String,p.~[String,String]],List[String]]] = Parser (~)
scala> p.parseAll(p.weeksDays, "weeks")
res4: p.ParseResult[String] = [1.6] parsed: weeks
scala> val input = """"paycheck for employee "Buck Trends"
  | is salary for 2 weeks minus deductions for {}""""
input: java.lang.String =
paycheck for employee "Buck Trends" is salary for 2 weeks minus deductions for {}
scala> p.parseAll(p.paycheck, input)
res5: p.ParseResult[p.~[p.~[String,p.~[String,String]],List[String]]] =
[2.46] parsed: (("Buck Trends"~(2-weeks))-List())
scala> val input = """"paycheck for employee "Buck Trends"
  | is salary for 2 weeks minus deductions for {}""""
input: java.lang.String =
paycheck for employee "Buck Trends" is salary for 2 weeks minus deductions for {}
scala> p.parseAll(p.paycheck, input)
res6: p.ParseResult[p.~[p.~[String,p.~[String,String]],List[String]]] =
[1.14] failure: 'employee' expected but ' ' found
paycheck for employee "Buck Trends"
^
```



Slide 7 of 14



## Domain Specific Languages (DSLs)

### Giving a Semantics to the DSL

Domain Specific Languages

Walter Cazzola

DSLs

parser  
combinator  
DSL grammar  
a simple parser  
parsers  
"seventies"

References

#### As we parse the DSL

- we had to look up the employee by name
- fetch his gross salary for the specified period and
- calculate the deductions

#### Once the parser finishes

- we need to return a pair with the Employee instance and the completed Paycheck.



Slide 8 of 14



## Domain Specific Languages (DSLs)

### Giving a Semantics to the DSL

Domain  
Specific  
Languages

Walter Cazzola

DSLs

parser  
combinator  
DSL grammar  
a simple parser  
parsina  
"semantics"

References

```
package payroll.pcdsl

import scala.util.parsing.combinator._
import payroll._
import payroll.Type2Money._

class UnknownEmployee(name: Name) extends RuntimeException(name.toString)

class PayrollParserCombinators(val employees: Map[Name, Employee]) extends JavaTokenParsers {
  var currentEmployee: Employee = null
  var grossAmount: Money = Money(0)

  /** @return Parser[(Employee, Paycheck)] */
  def paycheck = empl ~ gross ~ deduct ^^ {case e ~ g ~ d => (e, Paycheck(g, g-d, d))}

  /** @return Parser[Employee] */
  def empl = "paycheck" -> "for" -> "employee" -> employeeName ^^ { name =>
    val names = name.substring(1, name.length-1).split(" ")
    val n = Name(names(0), names(1));
    if (! employees.contains(n)) throw new UnknownEmployee(n)
    currentEmployee = employees(n); currentEmployee
  }

  /** @return Parser[Money] */
  def gross = "is" -> "salary" -> "for" -> duration ^^ {
    dur => grossAmount = salaryForDays(dur); grossAmount
  }

  def deduct = "minus" -> "deductions" -> "for" -> "{" -> deductItems <- "}"
```



Slide 9 of 14



## Domain Specific Languages (DSLs)

### Giving a Semantics to the DSL (Cont'd)

Domain  
Specific  
Languages

Walter Cazzola

DSLs

parser  
combinator  
DSL grammar  
a simple parser  
parsina  
"semantics"

References

```
/** "stringLiteral" provided by JavaTokenParsers */
* @return Parser[String] */
def employeeName = stringLiteral

/** "decimalNumber" provided by JavaTokenParsers */
* @return Parser[Int] */
def duration = decimalNumber ~ weeksDays ^^ {
  case n ~ factor => n.toInt * factor
}


def weeksDays = weeks | days
def weeks = "weeks?".r ^^ { _ => 5 }
def days = "days?".r ^^ { _ => 1 }

/** @return Parser[Money] */
def deductItems = repsep(deductItem, ",") ^^ {items => items.foldLeft(Money(0))(_ + _)}

def deductItem = deductKind -> deductAmount
def deductKind = tax | insurance | retirement
def tax = fedState <- "income" <- "tax"
def fedState = "federal" | "state"
def insurance = "insurance" -> "premiums"
def retirement = "retirement" -> "fund" -> "contributions"
def deductAmount = percentage | amount

def percentage = toBe -> doubleNumber <- "percent" <- "of" <- "gross" ^^ {
  percentage => grossAmount * (percentage / 100.)
}

def amount = toBe -> doubleNumber <- "in" <- "gross" <- "currency" ^^ { Money(_) }
def toBe = "is" | "are"
def doubleNumber = floatingPointNumber ^^ { _.toDouble }
def salaryForDays(days: Int) = (currentEmployee.annualGrossSalary / 260.0) * days
}
```



Slide 10 of 14



## Domain Specific Languages (DSLs)

### Giving a Semantics to the DSL (Cont'd)

Domain  
Specific  
Languages

Walter Cazzola

DSLs

parser  
combinator  
DSL grammar  
a simple parser  
parsina  
"semantics"

References

#### Notes on the DSL

- The parser uses a map (**Name**) of known employees for simplicity;
- currentEmployee and grossAmount respectively store the employee the parser is processing and they gross salary for the pay periods;
- this parser version is an evolution of the previous one which take in consideration what should be the final result, e.g.,

```
def paycheck = empl ~ gross ~ deduct ^^ {case e~g~d => (e, Paycheck(g, g-d, d))}
```

will return a **Pair** with the **Employee** and the computed **Paycheck**

- ^^ combinator, p1^^f1 applies f1 to the result of p1 when it succeeds

```
def empl = "paycheck" -> "for" -> "employee" -> employeeName ^^ {
  name =>
    val names = name.substring(1, name.length-1).split(" ")
    val n = Name(names(0), names(1));
    if (! employees.contains(n)) throw new UnknownEmployee(n)
    currentEmployee = employees(n); currentEmployee
}
```

- weeks and days ignore the parsed string; they just return a multiplication factor used to determine the total days in the duration production rule



Slide 11 of 14



## Domain Specific Languages (DSLs)

### Giving a Semantics to the DSL (Cont'd)

Domain  
Specific  
Languages

Walter Cazzola

DSLs

parser  
combinator  
DSL grammar  
a simple parser  
parsina  
"semantics"

References

```
import payroll._
import payroll.Type2Money._
import payroll.pcdsl._

object PayRollBuilder {
  def main(args: Array[String]) = {
    val buck = Employee(Name("Buck", "Trends"), Money(80000))
    val jane = Employee(Name("Jane", "Doe"), Money(90000))
    val employees = Map(buck.name -> buck, jane.name -> jane)
    val p = new PayrollParserCombinators(employees)

    args.foreach { filename =>
      val src = scala.io.Source.fromFile(filename)
      val lines = src.mkString
      p.parseAll(p.paycheck, lines) match {
        case p.Success(Pair(employee, paycheck), _) =>
          print(format("%s %s: %s\n", employee.name.first, employee.name.last, paycheck))
          case x => print(x.toString)
      }
      src.close()
    }
  }
}
```



Slide 12 of 14



## Domain Specific Languages (DSLs)

### Giving a Semantics to the DSL (Cont'd)

Domain  
Specific  
Languages

Walter Cazzola

DSLs

parser

combinator

DSL grammar

a simple parser

parsers

"semantics"

References

Considering the following

- 2 correct programs in the new DSL

```
paycheck for employee "Jane Doe"
is salary for 2 weeks minus deductions for {}
```

```
paycheck for employee "Buck Trends"
is salary for 2 weeks minus deductions for {
    federal income tax is 25. percent of gross,
    state income tax is 5. percent of gross,
    insurance premiums are 500. in gross currency,
    retirement fund contributions are 10. percent of gross
}
```

- and the wrong (inexistent employee) program

```
paycheck for employee "John Doe"
is salary for 2 weeks minus deductions for {}
```

They behave as follows

```
[16:29]cazzola@surtur:~/lp/scala/>scala PayRollBuilder test1.pr test2.pr test3.pr
Jane Doe: Paycheck($3461.54,$3461.54,$0.00)
Buck Trends: Paycheck($3076.92,$1346.15,$1730.77)
payroll.pcdsl.UnknownEmployee: Name(John,Doe)
at payroll.pcdsl.PayrollParserCombinators$$anonfun$empl$4.apply(payroll-pc.scala:24)
```

Slide 13 of 14



## References

Domain  
Specific  
Languages

Walter Cazzola

DSLs

parser

combinator

DSL grammar

a simple parser

parsers

"semantics"

References

- Martin Odersky and Matthias Zenger.

**Scalable Component Abstractions.**

In Richard P. Gabriel, editor, Proceedings of 19<sup>th</sup> ACM International Conference on Object-Oriented Programming Systems, Languages and Applications (OOPSLA'05), pages 41-57, San Diego, CA, USA, October 2005. ACM Press.

- Nathanael Schärli, Stéphane Ducasse, Oscar Nierstrasz, and Andrew P. Black.

**Traits: Composable Units of Behaviour.**

In Luca Cardelli, editor, Proceedings of the 17<sup>th</sup> European Conference on Object-Oriented Programming (ECOOP'03), Lecture Notes in Computer Science 2743, pages 248-274, Darmstadt, Germany, July 2003. Springer.

- Venkat Subramaniam.

**Programming Scala.**

The Pragmatic Bookshelf, June 2009.

- Dean Wampler and Alex Payne.

**Programming Scala.**

O'Reilly, September 2009.



Slide 14 of 14