

PT PJB SERVICES

PT KERTAS KRAFT ACEH

REHABILITASI PLTU UNIT #1 PT KERTAS KRAFT ACEH 2014



Doc. Ref	
Form No.	
Design Div.	LISTRIK
Rev. No.	0

INSPECTION SHEET

OIL TRANSFORMER P6 Description Asset No/Tag No Work Order No.

Date / Time

SPESIFIKASI PERALATAN

Spesifikasi Transformer

TOSHIBA SOZEN Manufactures

kVA Rating 1750 Impedance Voltage : 6.55 % Frequency : JEC-204-1978 50 Hz Standart : ONAN Phases : 3 Type of Cooling Rated Voltage HV : 6000 V Serial No. : 86059778

Rated Voltage LV : 231/400 V Type of Insulating liquid

Rated Current HV

: 168 A : 2530 A Mineral Oil JIS C 2320 CLASS I No.2 Rated Current LV 2530 A

Manufacured in : 1987 Plate Number : R - 701807/P-02

TEST DIELECTRIC STRENGTH

A. BOTTOM OIL SIDE

No	Hasil	Keterangan
1	40	
2	37	
3	52	
4	43	
5	37	
Rata-rata	42.2 kV	

Megger Transformer	VOLTAGE TEST (VDC)	HV (GΩ)
U - Ground	5000	24.9
V - Ground	5000	24.9
W - Ground	5000	24.9

Megger Transformer	VOLTAGE TEST (VDC)	LV (GΩ)
U - Ground	500	10.81
V - Ground	500	10.81
W - Ground	500	10.81

Keterangan

- Alat ukur / tes : Megger BM 25

Keterangan : Alat ukur / tes Liquid Dielectric Test Set Model LD60

> 2.5 mm Jarak electrode

ASTM STANDART D 877 Standart

> Acceptable >40 kVQuestionable 25 - 29 kV < 25 kV Un-Acceptable

шк	Diukur Oleh	Diperiksa oleh		Disetujui Oleh
SIGNATURE DIR SEDVICES			SIGNATURE PT. KKA	