

Computational Optimal Transportation

Michael Rawson

November 29, 2021

Sinkhorn Algorithm

Regularized optimal plan $P = \min_{P'} \sum_{i,j} C_{i,j} P'_{i,j} - \epsilon H(P)$, where H is entropy.

Sinkhorn Algorithm

Regularized optimal plan $P = \min_{P'} \sum_{i,j} C_{i,j} P'_{i,j} - \epsilon H(P)$, where H is entropy.

Algorithm 2: Sinkhorn Algorithm

Input:

$s, t \in \mathbb{P}(\{1, \dots, n\})$ are distributions

$C \in \mathbb{R}^{n \times n}$ is cost matrix

$\epsilon : 0 < \epsilon \ll 1$

$M \in \mathcal{N}$ is max iterations

Sinkhorn Algorithm

Regularized optimal plan $P = \min_{P'} \sum_{i,j} C_{i,j} P'_{i,j} - \epsilon H(P)$, where H is entropy.

Algorithm 3: Sinkhorn Algorithm

Input:

$s, t \in \mathbb{P}(\{1, \dots, n\})$ are distributions

$C \in \mathbb{R}^{n \times n}$ is cost matrix

$\epsilon : 0 < \epsilon \ll 1$

$M \in \mathcal{N}$ is max iterations

Output:

$d \in \mathbb{R}$

Sinkhorn Algorithm

Regularized optimal plan $P = \min_{P'} \sum_{i,j} C_{i,j} P'_{i,j} - \epsilon H(P)$, where H is entropy.

Algorithm 4: Sinkhorn Algorithm

Input:

$s, t \in \mathbb{P}(\{1, \dots, n\})$ are distributions

$C \in \mathbb{R}^{n \times n}$ is cost matrix

$\epsilon : 0 < \epsilon \ll 1$

$M \in \mathcal{N}$ is max iterations

Output:

$d \in \mathbb{R}$

Begin:

$K = \exp(-C/\epsilon)$; $u = v = \text{ones}(n, 1)$

$T = \text{diag}(u) \cdot K \cdot \text{diag}(v)$

for $i = 1, \dots, M$ **do**

$u = s / (Kv)$
 $v = t / (K^T u)$
 $T = \text{diag}(u) \cdot K \cdot \text{diag}(v)$

end

$d = \|C \cdot T\|_{fro}$


Sinkhorn Algorithm

Sinkhorn Algorithm

Sinkhorn Convergence over Iterations:


Sinkhorn Algorithm

Sinkhorn Convergence over Iterations:



Sinkhorn Algorithm


Sinkhorn Convergence over Iterations:



$$x, y \in \mathbb{P}(\{1, \dots, 5\}); x, y \sim \chi_1^2 \text{ normalized, } C(i, j) = |i - j|$$

Sinkhorn Algorithm

Sinkhorn Convergence over Iterations:




$$x, y \in \mathbb{P}(\{1, \dots, 5\}); \quad x, y \sim \chi_1^2 \text{ normalized}, \quad C(i, j) = |i - j|$$
$$\|x - y\|_1 = 0.8270, \quad \|x - y\|_2 = 0.4964, \quad \|x - y\|_\infty = 0.4135$$

Sinkhorn Algorithm

Sinkhorn Convergence over Dimensions:


Sinkhorn Algorithm

Sinkhorn Convergence over Dimensions:



Sinkhorn Algorithm

Sinkhorn Convergence over Dimensions:



$x, y \in \mathbb{P}(\{1, \dots, n\}); x, y \sim \chi_1^2$ normalized, $\epsilon = 0.01$, $C(i, j) = |i - j|$

Sinkhorn Application

Sinkhorn Application

Removing Noise from Signals

Sinkhorn Application

Removing Noise from Signals

Signals have low entropy: $\mu \in \mathbb{R}^n$ is sparse in a localized basis

Sinkhorn Application

Removing Noise from Signals

Signals have low entropy: $\mu \in \mathbb{R}^n$ is sparse in a localized basis

Noise is high entropy a.s. since independent with positive variance

Sinkhorn Application

Removing Noise from Signals

Signals have low entropy: $\mu \in \mathbb{R}^n$ is sparse in a localized basis

Noise is high entropy a.s. since independent with positive variance

Minimize entropy: $\nu = \arg \min_{\nu'} d_W(\mu + \eta, \nu') + \lambda H(\nu')$

Sinkhorn Application

Removing Noise from Signals

Signals have low entropy: $\mu \in \mathbb{R}^n$ is sparse in a localized basis

Noise is high entropy a.s. since independent with positive variance

Minimize entropy: $v = \arg \min_{v'} d_W(\mu + \eta, v') + \lambda H(v')$

$$H(v) = - \sum v_i \log(v_i)$$

Sinkhorn Application

Removing Noise from Signals

Signals have low entropy: $\mu \in \mathbb{R}^n$ is sparse in a localized basis

Noise is high entropy a.s. since independent with positive variance

Minimize entropy: $v = \arg \min_{v'} d_W(\mu + \eta, v') + \lambda H(v')$

$$H(v) = - \sum v_i \log(v_i)$$

$$\mu \in \mathbb{P}(\{1, \dots, 5\}), \mu = (0.65, 0, \dots, 0, 0.35), \|\mu\|_M = \text{rank}(H_0(\mu^{-1}([0.13, 1]))) = 2$$

Sinkhorn Application

Removing Noise from Signals


Signals have low entropy: $\mu \in \mathbb{R}^n$ is sparse in a localized basis

Noise is high entropy a.s. since independent with positive variance

Minimize entropy: $v = \arg \min_{v'} d_W(\mu + \eta, v') + \lambda H(v')$

$$H(v) = - \sum v_i \log(v_i)$$

$$\mu \in \mathbb{P}(\{1, \dots, 5\}), \mu = (0.65, 0, \dots, 0, 0.35), \|\mu\|_M = \text{rank}(H_0(\mu^{-1}([0.13, 1]))) = 2$$



Sinkhorn Application

Removing Noise from Signals



Signals have low entropy: $\mu \in \mathbb{R}^n$ is sparse in a localized basis

Noise is high entropy a.s. since independent with positive variance

Minimize entropy: $v = \arg \min_{v'} d_W(\mu + \eta, v') + \lambda H(v')$

$$H(v) = -\sum v_i \log(v_i)$$

$$\mu \in \mathbb{P}(\{1, \dots, 5\}), \mu = (0.65, 0, \dots, 0, 0.35), \|\mu\|_M = \text{rank}(H_0(\mu^{-1}([0.13, 1]))) = 2$$



Sinkhorn Application

Removing Noise from Signals



Signals have low entropy: $\mu \in \mathbb{R}^n$ is sparse in a localized basis

Noise is high entropy a.s. since independent with positive variance

Minimize entropy: $v = \arg \min_{v'} d_W(\mu + \eta, v') + \lambda H(v')$

$$H(v) = -\sum v_i \log(v_i)$$

$$\mu \in \mathbb{P}(\{1, \dots, 5\}), \mu = (0.65, 0, \dots, 0, 0.35), \|\mu\|_M = \text{rank}(H_0(\mu^{-1}([0.13, 1]))) = 2$$



$$\mu + \eta \in \mathbb{P}(\{1, \dots, 5\}), \epsilon = 0.01, C(i, j) = |i - j|$$

Optimal Transportation Reconstruction Theorem

Let $\tilde{w} = \text{sign}(w) \forall w \in \mathbb{R}^n$.

Optimal Transportation Reconstruction Theorem

Let $\tilde{w} = \text{sign}(w) \forall w \in \mathbb{R}^n$.

Theorem

Given a sparse signal $\mu \in \mathbb{P}(\{1, \dots, n\})$ ($\|\mu\|_0 < n$) with added noise $\eta : \mu + \eta \in \mathbb{P}(\{1, \dots, n\})$,

Optimal Transportation Reconstruction Theorem

Let $\tilde{w} = \text{sign}(w) \forall w \in \mathbb{R}^n$.

Theorem

Given a sparse signal $\mu \in \mathbb{P}(\{1, \dots, n\})$ ($\|\mu\|_0 < n$) with added noise $\eta : \mu + \eta \in \mathbb{P}(\{1, \dots, n\})$, the solution of $v = \arg \min_{v': d_W(\mu + \eta, v') \leq d_W(\mu, \mu + \eta)} H(v')$ will identify the structure of μ s.t. $\|\tilde{\mu} - \tilde{v}\|_0 = 0$ if η is such that

Optimal Transportation Reconstruction Theorem

Let $\tilde{w} = \text{sign}(w) \forall w \in \mathbb{R}^n$.

Theorem

Given a sparse signal $\mu \in \mathbb{P}(\{1, \dots, n\})$ ($\|\mu\|_0 < n$) with added noise $\eta : \mu + \eta \in \mathbb{P}(\{1, \dots, n\})$, the solution of $v = \arg \min_{v' : d_W(\mu + \eta, v') \leq d_W(\mu, \mu + \eta)} H(v')$ will identify the structure of μ s.t. $\|\tilde{\mu} - \tilde{v}\|_0 = 0$ if η is such that

- 1 for $v' \in \text{Ball}(\mu, 2d_W(\mu, \mu + \eta))$, $\|v'\|_0 \geq \|\mu\|_0$

Optimal Transportation Reconstruction Theorem

Let $\tilde{w} = \text{sign}(w) \forall w \in \mathbb{R}^n$.

Theorem

Given a sparse signal $\mu \in \mathbb{P}(\{1, \dots, n\})$ ($\|\mu\|_0 < n$) with added noise $\eta : \mu + \eta \in \mathbb{P}(\{1, \dots, n\})$, the solution of $v = \arg \min_{v' : d_W(\mu + \eta, v') \leq d_W(\mu, \mu + \eta)} H(v')$ will identify the structure of μ s.t. $\|\tilde{\mu} - \tilde{v}\|_0 = 0$ if η is such that

- 1 for $v' \in \text{Ball}(\mu, 2d_W(\mu, \mu + \eta))$, $\|v'\|_0 \geq \|\mu\|_0$
- 2 for solutions v_1, v_2 , both must agree in sparsity ($\|\tilde{v}_1 - \tilde{v}_2\|_0 = 0$)

Optimal Transportation Reconstruction Theorem

Let $\tilde{w} = \text{sign}(w) \forall w \in \mathbb{R}^n$.

Theorem

Given a sparse signal $\mu \in \mathbb{P}(\{1, \dots, n\})$ ($\|\mu\|_0 < n$) with added noise $\eta : \mu + \eta \in \mathbb{P}(\{1, \dots, n\})$, the solution of $v = \arg \min_{v': d_W(\mu + \eta, v') \leq d_W(\mu, \mu + \eta)} H(v')$ will identify the structure of μ s.t. $\|\tilde{\mu} - \tilde{v}\|_0 = 0$ if η is such that

- 1 for $v' \in \text{Ball}(\mu, 2d_W(\mu, \mu + \eta))$, $\|v'\|_0 \geq \|\mu\|_0$
- 2 for solutions v_1, v_2 , both must agree in sparsity ($\|\tilde{v}_1 - \tilde{v}_2\|_0 = 0$)

Remark: Noise is high entropy a.s.

Optimal Transportation Reconstruction Theorem

Let $\tilde{w} = \text{sign}(w) \forall w \in \mathbb{R}^n$.

Theorem

Given a sparse signal $\mu \in \mathbb{P}(\{1, \dots, n\})$ ($\|\mu\|_0 < n$) with added noise $\eta : \mu + \eta \in \mathbb{P}(\{1, \dots, n\})$, the solution of $v = \arg \min_{v': d_W(\mu + \eta, v') \leq d_W(\mu, \mu + \eta)} H(v')$ will identify the structure of μ s.t. $\|\tilde{\mu} - \tilde{v}\|_0 = 0$ if η is such that

- 1 for $v' \in \text{Ball}(\mu, 2d_W(\mu, \mu + \eta))$, $\|v'\|_0 \geq \|\mu\|_0$
- 2 for solutions v_1, v_2 , both must agree in sparsity ($\|\tilde{v}_1 - \tilde{v}_2\|_0 = 0$)

Remark: Noise is high entropy a.s. Minimize entropy of $\mu + \eta$.

Optimal Transportation Reconstruction Theorem

Let $\tilde{w} = \text{sign}(w) \forall w \in \mathbb{R}^n$.

Theorem

Given a sparse signal $\mu \in \mathbb{P}(\{1, \dots, n\})$ ($\|\mu\|_0 < n$) with added noise $\eta : \mu + \eta \in \mathbb{P}(\{1, \dots, n\})$, the solution of $v = \arg \min_{v': d_W(\mu + \eta, v') \leq d_W(\mu, \mu + \eta)} H(v')$ will identify the structure of μ s.t. $\|\tilde{\mu} - \tilde{v}\|_0 = 0$ if η is such that

- 1 for $v' \in \text{Ball}(\mu, 2d_W(\mu, \mu + \eta))$, $\|v'\|_0 \geq \|\mu\|_0$
- 2 for solutions v_1, v_2 , both must agree in sparsity ($\|\tilde{v}_1 - \tilde{v}_2\|_0 = 0$)

Remark: Noise is high entropy a.s. Minimize entropy of $\mu + \eta$. If noise is small enough, the noise can be removed, recovering sparse structure.

Proof:

Optimal Transportation Reconstruction Theorem

Let $\tilde{w} = \text{sign}(w) \forall w \in \mathbb{R}^n$.

Theorem

Given a sparse signal $\mu \in \mathbb{P}(\{1, \dots, n\})$ ($\|\mu\|_0 < n$) with added noise $\eta : \mu + \eta \in \mathbb{P}(\{1, \dots, n\})$, the solution of $v = \arg \min_{v': d_W(\mu + \eta, v') \leq d_W(\mu, \mu + \eta)} H(v')$ will identify the structure of μ s.t. $\|\tilde{\mu} - \tilde{v}\|_0 = 0$ if η is such that

- 1 for $v' \in \text{Ball}(\mu, 2d_W(\mu, \mu + \eta))$, $\|v'\|_0 \geq \|\mu\|_0$
- 2 for solutions v_1, v_2 , both must agree in sparsity ($\|\tilde{v}_1 - \tilde{v}_2\|_0 = 0$)

Remark: Noise is high entropy a.s. Minimize entropy of $\mu + \eta$. If noise is small enough, the noise can be removed, recovering sparse structure.

Proof: Apply triangle inequality to show feasible set does not have sparsity that μ does not have.

Optimal Transportation Reconstruction Theorem

Let $\tilde{w} = \text{sign}(w) \forall w \in \mathbb{R}^n$.

Theorem

Given a sparse signal $\mu \in \mathbb{P}(\{1, \dots, n\})$ ($\|\mu\|_0 < n$) with added noise $\eta : \mu + \eta \in \mathbb{P}(\{1, \dots, n\})$, the solution of $v = \arg \min_{v' : d_W(\mu + \eta, v') \leq d_W(\mu, \mu + \eta)} H(v')$ will identify the structure of μ s.t. $\|\tilde{\mu} - \tilde{v}\|_0 = 0$ if η is such that

- 1 for $v' \in \text{Ball}(\mu, 2d_W(\mu, \mu + \eta))$, $\|v'\|_0 \geq \|\mu\|_0$
- 2 for solutions v_1, v_2 , both must agree in sparsity ($\|\tilde{v}_1 - \tilde{v}_2\|_0 = 0$)

Remark: Noise is high entropy a.s. Minimize entropy of $\mu + \eta$. If noise is small enough, the noise can be removed, recovering sparse structure.

Proof: Apply triangle inequality to show feasible set does not have sparsity that μ does not have. We have μ is in the feasible set.

Optimal Transportation Reconstruction Theorem

Let $\tilde{w} = \text{sign}(w) \forall w \in \mathbb{R}^n$.

Theorem

Given a sparse signal $\mu \in \mathbb{P}(\{1, \dots, n\})$ ($\|\mu\|_0 < n$) with added noise $\eta : \mu + \eta \in \mathbb{P}(\{1, \dots, n\})$, the solution of $v = \arg \min_{v' : d_W(\mu + \eta, v') \leq d_W(\mu, \mu + \eta)} H(v')$ will identify the structure of μ s.t. $\|\tilde{\mu} - \tilde{v}\|_0 = 0$ if η is such that

- 1 for $v' \in \text{Ball}(\mu, 2d_W(\mu, \mu + \eta))$, $\|v'\|_0 \geq \|\mu\|_0$
- 2 for solutions v_1, v_2 , both must agree in sparsity ($\|\tilde{v}_1 - \tilde{v}_2\|_0 = 0$)

Remark: Noise is high entropy a.s. Minimize entropy of $\mu + \eta$. If noise is small enough, the noise can be removed, recovering sparse structure.

Proof: Apply triangle inequality to show feasible set does not have sparsity that μ does not have. We have μ is in the feasible set. Minimizing H maximizes sparsity. So v agrees with the sparsity of μ .

Optimal Transportation Reconstruction Failure

Optimal Transportation Reconstruction Failure

Failing Removing Noise from Signals

Optimal Transportation Reconstruction Failure

Failing Removing Noise from Signals

Signals have low entropy: $\mu \in \mathbb{R}^n$ is sparse in a localized basis

Optimal Transportation Reconstruction Failure

Failing Removing Noise from Signals

Signals have low entropy: $\mu \in \mathbb{R}^n$ is sparse in a localized basis

Noise is high entropy a.s.

Optimal Transportation Reconstruction Failure

Failing Removing Noise from Signals

Signals have low entropy: $\mu \in \mathbb{R}^n$ is sparse in a localized basis

Noise is high entropy a.s.

Minimize entropy: $\nu = \arg \min_{\nu'} d_W(\mu + \eta, \nu') + \lambda H(\nu')$

Optimal Transportation Reconstruction Failure

Failing Removing Noise from Signals

Signals have low entropy: $\mu \in \mathbb{R}^n$ is sparse in a localized basis

Noise is high entropy a.s.

Minimize entropy: $\nu = \arg \min_{\nu'} d_W(\mu + \eta, \nu') + \lambda H(\nu')$

$\mu \in \mathbb{P}(\{1, \dots, 5\})$, $\mu = (0.65, 0, \dots, 0, 0.35)$, $\|\mu\|_M = \text{rank}(H_0(\mu^{-1}([0.13, 1]))) = 2$

Optimal Transportation Reconstruction Failure

Failing Removing Noise from Signals

Signals have low entropy: $\mu \in \mathbb{R}^n$ is sparse in a localized basis

Noise is high entropy a.s.

Minimize entropy: $\nu = \arg \min_{\nu'} d_W(\mu + \eta, \nu') + \lambda H(\nu')$

$\mu \in \mathbb{P}(\{1, \dots, 5\}), \mu = (0.65, 0, \dots, 0, 0.35), \|\mu\|_M = \text{rank}(H_0(\mu^{-1}([0.13, 1]))) = 2$

$\mu + \eta \in \mathbb{P}(\{1, \dots, 5\}), \epsilon = 0.01, C(i, j) = |i - j|$

Optimal Transportation Reconstruction Failure

Failing Removing Noise from Signals


Signals have low entropy: $\mu \in \mathbb{R}^n$ is sparse in a localized basis

Noise is high entropy a.s.

Minimize entropy: $v = \arg \min_{v'} d_W(\mu + \eta, v') + \lambda H(v')$

$\mu \in \mathbb{P}(\{1, \dots, 5\})$, $\mu = (0.65, 0, \dots, 0, 0.35)$, $\|\mu\|_M = \text{rank}(H_0(\mu^{-1}([0.13, 1]))) = 2$

$\mu + \eta \in \mathbb{P}(\{1, \dots, 5\})$, $\epsilon = 0.01$, $C(i, j) = |i - j|$



Optimal Transportation Reconstruction Failure

Failing Removing Noise from Signals



Signals have low entropy: $\mu \in \mathbb{R}^n$ is sparse in a localized basis

Noise is high entropy a.s.

Minimize entropy: $\nu = \arg \min_{\nu'} d_W(\mu + \eta, \nu') + \lambda H(\nu')$

$\mu \in \mathbb{P}(\{1, \dots, 5\}), \mu = (0.65, 0, \dots, 0, 0.35), \|\mu\|_M = \text{rank}(H_0(\mu^{-1}([0.13, 1]))) = 2$

$\mu + \eta \in \mathbb{P}(\{1, \dots, 5\}), \epsilon = 0.01, C(i, j) = |i - j|$



Optimal Transportation Reconstruction Failure

Failing Removing Noise from Signals



Signals have low entropy: $\mu \in \mathbb{R}^n$ is sparse in a localized basis

Noise is high entropy a.s.

Minimize entropy: $\nu = \arg \min_{\nu'} d_W(\mu + \eta, \nu') + \lambda H(\nu')$

$\mu \in \mathbb{P}(\{1, \dots, 5\})$, $\mu = (0.65, 0, \dots, 0, 0.35)$, $\|\mu\|_M = \text{rank}(H_0(\mu^{-1}([0.13, 1]))) = 2$

$\mu + \eta \in \mathbb{P}(\{1, \dots, 5\})$, $\epsilon = 0.01$, $C(i, j) = |i - j|$



Approximate signal (left: $\lambda = [0.3, 0.7]$) not equal to true signal for any λ .

Optimal Transportation Failure Theorem

Let $\tilde{w} = \text{sign}(w) \forall w \in \mathbb{R}^n$.

Optimal Transportation Failure Theorem

Let $\tilde{w} = \text{sign}(w) \forall w \in \mathbb{R}^n$.

Theorem

Given a sparse signal $\mu \in \mathbb{P}(\{1, \dots, n\})$ ($\|\mu\|_0 < n$) with added noise $\eta : \mu + \eta \in \mathbb{P}(\{1, \dots, n\})$,

Optimal Transportation Failure Theorem

Let $\tilde{w} = \text{sign}(w) \forall w \in \mathbb{R}^n$.

Theorem

Given a sparse signal $\mu \in \mathbb{P}(\{1, \dots, n\})$ ($\|\mu\|_0 < n$) with added noise $\eta : \mu + \eta \in \mathbb{P}(\{1, \dots, n\})$, the solution of $v = \arg \min_{v' : d_W(\mu + \eta, v') \leq d_W(\mu, \mu + \eta)} H(v')$ will not agree with μ , that is $\|\tilde{\mu} - \tilde{v}\|_0 > 0$, if

Optimal Transportation Failure Theorem

Let $\tilde{w} = \text{sign}(w) \forall w \in \mathbb{R}^n$.

Theorem

Given a sparse signal $\mu \in \mathbb{P}(\{1, \dots, n\})$ ($\|\mu\|_0 < n$) with added noise $\eta : \mu + \eta \in \mathbb{P}(\{1, \dots, n\})$, the solution of $v = \arg \min_{v': d_W(\mu + \eta, v') \leq d_W(\mu, \mu + \eta)} H(v')$ will not agree with μ , that is $\|\tilde{\mu} - \tilde{v}\|_0 > 0$, if $d_W(\mu, \mu + \eta) > d_W(v', \mu + \eta)$ with $\|v'\|_0 \leq \|\mu\|_0$ and $\|\tilde{v}' - \tilde{\mu}\|_0 > 0$.

Optimal Transportation Failure Theorem

Let $\tilde{w} = \text{sign}(w) \forall w \in \mathbb{R}^n$.


Theorem

Given a sparse signal $\mu \in \mathbb{P}(\{1, \dots, n\})$ ($\|\mu\|_0 < n$) with added noise $\eta : \mu + \eta \in \mathbb{P}(\{1, \dots, n\})$, the solution of $v = \arg \min_{v': d_W(\mu + \eta, v') \leq d_W(\mu, \mu + \eta)} H(v')$ will not agree with μ , that is $\|\tilde{\mu} - \tilde{v}\|_0 > 0$, if $d_W(\mu, \mu + \eta) > d_W(v', \mu + \eta)$ with $\|v'\|_0 \leq \|\mu\|_0$ and $\|\tilde{v}' - \tilde{\mu}\|_0 > 0$.


Remark: When the signal-to-noise ratio (SNR) is too low, the reconstruction is underdetermined.

Application: Star Cluster Identification

Application: Star Cluster Identification




Application: Star Cluster Identification




From [1], LEGUS classification scheme. Examples of candidates from the LEGUS images of NGC 1566 classified as Class 1 (symmetric star cluster; top),

Application: Star Cluster Identification




From [1], LEGUS classification scheme. Examples of candidates from the LEGUS images of NGC 1566 classified as Class 1 (symmetric star cluster; top), Class 2 (elongated star cluster; middle-top),

Application: Star Cluster Identification




From [1], LEGUS classification scheme. Examples of candidates from the LEGUS images of NGC 1566 classified as Class 1 (symmetric star cluster; top), Class 2 (elongated star cluster; middle-top), Class 3 (compact, multi-peak association; middle-bottom), and

Application: Star Cluster Identification



From [1], LEGUS classification scheme. Examples of candidates from the LEGUS images of NGC 1566 classified as Class 1 (symmetric star cluster; top), Class 2 (elongated star cluster; middle-top), Class 3 (compact, multi-peak association; middle-bottom), and Class 4 (spurious object; bottom).

Application: Star Cluster Identification



From [1], LEGUS classification scheme. Examples of candidates from the LEGUS images of NGC 1566 classified as Class 1 (symmetric star cluster; top), Class 2 (elongated star cluster; middle-top), Class 3 (compact, multi-peak association; middle-bottom), and Class 4 (spurious object; bottom). The three-color image to the left is created using the NUV and U bands for the blue channel, the B band for green one, and the V and I bands for red one. The contour and 3D plots from the V-band are shown to the right of the figure.


Star Cluster Identification

Star Cluster Identification

Convolutional Neural Network:


Star Cluster Identification

Convolutional Neural Network:



Star Cluster Identification


Convolutional Neural Network:



From [1], the StarcNet pipeline.

Star Cluster Identification


Convolutional Neural Network:



From [1], the StarcNet pipeline. Graphic sketch of the machine learning pipeline used in this work to classify cluster candidates in the LEGUS images.

Star Cluster Identification

Convolutional Neural Network:



From [1], the StarcNet pipeline. Graphic sketch of the machine learning pipeline used in this work to classify cluster candidates in the LEGUS images. (Left): The Hubble Space Telescope images as processed by the LEGUS project through a custom pipeline to generate automatic catalogs of cluster candidates, which are part of the public LEGUS catalogs release (Calzetti et al. 2015; Adamo et al. 2017); we apply StarcNet to the LEGUS catalogs and images.

Star Cluster Identification

Star Cluster Identification


Convolutional Neural Network:

Star Cluster Identification

Convolutional Neural Network:

STARCNET Prediction					
		Class 1	Class 2	Class 3	Class 4
Human Classification	1	0.78 (410)	0.14 (75)	0.01 (6)	0.07 (37)
	2	0.17 (107)	0.55 (335)	0.12 (73)	0.16 (97)
	3	0.01 (3)	0.15 (92)	0.45 (279)	0.39 (243)
	4	0.03 (45)	0.06 (80)	0.09 (115)	0.82 (1098)

STARCNET Prediction			
		C	NC
Human	C	0.81 (927)	0.19 (213)
	NC	0.11 (220)	0.89 (1735)




Star Cluster Identification

Convolutional Neural Network:

STARCNET Prediction					
		Class 1	Class 2	Class 3	Class 4
Human Classification	1	0.78 (410)	0.14 (75)	0.01 (6)	0.07 (37)
	2	0.17 (107)	0.55 (335)	0.12 (73)	0.16 (97)
	3	0.01 (3)	0.15 (92)	0.45 (279)	0.39 (243)
	4	0.03 (45)	0.06 (80)	0.09 (115)	0.82 (1098)

STARCNET Prediction		
Human	C	NC
	0.81 (927)	0.19 (213)
NC	0.11 (220)	0.89 (1735)




From [1], performance of StarcNet on the test set.

Star Cluster Identification

Convolutional Neural Network:

STARCNET Prediction					
		Class 1	Class 2	Class 3	Class 4
Human Classification	1	0.78 (410)	0.14 (75)	0.01 (6)	0.07 (37)
	2	0.17 (107)	0.55 (335)	0.12 (73)	0.16 (97)
	3	0.01 (3)	0.15 (92)	0.45 (279)	0.39 (243)
	4	0.03 (45)	0.06 (80)	0.09 (115)	0.82 (1098)

STARCNET Prediction			
		C	NC
Human	C	0.81 (927)	0.19 (213)
	NC	0.11 (220)	0.89 (1735)




From [1], performance of StarcNet on the test set. Confusion matrix normalized over the classes in test set of the LEGUS dataset (20% of the total sources or about 3000 objects).

Star Cluster Identification

Convolutional Neural Network:

STARcNET Prediction					
		Class 1	Class 2	Class 3	Class 4
Human Classification	1	0.78 (410)	0.14 (75)	0.01 (6)	0.07 (37)
	2	0.17 (107)	0.55 (335)	0.12 (73)	0.16 (97)
	3	0.01 (3)	0.15 (92)	0.45 (279)	0.39 (243)
	4	0.03 (45)	0.06 (80)	0.09 (115)	0.82 (1098)

STARcNET Prediction			
		C	NC
Human	C	0.81 (927)	0.19 (213)
	NC	0.11 (220)	0.89 (1735)




From [1], performance of StarcNet on the test set. Confusion matrix normalized over the classes in test set of the LEGUS dataset (20% of the total sources or about 3000 objects). The rows show the distribution of the human-classified sources, while the columns are the predictions of StarcNet. Parenthesis in the confusion matrix refers to the unnormalized values.

Star Cluster Identification

Convolutional Neural Network:

STARcNET Prediction					
		Class 1	Class 2	Class 3	Class 4
Human Classification	1	0.78 (410)	0.14 (75)	0.01 (6)	0.07 (37)
	2	0.17 (107)	0.55 (335)	0.12 (73)	0.16 (97)
	3	0.01 (3)	0.15 (92)	0.45 (279)	0.39 (243)
	4	0.03 (45)	0.06 (80)	0.09 (115)	0.82 (1098)

STARcNET Prediction			
		C	NC
Human	C	0.81 (927)	0.19 (213)
	NC	0.11 (220)	0.89 (1735)




From [1], performance of StarcNet on the test set. Confusion matrix normalized over the classes in test set of the LEGUS dataset (20% of the total sources or about 3000 objects). The rows show the distribution of the human-classified sources, while the columns are the predictions of StarcNet. Parenthesis in the confusion matrix refers to the unnormalized values. (Left) Overall accuracy evaluated for 4 class classification using raw bands as input.

Star Cluster Identification

Convolutional Neural Network:

StARcNET Prediction					
		Class 1	Class 2	Class 3	Class 4
Human Classification	1	0.78 (410)	0.14 (75)	0.01 (6)	0.07 (37)
	2	0.17 (107)	0.55 (335)	0.12 (73)	0.16 (97)
	3	0.01 (3)	0.15 (92)	0.45 (279)	0.39 (243)
	4	0.03 (45)	0.06 (80)	0.09 (115)	0.82 (1098)

StarcNet Prediction		
	C	NC
Human	C	0.81 (927)
	NC	0.11 (220)
		0.19 (213)
		0.89 (1735)




From [1], performance of StarcNet on the test set. Confusion matrix normalized over the classes in test set of the LEGUS dataset (20% of the total sources or about 3000 objects). The rows show the distribution of the human-classified sources, while the columns are the predictions of StarcNet. Parenthesis in the confusion matrix refers to the unnormalized values. (Left) Overall accuracy evaluated for 4 class classification using raw bands as input. (Middle) Results calculated with 2 classes (cluster/non-cluster classification).

Star Cluster Identification

Convolutional Neural Network:

STARcNET Prediction					
		Class 1	Class 2	Class 3	Class 4
Human Classification	1	0.78 (410)	0.14 (75)	0.01 (6)	0.07 (37)
	2	0.17 (107)	0.55 (335)	0.12 (73)	0.16 (97)
	3	0.01 (3)	0.15 (92)	0.45 (279)	0.39 (243)
	4	0.03 (45)	0.06 (80)	0.09 (115)	0.82 (1098)

STARcNET Prediction			
		C	NC
Human	C	0.81 (927)	0.19 (213)
	NC	0.11 (220)	0.89 (1735)




From [1], performance of StarcNet on the test set. Confusion matrix normalized over the classes in test set of the LEGUS dataset (20% of the total sources or about 3000 objects). The rows show the distribution of the human-classified sources, while the columns are the predictions of StarcNet. Parenthesis in the confusion matrix refers to the unnormalized values. (Left) Overall accuracy evaluated for 4 class classification using raw bands as input. (Middle) Results calculated with 2 classes (cluster/non-cluster classification). (Right) Precision-recall curves for each of the four classes, as well as for binary classification.

Star Cluster Identification

Convolutional Neural Network:

STARcNET Prediction					
		Class 1	Class 2	Class 3	Class 4
Human Classification	1	0.78 (410)	0.14 (75)	0.01 (6)	0.07 (37)
	2	0.17 (107)	0.55 (335)	0.12 (73)	0.16 (97)
	3	0.01 (3)	0.15 (92)	0.45 (279)	0.39 (243)
	4	0.03 (45)	0.06 (80)	0.09 (115)	0.82 (1098)

STARcNET Prediction			
		C	NC
Human	C	0.81 (927)	0.19 (213)
	NC	0.11 (220)	0.89 (1735)



From [1], performance of StarcNet on the test set. Confusion matrix normalized over the classes in test set of the LEGUS dataset (20% of the total sources or about 3000 objects). The rows show the distribution of the human-classified sources, while the columns are the predictions of StarcNet. Parenthesis in the confusion matrix refers to the unnormalized values. (Left) Overall accuracy evaluated for 4 class classification using raw bands as input. (Middle) Results calculated with 2 classes (cluster/non-cluster classification). (Right) Precision-recall curves for each of the four classes, as well as for binary classification. The overall accuracy is 68.6% with 4 classes and 86.0% with binary classification.

Optimal Transportation Star Cluster Identification

Our method:

Optimal Transportation Star Cluster Identification

Our method:

Algorithm 6: Optimal Transportation Star Cluster Identification

Input:

X : images $N \times m \times m$

δ : noise level

Optimal Transportation Star Cluster Identification

Our method:

Algorithm 7: Optimal Transportation Star Cluster Identification

Input:

X : images $N \times m \times m$

δ : noise level

Output:

C : star cluster classification $N \times 1$

Optimal Transportation Star Cluster Identification

Our method:

Algorithm 8: Optimal Transportation Star Cluster Identification

Input:

X : images $N \times m \times m$

δ : noise level

Output:

C : star cluster classification $N \times 1$

for $n = 1, 2, \dots, N$ **do**

$V_n = \arg \min_{v': d_W(X_n, v') < \delta} H(v')$

Optimal Transportation Star Cluster Identification

Our method:

Algorithm 9: Optimal Transportation Star Cluster Identification

Input:

X : images $N \times m \times m$

δ : noise level

Output:

C : star cluster classification $N \times 1$

for $n = 1, 2, \dots, N$ **do**

$V_n = \arg \min_{v': d_W(X_n, v') < \delta} H(v')$

if $\text{rank}(H_0(V_n^{-1}([0.9, 1]))) == 1$ **then**

 |

Optimal Transportation Star Cluster Identification

Our method:

Algorithm 10: Optimal Transportation Star Cluster Identification

Input:

X : images $N \times m \times m$

δ : noise level

Output:

C : star cluster classification $N \times 1$

for $n = 1, 2, \dots, N$ **do**

$V_n = \arg \min_{v': d_W(X_n, v') < \delta} H(v')$

if $\text{rank}(H_0(V_n^{-1}([0.9, 1]))) == 1$ **then**

$C_n = 1$

else

$C_n = 0$

end

end

Optimal Transportation Star Cluster Identification

Evaluating the expression $\arg \min_{v': d_W(x, v') < \delta} H(v')$

Optimal Transportation Star Cluster Identification

Evaluating the expression $\arg \min_{v': d_W(x, v') < \delta} H(v')$

Note: Center the problem at x and add small vectors to stay in feasibility region.
Normalize vectors to stay in probability space.

Optimal Transportation Star Cluster Identification

Evaluating the expression $\arg \min_{v': d_W(x, v') < \delta} H(v')$

Note: Center the problem at x and add small vectors to stay in feasibility region.
Normalize vectors to stay in probability space.

- 1 Uniform grid search:

Optimal Transportation Star Cluster Identification

Evaluating the expression $\arg \min_{v': d_W(x, v') < \delta} H(v')$

Note: Center the problem at x and add small vectors to stay in feasibility region.
Normalize vectors to stay in probability space.

- 1 Uniform grid search:
 - 1 Converges first order (Taylors Remainder)

Optimal Transportation Star Cluster Identification

Evaluating the expression $\arg \min_{v': d_W(x, v') < \delta} H(v')$

Note: Center the problem at x and add small vectors to stay in feasibility region.
Normalize vectors to stay in probability space.

- ① Uniform grid search:
 - ① Converges first order (Taylors Remainder)
 - ② Computationally slow and exponentially slow in higher dimensions

Optimal Transportation Star Cluster Identification

Evaluating the expression $\arg \min_{v': d_W(x, v') < \delta} H(v')$

Note: Center the problem at x and add small vectors to stay in feasibility region.
Normalize vectors to stay in probability space.

- ① Uniform grid search:
 - ① Converges first order (Taylors Remainder)
 - ② Computationally slow and exponentially slow in higher dimensions
- ② Random search:

Optimal Transportation Star Cluster Identification

Evaluating the expression $\arg \min_{v': d_W(x, v') < \delta} H(v')$

Note: Center the problem at x and add small vectors to stay in feasibility region.
Normalize vectors to stay in probability space.

- ① Uniform grid search:
 - ① Converges first order (Taylors Remainder)
 - ② Computationally slow and exponentially slow in higher dimensions
- ② Random search:
 - ① Converges with high probability

Optimal Transportation Star Cluster Identification

Evaluating the expression $\arg \min_{v': d_W(x, v') < \delta} H(v')$

Note: Center the problem at x and add small vectors to stay in feasibility region.
Normalize vectors to stay in probability space.

- ① Uniform grid search:
 - ① Converges first order (Taylors Remainder)
 - ② Computationally slow and exponentially slow in higher dimensions
- ② Random search:
 - ① Converges with high probability
 - ② Exponentially slow in higher dimensions

Optimal Transportation Star Cluster Identification

Evaluating the expression $\arg \min_{v': d_W(x, v') < \delta} H(v')$

Note: Center the problem at x and add small vectors to stay in feasibility region.
Normalize vectors to stay in probability space.

- ① Uniform grid search:
 - ① Converges first order (Taylors Remainder)
 - ② Computationally slow and exponentially slow in higher dimensions
- ② Random search:
 - ① Converges with high probability
 - ② Exponentially slow in higher dimensions
- ③ Gradient Descent:

Optimal Transportation Star Cluster Identification

Evaluating the expression $\arg \min_{v': d_W(x, v') < \delta} H(v')$

Note: Center the problem at x and add small vectors to stay in feasibility region.
Normalize vectors to stay in probability space.

- ① Uniform grid search:
 - ① Converges first order (Taylors Remainder)
 - ② Computationally slow and exponentially slow in higher dimensions
- ② Random search:
 - ① Converges with high probability
 - ② Exponentially slow in higher dimensions
- ③ Gradient Descent:
 - ① Converges quickly to local minimum (usually)

Optimal Transportation Star Cluster Identification

Evaluating the expression $\arg \min_{v': d_W(x, v') < \delta} H(v')$

Note: Center the problem at x and add small vectors to stay in feasibility region.
Normalize vectors to stay in probability space.

- ① Uniform grid search:
 - ① Converges first order (Taylors Remainder)
 - ② Computationally slow and exponentially slow in higher dimensions
- ② Random search:
 - ① Converges with high probability
 - ② Exponentially slow in higher dimensions
- ③ Gradient Descent:
 - ① Converges quickly to local minimum (usually)
 - ② Misses global minimum and can even diverge

Optimal Transportation Star Cluster Identification

Results:

Preliminary results on class 2 cluster detection:

Optimal Transportation Star Cluster Identification

Results:

Preliminary results on class 2 cluster detection:

$$\text{precision} = \frac{tp}{tp+fp} = 1$$

$$\text{recall} = \frac{tp}{tp+fn} = 2/5$$

$$F_1 = 2 \frac{\text{precision} \cdot \text{recall}}{\text{precision} + \text{recall}} = \frac{4}{7} = 57\%$$

Optimal Transportation Star Cluster Identification

Results:

Preliminary results on class 2 cluster detection:

$$\text{precision} = \frac{tp}{tp+fp} = 1$$

$$\text{recall} = \frac{tp}{tp+fn} = 2/5$$

$$F_1 = 2 \frac{\text{precision} \cdot \text{recall}}{\text{precision} + \text{recall}} = \frac{4}{7} = 57\%$$

Future Work:

Optimal Transportation Star Cluster Identification

Results:

Preliminary results on class 2 cluster detection:

$$\text{precision} = \frac{tp}{tp+fp} = 1$$

$$\text{recall} = \frac{tp}{tp+fn} = 2/5$$

$$F_1 = 2 \frac{\text{precision} \cdot \text{recall}}{\text{precision} + \text{recall}} = \frac{4}{7} = 57\%$$

Future Work:

- 1 Investigate transporting data across spectrum, not just spacially.

Optimal Transportation Star Cluster Identification

Results:

Preliminary results on class 2 cluster detection:

$$\text{precision} = \frac{tp}{tp+fp} = 1$$

$$\text{recall} = \frac{tp}{tp+fn} = 2/5$$

$$F_1 = 2 \frac{\text{precision} \cdot \text{recall}}{\text{precision} + \text{recall}} = \frac{4}{7} = 57\%$$

Future Work:

- 1 Investigate transporting data across spectrum, not just spacially.
- 2 Estimate SNR parameter.

Optimal Transportation Star Cluster Identification

Results:

Preliminary results on class 2 cluster detection:

$$\text{precision} = \frac{tp}{tp+fp} = 1$$

$$\text{recall} = \frac{tp}{tp+fn} = 2/5$$

$$F_1 = 2 \frac{\text{precision} \cdot \text{recall}}{\text{precision} + \text{recall}} = \frac{4}{7} = 57\%$$

Future Work:

- 1 Investigate transporting data across spectrum, not just spacially.
- 2 Estimate SNR parameter.
- 3 Speedup on GPU.



G. Pérez, M. Messa, D. Calzetti, S. Maji, D. E. Jung, A. Adamo, and M. Sirressi.

StarcNet: Machine learning for star cluster identification.

The Astrophysical Journal, 907(2):100.