

CNCF CKA - Certified Kubernetes Administrator Exam

Download Exam

View Entire Exam

Collapse/Expand All

Expose All Answers

Page: 3 / 5

Total 23 questions

Question #11 (Topic: Single Topic)

SIMULATION

Set configuration context:

```
[student@node-1] $ | kubectl config use-context hk8s
```

Task

Create a persistent volume with name app-data, of capacity 2Gi and access mode ReadOnlyMany. The type of volume is hostPath and its location is /srv/app-data.

Reveal Solution

Next Question

Question #12 (Topic: Single Topic)

SIMULATION

Set configuration context:

```
[student@node-1] $ | kubectl config use-context k8s
```

Task

Monitor the logs of pod foo and:

- ⇒ Extract log lines corresponding to error file-not-found
- ⇒ Write them to /opt/KUTR00101/foo

Reveal Solution

Next Question

Question #13 (Topic: Single Topic)

SIMULATION

Set configuration context:

```
[student@node-1] $ | kubectl config use-context k8s
```

Context

An existing Pod needs to be integrated into the Kubernetes built-in logging architecture (e.g. kubectl logs). Adding a streaming sidecar container is a good and common way to accomplish this requirement.

Task

Add a sidecar container named sidecar, using the busybox image, to the existing Pod big-corp-app. The new sidecar container has to run the following command:

```
/bin/sh -c "tail -n+1 -f /var/log/big-corp-app.log"
```

Use a Volume, mounted at /var/log, to make the log file big-corp-app.log available to the sidecar container.

Don't modify the specification of the

existing container other than adding the required volume mount.

[Reveal Solution](#)[Next Question](#)

Question #14 (Topic: Single Topic)

SIMULATION

Set configuration context:

```
[student@node-1] $ | kubectl config  
use-context k8s
```

Task

From the pod label name=overloaded-cpu, find pods running high CPU workloads and write the name of the pod consuming most CPU to the file /opt/KUTR00401/KUTR00401.txt (which already exists).

[Reveal Solution](#)[Next Question](#)

Question #15 (Topic: Single Topic)

SIMULATION

Set configuration context:

```
[student@node-1] $ | kubectl config  
use-context wk8s
```

Task

A Kubernetes worker node, named wk8s-node-0 is in state NotReady.

Investigate why this is the case, and perform any appropriate steps to bring the node to a Ready state, ensuring that any changes are made permanent.

You can `ssh` to the failed node using:

```
[student@node-1] $ | ssh wk8s-node-  
0
```

You can assume elevated privileges on the node with the following command:

```
[student@wk8s-node-0] $ | sudo -i
```

[Reveal Solution](#)[Download Exam](#)

Page: 3 / 5
Total 23 questions

[Previous Page](#)[Next Page](#)

[BLOG](#) [TERMS & CONDITIONS](#) [PRIVACY POLICY](#) [DMCA & LEGAL](#) [NEW EXAMS](#)

ITExams.com is owned by MBS Tech Limited: Room 1905 Nam Wo Hong Building, 148 Wing Lok Street, Sheung Wan, Hong Kong. Company registration number: 2310926

ITExams doesn't offer Real Microsoft Exam Questions. ITExams doesn't offer Real Amazon Exam Questions.

ITExams Materials do not contain actual questions and answers from Cisco's Certification Exams.

CFA Institute does not endorse, promote or warrant the accuracy or quality of ITExams. CFA® and Chartered Financial Analyst® are registered trademarks owned by CFA Institute.