REST APIs
Webhooks
Guides
Overview
Errors
SafeSend Exchange
SafeSend Returns
SafeSend Signatures
SafeSend Organizers
SafeSend Gather
Client Management

What Are Webhooks?

A webhook is a method of augmenting or altering the behavior of a web application with custom callbacks. These callbacks are triggered by specific events (e.g. a tax return is signed or a source document is uploaded by your client) and are sent to a designated URL that you set, allowing real-time data sharing between SafeSend and your application. Unlike traditional APIs, which require continuous polling to check for updates, webhooks push information as soon as an event occurs.

How Do Webhooks Work?

- **Event Occurrence:** An event happens within the source application. This could be a tax returned being signed from SafeSend Returns or document being uploaded to a document request list in Gather.
- **Webhook Triggered:** SafeSend detects the event and sends a response with relevant data from SafeSend to the predefined webhook URL, which is the endpoint of your application.
- **Data Payload:** The response contains a data payload that provides detailed information about the event. This payload is in JSON format.
- **Processing the Data:** You receive the payload and perform predefined actions based on the event details. This could include updating records, triggering notifications, or routing delivered files.

Benefits of Webhooks

- **Real-Time Data:** Webhooks provide immediate notifications when an event occurs, ensuring that your application has the most up-to-date information without delays.
- **Reduced Server Load:** Since webhooks push data only when an event occurs, they eliminate the need for constant polling, reducing server load and bandwidth usage.
- **Automated Workflows:** By automating responses to specific events, webhooks streamline workflows and improve operational efficiency.
- **Scalability:** Webhooks facilitate seamless integration between various applications and services, allowing your systems to scale and adapt quickly.

Implementing Webhooks

To set up webhooks, follow these general steps:

REST APIs
Webhooks
Guides
Overview
Errors
SafeSend Exchange
SafeSend Returns
SafeSend Signatures
SafeSend Organizers
SafeSend Gather
Client Management

Common Webhook Errors

The errors you may encounter when using the webhooks will look different than the endpoints. Our webhooks will trigger on each event. Below are some possible errors you might encounter when using our webhooks.

- **The webhook has stopped even though I have received payloads.**

  We require an HTTP success code from your API after we send a payload. This is to ensure that we are not sending your SafeSend data to a server that is not operational. This is to prevent data loss. Ensure that your API sends us a 200 (2xx) response code after every payload received. We hold all delivered payloads in a queue when a previously active webhook stops for any reason. Once it resumes, we will send all the payloads in the queue to the endpoint specified.

- **I am not receiving payloads when I think I should.**

  Please ensure the webhook is set up correctly and your API can handle the incoming data we will send you. We will automatically turn off the webhook event subscription if we do not receive a success message. If your webhook subscription is still active then your API is telling us you are receiving the payloads.

REST APIs
Webhooks
Guides
SafeSend Exchange
Download DRL Document
Download Drop Off Link
SafeSend Returns
SafeSend Signatures
SafeSend Organizers
SafeSend Gather
Client Management

SafeSend Exchange

v1

These webhooks allow you to receive up-to-date data from items sent via Exchange. Webhooks are the only way to get uploaded request list documents out of the system via APIs. Please consult the Webhook Guide for more information about setting about connecting to our webhooks.

Download DRL Document

Once the client uploads the document from document request list, SSE API module will deliver the event information to an API endpoint including uploaded document SAS link. API endpoint configuration can be found in SSE Settings under Developer Section page.

API Specification

- This webhook will trigger whenever a document is uploaded against a delivered DRL request.
- Each document uploaded will be its own event trigger.

Download DRL Document

```
{
  "eventType": 4000,
  "eventData": {
    "documentRequestListId": "35fcbf38-924f-48f9-8a12-
276fc484b817",
    "clientEmailId": "steve.smith@safesend.com",
    "documentFieldName": "Steve Smith",
    "uploadedDate": "08/10/2023",
    "uniqueArgs": "Upload Complete",
    "document": {
      "name": "invoice.pdf",
      "sasUrl": "https://www.documentstore.com/filename.pdf"
    }
  }
}
```

REST APIs
Webhooks
Guides
SafeSend Exchange
Download DRL Document
Download Drop Off Link
SafeSend Returns
SafeSend Signatures
SafeSend Organizers
SafeSend Gather
Client Management

SafeSend Exchange

v1

These webhooks allow you to receive up-to-date data from items sent via Exchange. Webhooks are the only way to get uploaded request list documents out of the system via APIs. Please consult the Webhook Guide for more information about setting about connecting to our webhooks.

Download Drop Off Link

Once Sender Creates Dropoff from Any chosen Dropoff link, SSE module will deliver the event information to an API endpoint, including File uploaded and other information. API endpoint configuration can be found in Exchange Settings under the Developer Section page.

API Specification

- This webhook will be created each time a fresh request is submitted using the Dropoff link.
- All dropoff link types, including company, personal, and folder dropoff links, will cause this webhook to activate.
- For Black Listed senders as well, a webhook will be triggered.

Download Drop Off Link


```
{
  "eventType": 4001,
  "eventData": {
    "senderEmail": "user@email.com",
    "senderFirstName": "Jack",
    "senderLastName": "Anderson",
    "dropoffMessage": "Please find the attached File.",
    "dropoffRecipient": [
      "SSEInternalUser@email.com"
    ],
    "dropoffSubject": "Sample Subject",
    "dropoffType": "Company",
    "isBlacklisted": false,
    "timeDelivered": "01/21/2025"
```

REST APIs
Webhooks
Guides
SafeSend Exchange
SafeSend Returns
Download Esign Document
Return Status Changed
SafeSend Signatures
SafeSend Organizers
SafeSend Gather
Client Management

SafeSend Returns

v1

These webhooks allow you to receive up-to-date data from items sent via Returns. Webhooks are the only way to get tax returns out of the system via APIs. Please consult the Webhook Guide for more information about connecting to our webhooks.

Download Esign Document

Once the user completes the signing process, SSR API module will deliver the event information to an API endpoint including signed/uploaded documents SAS link. API endpoint configuration can be found in SSR Settings under Developer Section page.

API Specification

- This webhook will trigger when a delivered tax return is esigned or manually signed by the recipient.
- Download Esign Document webhook does not have an event type.
- This webhook will contain both esign and additional esign documents.

Download Esign Document


```
{
  "documentStatus": "USERSIGNED",
  "signatureStatus": "ESigned",
  "signedOn": "2023-07-03T06:23:13.3566291Z",
  "taxSoftware": "ProSystems",
  "deliveredOn": "2023-06-29T05:27:16.977",
  "taxYear": 2022,
  "engagementType": "E1120",
  "documentClients": [
    {
      "clientType": "PartnerShip",
      "name": "ENERGY AUDITORS",
      "email": "useremail@safesend.com",
```

REST APIs
Webhooks
Guides
SafeSend Exchange
SafeSend Returns
Download Esign Document
Return Status Changed
SafeSend Signatures
SafeSend Organizers
SafeSend Gather
Client Management

SafeSend Returns

v1

These webhooks allow you to receive up-to-date data from items sent via Returns. Webhooks are the only way to get tax returns out of the system via APIs. Please consult the Webhook Guide for more information about connecting to our webhooks.

Return Status Changed

Once the user completes the signing process, SSR API module will deliver the event information to an API endpoint including signed/uploaded documents SAS link. API endpoint configuration can be found in SSR Settings under Developer Section page.

API Specification

- This webhook will trigger whenever a tax return status is updated regardless of where in the product it was updated.
- The Return Status changed webhook does not have an event type.

Return Status Changed


```
{
  "status": "PROCESSING",
  "statusDate": "2022-12-20T07:14:58.9708711Z",
  "eroEmail": "user1@safesend.com",
  "assignedEmail": "user2@safesend.com",
  "formType": "E1040",
  "taxYear": 2021,
  "documentGuid": "53e12ecb-f233-429e-882d-59018a7ee8b2",
  "documentId": 147857,
  "clientId": "client_demo",
  "httpStatus": 0,
  "uniqueArgs": "Additional Data",
  "taxReturnId": "LCRKJF8TVXG47AT5E0YU6RYKYW"
}
```

REST APIs
Webhooks
Guides
SafeSend Exchange
SafeSend Returns
SafeSend Signatures
Document Signed
Signature Status Changed
SafeSend Organizers
SafeSend Gather
Client Management

SafeSend Signatures

v1

These webhooks allow you to receive up-to-date data from items sent via Signatures. Webhooks are the only way to get signed signature documents out of the system via APIs. Please consult the Webhook Guide for more information about setting about connecting to our webhooks.

Document Signed

Once the user completes the signing process, SIG API module will deliver the event information to an API endpoint including signed/partially documents SAS link. API endpoint configuration can be found in SIG Settings under Developer Section page.

API Specification

- This webhook will trigger when any recipient signs a delivered signature request.
- If a signature request has multiple recipients, this webhook will trigger with sign and the status will be “partially signed”. When all signers of the signature request have signed then the status will be “ESigned.”

Document Signed


```
{
  "eventType": 3000,
  "eventData": {
    "clientId": "client_post_test_demo",
    "clientName": "demo_client",
    "taxYear": 2021,
    "sentBy": "noreply@safesend.com",
    "totalRecipients": 2,
    "recipientList": [
      "user1@gmail.com",
      "user2@gmail.com"
    ]
```

REST APIs
Webhooks
Guides
SafeSend Exchange
SafeSend Returns
SafeSend Signatures
Document Signed
Signature Status Changed
SafeSend Organizers
SafeSend Gather
Client Management

SafeSend Signatures

v1

These webhooks allow you to receive up-to-date data from items sent via Signatures. Webhooks are the only way to get signed signature documents out of the system via APIs. Please consult the Webhook Guide for more information about setting about connecting to our webhooks.

Signature Status Changed

Once the user changes the status of any signature, the SIG API Module will deliver the event information to an API endpoint, including status and other information. API endpoint configuration can be found in SIG Settings under the Developer Section page.

API Specification

- This webhook will trigger whenever a signature status is updated regardless of where in the product it was updated.
- The following statuses will cause the web hook to activate: Processing, Out for Signature, Delivery Failed, E-Signed, Partially Signed, Signature Stamping Failed, Declined, Canceled.
- Webhook will provide signature status data that was changed via the 'status' property.

Signature Status Changed

```
{
  "eventType": "3001",
  "eventData": {
    "clientId": "Chrisst12",
    "clientName": "Chriss user",
    "documentInfo": [
      {
        "documentType": "Engagement Letter",
        "documentId": "RAJV5A9LKRW4J10D32VXV0AUTW"
      }
```

REST APIs
Webhooks
Guides
SafeSend Exchange
SafeSend Returns
SafeSend Signatures
SafeSend Organizers
Engagement Letter Signed
Organizer Completed
Source Document Uploaded
Accessed Organizer Notification
Questionnaire completed
SafeSend Gather
Client Management

SafeSend Organizers

v1

These webhooks allow you to receive up-to-date data from items sent via Organizers. Webhooks are the only way to get signed documents, filled questionnaires, filled organizers, and source documents out of the system via APIs. Please consult the Webhook Guide for more information about setting about connecting to our webhooks.

Engagement Letter Signed

Once the user completes the signing process, ORG API module will deliver the event information to an API endpoint including signed/uploaded documents SAS link. API endpoint configuration can be found in ORG Settings under Developer Section page.

API Specification

- This webhook will trigger when all delivered esign documents have been signed.
- Multiple signature files may have to be downloaded as a zip file.

Engagement Letter Signed


```
{
  "eventType": 2000,
  "eventData": {
    "taxPayerName": "Ashish Rathi",
    "clientId": "client_post_test_demo",
    "taxPayerEmail": "ashish@safesend.com",
    "taxYear": 2021,
    "eroSigner": "Demo User1",
    "assignedTo": "Demo User2",
    "uniqueArgs": "",
    "documentFile": {
      "fileName": "filename.pdf_or_filename.zip",
      "sasUrl": "https://www.documentstore.com/filename.pdf"
    },
    "documentGuid": "3fa85f64-5717-4562-b3fc-2c963f66afa6"
```

REST APIs
Webhooks
Guides
SafeSend Exchange
SafeSend Returns
SafeSend Signatures
SafeSend Organizers
Engagement Letter Signed
Organizer Completed
Source Document Uploaded
Accessed Organizer Notification
Questionnaire completed
SafeSend Gather
Client Management

SafeSend Organizers

v1

These webhooks allow you to receive up-to-date data from items sent via Organizers. Webhooks are the only way to get signed documents, filled questionnaires, filled organizers, and source documents out of the system via APIs. Please consult the Webhook Guide for more information about setting about connecting to our webhooks.

Organizer Completed

Once the user completes the signing process, ORG API module will deliver the event information to an API endpoint including signed/uploaded documents SAS link. API endpoint configuration can be found in ORG Settings under Developer Section page.

API Specification

- This webhook will trigger when the Organizer is marked as complete.
- If custom questions has been sent along with the organizer it will come with the organizer when the webhook is triggered.

Organizer Completed


```
{
  "eventType": 2001,
  "eventData": {
    "taxPayerName": "Ashish Rathi",
    "clientId": "client_post_test_demo",
    "taxPayerEmail": "ashish@safesend.com",
    "taxYear": 2021,
    "eroSigner": "Demo User1",
    "assignedTo": "Demo User2",
    "uniqueArgs": "",
    "documentFile": {
      "fileName": "filename.pdf_or_filename.zip",
      "sasUrl": "https://www.documentstore.com/filename.pdf"
    },
    "documentGuid": "3fa85f64-5717-4562-b3fc-2c963f66afa6"
```

REST APIs
Webhooks
Guides
SafeSend Exchange
SafeSend Returns
SafeSend Signatures
SafeSend Organizers
Engagement Letter Signed
Organizer Completed
Source Document Uploaded
Accessed Organizer Notification
Questionnaire completed
SafeSend Gather
Client Management

SafeSend Organizers

v1

These webhooks allow you to receive up-to-date data from items sent via Organizers. Webhooks are the only way to get signed documents, filled questionnaires, filled organizers, and source documents out of the system via APIs. Please consult the Webhook Guide for more information about setting about connecting to our webhooks.

Source Document Uploaded

Once the user completes the signing process, ORG API module will deliver the event information to an API endpoint including signed/uploaded documents SAS link. API endpoint configuration can be found in ORG Settings under Developer Section page.

API Specification

- This webhook will trigger whenever a source document is uploaded to a delivered organizer.
- Multiple source document uploads will trigger the webhook multiple times.

Source Document Uploaded

```
{
  "eventType": 2002,
  "eventData": {
    "taxPayerName": "Ashish Rathi",
    "clientId": "client_post_test_demo",
    "taxPayerEmail": "ashish@safesend.com",
    "taxYear": 2021,
    "eroSigner": "Demo User1",
    "assignedTo": "Demo User2",
    "uniqueArgs": "",
    "documentFile": {
      "fileName": "filename.pdf_or_filename.zip",
      "sasUrl": "https://www.documentstore.com/filename.pdf"
    }
```

REST APIs
Webhooks
Guides
SafeSend Exchange
SafeSend Returns
SafeSend Signatures
SafeSend Organizers
Engagement Letter Signed
Organizer Completed
Source Document Uploaded
Accessed Organizer Notification
Questionnaire completed
SafeSend Gather
Client Management

SafeSend Organizers

v1

These webhooks allow you to receive up-to-date data from items sent via Organizers. Webhooks are the only way to get signed documents, filled questionnaires, filled organizers, and source documents out of the system via APIs. Please consult the Webhook Guide for more information about setting about connecting to our webhooks.

Accessed Organizer Notification

Once the user completes the signing process, ORG API module will deliver the event information to an API endpoint including signed/uploaded documents SAS link. API endpoint configuration can be found in ORG Settings under Developer Section page.

API Specification

- This webhook will trigger when an organizer recipient accesses the taxpayer experience for that organizer.

Accessed Organizer Notification

```
{
  "eventType": 2003,
  "eventData": {
    "taxPayerName": "Ashish Rathi",
    "clientId": "client_post_test_demo",
    "taxPayerEmail": "ashish@safesend.com",
    "taxYear": 2021,
    "batchName": "Demo Batch",
    "accessedOn": "2022-12-14T02:36:19.494Z ",
    "uniqueArgs": "",
    "organizerId": "1KV9JWK448YMEGGYJLQE3HZQH4"
  }
}
```

Response Body

REST APIs
Webhooks
Guides
SafeSend Exchange
SafeSend Returns
SafeSend Signatures
SafeSend Organizers
Engagement Letter Signed
Organizer Completed
Source Document Uploaded
Accessed Organizer Notification
Questionnaire completed
SafeSend Gather
Client Management

SafeSend Organizers

v1

These webhooks allow you to receive up-to-date data from items sent via Organizers. Webhooks are the only way to get signed documents, filled questionnaires, filled organizers, and source documents out of the system via APIs. Please consult the Webhook Guide for more information about setting about connecting to our webhooks.

Questionnaire completed

Once the user completes the signing process, ORG API module will deliver the event information to an API endpoint including signed/uploaded documents SAS link. API endpoint configuration can be found in ORG Settings under Developer Section page.

API Specification

- This webhook will trigger when all delivered esign documents have been signed.
- Multiple signature files may have to be downloaded as a zip file.

Questionnaire completed


```
{
  "eventType": 2004,
  "eventData": {
    "uniqueArgs": "",
    "documentFile": {
      "fileName": "filename.pdf_or_filename.zip",
      "sasUrl": "https://www.documentstore.com/filename.pdf"
    },
    "taxPayerName": "Jannet Doe",
    "taxPayerEmail": "gantest2@yopmail.com",
    "clientId": "OrganizerWithELAndSpouse",
    "taxYear": 2023,
    "eroSigner": "Demo User1",
    "assignedTo": "Demo User2",
    "documentGuid": "3fa85f64-5717-4562-b3fc-2c963f66afa6"
```

REST APIs
Webhooks
Guides
SafeSend Exchange
SafeSend Returns
SafeSend Signatures
SafeSend Organizers
SafeSend Gather
Download Esign Documents
Download Fillable Organizer
Download Source Documents
Download Custom Questionnaire
Client Management

SafeSend Gather

v1

These webhooks allow you to receive up-to-date data from items sent via Gather. Webhooks are the only way to get signed documents, filled questionnaires, filled organizers, and source documents out of the system via APIs. Please consult the Webhook Guide for more information about setting about connecting to our webhooks.

Download Esign Documents

Once the user completes the signing process, GTR API module will deliver the event information to an API endpoint including signed/uploaded documents SAS link. API endpoint configuration can be found in GTR Settings under Developer Section page.

API Specification

- This webhook will trigger when all esign documents have been signed or declined to sign by the Gather request recipient.

Download Esign Documents


```
{
  "eventType": 6000,
  "eventData": {
    "gatherId": 2345,
    "taxpayerName": "Jack Murphy",
    "spouseName": "Jane Murphy",
    "clientId": "newClientId",
    "taxpayerEmail": "amit@gmail.com",
    "spouseEmail": "sejal@gmail.com",
    "taxYear": 2022,
    "eroSigner": "Morgan",
    "assignedTo": "Claire",
    "uniqueArgs": "",
    "documentFile": {
      "fileName": "2021_EL.pdf",
      "sasUrl": "https://www.documentstore.com/filename.pdf"
```

REST APIs
Webhooks
Guides
SafeSend Exchange
SafeSend Returns
SafeSend Signatures
SafeSend Organizers
SafeSend Gather
Download Esign Documents
Download Fillable Organizer
Download Source Documents
Download Custom Questionnaire
Client Management

SafeSend Gather

v1

These webhooks allow you to receive up-to-date data from items sent via Gather. Webhooks are the only way to get signed documents, filled questionnaires, filled organizers, and source documents out of the system via APIs. Please consult the Webhook Guide for more information about setting about connecting to our webhooks.

Download Fillable Organizer

Once the user completes the signing process, GTR API module will deliver the event information to an API endpoint including signed/uploaded documents SAS link. API endpoint configuration can be found in GTR Settings under Developer Section page.

API Specification

- This webhook will trigger when the organizer is marked as complete.
- If no organizer is delivered with the Gather request this webhook will no trigger.

Download Fillable Organizer


```
{
  "eventType": 6001,
  "eventData": {
    "gatherId": 2345,
    "taxpayerName": "Jack Murphy",
    "spouseName": "Jane Murphy",
    "clientId": "newClientId",
    "taxpayerEmail": "amit@gmail.com",
    "spouseEmail": "sejal@gmail.com",
    "taxYear": 2022,
    "eroSigner": "Morgan",
    "assignedTo": "Claire",
    "uniqueArgs": "",
    "documentFile": {
      "fileName": "2021_FL.pdf"
```

REST APIs
Webhooks
Guides
SafeSend Exchange
SafeSend Returns
SafeSend Signatures
SafeSend Organizers
SafeSend Gather
Download Esign Documents
Download Fillable Organizer
Download Source Documents
Download Custom Questionnaire
Client Management

SafeSend Gather

v1

These webhooks allow you to receive up-to-date data from items sent via Gather. Webhooks are the only way to get signed documents, filled questionnaires, filled organizers, and source documents out of the system via APIs. Please consult the Webhook Guide for more information about setting about connecting to our webhooks.

Download Source Documents

Once the user completes the signing process, GTR API module will deliver the event information to an API endpoint including signed/uploaded documents SAS link. API endpoint configuration can be found in GTR Settings under Developer Section page.

API Specification

- This webhook will trigger whenever a source document is uploaded to the Gather request.
- Multiple source document uploads will trigger the webhook multiple times.

Download Source Documents


```
{
  "eventType": 6002,
  "eventData": {
    "gatherId": 2345,
    "clientId": "newClientId",
    "clientName": "Jack Murphy",
    "taxpayerEmail": "amit@gmail.com",
    "assignedTo": "Claire",
    "eroSigner": "Morgan",
    "engagementType": "E1040",
    "taxYear": 2022,
    "batchName": "Batch1",
    "spouseName": "Jane Murphy",
    "spouseEmail": "sejal@gmail.com"
```

REST APIs
Webhooks
Guides
SafeSend Exchange
SafeSend Returns
SafeSend Signatures
SafeSend Organizers
SafeSend Gather
Download Esign Documents
Download Fillable Organizer
Download Source Documents
Download Custom Questionnaire
Client Management

SafeSend Gather

v1

These webhooks allow you to receive up-to-date data from items sent via Gather. Webhooks are the only way to get signed documents, filled questionnaires, filled organizers, and source documents out of the system via APIs. Please consult the Webhook Guide for more information about setting about connecting to our webhooks.

Download Custom Questionnaire

Once the user completes the questionnaire, GTR API module will deliver the event information to an API endpoint including the questionnaire document SAS link. API endpoint configuration can be found in GTR Settings under the Developer Section page.

API Specification

- This webhook will trigger when the custom questionnaire is marked as complete.
- If no questionnaire is delivered with the Gather request this webhook will not trigger.

Download Custom Questionnaire


```
{
  "eventType": 6003,
  "eventData": {
    "gatherId": 2345,
    "taxpayerName": "Jack Murphy",
    "spouseName": "Jane Murphy",
    "clientId": "newClientId",
    "taxpayerEmail": "amit@gmail.com",
    "spouseEmail": "sejal@gmail.com",
    "taxYear": 2022,
    "eroSigner": "Morgan",
    "assignedTo": "Claire",
    "uniqueArgs": "",
    "documentFile": {
```

REST APIs
Webhooks
Guides
SafeSend Exchange
SafeSend Returns
SafeSend Signatures
SafeSend Organizers
SafeSend Gather
Client Management
Client Information Change

Client Management

v1

These webhooks allow you to receive up-to-date data from changes in the client management database. Webhooks are the only way to get client data out of the system via APIs. Please consult the Webhook Guide for more information about setting about connecting to our webhooks.

Client Information Change

Once the user Add/Update/Delete any of the Client, CLIENT MANAGEMENT API module will deliver the event information to an API endpoint. API endpoint configuration can be found in Client Management Settings under Developer Section page

API Specification

- This webhook will trigger when a change is made to the client management database.
- These changes include adding a new client, editing the information of the client, or removing a client from client management.
- Change in Client Information webhook will provide the method in which the client data was changed via 'action type' property.
- This webhook will provide 'uid' which is unique to each client in client management database.

Client Information Change


```
{
  "eventType": 5001,
  "eventData": {
    "uId": "123",
    "clientId": "Test_clientID",
    "ero": "Macxin Poulose",
    "location": "Safe Send",
    "type": "Taxpayer",
    "mfj": true,
```