

Help for command ImageMetadata

Contents

1	Description of ImageMetadata	1
2	Display of values	1
3	Values specific to MMVII	2
4	Command related to ImageMetadata	2

1 Description of ImageMetadata

This command print on the console the meta-data on images that MMVII can extract. Meta-data on images are used at different step of images calculation :

- as initial value for computing the focal length in pixel;
- to decide which images correspond to the same camera,
- in radiometric processing

These meta data can come from :

- value stored in the `xif` part of the file
- rules added by user with command `EditCalcMTDI`;

2 Display of values

The printing depend of the different origin of the value :

- case value *exist* in xif and is *not specified* by MMVII: print the value ;
- case value *does not exist* in xif and is *not specified* by MMVII: print `null`;
- value *does not exist* in xif and *is specified* by MMVII: print the value and indicate MMVII, `SetByUserRule`
- value *exist* in xif and *is modified* by MMVII: indicate with *warning* color MMVII, `ModifiedByUserRule`, print the initial and modified values;

The optional parameter `Disp` control which meta-data information are printed, its default value `MainExif` prints the tags possibly involved in photogrammetric or photometric processing. The value `PhgrExif` prints only the tags used in photogrammetric computation.

If there is multiple file, the command groups the images by sets having exactly the same values in all the meta-data specified by `Disp`. For example with the ramses data set:

- `MMVII ImageMetadata .*JPG` will generate 9 group because there is different values of exposure time;
- `MMVII ImageMetadata .*JPG Disp=PhgrExif` will generate 1 group because all the images are acquired with the same camera;

3 Values specific to MMVII

There is values, specific to MMVII, usefull in processing that are not part of exif information. When they exist they are printed :

- if the camera is in the data base (see `EditCamDataBase`), the size of the sensor, and the size of the pixel are printed;
- if the camera identifier is known it is printed, this identifier depend of the focal length, the camera model and the possible additionnal name created with `AdditionalName` in `EditCalcMTDI`;

Note that when merging the images having the same meta data, when it exist, the camera identifier is used to decided is two images belong to the same subset. For example with polygon data set :

- `MMVII ImageMetadata C.*JPG Disp=PhgrExif`
- all images have same focal and same camera model, but there is two camera, they have been distinguished using `EditCalcMTDI`, and we have two different identifier of camera
 - `CalibIntr_CamILCE-6400_AddC1_Foc16000`
 - `CalibIntr_CamILCE-6400_AddC2_Foc16000`

- so we will print in 2 groups;

4 Command related to ImageMetadata

See also :

- `EditCalcMTDI`
- `EditCamDataBase`