The Neutrino Manual

A small functional array language

Mico Mrkaic

November 2026

Contents

1. Getting started . . . 1
2. The REPL . . . 2
3. Values and types . . . 4
4. Operators and expressions . . . 5
5. Variables and scope . . . 6
6. Control flow . . . 6
7. Functions . . . 6
8. Arrays and matrices . . . 8
9. Linear algebra . . . 9
10. Complex numbers . . . 10
11. Special functions and statistics . . . 10
12. Random numbers . . . 12
13. Plotting . . . 12
14. Data files . . . 13
15. Output and formatting . . . 13
15b. Strings as code, and the keyboard (since 2.19) . . . 14
16. Scripts and tools . . . 15
Editors . . . 15
17. Builtin reference . . . 16
18. Grammar summary . . . 23

This manual covers Neutrino as implemented: every example below was executed against the interpreter and shows its actual output. For a quick pitch and build instructions see the README; for the honest list of sharp edges see KNOWN_LIMITATIONS.

1. Getting started

Build (a C23 compiler and `libm`; readline optional — see the README for macOS notes):

```
make -j$(nproc)   # ./neutrino, the REPL (parallel; plain 'make' works too)
make test         # golden suite + codegen goldens
make install     # ~/.local: bin/neutrino + packages + man page (man neutrino)
```

One-liners from the shell, once installed:

```
$ neutrino -e '2^62 + 1'
4611686018427387905
```

REPL history persists in `~/.local/state/neutrino/history` (`$XDG_STATE_HOME` honored; a pre-2.35 `~/.neutrino_history` is read once as a fallback).

The banner shows the version, when the binary was built, and when the session started. `neutrino --version` prints the same from the command line. Start the REPL and type an expression; its value echoes back:

```
neutrino> 2 + 3 * 4
14
neutrino> [1, 2; 3, 4] * [5; 6]
[ 17
   39 ]
```

A trailing `;` evaluates a statement but suppresses the echo. `#` and `%` both start a comment that runs to end of line. Ctrl-D exits; Ctrl-C cancels the current input.

2. The REPL

The interactive shell adds conveniences on top of the language. None of them apply to scripts — they are REPL features.

Commands (typed bare, not as function calls):

Command	Effect
`help` / `help(f)`	catalogue of all builtins / details plus usage examples for one
`who`	your variables, with type and shape; `who("records")`, `who("functions")`, `who("vars")`, add `"sorted"`
`whov` / `whof` / `whor` / `whos`	shorthands: vars, functions, records, everything-sorted
`version`	the interpreter version, as a string
`clear()` / `clear("a", ...)`	remove all user variables / the named ones (builtins are safe)
`keep("a", ...)`	remove all user variables *except* the named ones (the complement of `clear`)
`mem`	workspace size and peak process memory
`format …`	number display: `format("fixed", 2)`, `format(8)` (significant), `format long`, `format` to show
`pretty on|off`	aligned multi-line matrix display (default on in the REPL)
`manual [doc]`	page a rendered document: `manual`, `manual packages`, `manual changelog`, `manual lessons`, `manual design`
`TAB`	complete builtins, your names, and keywords; inside a `"quoted string"` it completes file paths
`more on|off`	page long output through `$PAGER` (default off)
`!cmd`	run a shell command (`!ls`, `!git status`)
`dis(f)`	disassemble a function's bytecode

`keep` names what survives; everything else goes, standard library untouched:

```
neutrino> let rate = 0.0575; let n = 360; let scratch = 99; let tmp = [1, 2, 3];
neutrino> keep("rate", "n"); who
```

```
  rate          float      = 0.0575
  n             int        = 360
```

Every builtin's help includes executable examples with their actual output — the examples are machine-verified against the interpreter, like this manual:

```
neutrino> help(median)
  median(A) | median(A, dim)
      median of all elements, or along dim
      builtin, 1 to 2 arguments
      e.g.  median([1, 2, 3, 4])              % 2.5
```

Autocall. A bare name that is a zero-argument builtin or closure is called: `who`, `help`, `rand` work without parentheses, and so does your own `let f = fn -> 42; f`.

Line editing. With readline (or macOS libedit), you get history (persisted to `~/.neutrino_history`), completion on builtin and variable names, and the usual Emacs keys. Multi-line constructs continue with a `...>` prompt until the `end` arrives.

Display defaults. The REPL prints matrices as aligned blocks (`pretty on`) and numbers in a terse 6-significant-digit format; both are configurable — see Output and formatting.

The working directory. `pwd`, `cd("dir")`, and `ls` are ordinary builtins, so they work bare at the prompt (shell muscle memory intact) *and* as values: `ls` returns a string array you can pipe, and `cd` actually changes the interpreter's directory — which `!cd` cannot (the shell escape runs in a child process). Globs work: `ls("*.nu")`. Flags belong to the shell escape: `!ls -la`.

```
neutrino> ls("packages")
["astro.nu"; "demo.nu"; "dist.nu"; "finance.nu"; "phys.nu"; "poly.nu"; "rmt.nu"; "scatter.nu"; "sy
neutrino> cd("packages");
neutrino> load("dist.nu"); norm.cdf(0, 0, 1)
0.5
neutrino> cd("..");
```

`ans` — the last value you saw and didn't name. Every echoed expression statement rebinds `ans`; `let` statements don't (their result has a name), semicolon-suppressed statements don't, and `load()`ed scripts don't (they don't echo). One rule: *if a value printed without a name, it's in ans* — the screen is the spec. `ans` is an ordinary global: it shows in `who`, `clear("ans")` removes it, and a `let ans = ...` of your own is legal and simply gets overwritten by your next anonymous result.

```
neutrino> 3 + 4
7
neutrino> ans * 2
14
neutrino> sqrt(ans)
3.74166
neutrino> let named = ans
3.74166
neutrino> 9 * 9
81
neutrino> let x = 1
1
neutrino> ans
81
neutrino> ans + 100;
neutrino> ans
81
neutrino> s * 2 where s = 50
```

```
100
neutrino> ans
100
neutrino> who
  ans           int         = 100
  named         float       = 3.74166
  x             int         = 1
```

Note the quiet guarantees in that transcript: `ans` survived both the `let` and the suppressed statement — it can never hold something you didn't see — and a `where`-qualified expression sets it like any other, because a where clause is an anonymous expression, not a named binding. This differs from Octave, where `3 + 4;` sets `ans` silently and scripts clobber it as a side effect.

3. Values and types

Neutrino has nine value kinds. The scalar kinds:

Type	Literals	Notes
`Int`	`42`, `-7`	64-bit signed; exact while it fits — overflow promotes the result to `Float`
`Float`	`3.14`, `1e-9`, `2.5e3`	IEEE double
`Bool`	`true`, `false`	distinct from numbers: `1 == true` is an error
`Complex`	`2i`, `1 + 3i`, `2.5i`	double re/im pair
`String`	`"hello"`	byte strings: `+` concatenates, comparisons are lexicographic, `s[i]`/`s[a:b]` index bytes (see the Strings section)
`Null`	`null`	the "no value" value; a suppressed or valueless statement yields it

Integer arithmetic is exact up to the edge of int64 and honest past it: the instant an operation would overflow, the *result* promotes to `Float` — you get the right magnitude, never wrapped line noise. Stay under the edge and `Int` stays exact.

```
neutrino> 2^62
4611686018427387904
neutrino> 2^63
9.22337e+18
neutrino> 3^84
1.19725e+40
```

And the compound kinds: `Array` (the 2-D numeric matrix — every array is rows x cols; a scalar is *not* a 1x1 array), `Record` (`{x = 1, y = 2}`, fields via `.x`), and `Function` (builtins and closures).

The type discipline is strict rather than coercive: `Bool` does not silently become a number in arithmetic or comparison (`1 == true` errors), and mixing `Bool` with numerics in an array literal is an error. The one deliberate blur: `Int` and `Float` compare and combine freely (`5 == 5.0` is `true`), and `/` always produces a `Float` (`4 / 2` is `2.0`).

Floating point behaves like floating point:

```
neutrino> 0.1 + 0.2 == 0.3
false
neutrino> 5 / 0
inf
```

Division by zero yields `inf`/`nan` rather than an error — test with `isfinite`/`isnan` where it matters.

4. Operators and expressions

From loosest to tightest binding:

Level	Operators	Notes
pipe	`|> |>> ~>`	left-assoc; see Functions
logical or	`||`	short-circuit
logical and	`&&`	short-circuit
elementwise or	`|`	on logicals/arrays
elementwise and	`&`	on logicals/arrays
comparison	`== ~= < <= > >=`	elementwise on arrays -> logical array

Chained comparisons. Relational operators chain the way mathematics writes them: `a < b < c` means `a < b` **and** `b < c`, with the middle term evaluated exactly once. Chains must run in one direction — {`<, <=`}, {`>, >=`}, or all `==`; mixing directions is a parse error (write `(a < b) & (b > c)` for that), and `!=` never chains, because `a != b != c` would not mean "all distinct". The conjunction is the elementwise `&`, so a chain over an array is a mask — counting draws in a band is one `sum`:

```
neutrino> 0 <= 0.5 < 1
true
neutrino> let z = [-1, 0.5, 0.8, 3]; sum(0 < z < 1)
2
neutrino> rng(1); sum(-1.96 < randn(1, 100) < 1.96) >= 90
true
```

range | `a:b`, `a:step:b` | inclusive; float steps fine |
additive | `+ - \|\|` |
multiplicative | `* / .* ./ \ .\` | `*` is the **matrix** product on matrices; `.*` elementwise; `\` left division (solve) |
unary | `- ! ~` | binds looser than `^`: `-2^2` is `-4` |
power | `^ .^` | right-assoc: `2^3^2` is `512`; `^` on a square matrix is the matrix power |
postfix | `' .' f(x) a[i] .field` | `'` is **conjugate** transpose, `.'` plain |

The `.`-prefixed operators are the elementwise family, exactly as in Octave:

```
neutrino> [1, 2, 3] .* [4, 5, 6]
[4, 10, 18]
neutrino> 2 .^ [1, 2, 3]
[2, 4, 8]
neutrino> [1i, 2]'          # conjugate transpose
[  -1i
  2+0i ]
```

Scalars broadcast against arrays in every elementwise operation (`[1, 2] + 1` is `[2, 3]`); two arrays must agree in shape exactly.

5. Variables and scope

`let name = value` is the binding **statement**: at the top level it creates a global; inside a loop body or block it creates a local scoped to that construct. A bare `name = value` (no `let`) is **assignment**: it walks outward through the enclosing scopes and updates the nearest existing `name` — this is how a loop body updates an accumulator defined outside it.

`let name = value in body` is the binding **expression**: `name` is visible only in `body`, and the whole thing evaluates to `body`. Bindings nest and shadow:

```
neutrino> let a = 1 in a + (let a = 100 in a) + a
102
```

6. Control flow

`if` is an expression:

```
neutrino> let x = 5; if x > 3 then "big" else "small" end
"big"
```

The `else` branch is optional; if the condition is false and there is no `else`, the result is `null`. Conditions must be `Bool` — a number is not a condition.

Loops are statements (they yield `null`):

```
neutrino> let s = 0; for i = 1:10 do s = s + i end; s
55
neutrino> let n = 1; while n < 100 do n = n * 2 end; n
128
```

`break` leaves the nearest loop, `continue` skips to its next iteration, and `return [value]` exits the enclosing function. All three are safe anywhere — including mid-expression (`acc + (if bad then continue else v end)`): the VM restores the loop's stack state on a non-local exit.

Block expressions sequence statements inside parentheses; the value is the final expression, and `let` bindings are local to the block:

```
neutrino> (let x = 3; let y = 4; sqrt(x*x + y*y))
5
neutrino> (let q = 7; q); q
error: undefined name 'q'          # block locals do not leak
```

This is the natural shape for a multi-step function body.

`elseif` (since 2.19)

Chains share a single closing `end`; each condition is tried in order:

```
neutrino> if 1 > 2 then "a" elseif 3 > 2 then "c" else "d" end
"c"
neutrino> let sign_ = fn x -> if x < 0 then -1 elseif x == 0 then 0 else 1 end
<fn/1>
neutrino> [sign_(-7), sign_(0), sign_(4)]
[-1, 0, 1]
```

7. Functions

`fn params -> expr` is a lambda; its body is one expression (use a block expression or `let … in` for multiple steps). Functions are values: bind them, pass them, return them.

```
neutrino> let f = fn x -> x ^ 2 + 1; f(3)
10
neutrino> let add = fn a -> fn b -> a + b; add(2)(5)   # currying
7
neutrino> let g = fn x -> (let s = x * x; s + 1); g(4)
17
```

Closures capture by value at creation. Recursion works through the function's own name.

Sections. A parenthesised expression containing _ becomes a lambda; each _ is a fresh parameter, left to right: `(_ + 1)` is `fn x -> x + 1`, `(_ * _)` takes two arguments.

map. `map(f, A)` applies `f` elementwise: `map((_ * 10), [1, 2, 3])` is `[10, 20, 30]`.

The pipe. `x |> rhs` feeds a value forward. If `rhs` mentions `@`, the pipe binds `@` to `x` and evaluates `rhs`; if `rhs` is a bare callable, the pipe applies it:

```
neutrino> [1, 2, 3, 4] |> sum(@) |> sqrt
3.16228
neutrino> 5 |> @ + 1
6
neutrino> 9 |> sqrt              # bare callable: sqrt(9)
3
```

Index-bound reductions. Sigma notation, executable: `f[k = R] E` applies any callable `f` to the body `E` evaluated at each `k` in `R` — sugar for `R ~> (fn k -> E) |> f`, so `sum`, `prod`, `max`, `mean`, or your own function all reduce. The binder is scoped to the body; the body binds loose, exactly like a `fn` body, so `sum[k = 1:3] k + 1` sums `k + 1` per term — parenthesize the reduction to operate on its result, and likewise to qualify the range with a `where`: `(sum[k = 1:n] k ^ 2) where n = 3`.

```
neutrino> sum[k = 1:100] 1 / k ^ 2
1.63498
neutrino> pi ^ 2 / 6
1.64493
neutrino> let q = [0.1, 0.2, 0.15]; prod[j = 1:3] (1 - q[j])
0.612
neutrino> sum[i = 1:4] sum[j = 1:4] (i == j)
4
```

Where clauses. Any expression can name its constants after the fact, the way mathematics writes them: `expr where a = 1, b = -3`. Bindings are sequential (later ones may use earlier ones — not vice versa), scoped to that one expression (they never leak, and they shadow without damaging outer names), and the clause binds looser than everything else in the expression, so a whole pipeline can be qualified at its end. It is pure sugar for a `let..in` chain. The former `where(...)` builtin is now `find(mask)` (indices of true) and `pick(mask, a, b)` (elementwise select).

```
neutrino> let y = a * x ^ 2 + b * x + c where a = 1, b = -3, c = 2, x = 4
6
neutrino> sqrt(h) where hs = 3, h = hs + 1
2
neutrino> 1:n ~> (@ ^ 2) |> sum where n = 5
55
neutrino> b
```

Pipes chain left to right, which reads as a data-flow pipeline.

The elementwise pipe ~>. Where `|>` feeds the *whole* value, `~>` feeds each *element*: `x ~> f` is `map(f, x)`. The same right-hand-side rules apply, with one deliberate twist: under `~>`, `@`

binds the **element**, not the whole array. The operator extends Neutrino's whole-vs-elementwise distinction (`*` vs `.*`) to pipelines — and yes, in a language named Neutrino, the elementwise pipe oscillates. `~>` always means the map primitive itself, so shadowing the name `map` cannot change what the operator does.

```
neutrino> [0.5, 1.5, 2.5] ~> (@ * 2) ~> floor
[1, 3, 5]
neutrino> 1:5 ~> (@ ^ 2) |> sum
55
neutrino> [1, 2, 3] ~> (fn x -> x * 10)
[10, 20, 30]
```

The tee pipe `|>>`. Exactly `|>`, but the value flowing through is printed (echo style) before being passed on — pipeline debugging without dismantling the pipeline. Swap `|>` for `|>>` at the stage you want to watch, then swap back:

```
neutrino> [3, 1, 4, 1, 5] |>> sort |>> unique |> length
[3, 1, 4, 1, 5]
[1, 1, 3, 4, 5]
4
```

Fan-out. When the right-hand side of `|>` (or `|>>`) is a record literal, each field's callable is applied to the piped value, and the result is a record of results with the same keys — a `describe()` composed from syntax:

```
neutrino> [2.1, 3.7, 1.4, 5.0] |> {n = length, mu = mean, sd = std, top = max}
{n = 4, mu = 3.05, sd = 1.61761, top = 5}
```

Fan-out is one level deep and whole-value only (`~>` into a record is an error). A non-callable field is a type error, and `@` inside the fan-out record is rejected: each field already receives the piped value as its argument.

8. Arrays and matrices

Matrix literals use `,` between columns and `;` between rows; every array is two-dimensional and **1-indexed**. `[]` is the empty array.

Indexing supports scalars, ranges, `:` (everything along a dimension), `end` (the last index, with arithmetic), index vectors (gather), and logical masks:

```
neutrino> let A = [1, 2, 3; 4, 5, 6]
[ 1  2  3
  4  5  6 ]
neutrino> size(A)
[2, 3]
neutrino> A[2, 3]          # element
6
neutrino> A[1, :]          # row
[1, 2, 3]
neutrino> A[:, 2]          # column
[ 2
  5 ]
neutrino> A[end, end]
6
neutrino> let v = [10, 20, 30, 40]; v[2:3]
[20, 30]
neutrino> v[v > 15]        # logical mask
[20, 30, 40]
```

```
neutrino> v[[1, 4]]        # gather
[10, 40]
```

Indexed assignment works with the same selectors, copy-on-write: `A[1, 2] = 9`, `v[v < 0] = 0`, `A[2, :] = [7, 8, 9]`. The target must be a plain name and indices must be in range (no auto-growing).

`unique(A)` returns the sorted distinct elements — vectors keep their orientation, matrices flatten to a row. **Logical arrays** come from comparisons and drive masking and counting: `sum(A > 2)` counts, `any`/`all` test, `find(mask)` gives 1-based positions, `pick(mask, a, b)` selects elementwise.

Construction and reshaping: `zeros`, `ones`, `eye`, `diag`, `linspace`, `reshape` (row-major), `repmat`, ranges `1:n`. **Reductions** take an optional dimension: `sum(A, 1)` down columns, `sum(A, 2)` across rows, `max(A, [], dim)` for the extrema.

Descriptive statistics follow the same conventions. `var` and `std` normalize by N-1 by default (`var(A, 1)` divides by N), `median` handles even counts by averaging, and `quantile` uses linear interpolation between order statistics (the NumPy default):

```
neutrino> let x = [2, 7, 4, 9, 3]
neutrino> var(x)
8.5
neutrino> quantile(x, [0.25, 0.5, 0.75])
[3, 4, 7]
```

`cov(X)` and `corr(X)` treat a matrix's **columns as variables** and rows as observations, returning the p x p covariance / Pearson correlation matrix (`cov` takes the same `w` normalization as `var`). On two vectors they return the scalar: `cov(x, y)`, `corr(x, y)`. A constant column has no correlation to speak of — those entries are `nan`:

```
neutrino> corr([1, 2, 3, 4, 5], [2, 1, 4, 3, 5])
0.8
```

9. Linear algebra

`*` is the matrix product; `\` solves. Square systems use LU with partial pivoting; non-square `\` is least squares — overdetermined gives the LS fit, underdetermined the minimum-norm solution.

```
neutrino> [2, 1; 1, 3] \ [3; 5]
[ 0.8
  1.4 ]
neutrino> [1, 1; 1, 2; 1, 3] \ [1; 2; 2]     # regression: intercept, slope
[ 0.666667
       0.5 ]
```

The decompositions return records, so the pieces have names:

Call	Returns	Identity
`lu(A)`	`{L, U, p}`	`P*A = L*U`
`qr(A)`	`{Q, R}`	`A = Q*R`
`chol(A)`	`L`	`L*L' = A` (Hermitian PD)
`svd(A)`	`{U, S, V}`	`A = U*diag(S)*V'`
`eig(A)`	`{values, vectors}`	`A*V = V*diag(values)`

`eig` handles both Hermitian matrices (Jacobi; real ascending eigenvalues, orthonormal vectors) and general ones (complex QR + inverse iteration; complex pairs come out right). All of it is

complex-capable — ' being the conjugate transpose is what makes the identities hold. `kron(A, B)` is the Kronecker product, `det`, `inv`, `trace`, `norm`, `dot` round out the set.

10. Complex numbers

The imaginary literal is a number followed by `i`. Complex values propagate through arithmetic and the math library; results stay complex (`1i * 1i` is `-1+0i`, not `-1`). `real`, `imag`, `conj`, `angle` access the parts, `abs` is the modulus. Functions with limited real domains return complex off it: `sqrt(-4)` is `2i`, `log(-1)` is `3.14159i`, `asin(2)` is complex.

11. Special functions and statistics

The special-function set is chosen as *primitives* from which the classical distributions are one-liners:

```
neutrino> let normcdf = fn x -> 0.5 * erfc(-x / sqrt(2))
neutrino> normcdf(1.96)
0.975002
neutrino> norminv(0.975)
1.95996
```

`gammainc(x, a)` is the regularized lower incomplete gamma — the chi-square CDF is `gammainc(x/2, k/2)`. `betainc(x, a, b)` is the regularized incomplete beta — Student-t and F CDFs fall out of it. `erf`/`erfc`, `beta`/`lbeta`, `gamma`/`lgamma`, `digamma`, and integer-order Bessel `besselj`/`bessely` complete the set. All are real-domain, elementwise over arrays, and validated against SciPy.

Root finding, minimization, integration

These three take a **function argument** — a closure or builtin — and call it repeatedly. `fzero(f, a, b)` finds a root by Brent's method (`f(a)` and `f(b)` must differ in sign); `fminbnd(f, a, b)` minimizes on an interval and returns `{x, fx}`; `integral(f, a, b[, tol])` integrates adaptively (Simpson with Richardson estimate; finite limits; default tolerance 1e-10). Closures capture data, so parameterized problems read naturally — a bond's yield to maturity:

```
neutrino> let cf = [100, 100, 100, 1100]
neutrino> let npv = fn r -> sum(cf ./ ((1 + r) .^ (1:4))) - 1000
neutrino> format(6); fzero(npv, 0.01, 0.3)
0.100000
```

A divergent or wildly oscillatory integrand fails with an error rather than a wrong answer; infinite limits are rejected — substitute to a finite domain first.

Strings

Strings are byte sequences (UTF-8 passes through but is not interpreted; `length` and indexing count bytes). `+` concatenates; `==`, `!=`, `<` and friends compare lexicographically, shorter prefixes first; indexing uses the same machinery as arrays, so ranges, `end`, and even permutations work:

```
neutrino> let s = "neutrino"
neutrino> s[1:3] + "!" + s[end]
"neu!o"
neutrino> "apple" < "banana"
true
```

The library: `upper`, `lower`, `trim`, `contains(s, sub)`, `startswith(s, p)`, `endswith(s, p)`, `strrep(s, old, new)`. Two bridges: `str(x)` gives any value's display text as a string, `num(s)` parses

a string as a number (Int if exact, else Float). And `fmt(tmpl, ...)` is `print`'s template engine returning a string instead of printing:

```
neutrino> fmt("run {} done in {:.2f}s", 3, 1.234)
"run 3 done in 1.23s"
```

Strings also form **arrays**: `["a", "bb"; "c", "dd"]` is a 2x2 String matrix (mixing strings with numbers in one matrix is an error). Indexing, slicing, `end`, transpose, `reshape`, `sort`, and `unique` all work, and elementwise operations do what a data-frame user hopes:

```
neutrino> let names = ["si", "at", "de", "si"]
neutrino> names == "si"
[true, false, false, true]
neutrino> names[names == "si"]
["si", "si"]
neutrino> ["pre_", "un_"] + "fix"
["pre_fix", "un_fix"]
```

Numeric reductions (`min`, `max`, `sum`, `norm`, ...) refuse string arrays rather than computing nonsense, and assignment cannot mix kinds: a String cell never silently becomes a number, nor the reverse.

`strsplit(s, sep)` and `strjoin(a, sep)` convert between strings and string arrays; `fields(r)` returns a record's field names as a string column; `readtable` loads non-numeric CSV columns as string arrays (quoted cells, RFC-4180 style, are handled); `writecsv` writes string matrices with proper quoting; and plots take `{labels = ["low", "high"]}` for multi-series legends alongside the older `label1`, `label2`, ... form.

String-and-number arithmetic is still an error — there is no implicit conversion in either direction; use `str` and `num` to cross the bridge.

Packages: `load`

`load("file.nu")` runs a file in the current session; its `let` bindings persist afterwards. A package is just a file of definitions — and a record of closures makes a namespace, so packages don't collide:

```
neutrino> load("tests/data/mathlib.nu")
neutrino> cube(4)
64
neutrino> geo.hyp([3, 4])
5
```

`save("ws.nu")` writes the whole workspace — every variable and function — as reloadable source; restore it with `load("ws.nu")`. The file is plain Neutrino, so it is readable and editable. Functions that capture variables (closures made by other functions) cannot be serialized and refuse with a clear message; a failed save leaves no file behind. `body(f)` prints the source of a user-defined function:

```
neutrino> let cube = fn x -> x^3
neutrino> body(cube)
fn x -> x^3
```

Expressions may span lines wherever a `(`, `[`, or `{` is open — newlines there are plain whitespace (matrix rows still take an explicit `;`). At the top level a newline ends the statement, and the REPL reads continuation lines automatically while a bracket is open.

Packages validate their inputs with `error` and `assert`:

```
neutrino> let f = fn x -> (assert(x > 0, "f needs x > 0, got {}", x); sqrt(x))
neutrino> f(-4)
```

```
error: f needs x > 0, got -4
```

The standard packages — distributions, polynomials, finance, and the solar almanac — are documented with verified examples in PACKAGES.md. Packages can `load` other packages (nesting is capped, so circular loads error cleanly). Closures capture by value, so packages are libraries of functions rather than stateful modules. Errors inside a loaded file are reported with the file name; a parse error includes its line and column within the file.

Masks and reductions

Comparisons on arrays yield Bool masks, and the reductions treat `true` as 1: `sum` of a mask counts, `mean` of a mask is the fraction — the one-line statistic for any condition.

```
neutrino> let mask = [1, 5, 2, 8, 3] > 2.5
[false, true, false, true, true]
neutrino> sum(mask)
3
neutrino> mean(mask)
0.6
```

12. Random numbers

The generator is xoshiro256** seeded through splitmix64, and it is **reproducible by default**: every fresh session starts from the same fixed seed, so a script's random draws are stable run to run. `rng(seed)` reseeds — same seed, same stream. `rand`, `randn`, `randi` draw uniform, normal, and integer variates, scalar or matrix-shaped (`rand(3)`, `randn(2, 4)`).

13. Plotting

Plotting has three backends. **Natively** the default is **gnuplot**, out of process — a soft dependency: the language works without it, and `plot` reports cleanly if it is missing (`plot: gnuplot failed (exit 127) — is gnuplot installed?`). Setting `NEUTRINO_PLOT_TERM=ascii` renders deterministic text plots into the terminal instead, and `NEUTRINO_PLOT_TERM=svg` writes standalone `plot_N.svg` files (dark palette). In the **browser** the default is the SVG backend, rendered into the workbench's Plots pane. For scatter plots, `packages/scatter.nu` wraps the `style = "points"` path every backend honors.

`plot(y)` plots a vector against its index; `plot(x, y)` plots pairs; if `y` is a **matrix**, each column is a separate series. An optional trailing argument is either a gnuplot style string (`"points"`, `"lines lw 2"`, `"impulses"`) or an options record. The svg and ascii backends honor the marker family by substring — any style mentioning `point`, `circle`, or `dot` draws markers, everything else draws lines — so `"circle"` means the same thing on every backend:

```
neutrino> let x = linspace(0, 10, 200)
neutrino> plot(x, map(sin, x), {title = "sin(x)", xlabel = "x", grid = true})
```

Recognised options: `title`, `xlabel`, `ylabel`, `style` (strings); `logx`, `logy`, `grid` (booleans); `xrange`, `yrange` (`[lo, hi]` vectors) to fix an axis instead of letting gnuplot choose; and legend labels — `label` for a single series, `label1`, `label2`, … for several (unlabeled series keep the `series k` default):

```
neutrino> let t = (linspace(0, 6.28, 100))';
neutrino> plot(t, [map(sin, t), map(cos, t)], {label1 = "sin", label2 = "cos"})
``` `hist(y)` draws a histogram
(`hist(y, nbins)` to choose the bin count; the default follows Sturges' rule),
and accepts the same trailing options record:
```

neutrino> rng(7) neutrino> hist(randn(1, 5000), 40)
```

A word of caution that `yrange` exists to address: gnuplot auto-ranges the y-axis to the data, which can make pure sampling noise look like structure. A histogram of 100 000 uniform draws in 20 bins has bin counts of 5000 +/- 69 (one binomial standard deviation) — auto-ranged, that +/-1.4% wiggle fills the whole plot and looks alarming; anchored at zero it is the flat wall it should be:

neutrino> hist(rand(1, 100000), 20, {yrange = [0, 6000]})

Plots open in a gnuplot window that outlives the command (`gnuplot -persist`). For scripted rendering, two environment variables redirect output — `NEUTRINO_PLOT_TERM` sets the gnuplot terminal and `NEUTRINO_PLOT_OUT` the file:

```sh
NEUTRINO_PLOT_TERM="pngcairo size 800,500" NEUTRINO_PLOT_OUT=fig.png \
  ./neutrino script.nu
```

(`NEUTRINO_PLOT_TERM="dumb size 76,20"` draws ASCII plots straight into the terminal, which is occasionally exactly what you want.) Complex data is rejected — plot `real(z)`, `imag(z)`, or `abs(z)` explicitly.

14. Data files

`readcsv(file)` reads a numeric CSV into a Float matrix; `writecsv(file, A)` writes one at full precision, so values **round-trip bit-exactly**. Empty cells become `nan` (missing data), Windows line endings are tolerated, and `{delim = ";", skip = n}` options handle other separators and preamble lines. Ragged rows and non-numeric cells are errors that name the row and column.

`readtable(file)` reads a CSV whose first line is a header and returns a **record of column vectors**, keys sanitized from the column names (`"GDP Growth (%)"` becomes `gdp_growth`; duplicates get `_2`, `_3`, …). This is Neutrino's data frame — named columns plus the existing mask machinery:

```
neutrino> writecsv("/tmp/m.csv", [1, 2; 3, 4]); readcsv("/tmp/m.csv")
[ 1  2
  3  4 ]
```

```
neutrino> let d = readtable("tests/data/macro.csv")
neutrino> mean(d.gdp_growth)
1.93333
neutrino> d.cpi[d.year >= 2021]
[  nan
     8 ]
```

For a headerless file use `readcsv` — `readtable` will take the first line as a header regardless of its content. A column containing text (country names, tickers) is rejected with an error naming the column: representing it needs first-class strings, which the language does not yet have.

15. Output and formatting

Number display has one rule worth internalizing: **`format(n)` sets significant digits** (printf `%g`), which is why `format(2)` shows 100.51 as `1.0e+02` — two significant digits genuinely cannot spell 100.51. When you want *decimals* — bills, prices, fixed-width tables — say so explicitly with the systematic two-argument form:

- `format("fixed", d)` — d digits after the point (`%f`): the bill mode.
- `format("sci", d)` — scientific with d decimals (`%e`).
- `format("auto", d)` — d significant digits (`%g`); `format(d)` is its shorthand.
- `format` with no arguments reports the current setting; `format("default")` restores the terse startup style. The Octave-style names (`"short"`, `"long"`, `"short f"`, `"long f"`, `"short e"`, `"long e"`) remain as presets.

```
neutrino> let bill = 87.40; bill * 1.15
100.51
neutrino> format(2)
neutrino> bill * 1.15
1.0e+02
neutrino> format("fixed", 2)
neutrino> bill * 1.15
100.51
neutrino> ans / 4
25.13
neutrino> format("sci", 3)
neutrino> ans
2.513e+01
neutrino> format
format: scientific, 3 decimals
neutrino> format("default")
```

Strings interpolate with `fmt`, and `print` shares its template semantics (`{}` placeholders; double the braces for literals).

15b. Strings as code, and the keyboard (since 2.19)

`eval` runs a string as Neutrino code in the current session and returns its last value — which, among other things, gives dynamic record access: `eval("w." + col)`. `names` is the programmatic sibling of the `who` family (whose printed tables are unchanged): your workspace names as a sorted string column, with `"vars"`/`"funcs"` selectors.

```
neutrino> eval("2 + 2")
4
neutrino> let w = {temp = [21.5; 19.8], rain = [0; 4.2]};
neutrino> let col = "temp"; eval("w." + col)
[21.5; 19.8]
neutrino> let a = 1; let f = fn x -> x; names("vars")
["a"; "ans"; "col"; "w"]
neutrino> names("funcs")
["f"]
```

`input("prompt")` reads one line from the keyboard as a string, and `pause()` waits for Enter — `window.prompt` and an alert in the browser. Interactive by nature, so shown here rather than machine-replayed (under a pipe they consume the next stdin line; `tests/run_io.sh` checks exactly that):

```
let name = input("who are you? ");
print("hello, " + name)
pause("press Enter for the plot...")
```

Binding builtins: functions are values, commands autocall

`version` is a function; `let v = version` stores *the function* (like `let s = sin`), which `whof` lists. A bare zero-argument builtin — including through an alias — autocalls at the top level and prints

its result; in argument position it does not, so `length(v)` measures the function value (1). To store the *result*, call it: `let w = version()` — then `w` is an ordinary string variable. (The version string itself is suppressed below with `;` so this page never goes stale.)

```
neutrino> let v = version
<builtin version>
neutrino> whof
  v            builtin
neutrino> length(v)
1
neutrino> let w = version();
neutrino> w == version()
true
neutrino> names("vars")
["ans"; "w"]
```

16. Scripts and tools

`neutrino file.nu` runs a script (top level is a statement sequence; `#`/`%` comments). The binary also exposes the compiler pipeline:

Invocation	Shows
`neutrino --tokens file.nu`	the token stream
`neutrino --ast file.nu`	the parse tree
`neutrino --dis file.nu`	the compiled bytecode, statement by statement

`tic` starts a monotonic wall-clock timer and `toc()` returns the elapsed seconds — bare `toc` as a statement echoes it, but in an expression position write `toc()` (a bare name is a value reference, as with any function):

```
neutrino> tic; let A = randn(100, 100); let B = A * A; toc() < 60
true
```

`vmtest` is the headless driver used by the test suite: it reads stdin line by line and echoes each result, so `printf 'sum(1:100)\n' | ./vmtest` prints `5050`. `dis(f)` disassembles from inside the language. The golden suite (`make test`) and its ASan twin (`make test-asan`) are how changes prove themselves; `tests/dis/` pins the emitted bytecode for core constructs.

SVG plots. `NEUTRINO_PLOT_TERM=svg` makes `plot` and `hist` write `plot_N.svg` files instead of using gnuplot or ASCII. The browser build uses this by default: plots appear in the page's Plots panel, and "download new files" saves them.

Editors

Emacs. `editors/neutrino-mode.el` provides a major mode for `.nu` files: syntax highlighting (the builtin list is generated from the interpreter's own documentation table, so it cannot drift), `%` comments, block-aware indentation, and an inferior REPL. Put the file on your `load-path` and `(require 'neutrino-mode)`; then `M-x run-neutrino` starts the REPL, and from any `.nu` buffer `C-c C-r` sends the region, `C-c C-b` the buffer, `C-c C-l` loads the file, `C-c C-z` jumps to the REPL. On GitHub, a `.gitattributes` rule highlights `.nu` as Octave — close enough until linguist learns Neutrino.

packeur: the package picker

`packeur` (bare, at the prompt) opens a little table of every package beside the binary: arrow keys or `j`/`k` move, space toggles a checkbox, Enter applies — newly checked packages load, newly unchecked ones have their shelves cleared — `q` or ESC cancels. The checkboxes show live state: a box is checked exactly when `who` would show that shelf. It ends with a one-line summary of what changed. Piped input drives it headlessly (the keys ride the same stdin), which is how the test harness exercises it.

Finding packages: the load search path

`load` takes a bare name and finds the file itself: `load("dist")` tries `packages/dist.nu` in the current directory, then each directory in `$NEUTRINO_PATH` (colon-separated), then the user data directory (`$XDG_DATA_HOME/neutrino/packages`, default `~/.local/share/neutrino/packages` — where `make install` puts the standard packages), then `packages/` beside the real binary — symlinks resolved, so `ln -s ~/work/.../Neutrino/neutrino ~/.local/bin/neutrino` gives you a `neutrino` that loads its packages from anywhere, nothing copied or moved. Literal paths (`load("packages/dist.nu")`, absolute paths) work exactly as before, and also resolve beside the binary when the current directory lacks them.

```
neutrino> load("dist"); norm.cdf(1.96, 0, 1)
0.975002
```

The workspace stays readable: load groups

`load` remembers which names each file defined, and `who` collapses every loaded file to one summary line — so after a package-heavy session your own definitions stay findable at a glance. `who("name")` (the file's basename, or its full path) opens a shelf in full; `who("all")` restores the flat listing; the kind filters (`who("functions")`, `who("vars")`, …) remain flat, as before.

```
neutrino> load("packages/scatter.nu")
neutrino> let zq = 5
5
neutrino> who
  packages/scatter.nu      3 names   (who("scatter") to list)
  zq           int        = 5
neutrino> who("scatter")
  scatter      function   (2 params)
  scatter_titled function   (3 params)
  jitter       function   (2 params)
```

Re-loading a file replaces its shelf; `cleared` names drop from the counts; and `clear("scatter")` unloads a whole shelf — every member removed, the summary line gone, your own names untouched (a variable with the same name as a shelf wins the dispute). The registry follows names, not values — a rebound name stays on its shelf.

```
neutrino> load("packages/scatter.nu")
neutrino> let zq = 5
5
neutrino> clear("scatter"); who
  packages/scatter.nu      2 names   (who("scatter") to list)
  zq           int        = 5
```

17. Builtin reference

Generated from the interpreter's own documentation table (the same data `help` shows), so it cannot drift from the implementation.

Core & introspection

Signature	Description
`print(...) | print(tmpl, ...)`	print values; template fills {} in order; {:[-][w][.p][f|e|g]} formats a hole ({{ }} literal)
`fields(r)`	the record's field names, as a string column
`error(msg) | error(tmpl, ...)`	raise a runtime error (fmt-style template)
`assert(cond) | assert(cond, tmpl, ...)`	error unless cond is true
`version`	the interpreter version, as a string
`now`	current local date and time: {y, m, d, h, mi, s}
`whov | whov("sorted")`	your variables only (shorthand for who("vars"))
`whof | whof("sorted")`	your functions only (shorthand for who("functions"))
`whor | whor("sorted")`	your records only (shorthand for who("records"))
`whos`	the whole workspace, sorted by name (who("sorted"))
`who | who("functions", "sorted")`	list the workspace; filter by "records"/"functions"/"vars", add "sorted" for name order
`help / help(f)`	help lists every builtin; help(f) describes one
`system(cmd)`	run a shell command string; return its exit status
`dis(f)`	disassemble a function's bytecode (compiler/VM introspection)
`format / format(n) / format(mode, digits)`	number display: format(n) sets SIGNIFICANT digits; format("fixed", d) / format("sci", d) / format("auto", d) set the mode and digits explicitly; format() shows the current setting
`size(x)`	[rows, cols] of x (a scalar is 1x1)
`length(x)`	longest dimension of x (0 if empty)
`numel(x)`	number of elements (rows*cols)
`save("file.nu")`	write all variables and functions as reloadable source (restore with load)
`body(f)`	print the source of a user-defined function
`load("file.nu")`	run a file in the current session; its let-bindings persist (a record of closures makes a module)
`eval("code")`	run a string as Neutrino code in this session; returns the last value
`names() | names("vars"|"funcs")`	your workspace names as a sorted string column (the programmatic who)
`clear() | clear("a", ...)`	remove all user variables, or the named ones; clearing a shadow restores the standard-library original
`keep("a", "b", ...)`	remove all user variables except the named ones (the complement of clear)
`mem`	print workspace size (variables) and peak process memory
`tic`	start the wall-clock timer (monotonic)
`toc`	seconds elapsed since tic

Strings

Signature	Description
`upper(s)`	uppercase (ASCII bytes)
`lower(s)`	lowercase (ASCII bytes)
`trim(s)`	strip leading and trailing whitespace
`contains(s, sub)`	true if sub occurs in s
`startswith(s, p)`	true if s begins with p
`endswith(s, p)`	true if s ends with p
`strrep(s, old, new)`	replace every occurrence of old with new
`str(x)`	the display text of any value, as a string
`num(s)`	parse a string as a number (Int if exact, else Float)
`fmt(tmpl, ...)`	print's template, returned as a string instead of printed
`strsplit(s, sep)`	split a string on a separator, giving a string row vector
`strjoin(a, sep)`	join a string array with a separator

REPL commands

Signature	Description
`exit | exit(code)`	end the session (also: quit)
`manual [doc]`	page rendered documentation: manual, manual book|packages|changelog|lessons|design|readme
`pretty on|off`	aligned multi-line matrix display (default on in the REPL)
`more on|off`	page long output through $PAGER

Solvers

Signature	Description
`fzero(f, a, b)`	root of f in [a, b] (Brent; f(a), f(b) must differ in sign)
`fminbnd(f, a, b)`	minimum of f on [a, b] (Brent) -> {x, fx}
`integral(f, a, b[, tol])`	definite integral (adaptive Simpson, finite limits; default tol 1e-10)

Data files

Signature	Description
`readcsv(file[, opts])`	numeric CSV -> Float matrix; empty cells are nan; opts: {delim, skip}
`writecsv(file, A[, opts])`	matrix -> CSV, full precision (round-trips); opts: {delim}
`readtable(file[, opts])`	CSV with a header -> record of column vectors named from the header

Signature	Description
`pwd`	the current working directory, as a string
`cd("dir") | cd`	change the working directory (persists, unlike !cd); bare cd goes home
`ls | ls("dir") | ls("*.nu")`	directory listing as a string array (globs supported)
`input("prompt")`	read one line from the keyboard as a string (window.prompt in the browser)
`pause() | pause("msg")`	wait for the user before continuing (alert in the browser)

Plotting

Signature	Description
`plot(y) | plot(x, y) | plot(x, Y, opts)`	line plot via gnuplot; Y columns are series; opts: style string or {title, xlabel, ylabel, style, logx, logy, grid, xrange, yrange, label, label1..labelN}
`hist(y[, nbins][, opts])`	histogram via gnuplot; opts as in plot (yrange to anchor the axis, label for the legend)

Array construction

Signature	Description
`zeros(r, c)`	r-by-c matrix of zeros
`ones(r, c)`	r-by-c matrix of ones
`eye(n)`	n-by-n identity matrix
`diag(x)`	vector -> diagonal matrix; matrix -> its diagonal as a column
`linspace(a, b, n)`	row of n points evenly spaced from a to b inclusive
`reshape(A, r, c)`	reinterpret A's elements as r-by-c (row-major), element count must match
`repmat(A, m, n)`	tile A into an m-by-n grid of copies

Reductions

Signature	Description
`sum(A) | sum(A, dim)`	sum of all elements, or along dim (1 = columns, 2 = rows)
`prod(A) | prod(A, dim)`	product of all elements, or along dim
`cov(X[, w]) | cov(x, y[, w])`	covariance matrix of X's columns (rows = observations), or scalar cov of two vectors; w as in var
`corr(X) | corr(x, y)`	Pearson correlation matrix of X's columns, or scalar correlation of two vectors
`var(A) | var(A, w) | var(A, w, dim)`	variance; w = 0 divides by N-1 (default), w = 1 by N

Signature	Description
`std(A) | std(A, w) | std(A, w, dim)`	standard deviation (sqrt of var, same normalization)
`median(A) | median(A, dim)`	median of all elements, or along dim
`quantile(x, p)`	quantile(s) of the data at probability p (scalar or vector); linear interpolation
`mean(A) | mean(A, dim)`	mean of all elements, or along dim
`min(A) | min(a, b) | min(A, [], dim)`	smallest element; elementwise min; or min along dim
`max(A) | max(a, b) | max(A, [], dim)`	largest element; elementwise max; or max along dim
`any(mask) | any(mask, dim)`	true if any element is nonzero/true (overall or along dim)
`all(mask) | all(mask, dim)`	true if every element is nonzero/true (overall or along dim)

Constants

Signature	Description
`pi`	3.14159..., the circle constant
`e`	2.71828..., Euler's number
`eulergamma`	0.57722..., the Euler-Mascheroni constant
`phi`	1.61803..., the golden ratio
`eps`	machine epsilon for Float (2^-52)
`inf`	positive infinity (Float)
`nan`	not-a-number (Float); nan never equals anything, itself included

workspace

Signature	Description
`packeur`	pick packages in a little table: arrows or j/k move, space toggles, Enter applies (loads and clears), q cancels

Array utilities

Signature	Description
`unique(A)`	sorted distinct elements; vectors keep orientation, matrices flatten to a row
`sort(A)`	ascending sort: a vector as a whole, a matrix by column
`find(mask)`	1-based positions of nonzero/true elements (row-major)
`pick(mask, a, b)`	elementwise select: a where the mask is true, else b
`cumsum(A)`	cumulative sum along a vector, or down each column

Signature	Description
`cumprod(A)`	cumulative product along a vector, or down each column
`diff(A)`	consecutive differences along a vector, or down each column
`flipud(A)`	reverse row order (flip up-down)
`fliplr(A)`	reverse column order (flip left-right)

Mathematical functions

Signature	Description
`abs(x)`	absolute value, or complex magnitude
`sqrt(x)`	square root (complex result for negative reals)
`cbrt(x)`	real cube root
`exp(x)`	e raised to the x (complex-aware)
`log(x)`	natural logarithm (complex for negatives)
`ln(x)`	natural logarithm (alias for log)
`log10(x)`	base-10 logarithm (complex for negatives)
`log2(x)`	base-2 logarithm (complex for negatives)
`sign(x)`	-1 / 0 / +1 by sign; z/|z| for complex
`floor(x)`	round toward -infinity (componentwise on complex)
`ceil(x)`	round toward +infinity (componentwise on complex)
`round(x)`	round to nearest (componentwise on complex)
`trunc(x)`	round toward zero
`hypot(a, b)`	sqrt(a^2 + b^2) without overflow (elementwise)
`mod(a, b)`	modulo, result takes the sign of b (elementwise)
`rem(a, b)`	remainder, result takes the sign of a (elementwise)
`gamma(x)`	gamma function (real, elementwise)
`erf(x)`	error function (real, elementwise)
`erfc(x)`	complementary error function 1 - erf(x)
`beta(a, b)`	beta function (a, b > 0, elementwise)
`lbeta(a, b)`	log of the beta function
`gammainc(x, a)`	regularized lower incomplete gamma P(a, x) (the chi^2 CDF)
`betainc(x, a, b)`	regularized incomplete beta I_x(a, b) (Student-t / F CDFs)
`norminv(p)`	standard normal quantile (inverse CDF)
`digamma(x)`	digamma psi(x) = d/dx log gamma(x)
`besselj(n, x)`	Bessel function of the first kind, integer order n
`bessely(n, x)`	Bessel function of the second kind, integer order n (x > 0)
`lgamma(x)`	log of |gamma(x)| (real, elementwise)

Linear algebra

Signature	Description
`kron(A, B)`	Kronecker product: (m x n) kron (p x q) -> (mp x nq)
`dot(a, b)`	inner product of two vectors
`norm(x) | norm(x, p)`	vector p-norm (p = 1 or 2, default 2); matrix Frobenius norm
`trace(A)`	sum of the diagonal
`det(A)`	determinant via LU
`inv(A)`	matrix inverse (solves A I)
`lu(A)`	LU with partial pivoting -> {L, U, p}, so P*A* = *L*U
`qr(A)`	Householder QR -> {Q, R} (real or complex)
`chol(A)`	Cholesky factor L (lower), L*L' = A (SPD / Hermitian PD)
`eig(A)`	eigendecomposition -> {values, vectors}; Hermitian (ascending real) or general (complex)
`svd(A)`	thin SVD -> {U, S, V}, A = U*diag(S)*V' (S descending)

Trigonometric & hyperbolic

Signature	Description
`sin(x)`	sine (complex-aware, elementwise)
`cos(x)`	cosine (complex-aware, elementwise)
`tan(x)`	tangent (complex-aware, elementwise)
`asin(x)`	arcsine (complex outside [-1, 1])
`acos(x)`	arccosine (complex outside [-1, 1])
`atan(x)`	arctangent (complex-aware)
`atan2(y, x)`	two-argument arctangent (elementwise)
`sinh(x)`	hyperbolic sine (complex-aware)
`cosh(x)`	hyperbolic cosine (complex-aware)
`tanh(x)`	hyperbolic tangent (complex-aware)
`asinh(x)`	inverse hyperbolic sine (complex-aware)
`acosh(x)`	inverse hyperbolic cosine (complex below 1)
`atanh(x)`	inverse hyperbolic tangent (complex outside (-1, 1))

Complex accessors

Signature	Description
`real(z)`	real part (elementwise)
`imag(z)`	imaginary part (elementwise)
`conj(z)`	complex conjugate (elementwise)
`angle(z)`	argument atan2(im, re) (elementwise)
`arg(z)`	argument atan2(im, re) (alias for angle)

Random numbers

Signature	Description
`rng(seed)`	reseed the generator (xoshiro256**); same seed, same stream
`rand() | rand(n) | rand(r, c)`	uniform draws on [0, 1)
`randn() | randn(n) | randn(r, c)`	standard-normal draws
`randi(imax[, r, c]) | randi([lo, hi], ...)`	uniform random integers

Predicates

Signature	Description
`isnan(x)`	elementwise test for NaN -> logical
`isinf(x)`	elementwise test for +/-Inf -> logical
`isfinite(x)`	elementwise test for a finite value -> logical

Higher-order functions

Signature	Description
`map(f, A)`	apply f to each element of A, returning an array of results

18. Grammar summary

Reserved words: `let in fn if then else end true false null for while do break continue return`.

```
program    := statement*
statement  := 'let' NAME '=' expr            # binding (global at top level)
            | NAME '=' expr                  # assignment (walks scopes)
            | lvalue '[' indices ']' '=' expr
            | 'for' NAME '=' expr 'do' statement* 'end'
            | 'while' expr 'do' statement* 'end'
            | 'break' | 'continue' | 'return' expr?
            | expr
expr       := 'let' NAME '=' expr 'in' expr
            | 'if' expr 'then' expr ('else' expr)? 'end'
            | 'fn' NAME* '->' expr
            | '(' statement (';' statement)* ')'     # block expression
            | expr binop expr | unop expr | expr postfix
            | NAME | literal | '[' rows ']' | '{' fields '}'
            | expr '|>' expr | expr '|>>' expr | expr '~>' expr
           | expr relop expr relop expr ...   (* one direction; middles bound once *)
            | expr 'where' name '=' expr (',' name '=' expr)*
            | expr '[' name '=' expr ']' expr   (* index-bound reduction *)
postfix    := "'" | ".'" | '(' args ')' | '[' indices ']' | '.' NAME
```

Statements separate by newline or `;` (a trailing `;` also suppresses the REPL echo). Comments run from `#` or `%` to end of line.

Every example in this manual was executed against the current interpreter; the builtin reference is generated from the source. If you find a discrepancy, that is a bug — please report it.