

The Neutrino Packages

dist · poly · finance · astro · rmt · phys — with machine-verified examples

Mico Mrkaic

July 2026

Contents

A package is a file of let definitions; `load("packages/name.nu")` runs it in the current session and its bindings persist. Records of closures act as namespaces (`norm.cdf`), and packages validate their inputs with `assert`, so they fail like builtins do — with a message, not an accident. Every transcript below is machine-verified against the interpreter by `tests/run_manual.sh`, and every numerical claim is cross-checked in the package's own golden tests against an independent reference (SciPy, NumPy, Python's `datetime`, or the `astral` library — named in each section).

1. dist.nu — probability distributions

Six distributions — `norm`, `student`, `chi2`, `fdist`, `expo`, `unif` — each a record with `pdf`, `cdf`, `inv` (quantile), and `rand`. Parameters are explicit: `norm.cdf(x, mu, sigma)`. Quantiles with no closed form use bracket expansion plus `fzero` on the CDF; the quantile domain is $0 < p < 1$. Cross-checked against SciPy (`tests/34_dist.test`).

```
neutrino> load("packages/dist.nu")
neutrino> norm.cdf(1.96, 0, 1)
0.975002
neutrino> norm.inv(0.975, 0, 1)
1.95996
neutrino> student.inv(0.975, 30)
2.04227
neutrino> chi2.inv(0.95, 3)
7.81473
neutrino> fdist.cdf(3.0, 4, 20)
0.956799
```

A complete two-sample t-test — simulate, test, decide:

```
neutrino> load("packages/dist.nu")
neutrino> rng(42)
neutrino> let x1 = norm.rand(40, 100, 15)
[75.8016; 123.017; 111.725; 93.9971; 100.238; 98.0904; 107.158; 90.1486; 90.4082; 94.4609; 96.6851;
neutrino> let x2 = norm.rand(40, 108, 15)
[102.897; 92.0654; 112.122; 98.9768; 112.891; 112.931; 92.8931; 102.642; 111.903; 100.646; 100.94;
neutrino> let t = (mean(x2) - mean(x1)) / sqrt(var(x1)/40 + var(x2)/40)
2.46819
neutrino> 2 * (1 - student.cdf(abs(t), 78))
```

0.0157683

Out-of-domain probabilities refuse with the package's own message:

```
neutrino> load("packages/dist.nu")
error: quantile: p must be in (0,1), got 1.5
neutrino> student.inv(1.5, 10)
```

Function	Worked example	Result
norm.pdf/cdf/inv(x, mu, sigma)	norm.cdf(1.96, 0, 1)	0.975002
norm.rand(n, mu, sigma)	mean(norm.rand(500, 10, 2)) > 9	true
student.pdf/cdf/inv(x, v)	student.inv(0.975, 30)	2.04227
chi2.pdf/cdf/inv(x, k)	chi2.inv(0.95, 3)	7.81473
fdist.pdf/cdf/inv(x, d1, d2)	fdist.cdf(3.0, 4, 20)	0.956799
expo.pdf/cdf/inv(x, rate)	expo.inv(0.5, 2)	0.346574
unif.pdf/cdf/inv(x, a, b)	unif.cdf(3, 0, 10)	0.300000

2. poly.nu — polynomials

Coefficients are row vectors, highest power first: $[2, -3, 1]$ is $2x^2 - 3x + 1$. Roots come from the companion matrix and eig — the same algorithm Octave uses, on Neutrino's LAPACK-verified eigensolver. Cross-checked against NumPy (tests/37_poly.test).

```
neutrino> load("packages/poly.nu")
neutrino> polyval([2, -3, 1], 4)
21
neutrino> roots([1, -6, 11, -6])'
[1, 2, 3]
neutrino> roots([1, 0, 1])'
[1i, -1i]
neutrino> companion([1, -6, 11, -6])
[6, -11, 6; 1, 0, 0; 0, 1, 0]
```

Least-squares fitting (Vandermonde + backslash), and calculus that inverts:

```
neutrino> load("packages/poly.nu")
neutrino> let x = [0, 1, 2, 3, 4]
[0, 1, 2, 3, 4]
neutrino> let y = [1.1, 2.9, 9.2, 19.1, 32.8]
[1.1, 2.9, 9.2, 19.1, 32.8]
neutrino> polyfit(x, y, 2)
[1.95714, 0.131429, 1.01429]
neutrino> polyder([1, -6, 11, -6])
[3, -12, 11]
neutrino> polyint(polyder([1, -6, 11, -6]), -6)
[1, -6, 11, -6]
neutrino> conv([1, -1], [1, -2])
[1, -3, 2]
```

Function	Worked example	Result
polyval(c, x)	polyval([2, -3, 1], 4)	21
roots(c)	sort(real(roots([1, -6, 11, -6])))'	[1.00000, 2.00000, 3.00000]
companion(c)	companion([1, 0, -4])	[0.00000, 4.00000; 1.00000, 0.00000]
polyfit(x, y, n)	polyfit([1, 2, 3], [2, 5, 10], 2)	[1.00000, -8.32667e-16, 1.00000]
polyder(c)	polyder([1, -6, 11, -6])	[3, -12, 11]
polyint(c, k)	polyint([3, -12, 11], -6)	[1.00000, -6.00000, 11.0000, -6.00000]
conv(a, b)	conv([1, -1], [1, -2])	[1.00000, -3.00000, 2.00000]

3. finance.nu — the HP-12C's greatest hits

Time value of money, cash flows, bonds, amortization, and date arithmetic. Sign convention (HP-12C): money received is positive, money paid is negative; rates are per period, as decimals. Cross-checked against SciPy and Python's datetime (tests/38_finance.test).

The mortgage block — payment, implied rate, savings growth:

```
neutrino> load("packages/finance.nu")
neutrino> pmt(360, 0.005, 250000, 0)
-1498.88
neutrino> rate(360, 250000, -1498.876313, 0)
0.005
neutrino> fv(120, 0.004, 0, -200)
30726.4
```

Cash flows and bonds:

```
neutrino> load("packages/finance.nu")
neutrino> npv(0.10, [-1000, 300, 420, 680])
130.729
neutrino> irr([-1000, 300, 420, 680])
0.163406
neutrino> bond_price(100, 0.08, 0.06, 10, 1)
114.72
neutrino> bond_ytm(114.7202, 100, 0.08, 10, 1)
0.06
neutrino> bond_mduration(100, 0.08, 0.06, 10, 1)
7.0236
```

amort returns the whole schedule as a record of columns — a small data frame you can index, sum, and plot:

```
neutrino> load("packages/finance.nu")
neutrino> let s = amort(1000, 0.01, 3)
{period = [1; 2; 3], payment = [340.022; 340.022; 340.022], interest = [10; 6.69978; 3.36656], principal = [12]}
neutrino> fields(s)'
["period", "payment", "interest", "principal", "balance"]
neutrino> s.payment[1]
```

```
340.022
```

```
neutrino> s.balance'
```

```
[669.978, 336.656, 4.26326e-12]
```

```
neutrino> sum(s.principal)
```

```
1000
```

Dates, HP-12C style — actual day counts, date arithmetic, day of week, and the bond market's 30/360 convention. `datestr` returns a display string, `daterec` the {y, m, d} record, and `today()` a serial day number, so arithmetic reads naturally — `datestr(today() + 90)` is the date in 90 days:

```
neutrino> load("packages/finance.nu")
```

```
neutrino> days(2026, 1, 1, 2026, 7, 9)
```

```
189
```

```
neutrino> datestr(datenum(2026, 7, 17) + 90)
```

```
"2026-10-15"
```

```
neutrino> daterec(datenum(2024, 2, 29))
```

```
{y = 2024, m = 2, d = 29}
```

```
neutrino> dateadd(2024, 2, 28, 2)
```

```
{y = 2024, m = 3, d = 1}
```

```
neutrino> dow(2026, 7, 9)
```

```
4
```

```
neutrino> days360(2024, 1, 31, 2024, 7, 31)
```

```
180
```

```
neutrino> daterec(today()).y >= 2026
```

```
true
```

Function	Worked example	Result
<code>pmt(n, i, pv, fv)</code>	<code>pmt(360, 0.005, 250000, 0)</code>	-1498.88
<code>pv(n, i, pmt, fv)</code>	<code>pv(360, 0.005, -1498.88, 0)</code>	250001.
<code>fv(n, i, pv, pmt)</code>	<code>fv(120, 0.004, 0, -200)</code>	30726.4
<code>nper(i, pv, pmt, fv)</code>	<code>nper(0.005, 250000, -1498.88, 0)</code>	359.998
<code>rate(n, pv, pmt, fv)</code>	<code>rate(360, 250000, -1498.876313, 0)</code>	0.00500000
<code>npv(r, cfs)</code>	<code>npv(0.10, [-1000, 300, 420, 680])</code>	130.729
<code>irr(cfs)</code>	<code>irr([-1000, 300, 420, 680])</code>	0.163406
<code>bond_price(face, crate, y, n, freq)</code>	<code>bond_price(100, 0.08, 0.06, 10, 1)</code>	114.720
<code>bond_ytm(price, face, crate, n, freq)</code>	<code>bond_ytm(114.7202, 100, 0.08, 10, 1)</code>	0.0600000
<code>bond_duration(face, crate, y, n, freq)</code>	<code>bond_duration(100, 0.08, 0.06, 10, 1)</code>	7.44502
<code>bond_mduration(face, crate, y, n, freq)</code>	<code>bond_mduration(100, 0.08, 0.06, 10, 1)</code>	7.02360
<code>bond_convexity(face, crate, y, n, freq)</code>	<code>bond_convexity(100, 0.08, 0.06, 10, 1)</code>	65.1716
<code>amort(principal, i, n)</code>	<code>amort(1000, 0.01, 3).balance[3]</code>	4.26326e-12
<code>datenum(y, m, d)</code>	<code>datenum(2026, 7, 17)</code>	2.46124e+06
<code>datestr(jdn)</code>	<code>datestr(datenum(2026, 7, 17) + 90)</code>	"2026-10-15"

Function	Worked example	Result
<code>daterec(jdn)</code>	<code>daterec(datenum(2026, 7, 17))</code>	<code>{y = 2026.00, m = 7.00000, d = 17.0000}</code>
<code>dateadd(y, m, d, k)</code>	<code>dateadd(2024, 12, 31, 1)</code>	<code>{y = 2025.00, m = 1.00000, d = 1.00000}</code>
<code>today()</code>	<code>today() == datenum(now().y, now().m, now().d)</code>	<code>true</code>
<code>dow(y, m, d)</code>	<code>dow(2026, 7, 17)</code>	<code>5.00000</code>
<code>days(y1,m1,d1, y2,m2,d2)</code>	<code>days(2026, 1, 1, 2026, 7, 17)</code>	<code>197.000</code>
<code>days360(y1,m1,d1, y2,m2,d2)</code>	<code>days360(2024, 1, 31, 2024, 7, 31)</code>	<code>180</code>

4. astro.nu — the solar almanac

Sunrise, sunset, three grades of twilight, solar noon, day length, sun position, and moon phase, for any latitude and longitude (degrees; north and east positive). Times are local decimal hours given a UTC offset `tz`; `hm` renders them as “HH:MM”. NOAA solar position algorithm, within about a minute of the astral reference library (`tests/39_astro.test`). A `places` record preloads coordinates for several cities.

```
neutrino> load("packages/astro.nu")
neutrino> hm(sunrise(places.alexandria_va.lat, places.alexandria_va.lon, 2026, 7, 10, -4))
"05:52"
neutrino> hm(sunset(places.duluth_ga.lat, places.duluth_ga.lon, 2026, 7, 10, -4))
"20:50"
neutrino> hm(solar_noon(places.ljubljana.lon, 2026, 7, 10, 2))
"13:07"
neutrino> day_length(places.ljubljana.lat, places.ljubljana.lon, 2026, 7, 10)
15.5331
```

Planning a drive to arrive before dark — civil dawn at the origin to civil dusk at the destination:

```
neutrino> load("packages/astro.nu")
neutrino> let w = drive_daylight(places.alexandria_va, places.duluth_ga, 2026, 7, 10, -4)
{depart_dawn = 5.34382, depart_rise = 5.86728, arrive_set = 20.8376, arrive_dusk = 21.3161, window_h
neutrino> hm(w.depart_dawn) + " to " + hm(w.arrive_dusk)
"05:21 to 21:19"
neutrino> w.window_hours
15.9723
```

Sun position, moon illumination, and the honest polar refusal:

```
neutrino> load("packages/astro.nu")
error: the sun does not cross 90.833 degrees at latitude 80 on 2026-6-21
neutrino> let p = sun_position(38.8048, -77.0469, 2026, 7, 10, 13.22, -4)
{alt = 73.3594, az = 179.65}
neutrino> p.alt
73.3594
neutrino> moon_illum(2026, 7, 10)
0.19449
```

```
neutrino> sunrise(80, 0, 2026, 6, 21, 0)
```

Function	Worked example	Result
sunrise(lat, lon, y, m, d, tz)	hm(sunrise(38.8048, -77.0469, 2026, 7, 17, -4))	"05:57"
sunset(lat, lon, y, m, d, tz)	hm(sunset(38.8048, -77.0469, 2026, 7, 17, -4))	"20:31"
dawn_civil / dusk_civil(lat, lon, y, m, d, tz)	hm(dawn_civil(38.8048, -77.0469, 2026, 7, 17, -4))	"05:26"
dawn_nautical / dusk_nautical(lat, lon, y, m, d, tz)	hm(dawn_nautical(38.8048, -77.0469, 2026, 7, 17, -4))	"04:48"
dawn_astro / dusk_astro(lat, lon, y, m, d, tz)	hm(dusk_astro(38.8048, -77.0469, 2026, 7, 17, -4))	"22:23"
solar_noon(lon, y, m, d, tz)	hm(solar_noon(-77.0469, 2026, 7, 17, -4))	"13:14"
day_length(lat, lon, y, m, d)	day_length(46.0569, 14.5058, 2026, 7, 17)	15.3443
sun_position(lat, lon, y, m, d, hour, tz)	sun_position(38.8048, -77.0469, 2026, 7, 17, 13.2, -4).alt	72.2914
moon_age(y, m, d)	moon_age(2026, 7, 17)	2.70686
moon_illum(y, m, d)	moon_illum(2026, 7, 17)	0.0806581
hm(h)	hm(6.05)	"06:03"
places	places.duluth_ga.lat	34.0029
drive_daylight(from, to, y, m, d, tz)	drive_daylight(places.alexandria_la, places.duluth_ga, 2026, 7, 17, -4).window_hours	15.8284

5. rmt.nu — random matrices, structured

packages/rmt.nu is sugar over randn/qr/eye for the matrices you actually reach for at the prompt: symmetric, positive definite (chol-safe by construction: eigenvalues at least 1), Haar orthogonal, permutations and their matrices, correlation, row-stochastic (random Markov chains), and the Gaussian orthogonal ensemble — whose spectrum follows Wigner's semicircle on $[-2, 2]$, as the last line demonstrates on a 200×200 draw. Everything is reproducible under `rng(seed)`.

```
neutrino> load("packages/rmt.nu")
neutrino> format(6)
neutrino> rng(11)
neutrino> randorth(2)
[0.684752, 0.728776; -0.728776, 0.684752]
neutrino> let P = randspd(3); chol(P)[1, 1] > 0
true
neutrino> randperm(6)
[4, 5, 1, 2, 3, 6]
neutrino> permuat([3, 1, 2])
```

```
[0, 0, 1; 1, 0, 0; 0, 1, 0]
neutrino> let H = goe(200); max(abs(eig(H).values))
1.99476
```

Function	Worked example	Result
randsym(n)	let S = randsym(3); max(max(abs(S - S')) == 0	true
randspd(n)	let P = randspd(3); min(eig(P).values) >= 1	true
wishart(n)	let W = wishart(3); min(eig(W).values) > 0	true
randorth(n)	let Q = randorth(3); max(max(abs(Q' * Q - eye(3)))) < 1e-12	true
randperm(n)	sort(randperm(5)) == 1:5	[true, true, true, true, true]
permmat(p)	permmat([2, 3, 1])	[0, 1, 0; 0, 0, 1; 1, 0, 0]
randcorr(n)	let C = randcorr(3); max(abs(diag(C) - 1)) < 1e-12	true
randstoch(n)	let T = randstoch(4); max(abs(sum(T, 2) - 1)) < 1e-12	true
goe(n)	let H = goe(150); max(abs(eig(H).values)) < 2.4	true

6. phys.nu — physical constants

packages/phys.nu is the CODATA 2018 constants as a record — exact where the 2019 SI redefinition makes them exact (c, h, k, NA, qe), the recommended values elsewhere. The transcript computes Earth's surface gravity from G, recovers the speed of light from Maxwell's relation $1/\sqrt{\epsilon_0\mu_0}$, and expresses thermal energy at room temperature in electron volts:

```
neutrino> load("packages/phys.nu")
neutrino> format(6)
neutrino> phys.c
299792458
neutrino> phys.hbar
1.05457e-34
neutrino> phys.G * 5.972e24 / 6.371e6 ^ 2
9.81997
neutrino> 1 / sqrt(phys.eps0 * phys.mu0)
2.99792e+08
neutrino> phys.k * 300 / phys.eV
0.0258520
```

Function	Worked example	Result
phys.c	phys.c == 299792458	true
phys.h	phys.h	6.62607e-34
phys.hbar	abs(phys.hbar * 2 * pi - phys.h) < 1e-45	true
phys.G	phys.G	6.67430e-11
phys.k (thermal, in eV)	phys.k * 300 / phys.eV	0.0258520

Function	Worked example	Result
<code>phys.NA</code>	<code>phys.NA == 6.02214076e23</code>	<code>true</code>
<code>phys.R</code>	<code>phys.R</code>	<code>8.31446</code>
<code>phys.qe</code>	<code>phys.qe</code>	<code>1.60218e-19</code>
<code>phys.alpha</code>	<code>1 / phys.alpha</code>	<code>137.036</code>
<code>phys.sigma</code>	<code>phys.sigma</code>	<code>5.67037e-08</code>
<code>phys.ly / phys.au</code>	<code>phys.ly / phys.au</code>	<code>63241.1</code>

Writing your own

The pattern all four follow: a file of `let` definitions, `assert`-validated inputs, a record of closures when a namespace helps, and a golden test file whose reference values come from an independent implementation. Multi-line definitions are fine wherever a bracket is open. `save` your workspace, `load` it tomorrow — a package is just a workspace you chose to keep.