# The Neutrino Packages

dist · poly · finance · astro · rmt · phys · scatter · symb · demo

Mico Mrkaic

November 2026

## Contents

1. dist.nu — probability distributions . . . 1
2. poly.nu — polynomials . . . 2
3. finance.nu — the HP-12C's greatest hits . . . 3
4. astro.nu — the solar almanac . . . 5
5. rmt.nu — random matrices, structured . . . 6
6. phys.nu — physical constants . . . 7
7. scatter.nu — scatter plots without touching the core . . . 8
8. symb.nu — symbolic differentiation . . . 8
9. demo.nu — the tour . . . 10
Writing your own . . . 10

A package loads by bare name — `load("dist")` — searched in `packages/`, `$NEUTRINO_PATH`, `~/.local/share/neutrino/packages`, then beside the (symlink-resolved) binary; literal paths work as ever. Every exported name carries a docstring — comment lines directly above its `let` — which `help(f)` serves at the prompt with signature, description, provenance, and a machine-verified example (the `%=` marker in an `e.g.` line is executed by `tests/run_pkgdoc.sh`). A package is a file of `let` definitions; `load("packages/name.nu")` runs it in the current session and its bindings persist. Records of closures act as namespaces (`norm.cdf`), and packages validate their inputs with `assert`, so they fail like builtins do — with a message, not an accident. Every transcript below is machine-verified against the interpreter by `tests/run_manual.sh`, and every numerical claim is cross-checked in the package's own golden tests against an independent reference (SciPy, NumPy, Python's `datetime`, or the `astral` library — named in each section).

---

## 1. dist.nu — probability distributions

Six distributions — `norm`, `student`, `chi2`, `fdist`, `expo`, `unif` — each a record with `pdf`, `cdf`, `inv` (quantile), and `rand`. Parameters are explicit: `norm.cdf(x, mu, sigma)`. Quantiles with no closed form use bracket expansion plus `fzero` on the CDF; the quantile domain is `0 < p < 1`. Cross-checked against SciPy (`tests/34_dist.test`).

```
neutrino> load("packages/dist.nu")
neutrino> norm.cdf(1.96, 0, 1)
0.975002
neutrino> norm.inv(0.975, 0, 1)
1.95996
neutrino> student.inv(0.975, 30)
2.04227
neutrino> chi2.inv(0.95, 3)
```

```
7.81473
neutrino> fdist.cdf(3.0, 4, 20)
0.956799
```

A complete two-sample t-test — simulate, test, decide:

```
neutrino> load("packages/dist.nu")
neutrino> rng(42)
neutrino> let x1 = norm.rand(40, 100, 15)
[75.8016; 123.017; 111.725; 93.9971; 100.238; 98.0904; 107.158; 90.1486; 90.4082; 94.4609; 96.6851;
neutrino> let x2 = norm.rand(40, 108, 15)
[102.897; 92.0654; 112.122; 98.9768; 112.891; 112.931; 92.8931; 102.642; 111.903; 100.646; 100.94; 
neutrino> let t = (mean(x2) - mean(x1)) / sqrt(var(x1)/40 + var(x2)/40)
2.46819
neutrino> 2 * (1 - student.cdf(abs(t), 78))
0.0157683
```

Out-of-domain probabilities refuse with the package's own message:

```
neutrino> load("packages/dist.nu")
error: quantile: p must be in (0,1), got 1.5
neutrino> student.inv(1.5, 10)
```

| Function | Worked example | Result |
|---|---|---|
| `norm.pdf/cdf/inv(x, mu, sigma)` | `norm.cdf(1.96, 0, 1)` | `0.975002` |
| `norm.rand(n, mu, sigma)` | `mean(norm.rand(500, 10, 2)) > 9` | `true` |
| `student.pdf/cdf/inv(x, v)` | `student.inv(0.975, 30)` | `2.04227` |
| `chi2.pdf/cdf/inv(x, k)` | `chi2.inv(0.95, 3)` | `7.81473` |
| `fdist.pdf/cdf/inv(x, d1, d2)` | `fdist.cdf(3.0, 4, 20)` | `0.956799` |
| `expo.pdf/cdf/inv(x, rate)` | `expo.inv(0.5, 2)` | `0.346574` |
| `unif.pdf/cdf/inv(x, a, b)` | `unif.cdf(3, 0, 10)` | `0.300000` |

---

## 2. poly.nu — polynomials

Coefficients are row vectors, highest power first: `[2, -3, 1]` is $2x^2 - 3x + 1$. Roots come from the companion matrix and `eig` — the same algorithm Octave uses, on Neutrino's LAPACK-verified eigensolver. Cross-checked against NumPy (`tests/37_poly.test`).

```
neutrino> load("packages/poly.nu")
neutrino> polyval([2, -3, 1], 4)
21
neutrino> roots([1, -6, 11, -6])'
[1, 2, 3]
neutrino> roots([1, 0, 1])'
[1i, -1i]
neutrino> companion([1, -6, 11, -6])
[6, -11, 6; 1, 0, 0; 0, 1, 0]
```

Least-squares fitting (Vandermonde + backslash), and calculus that inverts:

```
neutrino> load("packages/poly.nu")
neutrino> let x = [0, 1, 2, 3, 4]
```

```
[0, 1, 2, 3, 4]
neutrino> let y = [1.1, 2.9, 9.2, 19.1, 32.8]
[1.1, 2.9, 9.2, 19.1, 32.8]
neutrino> polyfit(x, y, 2)
[1.95714, 0.131429, 1.01429]
neutrino> polyder([1, -6, 11, -6])
[3, -12, 11]
neutrino> polyint(polyder([1, -6, 11, -6]), -6)
[1, -6, 11, -6]
neutrino> conv([1, -1], [1, -2])
[1, -3, 2]
```

| Function | Worked example | Result |
|---|---|---|
| `polyval(c, x)` | `polyval([2, -3, 1], 4)` | `21` |
| `roots(c)` | `sort(real(roots([1, -6, 11, -6])))'` | `[1.00000, 2.00000, 3.00000]` |
| `companion(c)` | `companion([1, 0, -4])` | `[0.00000, 4.00000; 1.00000, 0.00000]` |
| `polyfit(x, y, n)` | `polyfit([1, 2, 3], [2, 5, 10], 2)` | `[1.00000, -8.32667e-16, 1.00000]` |
| `polyder(c)` | `polyder([1, -6, 11, -6])` | `[3, -12, 11]` |
| `polyint(c, k)` | `polyint([3, -12, 11], -6)` | `[1.00000, -6.00000, 11.0000, -6.00000]` |
| `conv(a, b)` | `conv([1, -1], [1, -2])` | `[1.00000, -3.00000, 2.00000]` |

---

## 3. finance.nu — the HP-12C's greatest hits

Time value of money, cash flows, bonds, amortization, and date arithmetic. Sign convention (HP-12C): money received is positive, money paid is negative; rates are per period, as decimals. Cross-checked against SciPy and Python's `datetime` (`tests/38_finance.test`).

The mortgage block — payment, implied rate, savings growth:

```
neutrino> load("packages/finance.nu")
neutrino> pmt(360, 0.005, 250000, 0)
-1498.88
neutrino> rate(360, 250000, -1498.876313, 0)
0.005
neutrino> fv(120, 0.004, 0, -200)
30726.4
```

Cash flows and bonds:

```
neutrino> load("packages/finance.nu")
neutrino> npv(0.10, [-1000, 300, 420, 680])
130.729
neutrino> irr([-1000, 300, 420, 680])
0.163406
neutrino> bond_price(100, 0.08, 0.06, 10, 1)
114.72
neutrino> bond_ytm(114.7202, 100, 0.08, 10, 1)
0.06
```

```
neutrino> bond_mduration(100, 0.08, 0.06, 10, 1)
7.0236
```

`amort` returns the whole schedule as a record of columns — a small data frame you can index, sum, and plot:

```
neutrino> load("packages/finance.nu")
neutrino> let s = amort(1000, 0.01, 3)
{period = [1; 2; 3], payment = [340.022; 340.022; 340.022], interest = [10; 6.69978; 3.36656], princi
12]}
neutrino> fields(s)'
["period", "payment", "interest", "principal", "balance"]
neutrino> s.payment[1]
340.022
neutrino> s.balance'
[669.978, 336.656, 4.26326e-12]
neutrino> sum(s.principal)
1000
```

Dates, HP-12C style — actual day counts, date arithmetic, day of week, and the bond market's 30/360 convention. `datestr` returns a display string, `daterec` the `{y, m, d}` record, and `today()` a serial day number, so arithmetic reads naturally — `datestr(today() + 90)` is the date in 90 days:

```
neutrino> load("packages/finance.nu")
neutrino> days(2026, 1, 1, 2026, 7, 9)
189
neutrino> datestr(datenum(2026, 7, 17) + 90)
"2026-10-15"
neutrino> daterec(datenum(2024, 2, 29))
{y = 2024, m = 2, d = 29}
neutrino> dateadd(2024, 2, 28, 2)
{y = 2024, m = 3, d = 1}
neutrino> dow(2026, 7, 9)
4
neutrino> days360(2024, 1, 31, 2024, 7, 31)
180
neutrino> daterec(today()).y >= 2026
true
```

| Function | Worked example | Result |
|---|---|---|
| `pmt(n, i, pv, fv)` | `pmt(360, 0.005, 250000, 0)` | `-1498.88` |
| `pv(n, i, pmt, fv)` | `pv(360, 0.005, -1498.88, 0)` | `250001.` |
| `fv(n, i, pv, pmt)` | `fv(120, 0.004, 0, -200)` | `30726.4` |
| `nper(i, pv, pmt, fv)` | `nper(0.005, 250000, -1498.88, 0)` | `359.998` |
| `rate(n, pv, pmt, fv)` | `rate(360, 250000, -1498.876313, 0)` | `0.00500000` |
| `npv(r, cfs)` | `npv(0.10, [-1000, 300, 420, 680])` | `130.729` |
| `irr(cfs)` | `irr([-1000, 300, 420, 680])` | `0.163406` |
| `bond_price(face, crate, y, n, freq)` | `bond_price(100, 0.08, 0.06, 10, 1)` | `114.720` |

| Function | Worked example | Result |
|---|---|---|
| `bond_ytm(price, face, crate, n, freq)` | `bond_ytm(114.7202, 100, 0.08, 10, 1)` | `0.0600000` |
| `bond_duration(face, crate, y, n, freq)` | `bond_duration(100, 0.08, 0.06, 10, 1)` | `7.44502` |
| `bond_mduration(face, crate, y, n, freq)` | `bond_mduration(100, 0.08, 0.06, 10, 1)` | `7.02360` |
| `bond_convexity(face, crate, y, n, freq)` | `bond_convexity(100, 0.08, 0.06, 10, 1)` | `65.1716` |
| `amort(principal, i, n)` | `amort(1000, 0.01, 3).balance[3]` | `4.26326e-12` |
| `datenum(y, m, d)` | `datenum(2026, 7, 17)` | `2.46124e+06` |
| `datestr(jdn)` | `datestr(datenum(2026, 7, 17) + 90)` | `"2026-10-15"` |
| `daterec(jdn)` | `daterec(datenum(2026, 7, 17))` | `{y = 2026.00, m = 7.00000, d = 17.0000}` |
| `dateadd(y, m, d, k)` | `dateadd(2024, 12, 31, 1)` | `{y = 2025.00, m = 1.00000, d = 1.00000}` |
| `today()` | `today() == datenum(now().y, now().m, now().d)` | `true` |
| `dow(y, m, d)` | `dow(2026, 7, 17)` | `5.00000` |
| `days(y1,m1,d1, y2,m2,d2)` | `days(2026, 1, 1, 2026, 7, 17)` | `197.000` |
| `days360(y1,m1,d1, y2,m2,d2)` | `days360(2024, 1, 31, 2024, 7, 31)` | `180` |

---

## 4. astro.nu — the solar almanac

Sunrise, sunset, three grades of twilight, solar noon, day length, sun position, and moon phase, for any latitude and longitude (degrees; north and east positive). Times are local decimal hours given a UTC offset `tz`; `hm` renders them as "HH:MM". NOAA solar position algorithm, within about a minute of the `astral` reference library (`tests/39_astro.test`). A `places` record preloads coordinates for several cities.

```
neutrino> load("packages/astro.nu")
neutrino> hm(sunrise(places.alexandria_va.lat, places.alexandria_va.lon, 2026, 7, 10, -
4))
"05:52"
neutrino> hm(sunset(places.duluth_ga.lat, places.duluth_ga.lon, 2026, 7, 10, -4))
"20:50"
neutrino> hm(solar_noon(places.ljubljana.lon, 2026, 7, 10, 2))
"13:07"
neutrino> day_length(places.ljubljana.lat, places.ljubljana.lon, 2026, 7, 10)
15.5331
```

Planning a drive to arrive before dark — civil dawn at the origin to civil dusk at the destination:

```
neutrino> load("packages/astro.nu")
neutrino> let w = drive_daylight(places.alexandria_va, places.duluth_ga, 2026, 7, 10, -
4)
{depart_dawn = 5.34382, depart_rise = 5.86728, arrive_set = 20.8376, arrive_dusk = 21.3161, window_h
neutrino> hm(w.depart_dawn) + " to " + hm(w.arrive_dusk)
```

```
"05:21 to 21:19"
neutrino> w.window_hours
15.9723
```

Sun position, moon illumination, and the honest polar refusal:

```
neutrino> load("packages/astro.nu")
error: the sun does not cross 90.833 degrees at latitude 80 on 2026-6-21
neutrino> let p = sun_position(38.8048, -77.0469, 2026, 7, 10, 13.22, -4)
{alt = 73.3594, az = 179.65}
neutrino> p.alt
73.3594
neutrino> moon_illum(2026, 7, 10)
0.19449
neutrino> sunrise(80, 0, 2026, 6, 21, 0)
```

| Function | Worked example | Result |
|---|---|---|
| `sunrise(lat, lon, y, m, d, tz)` | `hm(sunrise(38.8048, -77.0469, 2026, 7, 17, -4))` | `"05:57"` |
| `sunset(lat, lon, y, m, d, tz)` | `hm(sunset(38.8048, -77.0469, 2026, 7, 17, -4))` | `"20:31"` |
| `dawn_civil / dusk_civil(lat, lon, y, m, d, tz)` | `hm(dawn_civil(38.8048, -77.0469, 2026, 7, 17, -4))` | `"05:26"` |
| `dawn_nautical / dusk_nautical(lat, lon, y, m, d, tz)` | `hm(dawn_nautical(38.8048, -77.0469, 2026, 7, 17, -4))` | `"04:48"` |
| `dawn_astro / dusk_astro(lat, lon, y, m, d, tz)` | `hm(dusk_astro(38.8048, -77.0469, 2026, 7, 17, -4))` | `"22:23"` |
| `solar_noon(lon, y, m, d, tz)` | `hm(solar_noon(-77.0469, 2026, 7, 17, -4))` | `"13:14"` |
| `day_length(lat, lon, y, m, d)` | `day_length(46.0569, 14.5058, 2026, 7, 17)` | `15.3443` |
| `sun_position(lat, lon, y, m, d, hour, tz)` | `sun_position(38.8048, -77.0469, 2026, 7, 17, 13.2, -4).alt` | `72.2914` |
| `moon_age(y, m, d)` | `moon_age(2026, 7, 17)` | `2.70686` |
| `moon_illum(y, m, d)` | `moon_illum(2026, 7, 17)` | `0.0806581` |
| `hm(h)` | `hm(6.05)` | `"06:03"` |
| `places` | `places.duluth_ga.lat` | `34.0029` |
| `drive_daylight(from, to, y, m, d, tz)` | `drive_daylight(places.alexandria_va, places.duluth_ga, 2026, 7, 17, -4).window_hours` | `15.8284` |

---

## 5. rmt.nu — random matrices, structured

`packages/rmt.nu` is sugar over `randn`/`qr`/`eye` for the matrices you actually reach for at the prompt: symmetric, positive definite (chol-safe by construction: eigenvalues at least 1), Haar orthogonal, permutations and their matrices, correlation, row-stochastic (random Markov

chains), and the Gaussian orthogonal ensemble — whose spectrum follows Wigner's semicircle on [-2, 2], as the last line demonstrates on a 200×200 draw. Everything is reproducible under `rng(seed)`.

```
neutrino> load("packages/rmt.nu")
neutrino> format(6)
neutrino> rng(11)
neutrino> randorth(2)
[0.684752, 0.728776; -0.728776, 0.684752]
neutrino> let P = randspd(3); chol(P)[1, 1] > 0
true
neutrino> randperm(6)
[4, 5, 1, 2, 3, 6]
neutrino> permmat([3, 1, 2])
[0, 0, 1; 1, 0, 0; 0, 1, 0]
neutrino> let H = goe(200); max(abs(eig(H).values))
1.99476
```

| Function | Worked example | Result |
|---|---|---|
| `randsym(n)` | `let S = randsym(3); max(max(abs(S - S'))) == 0` | `true` |
| `randspd(n)` | `let P = randspd(3); min(eig(P).values) >= 1` | `true` |
| `wishart(n)` | `let W = wishart(3); min(eig(W).values) > 0` | `true` |
| `randorth(n)` | `let Q = randorth(3); max(max(abs(Q' * Q - eye(3)))) < 1e-12` | `true` |
| `randperm(n)` | `sort(randperm(5)) == 1:5` | `[true, true, true, true, true]` |
| `permmat(p)` | `permmat([2, 3, 1])` | `[0, 1, 0; 0, 0, 1; 1, 0, 0]` |
| `randcorr(n)` | `let C = randcorr(3); max(abs(diag(C) - 1)) < 1e-12` | `true` |
| `randstoch(n)` | `let T = randstoch(4); max(abs(sum(T, 2) - 1)) < 1e-12` | `true` |
| `goe(n)` | `let H = goe(150); max(abs(eig(H).values)) < 2.4` | `true` |

## 6. phys.nu — physical constants

`packages/phys.nu` is the CODATA 2018 constants as a record — exact where the 2019 SI redefinition makes them exact (`c`, `h`, `k`, `NA`, `qe`), the recommended values elsewhere. The transcript computes Earth's surface gravity from `G`, recovers the speed of light from Maxwell's relation `1/sqrt(eps0*mu0)`, and expresses thermal energy at room temperature in electron volts:

```
neutrino> load("packages/phys.nu")
neutrino> format(6)
neutrino> phys.c
299792458
neutrino> phys.hbar
1.05457e-34
```

```
neutrino> phys.G * 5.972e24 / 6.371e6 ^ 2
9.81997
neutrino> 1 / sqrt(phys.eps0 * phys.mu0)
2.99792e+08
neutrino> phys.k * 300 / phys.eV
0.0258520
```

| Function | Worked example | Result |
|---|---|---|
| `phys.c` | `phys.c == 299792458` | `true` |
| `phys.h` | `phys.h` | `6.62607e-34` |
| `phys.hbar` | `abs(phys.hbar * 2 * pi - phys.h) < 1e-45` | `true` |
| `phys.G` | `phys.G` | `6.67430e-11` |
| `phys.k (thermal, in eV)` | `phys.k * 300 / phys.eV` | `0.0258520` |
| `phys.NA` | `phys.NA == 6.02214076e23` | `true` |
| `phys.R` | `phys.R` | `8.31446` |
| `phys.qe` | `phys.qe` | `1.60218e-19` |
| `phys.alpha` | `1 / phys.alpha` | `137.036` |
| `phys.sigma` | `phys.sigma` | `5.67037e-08` |
| `phys.ly / phys.au` | `phys.ly / phys.au` | `63241.1` |

## 7. scatter.nu — scatter plots without touching the core

Proof that the frozen language plots more than it appears to: `plot()`'s `style = "points"` option is honored by every backend (SVG circles in the browser, point markers in ascii and gnuplot), so scatter plots are a pure package. `scatter(x, y)` and `scatter_titled(x, y, t)` wrap that fact; `jitter(x, amount)` spreads overplotted values for legibility. Per-point sizes and colors would need backend changes and are deliberately absent — the package's header says so. The transcript exercises the numeric helper; the SVG output itself is asserted by the plot test suite:

```
neutrino> load("packages/scatter.nu")
neutrino> rng(1); let j = jitter(1:100, 0.1);
neutrino> max(abs(j - (1:100))) <= 0.05
true
neutrino> size(jitter(rand(3, 4), 0.2))
[3, 4]
```

| Function | Worked example | Result |
|---|---|---|
| `jitter(x, a) stays within a/2` | `max(abs(jitter(1:100, 0.1) - (1:100))) <= 0.05` | `true` |
| `jitter preserves shape` | `size(jitter(rand(3, 4), 0.2)) == [3, 4]` | `[true, true]` |
| `mean displacement is small` | `abs(mean(jitter(zeros(1, 2000), 0.2))) < 0.01` | `true` |

## 8. symb.nu — symbolic differentiation

A symbolic differentiator in pure Neutrino, addressed in mathematics and answering in it. The front door is a string:

```
neutrino> format(6)
neutrino> load("packages/symb.nu")
neutrino> deriv("sin(x)/x")
"((cos(x) / x) - (sin(x) / x^2))"
```

```
neutrino> deriv("x^x")
"(exp((x * log(x))) * (log(x) + (x / x)))"
neutrino> deriv("exp(-x^2)")
"(-2 * (exp((-x^2)) * x))"
neutrino> let f = dfun("sin(x)/x");
neutrino> fzero(f, 4, 5)
4.49341
neutrino> fminbnd(ffun("sin(x)/x"), 4, 5)
{x = 4.49341, fx = -0.217234}
neutrino> integral(dfun("x^3"), 1, 2)
7.00000
```

`deriv` parses, differentiates, simplifies, and prints; `ffun` and `dfun` lift a string to an ordinary function (of the original, or of its derivative), which then rides the whole numeric ecosystem — the transcript above finds the tan x = x critical point of sin(x)/x twice over (fzero on the symbolic derivative, fminbnd on the original, agreeing at 4.49341) and checks the Fundamental Theorem of Calculus (the integral of dfun("x^3") over [1, 2] is 7, the function's change).

**How it works.** Expressions are nested records; `ddx` differentiates by structural recursion. `sub` and `divx` desugar into add/mul/negative powers at construction, so the product, power, and chain rules alone carry the whole calculus — the quotient rule falls out of $d(b^{-1})$ for free, which is why deriv("sin(x)/x") above prints the textbook form. The parser is recursive descent over `s[i]` (character classes are chained comparisons: `"0" <= c <= "9"`), unary minus binds looser than ^ so -x^2 means $-(x^2)$, and general powers desugar as f^g = exp(g·log f) — which is how x^x differentiates with no special case. The printer recognizes division and subtraction; `simp` folds and hoists constants. Since v2.19.2 the dispatchers are written with `elseif` — the package whose nine-deep end-cascades helped motivate the feature was first to enjoy it.

**The constructor layer** remains public — it *is* the representation, and remains the door for programmatic tree-building: `C(5)`, `X`, `add`, `mul`, `powc`, `sinx`, … plus `evalx` (evaluate at a point), `subst` (compose), `dn` (n-th derivative), and `taylor` (series coefficients by repeated ddx). The transcript cross-checks the symbolic answer against numeric differencing — two independent derivatives agreeing inside one verified session — and recovers the sine series (0, 1, 0, −1/6, …) from pure record recursion:

```
neutrino> format(4)
neutrino> load("packages/symb.nu")
neutrino> let e = add(powc(X, 3), mul(C(5), sinx(X)));
neutrino> show(simp(ddx(e)))
"((3 * x^2) + (5 * cos(x)))"
neutrino> let d = fn f -> fn x -> (f(x + h) - f(x - h)) / (2 * h) where h = 1e-6
<fn/1>
neutrino> abs(evalx(ddx(e), 2) - d(fn t -> t ^ 3 + 5 * sin(t))(2)) < 1e-8
true
neutrino> show(dn(powc(X, 5), 3))
"(60 * x^2)"
neutrino> taylor(sinx(X), 7)
[0.000, 1.000, -0.000, -0.1667, 0.000, 0.008333, -0.000, -0.0001984]
```

*(History, kept honest: v2.12.0 shipped constructor-only under a recorded limitation — "no substring access" — that v2.13.1 discovered was false all along: strings index like arrays, golden-tested since the strings phase. v2.14.0 built the parser that was always possible; v2.15.0 taught the printer textbook manners; v2.16.0 added the function-space lifts. The wrong entry and its correction are both in KNOWN_LIMITATIONS — the goldens outrank the maintainer's memory.)*

| Function | Worked example | Result |
|---|---|---|
| d/dx of x^3 at 2 is 12 | evalx(ddx(powc(X, 3)), 2) == 12 | true |
| chain rule through exp(2x) | abs(evalx(ddx(subst(expx(X), mul(C(2), X))), 0) - 2) < 1e-12 | true |
| taylor of exp begins 1, 1, 1/2 | max(abs(taylor(expx(X), 2) - [1, 1, 0.5])) < 1e-9 | true |
| parse then evaluate | abs(evalx(parse("2*pi"), 0) - 2 * pi) < 1e-12 | true |
| deriv: string in, string out | deriv("x^2") == "(2 * x)" | true |
| dfun: derivative as a function | abs(dfun("x^3")(2) - 12) < 1e-12 | true |
| FTC: integral of dfun is the change | abs(integral(dfun("x^3"), 1, 2) - 7) < 1e-6 | true |

## 9. demo.nu — the tour

Not a library: a performance. `load("packages/demo.nu")` plays a guided tour in six acts — executable mathematics (Basel, the Gaussian integral), the blackboard's word order (`where`, chained masks), functions as values (anonymous application, Euclid's recursion, n-fold self-composition converging on the golden ratio), the pipelines act with both crown jewels (the oscillation pipe — values flavor-changing between ~> and |> down one chain — and the fan-out dashboard), the calculus (symb.nu's `deriv` and a symbolic derivative fed to `fzero`), money (the HP-12C mortgage), and a plotted finale. Every demonstration is a SINGLE SOURCE STRING — printed as the caption and executed by `eval` — so what the tour shows is, byte for byte, what it runs; drift between shown and real code is impossible by construction. The pacing is deliberate: `pause()` waits for Enter after each feature at a live prompt — including the browser, where the pending output is streamed to the terminal first and the interpreter then truly waits for Enter (Asyncify) — while piped input or `make test` drains the pauses instantly at EOF. One file, every temperament. Seeded where random, deterministic throughout. Point a newcomer at this file first.

```
neutrino> load("packages/demo.nu")
```

### Writing your own

The pattern all four follow: a file of `let` definitions, `assert`-validated inputs, a record of closures when a namespace helps, and a golden test file whose reference values come from an independent implementation. Multi-line definitions are fine wherever a bracket is open. `save` your workspace, `load` it tomorrow — a package is just a workspace you chose to keep.