

Digital Control Loop Designer SDK User Guide



z-Domain Configuration Window

INTRODUCTION

The Digital Control Loop Designer SDK is a Software Development Kit (SDK) consisting of individual tools covering system definition, system modeling, code generation, control system fine tuning and real-time debugging of fully digital control systems for Switched-Mode Power Supplies (SMPS) for dsPIC® Digital Signal Controllers (DSC).

This user guide section is meant to be a quick start guide to the z-Domain Controller Configuration tool (DCLD.exe), which can be used to select and configure discrete time domain control systems, tailor their features to the specific controller device used and generate control libraries with a generic application programming interface (API) to allow fast and seamless integration of the generated source code in custom firmware projects.

PLEASE NOTE

This software is still in a preliminary, experimental state with limited support. All features and functions are subject to change at any time without further notice. Please always refer to the most recent readme.txt file to get updates on features and functions and to review the release history.




Figure 1: z-Domain Configuration Window of the Digital Control Loop Designer SDK

Recommended Literature:

Data sheets and reference manuals are available on <http://www.microchip.com>.

- [dsPIC33EP128GS806 data sheet](#)
- [dsPIC33CH128MP506 data sheet](#)
- [dsPIC33CK256MP506 data sheet](#)
-

Technical Specifications:

Minimum System Requirements:

- Microsoft Windows® 7 32-bit Operating System
- 1 GB RAM
- 24 MB of free hard drive space



Digital Control Loop Designer SDK User Guide

(this page was left blank intentionally)

TABLE OF CONTENTS

Introduction	1
Technical Specifications:.....	1
Recommended Literature:	1
Table of Contents	3
1.0 SOFTWARE OVERVIEW	4
2.0 CONTROLLER CONFIGURATION	9
Controller Selection	9
Why using s-Domain Prototype Filters?	9
Selecting the Right Controller.....	9
Scaling Mode Selection.....	9
Input Data Specification	10
3.0 TIMING ANALYSIS.....	10
4.0 BLOCK DIAGRAM VIEW.....	11
5.0 SOURCE CODE VIEW	11
6.0 CODE GENERATOR OPTIONS	12
7.0 CODE GENERATION.....	14
8.0 USING DCLD with MPLAB® X.....	15
9.0 COMMON USE CASES	16
10.0 LEGAL TERMS FOR DEVELOPMENT BOARDS SOLD AND USED IN EUROPE REGARDING ZVEI REGULATIONS	20
LEGAL NOTICE.....	21
TRADEMARKS.....	21
CONTACT INFORMATION	22

1.0 SOFTWARE OVERVIEW




Figure 2: Digital Control Loop Designer z-Domain Controller Configuration Main Window

TABLE 1: MAIN WINDOW DESCRIPTION

No	Description
1	Controller Order and Number Format Selection
2	Input Data Specification
3	Compensator Configuration
4	Frequency Response (Bode Plot) of s-Domain and z-Domain transfer function
5	Digital Filter Coefficients derivation transcript with accuracy analysis of final values
6	Status bar indicating background activity and output messages

The z-Domain Controller configuration window is ordered into a left configuration plane and a right plane showing the results based on recent settings. Both planes are separated in individual sub-planes (tabs) offering access to settings of individual, functional blocks.

The default view starts with the controller selection and frequency domain configuration on the left and the Bode plot graph of the transfer function on the right. Below the Bode plot a data table shows the derivation transcript of the calculation result. This table is also used to display warnings of the number accuracy analyzer.

Digital Control Loop Designer SDK User Guide




Figure 3: Block Diagram Overview

TABLE 2: BLOCK DIAGRAM OVERVIEW DESCRIPTION

No	Description
1	Controller block diagram with discrete time domain signal waveforms
2	Generic format of s- and z-domain compensator transfer function equivalents
3	Firmware module implementation block diagram and flow-chart

The block diagram overview shows three different block diagrams of the system which is configured by this tool, including system description block diagram, mathematical equations used and the firmware implementation and flow chart of the generated code modules.




Figure 4: Code Generator Configuration and Timing Diagram

TABLE 3: TIMING DIAGRAM OVERVIEW DESCRIPTION

No	Description
1	Code generator configuration option catalog
2	Timing diagram of control loop execution vs. SMPS switching waveform
3	Timing calculation output and target device parameter configuration

Each controller selection and code generation option is impacting the execution time of the control system and thus on the total CPU workload. This view allows the control block analysis and optimization with regards to device speed, core architecture, peripheral features and external physical parameters like switching period and duty ratio.

Digital Control Loop Designer SDK User Guide




Figure 5: Code Generator Output View

TABLE 4: CODE GENERATOR OUTPUT VIEW DESCRIPTION

No	Description
1	Control loop / Code generator configuration option catalog
2	Source code output tab controls (access to output windows of assembly and c-code modules)
3	Source code output window

Once controller and code generation has been configured, the code generator output is displayed in individual output windows for assembly and C-code modules, where the code can be reviewed and edited¹².

¹ user code changes may get overwritten by the generator without warning (see Code Generator Settings)

² code editor has no compiler support




Figure 6: Output Window

TABLE 5: OUTPUT WINDOW DESCRIPTION

No	Description
1	Control loop / Code generator configuration option catalog
2	Source code output tab controls (access to output windows of assembly and c-code modules)
3	Output Window view

The output window is an additional software debugging tool helping to verify proper and reliable output results and offers additional information for troubleshooting software and platform issues. It lists system information, folder settings, user inputs and internal messages during execution.

2.0 CONTROLLER CONFIGURATION

Controller Selection

After application start the main window is starting with the controller selection. All digital controllers supported by this tool are based on discrete time domain transfer functions, which have been derived from continuous time domain transfer function prototypes using the bi-linear transform (BLT).

The continuous time domain prototype transfer functions are based on conventional type I, II, III compensation circuits used in SMPS control systems the industry since the early 1980s. All higher order transfer functions used to create this tool, are mathematically up-scaled versions of the same control approach.

These controllers consist of lead-lag compensators of the n -th order multiplied with a simple integrator term incorporating the gain influence over frequency of the pole at the origin. The only difference between these transfer functions is the order of the lead-lag compensator term, which may include no pole/zero pair at all (1st order) or up to n pole/zero pairs (n -th order).

Why using s-Domain Prototype Filters?

Creating discrete time domain controllers would not necessarily require the deviation of their transfer function from a continuous time domain prototype filter. However, this deviation path allows to establish relations between continuous and discrete time domain control systems, which allows on one side to use the identical design techniques and tools for both systems while still being able to consider, incorporate or compensate for the differences between them.

The z-Domain Configuration Window of the Digital Control Loop Designer SDK takes pole and zero frequency locations to characterize the compensation filter and to adjust the total control loop gain and can therefore directly be applied to frequency domain system models, merging continuous and discrete time domain blocks.

Selecting the Right Controller

The selection of the right controller exclusively depends on the power supply plant and control mode used. In any case the controller selection depends on the number of poles and zeros required within the controller to compensate for poles and zeros of the power supply plant. The controller selection offers six orders:

- **1P1Z:**
1st order with integrator and no pole/zero pair
- **2P2Z:**
2nd order with integrator and one pole/zero pair
- **3P3Z:**
3rd order with integrator and two pole/zero pairs
- **4P4Z:**
4th order with integrator and three pole/zero pairs
- **5P5Z:**
5th order with integrator and four pole/zero pairs
- **6P6Z:**
6th order with integrator and five pole/zero pairs

Every pole and zero location can be set by either moving the respective pole or zero indicator in the Bode plot using the mouse pointer or edit the frequency in the respective entry boxes below the controller selection.

Scaling Mode Selection

Each controller design is a tradeoff between performance and accuracy. With increased number space the result accuracy can be enhanced. Enhanced accuracy, however, requires more CPU cycles for the computation. To solve these tradeoffs easily, the z-Domain Configuration Window offers four different scaling mode for each controller type:

- **Single Bit-Shift Scaling**
Highest performance is achieved by directly utilizing the fixed-point DSP core of the dsPIC® DSC by scaling all filter coefficients with the very same scaling factor. The factor scaling is implemented by shifting the number bit code to

the right (divide by power of 2) or left (multiply by power of 2). This scaling method is sufficient for a wide variety of applications with standard topologies.

- **Single Bit-Shift with Output Factor Scaling**

Occasionally coefficients with single fixed scalars may be affected by accuracy limitations, which, in the worst case, could corrupt the convolution process of the digital filter and negatively affect the error integration.

In this scaling mode one additional factor is added and all coefficients are rescaled to minimize the number error.

- **Dual Bit-Shift Scaling**

The single bit-shifting more with output factor scaling may come short, when coefficients of filter terms A and B vary significantly in size. For these conditions the Dual Bit Shift Mode was introduced, which applies two different scalars for A and B term coefficients. The performance impact is very similar to the Single Bit-Shift with Output Factor Scaling.

- **Fast Floating Point Coefficient Scaling**

Fast floating point numbers have re-ordered binary encoding. This number format is different from conventional IEEE 754 floating point numbers to optimize the computation process on fixed-point DSP cores. This number format computation is the most accurate but also most intensive in terms of CPU cycles.

The recommended process of determining the best scaling mode is to start from single bit-shifting, observing the coefficient output window below the Bode plot. Should one or more coefficients exceed 0.5% error, it will be marked in yellow (warning level), if the inaccuracy exceeds 1.0%, it will be marked red (error level).

Should any of these warning appear, increase the scaling option until all warning disappear. Observe the timing diagram on the right, to keep track on the CPU load and overall timing alignment.

Input Data Specification

This section is used to normalize the input data to the computation engine. The input data range needs to meet the number format of controller to prevent gain mismatches between model and desired control output. This usually strictly refers to the number bit resolution.

Additionally the Input Data Specification offers three additional options accounting for physical signal scaling:

- **Input Data Gain**

Assuming the input data is coming from an analog-to-digital converter (ADC) reading a pre-conditioned analog signal, the gain of the signal conditioning circuit can be entered here (e.g. reading voltage from a voltage divider).

As a result, the Bode plot graph on the right will show the impact on the frequency response of the controller (gains < 1 will drop the gain, gains > 1 will increase the gain)

- **Input Signal Gain Compensation**

In case the input data gain is different from 1, this option will automatically increase/decrease the gain of the controller to compensate for the physical signal gain. If this option is not selected, gain variations have to be compensated by manual adjustments of the Cross-over frequency of the pole at the origin.

- **Input Data Offsets in Bi-Directional Control Systems**

By selecting this option the input data is assumed to have a zero-point offset. This offset needs to be specified to allow positive and negative input data values.

3.0 TIMING ANALYSIS

In addition to the frequency response chart (Bode plot) a Timing graph is provided, showing the switching period and on-time of the nominal switching signal (blue), the ADC conversion time

(orange) and the control loop execution (red) based on the most recent settings.

The switching waveform, ADC timing parameters and CPU speed can be entered underneath the Timing graph. The graph shows the position of data acquisition events, control loop call events, READ and WRITE BACK events along the switching period.

Controller selection, Scaling Mode selection and Code Generation options influence the timing alignment. In high-speed systems this graph can help to analyze the estimated CPU load added by the recently configured controller and help to find the right tradeoff between performance and accuracy.

For more precise analysis the cursor can be used to measure relative time between events by moving/placing the cursor cross within the timing graph.

Additional presets allow to quickly position data acquisition triggers at common trigger points within the switching period (e.g. at 50% on-time, 50% off-time or at the beginning of the switching cycle).

It's also possible to place the trigger at any point by dragging the trigger cursor to the left/right to fine-tune trigger offsets.

4.0 BLOCK DIAGRAM VIEW

The block diagram view is static and will not reflect details of the most recent settings. Its purpose is to reflect the system level covered by the z-Domain Configuration Window.

The first view shows a high-level block diagram of the controller with its discrete time domain input signals and processing path.

The second section shows the continuous time domain transfer function equation and the resulting discrete time domain transfer function equation as reference.

The third section shows the controller implementation block diagram and flow chart.

5.0 SOURCE CODE VIEW

The Source Code View covers multiple sub windows for every generated code module. The generated control library source code provides four different files:

- **Optimized Assembly Code**

All runtime functions are generated as optimized assembly routines. These routines read data from and write data to a data structure (`cNPNZ16b_t`), which holds all parameters and pointers to Special Function Registers (SFRs) used by the library. This data is loaded into the data structure by the C-domain initialization code. Depending on code generator options selected, additional information will be written to the data structure, from which C-domain application code can gain access (e.g. status bits, most recent calculation results, etc.)

- **C-Source File**

The C-source file contains the static set of filter coefficients and the data structure initialization function of this individual controller.

PLEASE NOTE

The C source initialization routine only initializes the digital filter coefficients and number scaling settings. Controller/system-specific parameters like anti-windup thresholds, source and target registers as well as ADC trigger offsets must be set in user code!

- **C-Header File**

The C-header file holds all public variable and function declarations of this individual controller, which need to be accessible from application code.

- **C-Library Header File**

The library header is generic and would only have to be added once, even if the control system is based on multiple, individual controllers. This file also holds the declaration of the `cNPNZ16b_t` data structure. This data structure is the sole access

point to configure, control and monitor the controller block.

PLEASE NOTE

The `CNPZN16b_t` data structure declared in the library header file may be different for different scaling modes and code generator options. When controllers with fundamentally different configuration sare used, conflicts may occur.

6.0 CODE GENERATOR OPTIONS




Figure 7: Code Generator Options

The code generator offers several options helping to tailor the code implementation, features and overall timing to application specific needs.

FILE & FUNCTION LABEL

Variable, control loop object and file names are using the control loop label specified here. The automatically generated label may not be unique or may not reflect the function the control loop serves within the application code.

This label can be changed here to enhance the flexibility and compatibility with user application code.

- **Overwrite Default Controller Name Prefix**

this option will replace the automatically generated label used for file names and function calls.

- **Overwrite Default variable Name Prefix**

When selected, this option will also replace the name prefix of all global variables, tying them more closely to the controller block configured by this application (mandatory when building multi-loop systems to prevent naming conflicts)

Please observe the C-source file generator output to see how name prefixes change.

Save/Restore Context

Across device families there are different features which can be utilized to reduce interrupt latency by handling context save and restore processes in silicon or software. For example, dsPIC33FJ DSCs only have one set of shadow registers where working registers (WREGs) need to be pushed to and popped from individually. dsPIC33EP, in comparison, offer additional sets of alternative working registers where the recent context can be swapped over to in a single CPU cycle. dsPIC33CH and dsPIC33CK have even further extended features including DSP accumulators and the core configuration register.

Depending on which feature is used in which application code context, one may or may not have to save and restore certain registers and settings. By selecting specific options from this option list, code

Digital Control Loop Designer SDK

User Guide



for saving and restoring will be added/removed from the generated assembly code file.

PLEASE NOTE

All these settings need to be configured individually using dedicated SFRs and configuration bits. These configuration steps are not included by this code generator

- **Shadow Registers**

covering working registers WREG to WREG 3 only. These registers usually hold function parameters like the start address of the `cNPNZ16b_t` data structure.

- **MAC Working Registers**

covering working registers WREG4 through WREG10 used for the filter computation.

- **Accumulators**

if the DSP core is used by other application code modules, it may be that the DSP accumulator contents need to be kept available. As the generated controller library will always start with a cleared accumulator and leave the result in the accumulator until the next computation step, it will not be affected by other code modules changing the content of the accumulators. In return, however, these control libraries will override any contents of accumulators which have been stored previously.

- **Core Status Register**

The core status register may hold information about active calculation status bits any may therefore be affected by computations run by the control library. If any additional application code module may rely on this information, this register needs to be saved and restored.

- **Core Configuration Register**

The control library computation requires a specific DSP configuration to run the control code most efficiently. If the DSP is used by any other application code module, which may use a different core configuration, this register needs to be saved, changed and restored.

Optional Features

This section can be used to add specific, generic features to the control code, which will be embedded in the assembly code for most efficient execution.

- **Add Core Configuration**

This option may need to be selected if other application code modules are using the DSP with different configurations.

If it is sufficient to go with one DSP configuration for the entire application, it is recommended to configure the core in a separated initialization routine executed during startup rather than changing the contents of the core configuration in every control loop execution call.

- **Add Enable/Disable Switch**

When enabled, this option will add a status bit to the `cNPNZ16b_t` data structure. This enable bit will be checked before every execution of the control update library code. When disabled, the control code will be bypassed and no data will be read nor written. When disabled, the histories will be frozen to their latest state, the last control output will remain as a constant, no ADC buffer reads and no output anti-windup (if selected) will be performed.

- **Add Input Normalization**

dsPIC33FJ, dsPIC33EP, dsPIC33CH and dsPIC33CK ADC converters offer different data format options. Further data format may be different when multiple compensators are coupled in multi-loop systems. To deal with these differences in number scaling, the input data may or may not have to be normalized during the execution of the control loop code.

- **Add ADC Trigger Placement**

Control loops, which depend on a precise ADC trigger point which needs to be synchronized to varying duty cycles or periods, will need the ADC trigger to be repositioned with the control output. This option should be selected to account for these requirements and execute the repositioning in the most efficient way

• Create Local Copies

To allow other application code modules to track and monitor internal data, which will not be accessible from external code otherwise, local copies of specific data points can be copied to the data structure, through which they get published globally. These data points are

- Most recent ADC sample
- Most recent error
- Most recent control output

Anti-Windup

Digital controllers can clamp the control output to a user defined level. When using number clamping, the control history will be clamped at the defined maximum value without saturation effects known from analog control systems. When a digital controller with proper anti-windup clamping is used and the control loop hits output limits (minimum or maximum), it will be clamped there. When the system recovers the control loop will start to respond immediately.

• Clamp Control Output Maximum

The control output will be monitored and clamped to a maximum value when exceeded

• Generate Upper Saturation Status Flag Bit

When the control output gets overwritten by the defined maximum value, a status bit will be set within the status word of the controller to allow external application code modules to detect the saturation condition and respond to it accordingly.

• Clamp Control Output Minimum

The control output will be monitored and clamped to a minimum value when underrun.

• Generate Lower Saturation Status Flag Bit

When the control output gets overwritten by the defined minimum value, a status bit will be set within the status word of the controller to allow external application code modules to detect the saturation condition and respond to it accordingly.

7.0 CODE GENERATION

The code generator does not generate output files by default. This process must be deliberately executed by the user.

Figure 8 shows the file location entry on to of every generated code file (assembly source, C-source, C-header and library header). Use this entry text box to declare the path to the directory in which the generated code file should be generated in.




Figure 8: Source Code File Target Directory Declaration

Once all file locations have been declared, code can be generated by clicking on Tools → Export Generated Files → Export Files.




Figure 9: Code Generator Menu

If you'd like to restrict the generation of files to individual items, use the check box list within the same menu to determine which files should be generated. (see Figure 9)

PLEASE NOTE

The file location declarations also support relative file paths. The root path to which relative target paths are referred to is the physical file location of the recently opened DCLD configuration file.

Digital Control Loop Designer SDK

User Guide



8.0 USING DCLD WITH MPLAB® X

When installing DCLD on a Windows® computer, the setup program will associate the file type *.dcl with the Digital Control Loop Designer application executable DCLD.exe.

When you use this tool to create a control library for your dsPIC® project, the DCLD configuration file can be included in your MPLAB® X project files to ease access while working on application code.

Adding DCLD Configuration Files to MPLAB® X

The recommended procedure to add DCLD configuration files to your project is to place them in the *Important Files* folder, which is automatically created with the new project. This folder is also the home of the *Makefile* used by compiler and linker to build the project.




Figure 10: Adding DCLD Configuration Files to a Project

Right-click on the **Important Files** folder in the project manager and select **Add Item to Important Files**.




Figure 11: Select the DCLD Configuration File

From the File Browser dialog, select the DCLD configuration file which should be added to the project and click **Open**.

The selected DCLD configuration file will now be shown in the **Important Files** folder in the **Project Manager**. You can now open and access DCLD from the Project Manager view in MPLAB® X.

If you'd like to add multiple configurations for more than one control loop, repeat the described process until all control loop configurations for this project have been added.

PLEASE NOTE

When creating multi-loop systems, each loop must have a unique name to prevent conflicts between files, variables and objects.

Opening DCLD from MPLAB® X Project Manager

When a control loop needs to be reconfigured during the development process, you can open the DCLD GUI directly from MPLAB® X Project Manager by following these steps:




Figure 12: Opening DCLD from the MPLAB® X Project Manager

Right-click on the DCLD configuration file in the MPLAB® X Project Manager and click on **Open in System**. This will open your saved DCLD configuration in the DCLD GUI where you can modify your configuration.

When your edits to the settings are complete, click on Generate Files to update the control loop project files. MPLAB® X will immediately recognize the changed files and refresh them. The project can then be immediately be built without further steps. The

DCLD GUI can remain open to make further adjustments, if necessary.

9.0 COMMON USE CASES

Depending on how complex the control system is you try to create, DCLD offers multiple options to only create content that's essentially required without wasting Flash memory of the target device.

The DCLD code generators is by default creating the following four essential library files described in 5.0 SOURCE CODE VIEW.

- **Assembly Library File**
- **Library C-Source File**
- **Library C-Header Files**
- **Generic Library Header File**

When creating a single-loop control system, all four files are required for a proper implementation of the control loop library code. In multi-loop systems, however, it might be beneficial to limit the number of generated files to save memory space in the target device.

Multiple Controllers using the same Assembly Code

A most common use-case are average current controllers consisting of an outer voltage loop and an inner current loop. Usually both controllers are of Type II (2P2Z in digital) so that only one assembly library but multiple sets of coefficients as well as controller history arrays would be required.

In this case it's recommended to create two independent DCLD configuration files (one for the voltage loop and one for the current loop).

One of both configuration files needs to use the default setting, which will export all four library files. For every additional loop *based on the same compensator type, using the same number scaling method and code feature options*, it's only required to export the C-Source and C-Header file containing the coefficient and controller object declarations.

Digital Control Loop Designer SDK

User Guide



This can be configured individually by clicking on menu Tools → Export Generated Files. The File Export context menu offers options for every individual file to be exported or not (see




Figure 13)




Figure 13: Selecting Files to be Exported

In this example, only the C-Header and C-Source File will be exported.

PLEASE NOTE

Function name labels of the initially generated assembly code will be determined by the DCLD configuration which was used to generate them.

When assembly files are used for multiple controllers, make sure the function calls placed in user code use the correct function name labels and hand over the correct pointer to the individual controller object.

For Example:

```
my_controller_Update(&controller_A);  
    (...)  
my_controller_Update(&controller_B);  
    (...)  
my_controller_Update(&controller_C);
```

Limitations

Using generated code for multiple loops has some limitation which need to be kept in mind to prevent

address errors and other undesired conflicts. Preventing these conflicts is the full responsibility of the user!

• Main Filter Type Implementation

The selected compensator type (e.g. 2P2Z, 3P3Z, 4P4Z, etc.) will be used as template to determine how many filter iterations will be executed by the assembly code library block. To make this most efficient in terms of execution time, no dynamic adjustment to different filter types is made. Thus the generated assembly library only supports the filter type selected.

• Scaling Options

Different scaling options will equally result in incompatible code when used by different controller objects, which are not using the same number scaling format. Scaling factors, number normalization and resolution differ significantly depending on the selection made. Using controller objects configured for different scaling options therefore cannot use the same assembly library.

• Code Features

Code feature selection will have an equally vital impact on the code integrity but does not necessarily exclude multiple controller object from using the same assembly library.

Assuming multiple controller objects are built using the same controller/filter type and number-scaling method, but one controller needs anti-windup clamping while the other controller doesn't. In this case it is still possible to use the same assembly library, which, however, will always execute the anti-windup code block. Thus, the second controller needs to hold reasonable thresholds in its respective data structure spaces to not get cut off by clamping-to-zero.

• Context Save/Restore

As long as all controller objects are based on the same compensator/filter type and using the same number scaling method, context save/restore options should be consistent. Nevertheless, if alternate working registers (ALTWREG) on dsPIC33EP, dsPIC33CH or dsPIC33CK are used,

it is important to verify that all control library function calls like `xxx_Update(yyy)` are called on the same interrupt priority with a properly associated ALWREG set. These ALTWREG sets can be different but must be accessible and changes to the working registers must not result in conflicts with other tasks.

Digital Control Loop Designer SDK

User Guide



10.0 LEGAL TERMS FOR DEVELOPMENT BOARDS SOLD AND USED IN EUROPE REGARDING ZVEI REGULATIONS

IMPORTANT NOTICE TO CUSTOMERS

Boards marked as “NON-PUBLIC CONCEPT BOARD” are NOT part of Microchip’s usual development tool portfolio and no support is provided through Microchip’s common support channels. Changes may be applied without any further notice.

This specific hardware has been developed as proof-of-concept board or for training purposes for PROFESSIONAL USERS ONLY. You are not allowed to use this development board in any real application and others than professional lab environments. This board has not been certified or tested for any standards or any requirement such like EMC or safety.

SOFTWARE LICENSE AGREEMENT

Copyright © 2012 Microchip Technology Inc. All rights reserved.

Microchip licenses to you the right to use, modify, copy and distribute Software only when embedded on a Microchip microcontroller or digital signal controller, which is integrated into your product or third party product (pursuant to the sublicense terms in the accompanying license agreement). You should refer to the license agreement accompanying this Software for additional information regarding your rights and obligations. SOFTWARE AND DOCUMENTATION ARE PROVIDED "AS IS" WITHOUT WARRANTY OF ANY KIND, EITHER EXPRESS OR IMPLIED, INCLUDING WITHOUT LIMITATION, ANY WARRANTY OF MERCHANTABILITY, TITLE, NON-INFRINGEMENT AND FITNESS FOR A PARTICULAR PURPOSE. IN NO EVENT SHALL MICROCHIP OR ITS LICENSORS BE LIABLE OR OBLIGATED UNDER CONTRACT, NEGLIGENCE, STRICT LIABILITY, CONTRIBUTION, BREACH OF WARRANTY, OR OTHER LEGAL EQUITABLE THEORY ANY DIRECT OR INDIRECT DAMAGES OR EXPENSES INCLUDING BUT NOT LIMITED TO ANY INCIDENTAL, SPECIAL, INDIRECT, PUNITIVE OR CONSEQUENTIAL DAMAGES, LOST PROFITS OR LOST DATA, COST OF PROCUREMENT OF SUBSTITUTE GOODS, TECHNOLOGY, SERVICES, OR ANY CLAIMS BY THIRD PARTIES (INCLUDING BUT NOT LIMITED TO ANY DEFENSE THEREOF), OR OTHER SIMILAR COSTS.

Digital Control Loop Designer SDK

User Guide



LEGAL NOTICE

Information contained in this publication regarding device applications and the like is provided only for your convenience and may be superseded by updates. It is your responsibility to ensure that your application meets with your specifications.

MICROCHIP MAKES NO REPRESENTATIONS OR WARRANTIES OF ANY KIND WHETHER EXPRESS OR IMPLIED, WRITTEN OR ORAL, STATUTORY OR OTHERWISE, RELATED TO THE INFORMATION, INCLUDING BUT NOT LIMITED TO ITS CONDITION, QUALITY, PERFORMANCE, MERCHANTABILITY OR FITNESS FOR PURPOSE.

Microchip disclaims all liability arising from this information and its use. Use of Microchip devices in life support and/or safety applications is entirely at the buyer's risk, and the buyer agrees to defend, indemnify and hold harmless Microchip from any and all damages, claims, suits, or expenses resulting from such use. No licenses are conveyed, implicitly or otherwise, under any Microchip intellectual property rights.

TRADEMARKS

The Microchip name and logo, the Microchip logo, Accuron, dsPIC, KEELOQ, KEELOQ logo, MPLAB, PIC, PICmicro, PICSTART, rPIC and SmartShunt are registered trademarks of Microchip Technology Incorporated in the U.S.A. and other countries.

FilterLab, Linear Active Thermistor, MXDEV, MXLAB, SEEVAL, SmartSensor and The Embedded Control Solutions Company are registered trademarks of Microchip Technology Incorporated in the U.S.A.

Analog-for-the-Digital Age, Application Maestro, CodeGuard, dsPICDEM, dsPICDEM.net, dsPICworks, dsSPEAK, ECAN, ECONOMONITOR, FanSense, In-Circuit Serial Programming, ICSP, ICEPIC, Mindi, MiWi, MPASM, MPLAB Certified logo, MPLIB, MPLINK, mTouch, PICkit, PICDEM, PICDEM.net, PICtail, PIC32 logo, PowerCal, PowerInfo, PowerMate, PowerTool, REAL ICE, rLAB, Select Mode, Total Endurance, UNI/O, WiperLock and ZENA are trademarks of Microchip Technology Incorporated in the U.S.A. and other countries. SQTP is a service mark of Microchip Technology Incorporated in the U.S.A. All other trademarks mentioned herein are property of their respective companies.

© 2012, Microchip Technology Incorporated, All Rights Reserved.

QUALITY MANAGEMENT SYSTEM
CERTIFIED BY DNV
== ISO/TS 16949 ==

Microchip received ISO/TS-16949:2009 certification for its worldwide headquarters, design and wafer fabrication facilities in Chandler and Tempe, Arizona; Gresham, Oregon and design centers in California and India. The Company's quality system processes and procedures are for its PIC® MCUs and dsPIC® DSCs, KEELOQ® code hopping devices, Serial EEPROMs, microperipherals, nonvolatile memory and analog products. In addition, Microchip's quality system for the design and manufacture of development systems is ISO 9001:2000 certified.



Digital Control Loop Designer SDK User Guide

CONTACT INFORMATION

Corporate Office

2355 West Chandler Blvd.

Chandler, AZ 85224-6199

Tel: 480-792-7200 • Fax: 480-792-7277

Technical Support:

<http://www.microchip.com/support>

Web Address:

www.microchip.com

AMERICAS

Atlanta

Duluth, GA

Tel: 678-957-9614

Fax: 678-957-1455

Boston

Westborough, MA

Tel: 774-760-0087

Fax: 774-760-0088

Chicago

Itasca, IL

Tel: 630-285-0071

Fax: 630-285-0075

Cleveland

Independence, OH

Tel: 216-447-0464

Fax: 216-447-0643

Dallas

Addison, TX

Tel: 972-818-7423

Fax: 972-818-2924

Detroit

Farmington Hills, MI

Tel: 248-538-2250

Fax: 248-538-2260

Indianapolis

Noblesville, IN

Tel: 317-773-8323

Fax: 317-773-5453

Los Angeles

Mission Viejo, CA

Tel: 949-462-9523

Fax: 949-462-9608

Santa Clara

Santa Clara, CA

Tel: 408-961-6444

Fax: 408-961-6445

Toronto

Mississauga, Ontario,

Canada

Tel: 905-673-0699

Fax: 905-673-6509

ASIA/PACIFIC

Asia Pacific Office

Suites 3707-14, 37th Floor

Tower 6, The Gateway

Harbour City, Kowloon

Hong Kong

Tel: 852-2401-1200

Fax: 852-2401-3431

Australia - Sydney

Tel: 61-2-9868-6733

Fax: 61-2-9868-6755

China - Beijing

Tel: 86-10-8569-7000

Fax: 86-10-8528-2104

China - Chengdu

Tel: 86-28-8665-5511

Fax: 86-28-8665-7889

China - Chongqing

Tel: 86-23-8980-9588

Fax: 86-23-8980-9500

China - Hangzhou

Tel: 86-571-2819-3187

Fax: 86-571-2819-3189

China - Hong Kong SAR

Tel: 852-2401-1200

Fax: 852-2401-3431

China - Nanjing

Tel: 86-25-8473-2460

Fax: 86-25-8473-2470

China - Qingdao

Tel: 86-532-8502-7355

Fax: 86-532-8502-7205

China - Shanghai

Tel: 86-21-5407-5533

Fax: 86-21-5407-5066

China - Shenyang

Tel: 86-24-2334-2829

Fax: 86-24-2334-2393

China - Shenzhen

Tel: 86-755-8203-2660

Fax: 86-755-8203-1760

China - Wuhan

Tel: 86-27-5980-5300

Fax: 86-27-5980-5118

China - Xian

Tel: 86-29-8833-7252

Fax: 86-29-8833-7256

China - Xiamen

Tel: 86-592-2388138

Fax: 86-592-2388130

China - Zhuhai

Tel: 86-756-3210040

Fax: 86-756-3210049

ASIA/PACIFIC

India - Bangalore

Tel: 91-80-3090-4444

Fax: 91-80-3090-4123

India - New Delhi

Tel: 91-11-4160-8631

Fax: 91-11-4160-8632

India - Pune

Tel: 91-20-2566-1512

Fax: 91-20-2566-1513

Japan - Osaka

Tel: 81-66-152-7160

Fax: 81-66-152-9310

Japan - Yokohama

Tel: 81-45-471- 6166

Fax: 81-45-471-6122

Korea - Daegu

Tel: 82-53-744-4301

Fax: 82-53-744-4302

Korea - Seoul

Tel: 82-2-554-7200

Fax: 82-2-558-5932 or

82-2-558-5934

Malaysia - Kuala Lumpur

Tel: 60-3-6201-9857

Fax: 60-3-6201-9859

Malaysia - Penang

Tel: 60-4-227-8870

Fax: 60-4-227-4068

Philippines - Manila

Tel: 63-2-634-9065

Fax: 63-2-634-9069

Singapore

Tel: 65-6334-8870

Fax: 65-6334-8850

Taiwan - Hsin Chu

Tel: 886-3-5778-366

Fax: 886-3-5770-955

Taiwan - Kaohsiung

Tel: 886-7-536-4818

Fax: 886-7-330-9305

Taiwan - Taipei

Tel: 886-2-2500-6610

Fax: 886-2-2508-0102

Thailand - Bangkok

Tel: 66-2-694-1351

Fax: 66-2-694-1350

EUROPE

Austria - Wels

Tel: 43-7242-2244-39

Fax: 43-7242-2244-393

Denmark - Copenhagen

Tel: 45-4450-2828

Fax: 45-4485-2829

France - Paris

Tel: 33-1-69-53-63-20

Fax: 33-1-69-30-90-79

Germany - Munich

Tel: 49-89-627-144-0

Fax: 49-89-627-144-44

Italy - Milan

Tel: 39-0331-742611

Fax: 39-0331-466781

Netherlands - Drunen

Tel: 31-416-690399

Fax: 31-416-690340

Spain - Madrid

Tel: 34-91-708-08-90

Fax: 34-91-708-08-91

UK - Wokingham

Tel: 44-118-921-5869

Fax: 44-118-921-5820

Digital Control Loop Designer SDK

User Guide



NOTES: