
# Clarke Variable Transformation

# **Description**

Converts balanced three phase quantities into balanced two phase quadrature quantities.



**Availability** 

This IQ module is available in one interface format:

1) The C interface version

**Module Properties** 

Type: Target Independent, Application Independent

Target Devices: 28x Fixed Point or Piccolo

C Version File Names: clarke.h

IQmath library files for C: IQmathLib.h, IQmath.lib

#### C Interface

### **Object Definition**

The structure of CLARKE object is defined by following structure definition

typedef CLARKE \*CLARKE\_handle;

Item	Name	Description	Format <sup>*</sup>	Range(Hex)
Innuto	As	Phase 'a' component of the balanced three phase quantities	GLOBAL_Q	80000000-7FFFFFF
Inputs	Bs	Phase 'b' component of the balanced three phase quantities	GLOBAL_Q	80000000-7FFFFFF
Outputs	Alpha	Direct axis(d) component of the transformed signal	GLOBAL_Q	80000000-7FFFFFF
	Beta	Quadrature axis(q) component of the transformed signal	GLOBAL_Q	80000000-7FFFFFF

GLOBAL Q valued between 1 and 30 is defined in the IQmathLib.h header file.

## **Special Constants and Data types**

### **CLARKE**

The module definition is created as a data type. This makes it convenient to instance an interface to the Clarke variable transformation. To create multiple instances of the module simply declare variables of type CLARKE.

### **CLARKE** handle

User defined Data type of pointer to CLARKE module

### **CLARKE DEFAULTS**

Structure symbolic constant to initialize CLARKE module. This provides the initial values to the terminal variables as well as method pointers.

### Methods

### CLARKE MACRO(CLARKE handle);

This definition implements one method viz., the Clarke variable transformation computation macro. The input argument to this macro is the module handle.

## Module Usage

# Instantiation

The following example instances two CLARKE objects CLARKE clarke1, clarke2;

### Initialization

```
To Instance pre-initialized objects
CLARKE clarke1 = CLARKE_DEFAULTS;
CLARKE clarke2 = CLARKE_DEFAULTS;
```

# Invoking the computation macro

```
CLARKE_MACRO (clarke1);
CLARKE_MACRO (clarke2);
```

# **Example**

The following pseudo code provides the information about the module usage.


```
main()
{
}
void interrupt periodic_interrupt_isr()
        clarke1.As = as1;
                                        // Pass inputs to clarke1
       clarke1.Bs = bs1;
                                        // Pass inputs to clarke1
       clarke2.As = as2;
                                        // Pass inputs to clarke2
                                        // Pass inputs to clarke2
       clarke2.Bs = bs2;
       CLARKE_MACRO (clarke1);
                                        // Call compute macro for clarke1
       CLARKE_MACRO (clarke2);
                                        // Call compute macro for clarke2
       ds1 = clarke1.Alpha;
                                        // Access the outputs of clarke1
       qs1 = clarke1.Beta;
                                        // Access the outputs of clarke1
       ds2 = clarke2.Alpha;
                                        // Access the outputs of clarke2
       qs2 = clarke2.Beta;
                                        // Access the outputs of clarke2
}
```

## **Technical Background**

Implements the following equations:

$$\begin{cases} Id = Ia \\ Iq = (2Ib + Ia) / \sqrt{3} \end{cases}$$

This transformation converts balanced three phase quantities into balanced two phase quadrature quantities as shown in figure below:



The instantaneous input and the output quantities are defined by the following equations:

$$ia = I \times \sin(\omega t)$$
 $ib = I \times \sin(\omega t + 2\pi/3)$ 
 $ic = I \times \sin(\omega t - 2\pi/3)$ 

$$\begin{cases} id = I \times \sin(\omega t) \\ iq = I \times \sin(\omega t + \pi/2) \end{cases}$$
lb
$$\begin{cases} ia = I \times \sin(\omega t) \\ id = I \times \sin(\omega t) \\$$

Next, Table 1 shows the correspondence of notations between variables used here and variables used in the program (i.e., clarke.c, clarke.h). The software module requires that both input and output variables are in per unit values.

	Equation Variables	Program Variables
Inputs	ia	As
-	ib	Bs
Outputs	id	Alpha
	iq	Beta

Table 1: Correspondence of notations