

Advanced Sender Codes

Callable Functions

Most functions start in the form of `##<function-name>(data to function)##`

url

`##url()##` : url encodes anydata passed to it

Example: `##url(https://google.com###victimemail##)##`

base64

`##base64()##` : base64 encodes anydata passed to it

Example: `##base64(Any random data)##`

censor

`##censor()##` : censors/redact any email passed to it

Example: `##censor(##victimemail##)##`

`##censor(test@domain.com)##`

randomise

`###(<word1>|<word2>|...<word(n)>)###` : Randomly choses between given words or data

Example: `###(google|aol|yahoo)###` : will randomly pick between google,aol,yahoo

`###(Nigga|Lorem ipsum|This is a data also)###`

can work for html data too

`###(<p class="##randchar4"><\p> |
<\span>)###`

[Replacable Codes](#)

Most replaces are in the form of `##<replaceable>##`

Tip: if you put wrong replaceable, sender will let you know

##victimdomain## : The processed domain of the recipient, not the full domain

if there be any special character it gets removed and the name gets converted to case

Example: (test@domain.com) => Domain

(test@company-domain.com.in) => Company Domain

(test@another-domain.com.in) => Another Domain

##victimfulldomain## : The full domain of the recipient, the unprocessed domain

Example: (test@domain.com) => domain.com

(test@another-domain.com.au) => another-domain.com.au

##victimname## : The processed name of the recipient
if there be any special character it gets removed and the name gets converted to case

Example: (test@domain.com) => Test

(victor.darwin@another-domain.com.au) => Victor Darwin

(b-stewart@a-random-domain.com) => B Stewart

##victimemail## : The email of the recipient

##victimb64email## : The base64 encoded email of the recipient

##victimb64emailnp## : The base64 encoded email of the recipient

But the "np" stands for no padding, that means remove any trailing =

##victimhexemail## : The hex encoded email of the recipient
Usually in cases you dont want to get caught using email raw or base64 email

Example: (test@domain.com) => 7465737440646f6d61696e2e636f6d

##victimdomainlogo## : The html version of the branded logo of the recipient

Usually in cases where you want to brand or letter head your logo

Example: will result to

##victimrealdomain## : The real name of the recipient's domain

it's similar to ##victimdomain## but it's different

This fetches the real name of the recipient's domain from the database

Example: (test@domain2.com) => Domain2 Inc.

##victimdomainlogosrc## : This gets the base64 value of the victim's domain

Example: () =>

##victimobfhexemail## : The obfuscated encoded hex email of the recipient

##victimb64domain## : The base64 encoded domain of the recipient

##victimb64name## : The base64 encoded name of the recipient

##myname## : The processed name of the sender
if there be any special character it gets removed and the name gets converted to case

##mydomain## : The processed domain of the sender
if there be any special character it gets removed and the name gets converted to case

##link## : The value of the link in the "LINK=" field in config

##linkb64## : The base64 value of the link in the "LINK=" field in config

##qrcode## : The qrcode image of the link in the "LINK=" field in config
Usually in html tag
Example: will result in

##qrcoodedata## : The base 64 value of the qrcode image of the link in the "LINK=" field in config
Example: () =>
(##qrcoodedata##) => data:image/png;base64,...

##date(n)## : Generates the date attribute of the given (n)
Example: ##date## : e.g wednesday-April-2024 15:09 PM
##date1## : e.g wednesday/April/2024 15:09 PM
##date2## : e.g wednesday April 2024
##date3## : e.g April 2024
##date4## : e.g 15:09

```
##date5## : e.g Wednesday  
##date6## : e.g April  
##date7## : e.g 2024  
##date8## : e.g 20/04/24  
##date9## : e.g 20/Apr/2024
```

##num(count)## : Generates a random number of the given count

Example:

```
##num1## => generates a random number  
##num2## => generates two random numbers  
##num3## => generates three random numbers
```

•
•
•

```
##num(n)## => generates (n) random nummber(s)
```

##stringlower(count)## : Generates a random lower case string of the given count

Example:

```
##stringlower1## => generates a random Lower Case String  
##stringlower2## => generates two random Lower Case Strings  
##stringlower3## => generates two three Lower Case Strings
```

•
•
•

```
##stringlower(n)## => generates (n) random Lower Case  
String(s)
```

##stringupper(count)## : Generates Upper case strings of the given count

Example:

```
##stringupper1## => generates a random Upper Case String  
##stringupper2## => generates two random Upper Case Strings
```

`##stringupper3##` => generates three random Upper Case Strings

.

.

.

`##stringupper(n)##` => generates (n) random Upper Case String(s)

`##randchar(count)##` : Generates random characters of the given count

Example:

`##randchar1##` => generates a random string

`##randchar2##` => generates two random strings

`##randchar3##` => generates three random strings

.

.

.

`##randchar(n)##` => generates (n) random string(s)

`##random(tag)##` : Generates a random of the given tag

Example: `##randomip##` : Random Ip address

`##randomemail##` : Random Company Email

`##randomemail##` : Random Email

`##randomdname##` : Random Name

`##randomaddress##` : Random Street Address

`##randomcountry##` : Random Country

`##randomcountrycode##` : Random Country Code

`##randomcity##` : Random City

`##randomfname##` : Random First name

`##randomlname##` : Random Last name

`##randomname##` : Random Full Name

`##randomdevice##` : Random device

`##randomuseragent##` : Random Browser

`##randombrowser##` : Random Browser

