2022-04-14 22:38:35 - Validation Report

Supported Role-Types:

Management - Fail

Compute (Standard) - Fail

Compute (SDN) - Fail

Storage - Fail

Feature Test Result List:

Feature	BGP
Result	Pass
Log	
RoleType	Compute (SDN)
Feature	VLAN
Result	Fail
Log	No VLAN detected, please check the VLAN configuration on switch
RoleType	Management, Compute (Standard), Compute (SDN), Storage
Feature	DHCP - Relay Agent IP
Result	Pass
Log	
RoleType	Management
Feature	LLDP - Port VLAN ID (Subtype = 1)
Result	Pass
Log	
RoleType	Management
Feature	LLDP - VLAN Name (Subtype = 3)
Result	Fail
Log	LLDP Subtype3 not detected from switch
RoleType	Compute (Standard), Compute (SDN), Storage
Feature	LLDP - Maximum Frame Size (Subtype = 4)
Result	Fail
Log	LLDP Subtype4 Mismatch, please check switch MTU configuration - Detect: 9216, but Input: 9214

RoleType	Compute (Standard), Compute (SDN), Storage
Feature	LLDP - Link Aggregation (Subtype = 7)
Result	Pass
Log	
RoleType	Management, Compute (Standard), Compute (SDN), Storage
Feature	LLDP - ETS Maximum Number of Traffic Classes (Subtype = 9)
Result	Pass
Log	
RoleType	Storage
Feature	LLDP - ETS Class Bandwidth Configuration (Subtype = 9)
Result	Fail
Log	Priority 0~7 Mismatch - Detect 0:46,1:1,2:1,3:48,4:1,5:1,6:1,7:1, but should be 0:48,1:0,2:0,3:50,4:0,5:2,6:0,7:0
RoleType	Storage
Feature	LLDP - PFC Maximum Number of Traffic Classes (Subtype = B)
Result	Pass
Log	
RoleType	Storage
Feature	LLDP - PFC Priority Class Enabled (Subtype = B)
Result	Pass
Log	
RoleType	Storage
	

ALL Detail Logs

- Compute (SDN)

TestDate: 2022-04-14T22:38:35.099334Z RoleSummary: Compute (SDN): Fail Compute (Standard): Fail Management: Fail Storage: Fail FeatureSummary: - featurename: BGP featurepass: Pass featurelog: "" featureroles: - Compute (SDN) - featurename: VLAN featurepass: Fail featurelog: No VLAN detected, please check the VLAN configuration on switch featureroles: - Management - Compute (Standard) - Compute (SDN) - Storage - featurename: DHCP - Relay Agent IP featurepass: Pass featurelog: "" featureroles: - Management - featurename: LLDP - Port VLAN ID (Subtype = 1) featurepass: Pass featurelog: "" featureroles: - Management - featurename: LLDP - VLAN Name (Subtype = 3) featurepass: Fail featurelog: LLDP Subtype3 not detected from switch featureroles: - Compute (Standard) - Compute (SDN) - Storage - featurename: LLDP - Maximum Frame Size (Subtype = 4) featurepass: Fail featurelog: 'LLDP Subtype4 Mismatch, please check switch MTU configuration - Detect: 9216, but Input: 9214' featureroles: - Compute (Standard) - Compute (SDN) - Storage - featurename: LLDP - Link Aggregation (Subtype = 7) featurepass: Pass featurelog: "" featureroles: - Management - Compute (Standard)

```
- Storage
  - featurename: LLDP - ETS Maximum Number of Traffic Classes (Subtype = 9)
   featurepass: Pass
   featurelog: ""
   featureroles:
    - Storage
  - featurename: LLDP - ETS Class Bandwidth Configuration (Subtype = 9)
   featurepass: Fail
   featurelog: Priority 0~7 Mismatch - Detect 0:46,1:1,2:1,3:48,4:1,5:1,6:1,7:1, but should be 0:48,1:0,2:0,3:50,4:0,5:2,6:0,7:0
   featureroles:
    - Storage
  - featurename: LLDP - PFC Maximum Number of Traffic Classes (Subtype = B)
   featurepass: Pass
   featurelog: ""
   featureroles:
    - Storage
  - featurename: LLDP - PFC Priority Class Enabled (Subtype = B)
   featurepass: Pass
   featurelog: ""
   featureroles:
    - Storage
VLANResult:
  nativevlanid: 710
  allvlanids: []
LLDPResult:
    sysdes: "Dell EMC Networking OS10 Enterprise.\r\nCopyright (c) 1999-2021 by Dell Inc. All Rights Reserved.\r\nSystem Description: OS10
Enterprise.\r\nOS Version: 10.5.3.0.\r\nSystem Type: S5248F-VM"
  portname: ethernet1/1/1
  chasisid: 0cc23e6c0000
  chasisidtype: MAC Address
  subtype1_portvlanid: 710
  subtype3_vlanlist: []
  subtype4_maxframesize: 9216
  subtype7_linkaggcap: true
  subtype9_ets:
    etstotalpg: 8
    etsbwbypgid:
       0:46
       1: 1
       2: 1
       3: 48
       4: 1
       5: 1
       6: 1
       7: 1
  subtypeb_pfc:
    pfcmaxclasses: 8
    pfcconfig:
       0:0
       1:0
       2: 0
       3: 1
       4: 0
```

5: 0

6: 0

7: 0

DHCPResult:

dhcppacketdetected: true relayagentip: 10.10.12.1

BGPResult:

bgptcppacketdetected: true switchinterfaceip: 10.10.10.1

switchinterfacemac: 0c:c2:3e:6c:00:a1

hostinterfaceip: 10.10.10.100

hostinterfacemac: 0c:b0:99:4a:00:01

Input Variables

interfacename: ""
interfaceguid: ""
interfacealias: ""
nativevlanid: 0
allvlanids: []
mtusize: 0
etsmaxclass: 0
etsbwbypg: ""
pfcmaxclass: 0
pfcpriorityenabled: ""