2022-11-06 05:22:06 - Validation Report

Supported Role-Types

Storage Pass

Management Fail

Compute(Basic) Pass

Compute(SDN) Fail

Test Fail Types

 typename: BGP typepass: Fail

typelog: TCP 179 Packet Not Detected from switch

typeroles:

- Compute(SDN)

- typename: DHCP Relay Agent IP

typepass: Fail

typelog: DHCP Relay Agent IP Not Detected from switch

typeroles:

- Management

ALL Detail Logs

TestDate: 2022-11-06T05:22:06.701322Z ResultSummary: Compute(Basic): Pass Compute(SDN): Fail Management: Fail Storage: Pass TypeSummary: - typename: BGP typepass: Fail typelog: TCP 179 Packet Not Detected from switch typeroles: - Compute(SDN) - typename: VLAN typepass: Pass typelog: "" typeroles: - Management - Compute(Basic) - Compute(SDN) - Storage - typename: DHCP Relay Agent IP typepass: Fail typelog: DHCP Relay Agent IP Not Detected from switch typeroles: - Management - typename: LLDP-Port VLAN ID (Subtype = 1) typepass: Pass typelog: "" typeroles: - Management - typename: LLDP-VLAN Name (Subtype = 3) typepass: Pass typelog: "" typeroles: - Compute(Basic) - Compute(SDN) - Storage - typename: LLDP-Maximum Frame Size typepass: Pass typelog: "" typeroles: - Compute(Basic) - Compute(SDN) - Storage - typename: LLDP-Link Aggregation typepass: Pass typelog: "" typeroles: - Management - Compute(Basic)

- Compute(SDN)

```
- Storage
  - typename: LLDP-ETS Maximum Number of Traffic Classes
   typepass: Pass
   typelog: ""
   typeroles:
    - Storage
  - typename: LLDP-ETS Class Bandwidth Configured
   typepass: Pass
   typelog: ""
   typeroles:
    - Storage
  - typename: LLDP-PFC Maximum Number of Traffic Classes
   typepass: Pass
   typelog: ""
   typeroles:
    - Storage
  - typename: LLDP-PFC Priority Class Enabled
   typepass: Pass
   typelog: ""
   typeroles:
    - Storage
VLANResult:
  nativevlanid: 1
  allvlanids:
    - 1
    - 710
    - 711
    - 712
LLDPResult:
  sysdes: Cumulus Linux version 5.2.1 running on Mellanox Technologies Ltd. MSN2100
  portname: swp1
  chasisid: 98039b5cbb20
  chasisidtype: MAC Address
  subtype1_portvlanid: 1
  subtype3_vlanlist:
    - 1
    - 710
    - 711
    - 712
  subtype4_maxframesize: 9214
  subtype7_linkaggcap: true
  subtype9_ets:
    etstotalpg: 8
    etsbwbypgid:
       0: 48
       1: 0
       2: 0
       3: 50
       4: 0
       5: 2
       6: 0
       7:0
  subtypeb_pfc:
```

pfcmaxclasses: 8 pfcconfig: 0: 0 1: 0 2: 0 3: 1 4: 0 5: 0 6: 0 7: 0 DHCPResult: dhcppacketdetected: true relayagentip: "" BGPResult: bgptcppacketdetected: false switchinterfaceip: "" switchinterfacemac: "" hostinterfaceip: "" hostinterfacemac: ""

Input Variables

interfaceguid: "" interfacealias: "" nativevlanid: 1 allvlanids:

- 1

- 710

- 711

- 712

mtusize: 9214 etsmaxclass: 8

etsbwbypg: 0:48,1:0,2:0,3:50,4:0,5:2,6:0,7:0

pfcmaxclass: 8

pfcpriorityenabled: 0:0,1:0,2:0,3:1,4:0,5:0,6:0,7:0