GraphDecide: Benchmarking Decision Models on Graphs

Xianliang Yang[1] Yapu Zhang[2] Li Zhao[1*]

[1]Microsoft [2]Beijing University of Technology

xianya@microsoft.com zhangyapu@bjut.edu.cn

lizo@microsoft.com

September 27, 2026

Abstract

Can valid local decisions compose into good graph solutions? GraphDecide evaluates Jev and open decision-oriented models on six exact graph tasks and four irreversible construction tasks. Small graphs permit independently checked labels, exact optima and own-history error analysis. Twelve configurations share 960 instances: ten direct-decision configurations and two GPT upper reference points with different reasoning budgets. Jev achieves 100% adjacency accuracy but 61.43% degree accuracy and 58.75% distance accuracy. Its mean TSP gap is 45.85 versus 100.90 for bounded Qwen3.5-27B; on influence maximization their gaps are 0.600 and 0.425. Jev has smaller construction gaps than added Qwen3.8-27B and Qwen2.5-72B configurations, without establishing general parameter equivalence. A separate 952-instance confirmation covers the original four configurations. Classical references, presentation controls and probability audits distinguish valid actions from correct decisions and competitive solutions. The benchmark characterizes task-dependent capabilities, not a universal ranking or a fitted size limit.

1 Introduction

Decision models offer a finite choice instead of an open-ended response. This makes them attractive for controllers and sequential workflows, but output validity does not establish algorithmic competence. Recognizing an edge, counting neighbors, identifying a path and choosing the next city in a tour require different capabilities. A model can consistently return legal actions while accumulating irreversible errors.

We study *bounded graph decisions*: the model receives a public state and legal actions; deterministic code applies the chosen transition without providing an oracle action or repairing a poor choice. Exact tasks require one decision, while optimization tasks require complete model-generated trajectories. All configurations receive identical initial logical information, but their renderings, subsequent histories and compute are not identical. "Jev-like" denotes open decision-oriented readouts, not verified reconstructions of Jev's undisclosed architecture.

Our contribution is a diagnostic evaluation package combining consecutive size strata, matched binary pairs, exact objectives, explicit failure accounting and independently replayable own-history decisions. The completed twelve-configuration matrix connects primitive correctness to construction quality, while a separate confirmation and targeted controls qualify what can be inferred. The research questions are:

*Corresponding author: lizo@microsoft.com.

Task	Answer or objective	Cases	Choices/case
Adjacency	Shared edge: yes/no	80	1
Degree	Neighbor count: $0, \ldots, n-1$	400	1
Cycle	Cycle exists: yes/no	80	1
Connectivity	Path exists: yes/no	80	1
Distance	Distance $\leq h$: yes/no	80	1
Articulation	Components increase: yes/no	80	1
MaxCut	Maximize crossing edges	40	$n-1$
Manhattan TSP	Minimize closed-tour length	40	$n-2$
Deterministic LT	Maximize activated nodes	40	2
Modularity	Maximize two-group modularity	40	$n-1$

Table 1: Canonical task inventory on the shared $n = 8, \ldots, 12$ bank. Counts are scheduled cases per configuration, not independent graphs. Construction choices form one complete own-history trajectory.

RQ1: Primitive discrimination. Which graph decisions distinguish Jev, open trained readouts and bounded language-model baselines?

RQ2: Sequential composition. Do local choices yield good complete solutions, and where does a trajectory lose attainable quality?

RQ3: Interpreting failure. Which findings survive fresh graphs and interface checks rather than merely reflecting valid output?

The objective is not to increase difficulty until Astra fails. Easy adjacency cases are positive controls; low optimum-hit rates motivate graded quality measures rather than automatic expansion to larger graphs. GPT configurations are upper reference points under different budgets. Code and aggregate results are released at `https://github.com/microsoft/HeurAgenix.git`, on branch `graph_benchmark`, in `benchmarks/graphdecide`. Raw provider logs and model weights are not included in this code release.

Positioning. NLGraph and GraphArena establish graph reasoning and verified solution quality as existing evaluation directions [17, 21]; GraphWiz, GraphLLM and CLRS address graph-specific training, representations or algorithmic learning [2, 3, 20]. Learned constructive optimization also predates Jev [11, 12]. Jev's typed-decision claims, SemIf's option-logit readout, WorldTour's Jev-guided routing and JevBench's decision leaderboard motivate this study, not a priority claim for typed choices or Jev-guided TSP [1, 5, 13, 18]. Our focus is exactly scored graph decisions and accumulated own-history errors under explicit interface controls. Extended context is in Appendix F.

2 Tasks and benchmark data

Public inputs contain graph structure and the current question, never generation-family labels, reference answers or optimum values. Unless specified otherwise, graphs are simple, undirected and unweighted, with integer vertices including isolates.

Exact decisions. The six tasks ask whether two vertices share an edge (*adjacency*), the number of distinct neighbors (*degree*), whether any component has a simple cycle of length at least three

(*cycle*), whether a path connects a pair (*connectivity*), whether shortest-path distance is at most a supplied threshold (*distance*), and whether deleting a vertex increases the total component count (*articulation*). Degree offers all n answers from 0 to $n-1$; the other tasks are binary. Distance challenge pairs have finite distances exactly h and $h+1$.

Irreversible constructions. MaxCut assigns vertices in order to two sides, fixing vertex 0 in A, to maximize crossing edges in $n-1$ choices. Manhattan TSP starts at city 0 and chooses unvisited cities in $n-2$ decisions; the final city and return edge are forced, and full closed-tour distance is minimized. Deterministic normalized linear-threshold (LT) influence selects two distinct seeds on a directed graph to maximize final activated nodes. Incoming weights are $1/d^-(v)$, threshold is $1/2$, seeds activate simultaneously, and diffusion is synchronous and irreversible. The modularity task assigns vertices to at most two communities, again fixing vertex 0, to maximize standard resolution-1 modularity [16]. Empty sides and one community are legal. This is neither unrestricted community detection nor the random-threshold LT model: its classical submodularity guarantee is not assumed [10]. Exact contracts and invariants are in Appendices A and L.

Consecutive sizes and coverage. Development contains 356 realized cases at every integer size 5–12; the canonical challenge contains 960 at sizes 8–12. At each challenge size there are sixteen queries for each binary task, $8n$ degree queries, and eight episodes for each construction. Thus every model receives 800 exact queries and 160 constructions, requiring at most 1,920 calls. Four development cases were not generated within the bounded proposal budget; the canonical challenge has no omissions. The separate prospective confirmation realizes 952 of 960 requested cases, retaining eight missing cycle cases as generation shortfalls. Full counts and chronology are in Appendix B.

Controls and exact verification. Heterogeneous graph-generation procedures vary structure within sizes. Binary positive/negative pairs match audited degree-based attributes: query tasks generally share a graph; cycle twins share n, m and the degree multiset. The audited cells are label-balanced, giving a 50% empirical lookup ceiling for those attributes, not immunity to every shortcut. Graph fingerprints select candidate identity matches; exact isomorphism checks enforce exclusion against the recorded prior pool. TSP identity uses weighted distance graphs and LT uses directed topology.

Labels and objectives are independently checked. Adjacency, distance and articulation oracles were tested on all 1,024 labeled five-vertex graphs; subset dynamic programming checks TSP optima, while small partition and seed spaces permit exhaustive checks. Public request construction is separate from privileged references. "Independent" here means separate computation within this project, not external replication. The canonical bank was already inspected before later model extensions; it is not a newly blind test. Locally frozen registrations are not external preregistration.

3 Evaluation protocol

Models and budgets. The ten direct-decision configurations are Jev's native action selection; no-thinking Qwen3.5-4B/9B/27B grammar generation; a Qwen3.5-4B candidate-token-score reference; trained Decider-2B v11, Kev-4B and Laya; and full-BF16 Qwen3.8-27B and Qwen2.5-72B-Instruct. Grammar configurations use greedy legal-choice generation with a 64-token ceiling. The larger/newer local lanes use a 180-second request deadline; thinking is disabled for Qwen3.8, while Qwen2.5 uses its standard instruct template without added reasoning. The older-generation 72B is not a scale-only

ablation of Qwen3.5/3.8. GPT-5.4 and Astra use tool-free default reasoning, a 4,096-token ceiling and a 180-second deadline, and remain separately grouped. No Jev outputs are used to train a replacement. Checkpoints, serving settings and compatibility qualifications are in Appendix C.

Interactions and failures. Every model receives the same initial logical request with explicit action descriptions. Each later state follows that model's actual previous choices, not teacher-forced or oracle prefixes. A valid native Jev action is not replaced by probability argmax; probability conformance is audited separately. Unsupported inputs, timeouts and invalid outputs remain in scheduled denominators. There is no answer repair, silent truncation or replacement of failed cases. Feasibility means a valid answer or complete legal trajectory, not mathematical correctness. All tied optima are accepted.

Metrics and uncertainty. Exact-task accuracy is the equal-weight mean of five size-specific accuracies. Degree's pooled correct count is different because each size has $8n$ queries. The primary construction-quality metric is mean additive objective gap over feasible completed episodes, always accompanied by feasible coverage over all scheduled episodes:

$$\mathrm{gap}_i = \begin{cases} f_i^\star - f_i, & \text{maximization,} \\ f_i - f_i^\star, & \text{minimization.} \end{cases}$$

We average per-episode gaps, not optimum-hit indicators. Units are crossing edges, Manhattan distance, activated nodes and modularity; absolute gaps must not be pooled across tasks or interpreted as percentages. Zero conditional gap does not imply zero failures. Optimum-hit counts are supplementary (Appendix H).

The twelve-configuration tables are descriptive point estimates, not family-wise significance claims. Original four-configuration uncertainty uses 2,000 size-stratified paired bootstrap replicates over clusters joining graph identity and matched-pair relations, rather than treating related queries as independent (Appendix C). Generation omissions have no model prediction and are not scored as model errors; model failures on generated cases remain in the denominator. Only the original four configurations receive prospective new-graph confirmation; model extensions do not inherit that replication.

Model	Exact feasible	Construct feasible	Input rejects	Exec. failures	Unattempted
Jev	800/800	160/160	0	0	0
Qwen4 G	800/800	160/160	0	0	0
Qwen9 G	800/800	160/160	0	0	0
Qwen27 G	800/800	160/160	0	0	0
Qwen3.8-27B	800/800	160/160	0	0	0
Qwen2.5-72B	800/800	160/160	0	0	0
Qwen4 scores	800/800	160/160	0	0	0
Decider	800/800	160/160	0	0	0
Kev	800/800	160/160	0	0	0
Laya	800/800	151/160	9	0	0
GPT-5.4	800/800	151/160	0	9	0
Astra	800/800	160/160	0	0	0

Table 2: Full canonical coverage. Exact feasibility means a valid returned answer, not a correct answer. Construction feasibility requires a complete legal trajectory. Input rejects and execution failures are episode counts. All twelve configurations retain 960 scheduled cases. The lower block contains GPT default-reasoning anchors, not matched-compute direct-decision baselines.

4 Canonical results

The complete comparison comprises 11,520 scheduled episode evaluations on the same 960 instances, not 11,520 independent graphs. Frozen results are reused when adding models. The public presentation contains 720 task/size/configuration cells. Historical pilots and legacy Astra protocols are separate, not mixed into the main columns.

Coverage. All configurations except Laya and GPT-5.4 complete 960/960 episodes. Laya rejects nine LT inputs at its lossless context/head limits, leaving 31/40 feasible LT episodes. GPT-5.4 retains nine construction timeouts: 36/40 cut, 39/40 TSP, 40/40 LT and 36/40 modularity episodes are feasible. Every other construction cell has 40/40 feasible episodes. Table 2 gives the complete counts; integrity checks are in Appendix D.

RQ1: Strengths are task dependent. Jev's 100% adjacency accuracy does not extend to uniform structural reliability: degree is 61.43%, cycle 66.25%, and distance 58.75% (Table 3). Open trained readouts do not recover its exact-task profile. Kev reaches 78.75% adjacency and 19.88% degree; Decider reaches 58.75% and 12.09%. Laya selects `yes` on all 400 binary queries. Native-score, mapping and replay checks retain that outcome as observed behavior, not an assumed parser failure.

Jev's exact-task point estimates exceed bounded Qwen3.5-27B on all six tasks, but this does not establish general parameter equivalence. The newer Qwen3.8-27B and larger Qwen2.5-72B reach degree macro accuracies of 45.50% and 41.24%, respectively, not their pooled rates of 44.50% and 40.50%. The 72B connectivity and distance estimates exceed Jev by only one answer out of eighty each. Model size and generation therefore do not induce a monotone ordering under this bounded protocol.

RQ2: Quality is not optimum-hit frequency. Jev's TSP gap is 45.85, compared with 100.90 for Qwen3.5-27B and 349.65 for Kev (Table 4). LT reverses the Jev–Qwen3.5-27B ordering: their gaps are 0.600 and 0.425. Kev ties Jev at 0.600; its larger optimum-hit count does not establish

Model	Adjacency	Degree	Cycle	Connectivity	Distance	Articulation
Jev	100.00	61.43	66.25	85.00	58.75	65.00
Qwen4 G	60.00	18.32	55.00	50.00	50.00	50.00
Qwen9 G	58.75	26.99	51.25	53.75	42.50	50.00
Qwen27 G	98.75	47.70	63.75	80.00	52.50	47.50
Qwen3.8-27B	90.00	45.50	61.25	85.00	48.75	50.00
Qwen2.5-72B	92.50	41.24	50.00	86.25	60.00	46.25
Qwen4 scores	77.50	23.89	51.25	51.25	52.50	50.00
Decider	58.75	12.09	50.00	50.00	46.25	50.00
Kev	78.75	19.88	57.50	58.75	51.25	45.00
Laya	50.00	10.87	50.00	50.00	50.00	50.00
GPT-5.4	100.00	100.00	100.00	100.00	100.00	100.00
Astra	100.00	100.00	100.00	100.00	100.00	100.00

Table 3: Canonical exact-task macro-size accuracy (%). Qwen4/9/27 G denote Qwen3.5 no-thinking grammar configurations; other Qwen generations are named. GPT default-reasoning anchors form a separate lower block.

better mean quality. Qwen3.5-27B also has a slightly smaller cut gap (8.025 versus 8.150), whereas Jev has the smaller modularity gap (0.1694 versus 0.2810). These are taskwise observations, not established significant differences.

Jev has smaller mean gaps on all four constructions than either added Qwen3.8-27B or Qwen2.5-72B configuration, each with complete feasible coverage. In TSP their gaps are 183.70 and 152.40, respectively. This supports a direct-decision advantage on these instances, not a claim that Jev matches a general 72B model. No equal-hardware latency comparison or causal architecture attribution follows from these scores.

Absolute quality requires algorithmic references. Jev's MaxCut gap of 8.150 exceeds the uniform legal policy's exact expected gap of 5.325; classical cut search achieves 0.450. Nearest-neighbor plus 2-opt has TSP gap 0.200 versus Jev's 45.850. These algorithms may revise choices and are quality references, not equal-budget online competitors. Relative neural superiority is not competitiveness with classical solvers. Own-history continuation analysis gives a complementary error measure: over 640 constructions of the original four configurations, stepwise continuation losses telescope to final gap for all 4,480 decisions. Jev loses TSP optimality at its first choice in 3/40 episodes, compared with 22/40 for grammar-4B (Appendix I.3).

Reasoning anchors. Both GPT configurations answer all 800 exact queries correctly. Astra reaches zero gap with all 160 constructions feasible; GPT-5.4 reaches zero conditional gap with 151/160 feasible. This demonstrates that stronger reasoning can solve these small instances, without making matched-compute claims or requiring further difficulty escalation.

5 Robustness and interpretation

RQ3: Confirmation has a defined scope. The topology-excluded prospective confirmation contains 952 new instances for the original four configurations, not all twelve. Jev retains perfect adjacency, and all four again have larger MaxCut gaps than the uniform policy. Some rankings

Model	MaxCut	TSP	Deterministic LT	Modularity
Jev	8.1500	45.8500	0.6000	0.1694
Qwen4 G	11.1250	338.1500	2.6250	0.2900
Qwen9 G	11.0500	306.4500	3.7250	0.3203
Qwen27 G	8.0250	100.9000	0.4250	0.2810
Qwen3.8-27B	11.1500	183.7000	2.6750	0.3012
Qwen2.5-72B	9.7750	152.4000	1.9500	0.2645
Qwen4 scores	9.2000	351.0000	4.1250	0.2810
Decider	11.1250	355.7000	4.1000	0.2810
Kev	11.0750	349.6500	0.6000	0.2502
Laya	15.2500	344.7500	2.8710	0.3039
GPT-5.4	0.0000	0.0000	0.0000	0.0000
Astra	0.0000	0.0000	0.0000	0.0000

Table 4: Primary construction outcome: mean additive objective gap over feasible completions; lower is better. Units differ across columns. All cells use forty episodes except Laya LT (31), GPT-5.4 cut (36), TSP (39) and modularity (36). Different coverage is not a matched-subset comparison.

change, so confirmation supports selected patterns rather than every canonical estimate (Appendix J). Likewise, Kev's community advantage in an exploratory 64-case panel does not persist on the canonical bank. The smaller and larger panels are different graph sets, not a paired sample-size intervention.

Interface and probability controls. Option/state transformations expose semantic-choice reversals that aggregate accuracy can hide. At an identical token prefix, 4B candidate-score argmax and masked greedy agree on 100/100 states: argmax alone does not explain the main pipeline's gains. A separate CPU/GPU SemIf check matches choices but exceeds the registered 0.01 probability-error tolerance; the failed numerical reproduction gate remains unresolved. Hence the score baseline is an interface reference, not a certified reproduction. Laya's option-reversal pilot argues against a simple first-option bias, not against all prompting effects.

Numeric probability output does not imply calibration [6, 7]. Jev's above-chance distance accuracy coexists with probability losses worse than uniform on common-valid audit rows. These diagnostics separate mathematical correctness, action validity and probability quality; they do not prove absence of every implementation error. Full controls and probability tables remain in Appendix K.

Size and speed are bounded observations. Consecutive sizes reveal different profiles, not a fitted common boundary. Jev degree accuracy decreases from 70.3% at $n = 8$ to 49.0% at $n = 12$; cycle decreases from 81.25% to 50%, with nonmonotone intermediate cells. Adjacency stays perfect. Binary cells have only sixteen queries and construction cells eight episodes, and degree's number of classes grows. These observations do not identify "failure at twelve vertices." In the original four-configuration timing panel, Jev's median response is 70.01 ms, versus 64.41 ms for 4B candidate scoring and 94.24 ms for 4B grammar generation. Jev is not invariably fastest; different hardware, network paths and serving conditions prevent architecture or cost attribution (Appendix I).

6 Limitations and conclusion

Small graphs enable exact checking but do not establish operational-scale performance, size-OOD generalization or an ordering of causal difficulty. Finite generation procedures, degree conditioning and matching determine the tested distribution. Prior-topology exclusion is local, not proof against pretraining contamination. Later model choices use inspected banks; only four configurations have prospective new-graph confirmation. Taskwise estimates and exploratory bootstrap intervals do not correct all selection or multiplicity. Jev is closed, renderings and budgets are not fully matched, and trained readouts use compatible rather than identical upstream environments. Extended limitations and protocol details are retained in the appendices.

The artifacts contain synthetic graph states, not personal-network data; deterministic LT is not a validated model of human behavior. Public aggregates and scoring artifacts exclude credentials and raw provider responses. Local registrations and independent replay are not third-party attestation; extension-artifact distribution and publication permissions remain release requirements.

GraphDecide shows why valid choices, exact reasoning and good complete solutions must be evaluated separately. Jev has task-specific advantages over open readouts and several bounded Qwen configurations, including the added 72B baseline, yet remains far from classical optimization quality. Mean gaps reveal differences hidden by optimum-hit counts. The supported result is a capability profile with explicit uncertainty, not a universal model ranking. Fresh-graph confirmation and controlled transition-region studies are more informative next steps than increasing size solely because the GPT anchors remain successful.

References

[1] Diogo Almeida. Introducing system one models & Jev. TypeSafe AI company blog, September 2026. URL https://typesafe.ai/blog/introducing-system-one-models-and-jev. Vendor report. Body dated September 15, 2026. Accessed September 24, 2026. Not peer reviewed.

[2] Ziwei Chai, Tianjie Zhang, Liang Wu, Kaiqiao Han, Xiaohai Hu, Xuanwen Huang, and Yang Yang. GraphLLM: Boosting graph reasoning ability of large language model, 2023. URL https://arxiv.org/abs/2310.05845. Preprint.

[3] Nuo Chen, Yuhan Li, Jianheng Tang, and Jia Li. GraphWiz: An instruction-following language model for graph computational problems. In *Proceedings of the 30th ACM SIGKDD Conference on Knowledge Discovery and Data Mining*, pages 353–364. Association for Computing Machinery, 2024. doi: 10.1145/3637528.3672010. URL https://doi.org/10.1145/3637528.3672010.

[4] convaiinnovations. Laya typed decisions. Hugging Face model card and checkpoint, 2026. URL https://huggingface.co/convaiinnovations/laya-typed-decisions/tree/1a793eb568e6718f15941d08f85432581df534e3. Repository-owner attribution. Revision 1a793eb568e6718f15941d08f85432581df534e3. Inference code NandhaKishorM/laya, commit 970dc8c5f63d7b886a68409493f37d569424f933. Accessed September 25, 2026 (UTC). Non-peer-reviewed software.

[5] fstandhartinger. JevBench: Typed-decision evaluation, version 1.4.2. GitHub software and methodology release, 2026. URL https://github.com/fstandhartinger/jevbench/tree/1df665e3956d7aab7fa0208ff6c4f2d8557f9f90. Repository-owner attribution. Commit 1df665e3956d7aab7fa0208ff6c4f2d8557f9f90. Accessed September 25, 2026 (UTC). Non-peer-reviewed evaluation.

[6] Tilmann Gneiting and Adrian E. Raftery. Strictly proper scoring rules, prediction, and estimation. *Journal of the American Statistical Association*, 102(477):359–378, 2007. doi: 10.1198/016214506000001437. URL https://sites.stat.washington.edu/raftery/Research/PDF/Gneiting2007jasa.pdf.

[7] Chuan Guo, Geoff Pleiss, Yu Sun, and Kilian Q. Weinberger. On calibration of modern neural networks. In *Proceedings of the 34th International Conference on Machine Learning*, volume 70 of *Proceedings of Machine Learning Research*, pages 1321–1330. PMLR, 2017. URL https://proceedings.mlr.press/v70/guo17a.html.

[8] jaredpalmer. Kev: Small jev-like decision models. GitHub inference software and documentation, 2026. URL https://github.com/jaredpalmer/kev/tree/569ea449b1033c5aa8f149ec5e20d0c7a296d24a. Repository-owner attribution. Pinned code and documentation inspected locally September 25, 2026 (UTC). Non-peer-reviewed software.

[9] jaredpalmer. Kev-4B. Hugging Face model card, adapter and decision head, 2026. URL https://huggingface.co/jaredpalmer/kev-4b/tree/139fdd94f1b6a6ad80cc15e08fcb99cac885a101. Repository-owner attribution. Pinned card inspected locally September 25, 2026 (UTC). Base: Qwen/Qwen3.5-4B-Base, revision 1001bb4d826a52d1f399e183466143f4da7b741b. Non-peer-reviewed software.

[10] David Kempe, Jon Kleinberg, and Éva Tardos. Maximizing the spread of influence through a social network. *Theory of Computing*, 11(4):105–147, 2015. doi: 10.4086/toc.2015.v011a004. URL https://theoryofcomputing.org/articles/v011a004/.

[11] Elias Khalil, Hanjun Dai, Yuyu Zhang, Bistra Dilkina, and Le Song. Learning combinatorial optimization algorithms over graphs. In *Advances in Neural Information Processing Systems*, volume 30, 2017. URL https://proceedings.neurips.cc/paper_files/paper/2017/hash/d9896106ca98d3d05b8cbdf4fd8b13a1-Abstract.html.

[12] Wouter Kool, Herke van Hoof, and Max Welling. Attention, learn to solve routing problems! In *International Conference on Learning Representations*, 2019. URL https://arxiv.org/abs/1803.08475.

[13] krushideep. WorldTour. GitHub software repository, 2026. URL https://github.com/krushideep/Worldtour/tree/30ba1a6f5e5252e4b7521d464d7c2de158d746d2. Repository-owner attribution. Commit 30ba1a6f5e5252e4b7521d464d7c2de158d746d2, September 21, 2026. Accessed September 24, 2026. Non-peer-reviewed software.

[14] Mapika. Decider: One-pass typed decisions with calibrated probabilities. GitHub inference software and documentation, version 1.4.0, 2026. URL https://github.com/Mapika/decider/tree/15ab28e8d8e4ec49728165b3426d81de5b77f864. Repository-owner attribution. Pinned code and documentation inspected locally September 25, 2026 (UTC). Non-peer-reviewed software.

[15] Mapika. Decider-2B: Typed decisions with calibrated probabilities in one forward pass. Hugging Face model card and checkpoint, v11, 2026. URL https://huggingface.co/Mapika/decider-2b/tree/533964dae8be954c5b5e19fa4948e48408094c1e. Repository-owner attribution. Pinned model card inspected locally September 25, 2026 (UTC). Non-peer-reviewed software; calibration terminology describes the source's claim.

[16] M. E. J. Newman and M. Girvan. Finding and evaluating community structure in networks. *Physical Review E*, 69(2):026113, 2004. doi: 10.1103/PhysRevE.69.026113. URL https://doi.org/10.1103/PhysRevE.69.026113.

[17] Jianheng Tang, Qifan Zhang, Yuhan Li, Nuo Chen, and Jia Li. GraphArena: Evaluating and exploring large language models on graph computation. In *International Conference on Learning Representations*, 2025. URL https://openreview.net/forum?id=Y1r9yCMzeA.

[18] TheoLeeCJ. SemIf. GitHub software repository, 2026. URL https://github.com/TheoLeeCJ/SemIf/tree/23cf1f39fc9534fe81437200959b6dfc7106e45a. Repository-owner attribution. Commit 23cf1f39fc9534fe81437200959b6dfc7106e45a, September 23, 2026. Accessed September 24, 2026. Non-peer-reviewed software.

[19] TypeSafe AI. Jev 1.13 jaggedness. Official model documentation, 2026. URL https://docs.typesafe.ai/model-jaggedness/jev-1.13. Vendor documentation. Body states last reviewed September 17, 2026. Accessed September 24, 2026. Not peer reviewed.

[20] Petar Veličković, Adrià Puigdomènech Badia, David Budden, Razvan Pascanu, Andrea Banino, Misha Dashevskiy, Raia Hadsell, and Charles Blundell. The CLRS algorithmic reasoning benchmark. In *Proceedings of the 39th International Conference on Machine Learning*, volume 162 of *Proceedings of Machine Learning Research*, pages 22084–22102. PMLR, 2022. URL https://proceedings.mlr.press/v162/velickovic22a.html.

[21] Heng Wang, Shangbin Feng, Tianxing He, Zhaoxuan Tan, Xiaochuang Han, and Yulia Tsvetkov. Can language models solve graph problems in natural language? In *Advances in Neural Information Processing Systems*, volume 36, 2023. URL https://arxiv.org/abs/2305.10037.

A Task and interaction contracts

Unless stated otherwise, $G = (V, E)$ is simple, undirected and unweighted, with integer vertices $V = \{0, \ldots, n-1\}$, including isolates. Public data contain the graph and the query; action identifiers are strings. Generation families, reference answers, optimum values, and paired-label annotations are not model inputs.

A.1 Six exact decisions

Adjacency. Decide whether $\{u, v\} \in E$ for distinct supplied vertices.

Degree. Return $d(v)$ from the full choice set $\{0, \ldots, n-1\}$. The growing output cardinality is an explicit size confound.

Cycle. Decide whether any component contains an undirected simple cycle of length at least three.

Connectivity. Decide whether a path connects the supplied vertices.

Distance. Decide whether the shortest-path distance is at most a supplied threshold h. Matched challenge pairs have finite distances exactly h and $h+1$, rather than disconnected negative examples.

Articulation. Decide whether deleting a supplied vertex increases the total number of connected components, including on disconnected graphs.

A.2 Four irreversible constructions

MaxCut. Vertex 0 is fixed in side A. In increasing vertex order, the model assigns each remaining vertex to A or B, using $n-1$ decisions. The maximized objective is the number of edges crossing the partition. Empty sides are legal.

Manhattan TSP. Distinct integer coordinates define a complete weighted graph with $d_{ij} = |x_i - x_j| + |y_i - y_j|$. Starting at 0, the model selects the next unvisited vertex for $n-2$ decisions. The final unvisited vertex and edge returning to 0 are then forced. This deterministic completion is part of the contract, not answer repair. The minimized objective is full tour length.

Deterministic normalized linear threshold (LT). On a directed graph, every incoming edge to v has weight $1/d^-(v)$ and the threshold is $1/2$, with equality activating. The model selects two distinct seeds, which activate simultaneously at time zero. Subsequent updates are synchronous and irreversible. A zero-indegree nonseed never activates. The maximized objective is final active-set size. This fixed-threshold variant is not the random-threshold classical LT model; we do not import its submodularity or greedy approximation guarantee.

At-most-two-community modularity. Using the same fixed-0, $n-1$ binary assignment protocol, maximize

$$Q(c) = \frac{1}{2m} \sum_{u,v} \left(A_{uv} - \frac{d_u d_v}{2m} \right) \mathbf{1}[c_u = c_v].$$

All-A is a valid one-community solution with $Q = 0$. This is a restricted bipartition task, not unrestricted community detection.

Task	Development	Challenge	Decisions per instance
Adjacency	32	80	1
Degree	136	400	1
Cycle	30	80	1
Connectivity	32	80	1
Distance	32	80	1
Articulation	30	80	1
MaxCut	16	40	$n-1$
TSP	16	40	$n-2$
Deterministic LT	16	40	2
Modularity	16	40	$n-1$
Total	356	960	668 / 1,920 per model

Table 5: Dataset counts and maximum calls. An additional forty weighted TSP instances support wording confirmation and bring the release to 1,356. They are not additional rows of the canonical comparison.

Shared policy. Every tied optimum is accepted; matching a particular reference trajectory is unnecessary. Models see their own previous choices, not teacher-forced prefixes, except in explicitly separate diagnostic controls. Invalid or incomplete episodes remain infeasible, with no imputed objective, retries, or silent substitution of an action.

B Controlled data generation and verification

B.1 Size, structure and pairing

Development covers each integer $n = 5, \ldots, 12$ with two repetitions; the structural challenge covers $n = 8, \ldots, 12$ with eight repetitions. Each size/repetition requests $n + 14$ instances and $4n + 8$ maximum calls. Size is a consecutive descriptive axis, not a guarantee of increasing difficulty or a causal intervention holding every other property fixed.

We use heterogeneous block, core–periphery and geometric procedures for query tasks; forests and degree-preserving switches for cycle twins; small-world and switched regular bases for cuts; clustered or perturbed-ring coordinates for TSP; layered directed acyclic graphs for LT; and heterogeneous blocks for modularity. These are finite, overlapping procedures, not uniform samples from all graphs or disjoint mathematical families. Degree conditioning can change a proposal's original family characteristics.

For adjacency, connectivity and distance, positive and negative queries share a graph and have identical unordered endpoint-degree signatures. Articulation queries share a graph and equal vertex degrees. Cycle twins are different graphs with equal n, m and degree multiset but opposite labels. All five binary tasks are balanced within the audited cells defined by n, m, degree multiset, query degrees and (where applicable) h, giving a 50% empirical lookup ceiling for those cells. This does not rule out unexamined shortcuts. For example, component count plus n, m determines undirected cycle existence.

Generation allows at most 128 proposals per cell and records unsupported cells rather than weakening constraints. Four development instances are missing: one cycle pair and one articulation pair at $n = 5$. Exhaustion of all 34 unlabeled five-vertex graphs finds one eligible forest/cyclic topology pair but two eligible articulation topologies; the latter shortfall is therefore a generator-support/budget limitation, not a theorem of impossibility. The original 960-instance challenge has

no omissions.

B.2 Identity exclusion and evidence chronology

The original challenge excludes an audited pool of 1,040 exact-labeled deduplicated records from 121 earlier artifacts. Fingerprints select candidate buckets; exact VF2 comparisons determine identity. TSP uses complete weighted distance graphs, and LT uses directed topology. Independent checks found no prior overlap and no same-task duplicate across nominally independent clusters. The 1,040 records are not claimed to be 1,040 isomorphism classes.

Crucially, the common-interface matrix in this paper reuses these already inspected banks. Its protocol was frozen before its own calls, but it is *not a newly blind test*. Earlier development diagnosed wording and conformance issues. A subsequent prospective confirmation excludes these banks and retains its own results, including missing cells, rather than replacing them after inspecting outcomes (Section J). We preserve the chronological distinction between original strict experiments, diagnostic controls and the revised common-interface matrix.

Meaning of registration and independent checking. Here, "registered" or "preregistered" means a locally persisted design record frozen before the specified calls (and, for the confirmation, before generation), not a deposit in an external public preregistration registry. Source and artifact hashes detect changes relative to those records; they are not third-party timestamps or cryptographic proof of the full chronology. Independent verification means separate replay or mathematical computation within this project, not replication by an external research group.

B.3 Independent truth and artifact boundaries

New adjacency, distance and articulation oracles were exhaustively checked on all 1,024 labeled five-vertex graphs. Every released label, feasible reference, baseline and optimum passes independent validation; TSP uses exact subset dynamic programming and an independent optimum check, while the small partition and seed spaces permit exhaustive verification.

The portable artifact separates five public fields (identifier, task, kind, state, query budget), private references, and analysis metadata. Its request builder does not read references. Offline scoring is deliberately privileged: giving that scorer to a model would change the benchmark. The archive was extracted into an isolated Python process and all 1,356 instances were verified without importing model clients, Torch or the Copilot SDK.

C Evaluation design

C.1 Evidence sets and permissible comparisons

Table 6 distinguishes the complete canonical comparison from its four-configuration diagnostic and confirmation subsets. Reusing graph instances allows paired comparisons but does not add independent test graphs. Freezing a later model's protocol before its calls does not make an already inspected bank a blind holdout.

C.2 Completed common-interface configurations

Every method receives the same initial logical request, including explicit action descriptions. Questions specify mathematics rather than requiring a wire encoding that could conflict with a letter-based readout. TSP explicitly names the current endpoint and actual visited prefix.

Evidence set	Cases per method	Interpretation
Original four-configuration matrix	1,316	356 development and 960 inspected challenge cases.
Prospective confirmation	952	Same four configurations; new seed and prior-topology exclusion, but unchanged generator procedures and sizes.
Canonical GPT-5.4	960	Reuses the inspected challenge; identical initial logical requests, not matched reasoning or compute.
Full cross-family matrix	960	Twelve configurations on that same challenge, including canonical Astra; ten direct-decision configurations and two separately labeled GPT reasoning anchors.
Larger/newer local extension	960	Qwen3.8-27B and Qwen2.5-72B-Instruct, included in the twelve above; not additional graphs or a scale-only ablation.
Legacy Astra	960	Same challenge graphs, different instructions and option descriptions; separate protocol.
Expanded local/readout panel	64	Reuses selected confirmation cases at $n = 8, 12$; exploratory, not a new blind replication.

Table 6: Core evidence sets, not a sum of independent graphs. Later presentation, probability and deadline controls reuse their explicitly named banks. Cases are scheduled episodes, not necessarily completed ones.

Jev action. Native supplied choices under an explicitly registered action-eligibility policy. Expected model, response shape, legal choice, probability keys and finite ranges, confidence and usage must still validate. Probability normalization and choice/argmax disagreement are separately recorded observations, not reasons to replace the supplied action.

4B and 9B grammar. Qwen3.5-4B and Qwen3.5-9B, greedy no-thinking generation, 64-token ceiling and legal-choice grammar, with the existing output parser. Thinking-enabled extensions are reported separately.

4B scores. The existing 4B checkpoint with pinned SemIf-style rendering and exact requested candidate-token log probabilities from vLLM. The chosen action is the conditional argmax over *all* candidates, not a natural top-K approximation. One API-generated token is unused for selection and is counted in resource accounting.

27B grammar. Qwen3.5-27B with the same no-thinking, 64-token, legal-choice grammar policy and a 180-second request deadline.

Larger/newer local grammar. Qwen3.8-27B and Qwen2.5-72B-Instruct use full BF16 weights, greedy legal-choice grammar, a 64-token ceiling and a 180-second deadline. Thinking is explicitly disabled for Qwen3.8; Qwen2.5 uses its standard instruct template without added reasoning. They use two and four RTX A6000 GPUs, respectively. The 72B checkpoint is an older-generation dense model, not a scale-only variant of Qwen3.5/3.8.

Trained Jev-like readouts. Decider-2B v11 and Kev-4B use their pinned upstream native inference paths; Laya uses its encoder and trained choice head in CPU FP32. Lossless context checks remain binding. These are compatible-runtime evaluations, not certifications of identical upstream environments.

Reasoning anchors. GPT-5.4 and Astra use tool-free, default-reasoning clients with 4,096 output tokens and a 180-second deadline. They are separated from the ten direct-decision configurations throughout.

No Jev outputs are used to train or distill a replacement model. The original four-configuration matrix retained the existing RTX A6000 services. Later GPU extensions used recorded resource leases and restored the original services. The earlier extensions protected 4B/9B; the final BF16 extension temporarily leased all four GPUs with authorization and restored all original endpoints after completion. The 4B generation/scoring methods share a physical-resource lock. The checkpoint, renderer, environment and per-call settings are recorded. This controls some factors, but the 4B readout comparison also changes rendering and cannot identify a pure causal effect of the scoring rule.

A failed reproduction check is retained. On twelve matched CPU SemIf probes, both GPU scoring routes matched every chosen action. However, maximum probability errors were 0.0166305 for requested token scores and 0.0379656 for teacher forcing, both exceeding the pre-frozen 0.01 threshold; the routes differed by 0.0213351. Independent token indexing and high-precision softmax recomputation found no parser mismatch. The numerical cause remains unresolved. Thus "4B scores" is an independent reference using SemIf rendering, not certified numerical reproduction of CPU SemIf, and the failed gate is not relaxed.

C.3 Metrics and statistical units

For an exact task, the primary accuracy is the mean of the size-specific accuracies, with invalid/unattempted scheduled cases retained in denominators. For degree, macro-size and pooled accuracy differ because there are n classes per size. The primary construction-quality metric is mean additive objective gap over feasible completed episodes, accompanied by feasible coverage over all scheduled episodes. Optimum-hit counts are supplementary diagnostics, not the primary comparison or a substitute for graded quality. For maximization gap $= f^\star - f$, and for minimization gap $= f - f^\star$. The mean averages per-episode gaps, not graph sizes or success indicators. Lower is better, and zero means optimal on the evaluated feasible cases. The headline tables use absolute gaps: edges for MaxCut, distance units for TSP, activated vertices for LT, and modularity units for community partitioning. The separately recorded TSP relative gap divides each episode's gap by its positive optimum; an average relative gap must not be inferred by dividing aggregate means. Modularity ratios are not used. Different task units are never pooled into one quality score.

Generation omissions and model failures have different denominators. An ungenerated case is a coverage shortfall, with no model prediction to score; confirmation accuracy is conditional on the 952 realized cases, not all 960 requested generation slots. Once an instance is generated and scheduled for a method, unsupported input, timeout, or invalid output remains in that method's scheduled denominator. Such failures do not receive a fabricated objective. Conditional gap zero means only that all completed solutions are optimal; it does not imply perfect scheduled performance.

For the original four-configuration evidence, uncertainty is estimated by 2,000 paired bootstrap replicates, stratified by size. The full twelve-configuration tables report descriptive point estimates, not new all-pairs significance tests. Resampling units are the transitive union of graph identity and paired construction relations: cycle twins must remain together even though they have different graphs. The reported intervals are exploratory pointwise percentile intervals conditional on these generators and samples. They are not family-wise significance tests; degenerate intervals do not establish equivalence or population certainty.

Classical and uniform references. We include greedy cut plus best-improvement vertex flips, nearest-neighbor TSP plus best-improvement 2-opt, deterministic-LT marginal greedy, and deterministic multistart single-vertex modularity search. These methods can revise choices and are quality anchors, not equal-budget online methods. For each task we additionally compute the exact expected objective under uniform legal sequential actions, rather than relying on one random rollout. An all-A, strict-positive-improvement modularity sweep is a weak reference that remains at zero; it is not our sole classical comparator.

D Coverage and evidence integrity

Complete accounting, including unsupported inputs. Qwen3.5-27B, Qwen3.8-27B, Qwen2.5-72B, Decider and Kev each complete 960 episodes in 1,920 calls without execution failures. Laya completes 951 episodes; nine initial LT inputs fail its lossless native context/head limits. Its ledger has 1,911 entries but only 1,902 model forwards: pre-inference rejections are not credited as inference. GPT-5.4 retains its nine construction timeouts, while canonical Astra completes all 960 episodes in 1,920 calls. No failed or unsupported case is replaced, retried, truncated, or removed from scheduled denominators (Table 2).

Evidence integrity. The original combined offline exporter admits only verified terminal real-model lanes, reconstructs 9,600 episode records, and independently checks every feasible construction objective. A versioned publication export adds the two completed BF16 lanes, whose 1,920 episodes and 320 constructions have separate runner verification and independent mathematical replay. The combined presentation contains 720 task/size/configuration cells, preserving the original 600. No new model calls are made during export. Compact tables are generated from the sealed task/size metrics and retain macro versus pooled exact accuracy and conditional versus scheduled outcomes. Recorded Python-version aggregate roundoff is handled separately from exact request, action, episode and count checks. An initially empty process metadata capture is preserved alongside a later parent observation that verifies the trained supervisor's command, process identity and GPU UUID; neither local record constitutes third-party attestation. The larger-local extension also checks served tokenization against pinned nonthinking rendering. Its earlier startup failure occurred before inference; that zero-call attempt is preserved as infrastructure history, not a model quality observation. No failed answer is rerun to improve the reported result.

E Limitations and responsible use

Diagnostic scale and distribution. Graphs have at most twelve vertices. This enables exhaustive validation and continuation analysis but does not establish performance at operational scale. Consecutive sizes are neither a size-OOD test nor a universal difficulty ordering. Finite generator support, degree conditioning, and matched-pair selection change the evaluated distribution. Topology exclusion is relative to an auditable local history, not proof of absence from pretraining.

Model and interface coverage. Jev is a closed service; no architecture or training attribution can be independently established here. No-thinking Qwen is a bounded baseline, not its full reasoning capacity. The Laya, Decider and Kev extensions test open trained readouts, not reproductions of Jev's undisclosed architecture. Decider/Kev are compatible-runtime upstream-inference evaluations, not complete upstream-environment reproductions or broad CPU/GPU numerical-parity claims. Fully matched rendering across readouts and deployment-matched latency experiments remain

distinct research questions. The earlier SemIf candidate-token CPU/GPU numerical reproduction failure is explicitly unresolved.

Inference and statistical uncertainty. The main common-interface matrix follows inspected development evidence. Small numbers of construction clusters, multiple task comparisons and API variability limit inference. Pointwise bootstrap intervals do not correct selection or multiplicity, and no overall "best model" score is defined. Repeated requests and option ordering receive diagnostic, not exhaustive, coverage. The prospective replication is complete. The sealed canonical strong-model anchor is reported separately with its own reasoning and serving conditions; it is not a matched-compute comparison. Only the original four configurations receive the prospective new-graph confirmation. GPT, the larger-local and trained-readout extensions therefore do not establish replicated rankings on fresh graphs. Larger graphs, unseen generator families, more independent seeds, and specialized graph-trained policies remain external-validity extensions, not completed evidence. The present scope is a diagnostic benchmark rather than a general solver leaderboard; extra inference is not needed to verify the reported small-graph outcomes, but would be needed to support those broader claims.

Artifact and societal scope. All model prompts in this release are synthetic graphs, not personal-network records. The LT task is an abstract diffusion objective; it does not validate manipulation of people or predict real social behavior. The release excludes credentials, weights, provider response bodies and hidden reasoning. The code and aggregate presentation are released separately from local experimental ledgers. A stable archival identifier, raw-evidence distribution permissions, author disclosures and any required license decisions must be finalized before public submission. We do not invent author affiliations, funding, publication approval or acceptance.

F Related work

Graph reasoning benchmarks. NLGraph evaluates language models on graph problems expressed in natural language, while GraphArena extends graph-computation evaluation to real-world-derived graphs and distinguishes optimal, feasible but suboptimal, infeasible, and missing solutions [17, 21]. These benchmarks establish graph computation and solution verification as existing evaluation directions. GraphWiz uses the GraphInstruct instruction-tuning corpus to train models that produce explicit reasoning paths for graph problems [3]. GraphLLM integrates graph learning models with language models, illustrating that graph representation and model design can change together [2]. CLRS provides a complementary algorithmic-learning perspective spanning graph algorithms and other classical procedures [20]. Our study examines exact decisions and bounded-choice construction under interface and verification controls, rather than proposing a graph-trained model or a general algorithmic-learning benchmark.

Learned constructive optimization. Sequential neural decisions for combinatorial optimization predate the systems evaluated here. Khalil et al. combine graph embeddings and reinforcement learning to learn greedy constructive policies for problems including MaxCut and TSP; Kool et al. train attention-based routing policies using REINFORCE with a greedy rollout baseline [11, 12]. Our tasks share the incremental-decision setting but evaluate general-purpose decision interfaces without claiming to replace specialized learned policies. The community task uses standard modularity [16], restricted to at most two communities; it is not unrestricted community detection or recovery of ground-truth communities. Likewise, our influence task uses fixed thresholds and deterministic

diffusion. It must not be conflated with the classical independently randomized-threshold LT model whose expected spread is submodular [10]. That model's greedy approximation guarantee is not assumed here.

Typed decisions and contemporary systems. TypeSafe's launch article describes Jev as returning typed probabilistic decisions rather than generated strings [1]. Its model documentation identifies weaknesses in numeric precision and multi-step indirection [19]. These are vendor descriptions, not independent architecture or graph-performance evidence. Two contemporary, non-peer-reviewed software projects are relevant [13, 18]. SemIf implements direct option-logit readout from open models and distinguishes reproducing an interface pattern from reproducing Jev's undisclosed model. WorldTour already evaluates Jev-guided next-city choices for heuristic routing and disclaims global optimality of its large tour. We therefore make no priority claim for typed-choice evaluation or Jev-guided TSP.

Typed-decision leaderboards. JevBench evaluates bounded decisions across routing, policy application, answer judgment and related reasoning tasks [5]. Its v1.4.2 ranking combines accuracy-related and calibration axes with deployment-dependent speed and cost; outranking Jev therefore need not mean better decision accuracy or predictive-distribution equivalence. The published label-scoring protocol does not verify complete graph constructions. We do not exclude graph-related content in private items, but distinguish that decision-evaluation contract from our exact objectives and accumulated own-history construction errors. Leaderboard ranks provide context for candidate selection, not evidence of transfer to our tasks.

Scope of this benchmark. Our combination of matched query pairs, explicit identity checks and exactly scored own-history construction addresses particular shortcuts and accumulated decision errors. It does not establish immunity to every shortcut or training-data contamination. Same-backbone interface comparisons do not identify a closed service's architecture; exact performance on tiny instances does not establish large-graph scaling or general solver superiority.

Predictive reliability. Returning a numeric distribution is not evidence of calibrated uncertainty. Proper scoring rules evaluate the predictive distribution against outcomes [6]; modern-network calibration studies distinguish classification accuracy from confidence reliability [7]. These motivate separate probability diagnostics rather than treating a typed API or normalized option logits as calibrated by construction. We do not transfer published calibration findings to the present models without data.

G Capability profile and diagnostic interpretation

G.1 RQ1: Discrimination is task dependent

The benchmark distinguishes several capabilities rather than defining one hardness scale. On the canonical challenge, Jev answers every adjacency query correctly, whereas Kev reaches 78.75%, Decider 58.75%, and Laya 50%. Jev's degree macro accuracy is 61.43%, versus 19.88% for Kev, and its connectivity accuracy is 85%, versus 58.75%. Conversely, distance accuracy is 58.75% for Jev and 42.5–52.5% for the earlier direct configurations; the added Qwen3.8-27B and Qwen2.5-72B score 48.75% and 60%, respectively. Close scores around the balanced binary baseline do not support a stable fine-grained ranking.

Consecutive graph sizes offer descriptive resolution, not identified capacity thresholds. Jev degree accuracy is 70.3% at eight vertices and 49.0% at twelve; cycle accuracy is 81.25% and 50%, respectively, with nonmonotone intermediate values. Connectivity does not exhibit the same decline, and adjacency remains perfect throughout. The degree task also increases its number of classes with size. These observations cannot be reduced to "Jev fails at twelve vertices." Each binary size cell contains only sixteen queries in eight pairs; each construction cell has eight episodes. We therefore do not assign empirically fitted reliability bands or claim a statistically identified breakpoint.

G.2 RQ2: Construction needs graded quality and actual histories

Mean objective gap is the primary construction-quality comparison. TSP illustrates its discrimination: Jev's gap is 45.85, versus 100.90 for Qwen3.5-27B and 349.65 for Kev. LT supplies a complementary regime: Qwen3.5-27B has a smaller gap than Jev (0.425 versus 0.600), while Kev and Jev tie at 0.600. Community gaps favor Jev over those two configurations (0.1694 versus 0.2810 and 0.2502). All three complete the same forty episodes per task; comparisons involving incomplete configurations must also account for coverage. Optimum-hit counts can conceal large quality differences or suggest an ordering absent from mean gaps, so we retain them only as supplementary diagnostics. The added Qwen3.8-27B and Qwen2.5-72B have larger mean gaps than Jev on all four constructions. This supports a task-specific direct-decision advantage over those configurations, not equivalence to a general 72B model. The 72B baseline differs in generation as well as scale, and no matched latency or training-data control isolates the cause.

Absolute usefulness requires non-neural references. In the original four-configuration challenge, all neural MaxCut gaps exceed the exact uniform-policy expected gap (Jev: 8.150, uniform: 5.325); classical cut search has mean gap 0.450. Nearest-neighbor plus 2-opt has mean TSP gap 0.200 versus Jev's 45.850. These algorithms may revise earlier choices and are quality references, not equal-budget online competitors (Appendix I).

Exact continuation analysis explains where completed trajectories become irreversibly suboptimal. On 640 constructions of the original four configurations, the sum of stepwise continuation losses equals the final objective gap for all 4,480 decisions. For TSP, optimality is already lost at the first choice in 3/40 Jev episodes, compared with 22/40 grammar-4B episodes. Later valid actions need not recover the lost optimum. This analysis uses actual model histories after inference; favorable oracle-prefix choices are not substituted for rollout performance (Appendix I.3).

G.3 RQ3: Replication and controls constrain the interpretation

The prospective 952-instance, topology-excluded confirmation covers the original four configurations, not all twelve. All four again have larger MaxCut gaps than the uniform legal policy; Jev retains perfect adjacency accuracy. Individual rankings do change, so this supports selected qualitative findings rather than every canonical point estimate (Appendix J).

Controls distinguish behavioral weakness from several identifiable artifacts. Full native-score and action replay retains Laya's constant-yes outcome; its selected option-reversal pilot argues against a simple first-option explanation, not against every possible prompting effect. For the original local baselines, identical aggregate accuracy can conceal complete semantic-choice reversal. At a fixed token prefix, 4B score argmax and masked greedy generation agree on 100/100 states, preventing attribution of the main pipeline's gains to argmax alone. Jev's above-chance distance accuracy also coexists with probability losses worse than uniform on the common-valid probability-audit rows. These checks address distinct failure modes; they are not a proof of freedom from all implementation errors (Appendix K).

What the current boundary evidence establishes. The suite contains positive controls, partially successful structural decisions, and construction failures with measurable quality differences. This is enough to characterize task-dependent strengths and weaknesses within the tested protocols. It does not locate the onset of every failure or establish size generalization. Additional research should preferentially confirm the open readouts on fresh graphs and resolve transition regions with controlled structure, including simpler cases where necessary. Increasing graph size merely because Astra remains successful is not a requirement of this diagnostic objective.

H Supplementary construction optimum-hit counts

The primary construction comparison uses mean objective gaps and feasible coverage (Table 4). Counts below are retained for continuity with the frozen experiment outputs; they are not the primary quality metric.

Model	MaxCut	TSP	Deterministic LT	Modularity
Jev	0/40	3/40	23/40	7/40
Qwen4 G	0/40	0/40	13/40	0/40
Qwen9 G	0/40	0/40	5/40	0/40
Qwen27 G	0/40	1/40	29/40	0/40
Qwen3.8-27B	0/40	0/40	10/40	0/40
Qwen2.5-72B	0/40	1/40	5/40	0/40
Qwen4 scores	0/40	0/40	3/40	0/40
Decider	0/40	0/40	1/40	0/40
Kev	0/40	0/40	26/40	1/40
Laya	0/40	0/40	6/40	0/40
GPT-5.4	36/40	39/40	40/40	36/40
Astra	40/40	40/40	40/40	40/40

Table 7: Supplementary complete canonical optimum hits over all forty scheduled episodes per task. All tied optima are accepted. Laya's nine LT input rejects and GPT-5.4's nine timeouts remain in denominators.

I Results on the inspected structural challenge

I.1 Primitive correctness is task dependent

Jev obtains 100% adjacency accuracy but 58.75% distance and 65% articulation accuracy (Table 8). Its degree macro accuracy is 61.43%, whereas pooled accuracy is 241/400, or 60.25%. Reporting only the direct-lookup ceiling would obscure these differences.

Candidate scoring improves 4B adjacency from 60% to 77.5% but does not uniformly improve other tasks. Nor does the bounded 9B configuration uniformly improve on 4B. Binary chance-level results are accompanied by prediction counts and per-label/per-degree recall, since a constant answer can achieve 50% on balanced pairs without discriminating either case. The size curves (Figure 1) are descriptive; topology, serialization length and action cardinality also vary.

Exact task (macro %)	Jev action	4B grammar	9B grammar	4B scores
Adjacency	100.00	60.00	58.75	77.50
Degree	61.43	18.32	26.99	23.89
Cycle	66.25	55.00	51.25	51.25
Connectivity	85.00	50.00	53.75	51.25
Distance	58.75	50.00	42.50	52.50
Articulation	65.00	50.00	50.00	50.00

Table 8: Exact-task macro-size accuracy (%). All four methods complete all 960 challenge instances. Each binary task has eighty cases; degree has 400. These are bounded configurations, not unrestricted model-capacity rankings.

Task	Jev action	4B grammar	9B grammar	4B scores	Classical
MaxCut	0/40	0/40	0/40	0/40	29/40
TSP	3/40	0/40	0/40	0/40	37/40
Deterministic LT	23/40	13/40	5/40	3/40	35/40
Modularity	7/40	0/40	0/40	0/40	35/40

Table 9: Optimal solutions over forty scheduled episodes per construction task. Classical references use separate revisable full-solution algorithms. All model episodes in this table are feasible.

I.2 Legal construction does not imply competitive optimization

All four primary bounded configurations miss every MaxCut optimum; their mean gaps also exceed the uniform-policy expected gap (Table 10). Classical cut search reaches 29/40 optima. For TSP, Jev reaches 3/40 optima versus 37/40 for nearest-neighbor plus 2-opt. Thus neither legal output nor relative improvement over a weak neural configuration implies a useful solver. On LT, 4B scoring attains only 3/40 optima versus 13/40 for 4B generation; the same readout that improves adjacency can harm sequential performance.

The suspicious cut and modularity floors triggered independent NetworkX objective recomputation, with zero mismatches. The 4B grammar configuration assigns every remaining vertex to B in all forty cuts; 9B does so in 39/40, scoring in 20/40, and Jev in 13/40. The scoring method chooses all-A on every modularity episode, legally obtaining $Q = 0$. These are observed policies, not proofs of an internal failure mechanism or an exhaustive absence of bugs.

I.3 Where actual trajectories lose optimality

Let s_t include all choices through time t, and let $V(s_t)$ be the best final objective still reachable by any legal completion. Define

$$r_t = \begin{cases} V(s_{t-1}) - V(s_t), & \text{maximization,} \\ V(s_t) - V(s_{t-1}), & \text{minimization.} \end{cases}$$

Restricting the completion set cannot improve the optimum, so $r_t \geq 0$. For a complete trajectory, $V(s_0) = f^\star$ and $V(s_T) = f$; consequently $\sum_{t=1}^{T} r_t = \text{gap}$. This elementary telescoping identity distinguishes the first irreversible loss from a later locally optimal action in an already damaged state. It does not require one unique optimal action.

We compute this diagnostic *after inference* from actual histories, using exact prefix-conditioned continuations. Across 640 complete construction episodes and 4,480 decisions, every decomposition




Figure 1: Selected size curves on the structural challenge. Exact-task accuracy and construction optimum-hit rate are different metrics. Each construction point has eight episodes; curves do not imply monotone or size-causal difficulty. Full task/size counts are in the artifact.

equals the independently replayed final gap within 10^{-12}. Table 11 shows how often optimality is lost immediately. For MaxCut, only 7–8 of forty episodes lose optimality at the first action despite every complete neural solution being suboptimal. In TSP, the first action already loses optimality in 22/40 grammar-4B and 29/40 scoring episodes, versus 3/40 for Jev. No oracle continuation value was returned to the model.

I.4 Latency and native conformance are separate outcomes

Across development and challenge, the four-method matrix makes 10,352 actual calls for 5,264 scheduled instance evaluations. Jev retains 25 strict native observations: 24 probability-sum checks and one choice/argmax check. All supplied actions are eligible under the separately frozen action protocol. We neither normalize probabilities nor infer replacement choices. The unchanged strict production parser and its historical results remain available as a different protocol.

The challenge scoring method evaluates 8,880 candidates in 1,920 prefixes, with 1,920 unused generated tokens. Median request latency is 64.41 ms, compared with Jev's 70.01 ms (Table 12). This is not evidence that one architecture is inherently faster. Vendor-reported tokens are preserved but are not interchangeable autoregressive steps, FLOPs, energy, or monetary cost. No unsupported carbon or cost saving is inferred.

Task	Jev action	4B grammar	9B grammar	4B scores	Classical	Uniform
MaxCut	8.150	11.125	11.050	9.200	0.450	5.325
TSP	45.850	338.150	306.450	351.000	0.200	331.288
Deterministic LT	0.600	2.625	3.725	4.125	0.175	4.182
Modularity	0.169	0.290	0.320	0.281	0.007	0.338

Table 10: Mean additive objective gap, lower is better. Uniform is the exact expected gap of uniform legal decisions, not a sampled solver. Columns are comparable within a row only; the four objectives have different units.

Task	Jev action	4B grammar	9B grammar	4B scores
MaxCut	8/40	8/40	8/40	7/40
TSP	3/40	22/40	21/40	29/40
Deterministic LT	8/40	12/40	24/40	26/40
Modularity	12/40	10/40	23/40	23/40

Table 11: Episodes losing every globally optimal completion at the first decision, over all forty feasible episodes. Later errors remain represented in the full per-step regret artifact. This is a retrospective diagnostic, not a new inference experiment.

J Prospective new-seed confirmation

After fixing the common-interface protocol and four configurations, we registered a separate confirmation before generating or evaluating its graphs. Seed 20261012, sizes 8–12, eight repetitions and the same 128-proposal cap were fixed. The prior pool includes the earlier exclusion pool, both inspected development banks, the original challenge, and forty executed TSP confirmation metrics: 2,052 labeled normalized graph records after deduplication. These are not 2,052 isomorphism classes. Independent graph reconstruction and 1,421 exact VF2 comparisons after necessary invariant screening found zero prior overlaps.

The generator fills 952/960 requested instances. Four cycle pairs at $n = 8$ exhaust the finite proposal budget, leaving eight explicitly missing cases; cycle has 72 instances and every other task reaches its quota. The seed is not retried and no unmatched fallback is introduced. This limitation affects coverage and precision, not just implementation bookkeeping: only four cycle-pair clusters remain at $n = 8$. The repeated task/size quotas are not changed after observing any model answer.

All four methods complete all 952 realized cases, using 1,912 calls each: 3,808 instance evaluations and 7,648 actual calls. The eight Jev probability-sum observations remain conformance diagnostics; no action execution fails. Sealed attempts, scores and requests replay successfully, and initial public requests agree across all methods. The same diagnostic exporter checks another 640 construction trajectories and 4,480 decisions, again with zero continuation-loss telescoping mismatches.

The confirmation preserves the principal qualitative observations without reproducing every numerical ranking. Jev retains its adjacency ceiling; 4B scoring again improves adjacency over 4B grammar (85% versus 63.75%). All methods again miss every MaxCut optimum and have larger expected gap than the uniform legal policy. TSP optimum hits are 2/40 for Jev, zero for the other neural configurations, and 40/40 for the classical reference. Such a classical ceiling is evidence that these particular small TSP instances are controls for neural interfaces, not difficult classical optimization benchmarks. On LT, scoring reaches 2/40 optima versus 6/40 for 4B grammar, retaining the task-dependent tradeoff.

Method	Median (ms)	p95 (ms)
Jev action	70.01	115.55
4B grammar	94.24	146.18
9B grammar	148.64	235.12
4B scores	64.41	139.83

Table 12: Observed client-path request latency on the challenge. Network, rendering, cache and hosting differ; this is not an architecture-isolated speed comparison. No compute-equivalence claim is made.

Exact task (macro %)	Jev action	4B grammar	9B grammar	4B scores
Adjacency	100.00	63.75	58.75	85.00
Degree	64.15	17.38	25.73	20.26
Cycle	71.25	51.25	53.75	50.00
Connectivity	87.50	50.00	55.00	53.75
Distance	58.75	50.00	57.50	50.00
Articulation	58.75	50.00	50.00	50.00

Table 13: Prospective confirmation exact macro-size accuracy (%). Cycle has 72 cases, degree 400, and the other binary tasks eighty each. The macro estimator weights the five sizes equally, not by their case counts.

Conversely, 9B distance accuracy changes from 42.5% on the inspected bank to 57.5% here; an individual ranking from one small sample is not a universal capacity claim. Jev-minus-4B-grammar articulation accuracy is 8.75 percentage points with pointwise interval [0,17.5], not a separately established family-wise significant improvement. Full paired intervals appear in the appendix. This confirmation addresses reuse of inspected graphs, but not unseen generator families, larger sizes, pretraining contamination or closed-model service drift.

K Interface controls and stronger-model context

Graph-preserving presentation changes. We preregistered 120 exact-task cases from the confirmation bank: four per task and size. Binary tasks use two complete query/construction pairs; degree uses four prespecified degree strata, not every class. Original, identical-repeat, node-relabeling, edge-shuffling and option-reversal arms produce 2,400 decisions across the four methods. Independent NetworkX checks preserve every transformed label. The relabeling consistently transforms queries and edge endpoints without also shuffling edge positions. Two edge permutations leave the actual serialized input unchanged; both are retained and identified rather than replaced.

All actions are valid. Four Jev strict-native observations are retained separately. Adjacency remains robust for Jev on all twenty selected cases, but its degree correctness falls from 15/20 in the original arm to 11/20 after relabeling; only 9/20 are correct across all five arms (Table 16). An identical repeat already changes two Jev degree choices, so individual flips cannot all be causally attributed to the intervention.

Conversely, 4B grammar connectivity chooses the same answer across all five arms on every case, yet is consistently wrong on ten of twenty cases. For 9B articulation, original and reversed-option accuracy are both 10/20, yet reversing options flips all twenty semantic choices; identical repeats, relabeling and edge shuffling flip none. No case is correct across all five arms. Marginal accuracy can therefore hide severe semantic-choice instability; invariant wrong output is not successful robustness.

Task	Jev action	4B grammar	9B grammar	4B scores	Classical
MaxCut	0/40	0/40	0/40	0/40	20/40
TSP	2/40	0/40	0/40	0/40	40/40
Deterministic LT	21/40	6/40	2/40	2/40	34/40
Modularity	2/40	0/40	0/40	0/40	34/40

Table 14: Prospective confirmation optimal solutions over forty scheduled episodes per construction. All episodes are feasible; classical algorithms are independently recomputed on these new graphs.

Task	Jev action	4B grammar	9B grammar	4B scores	Classical	Uniform
MaxCut	9.000	11.575	11.375	9.825	0.725	5.475
TSP	45.300	315.950	298.250	345.100	0.000	334.111
Deterministic LT	0.825	2.600	3.575	3.425	0.250	3.677
Modularity	0.209	0.290	0.294	0.269	0.005	0.326

Table 15: Prospective confirmation mean additive gaps. Uniform columns are exact policy expectations. No graph, task or method is selected for inclusion based on its observed score.

This is a finite descriptive panel with dependent query pairs, one repeat, and fixed arm ordering, not a population guarantee or a comparison over 600 independent graphs per method.

Isolating the readout at a fixed token prefix. The main 4B comparison changes rendering, label coding and decoding, not only the mathematical selection rule. To test the latter directly, we registered 100 initial states: two opaque-ID-first cases per task and size from the completed confirmation bank. Three rotating-order arms use exactly the same prompt token IDs and candidate tokens: requested candidate scores, an identical repeat, and candidate-masked greedy one-token generation. The greedy action is mapped from its actually emitted token; it is not substituted by a post-hoc argmax. The generated token is ignored only in the score arms, and all generated tokens are counted.

All 300 calls succeed. Score argmax and greedy generation agree on 100/100 choices, as do the score repeats. The largest conditional-probability difference is exactly zero in these observed responses. Payload replay checks identical prefixes, the mask, candidate mapping and token accounting. This is consistent with the elementary equivalence of greedy selection and argmax on the same logits; it is not a universal backend equivalence or a successful CPU SemIf reproduction. In particular, the main adjacency gain must be described as a *decision-pipeline* effect, not an isolated benefit of using argmax. Which remaining rendering or coding component causes that gain is not identified by this control. Construction states here are initial states only, not new rollout scores.

Teacher-forced controls are not rollout scores. On 24 development graphs, 48 informative optimum-prefix states were tested with original, repeated, reversed-option and explicit-description arms: 384 real decisions across Jev and constrained 9B. Relative to the original, 9B changed 15/48 valid choices under option reversal and 0/48 on identical repeats; Jev changed 5/46 and 2/46. Repetition variability prevents attributing every changed choice to the treatment. Both methods solve all six late MaxCut original-arm states, despite poor free-running cut performance. This illustrates why favorable oracle-prefix decisions cannot substitute for own-history episodes.

Task	Jev action	4B grammar	9B grammar	4B scores
Adjacency	20/20	10/20	11/20	8/20
Degree	9/20	1/20	3/20	3/20
Cycle	9/20	4/20	10/20	10/20
Connectivity	13/20	10/20	10/20	8/20
Distance	10/20	10/20	5/20	0/20
Articulation	9/20	1/20	0/20	0/20

Table 16: Cases correct in all five presentation arms, over twenty selected cases per task. Full arm accuracies and paired choice-flip counts appear in the appendix. The degree panel uses four prespecified degree strata per size.

Task	Valid J/T	Common	Jev	4B scores	Uniform
Adjacency	80/80	80	0.000	0.199	0.500
Degree	382/400	382	0.458	0.841	0.900
Cycle	72/72	72	0.420	0.720	0.500
Connectivity	80/80	80	0.152	0.682	0.500
Distance	80/80	80	0.509	0.550	0.500
Articulation	80/80	80	0.508	0.534	0.500

Table 17: Prospective probability audit: summed multiclass Brier, lower is better. "Valid J/T" gives each method's own vector denominator; loss columns use exactly the common-valid rows. Uniform is evaluated on the same rows with their actual option cardinalities. No cross-task aggregate is used.

Prospective probability diagnostics. Earlier canonical Jev logs do not retain complete probability vectors, so their calibration cannot be reconstructed from choices or sum diagnostics. We instead register new calls on all 792 exact cases of the confirmation bank, for Jev action and 4B candidate scores: 1,584 observations. Raw vector entries are neither normalized nor clipped. Probability scores require action eligibility, exact option keys, finite entries in $[0, 1]$ and mass within the frozen 10^{-6} tolerance. Omitted vectors and all-scheduled action accuracy remain separate outcomes.

For accepted vectors, summed multiclass Brier loss is $\sum_k (p_k - \mathbf{1}[k = y])^2$ and logarithmic loss is $-\log p_y$. A zero true-label probability has positive-infinite loss; it is not replaced by a small epsilon or silently dropped from an average. Binary uniform Brier is therefore 0.5 under this summed convention, not 0.25. We compare both models and the uniform reference only on the common-valid intersection, alongside each model's own retained-vector count. Five fixed reliability bins use the probability of the *actually supplied choice*, not an inferred replacement argmax or an assumed interpretation of a vendor confidence scalar. No calibration parameter or threshold is fitted. These are row-averaged, task-specific diagnostics on inspected synthetic graphs, not population calibration guarantees.

All 792 actions per method are eligible. Jev retains 774 vectors after eighteen sum-invalid degree vectors are omitted; both choice/argmax-disagreeing vectors are retained with the actual supplied choices. All 792 token-score vectors are valid, giving 774 common-valid rows across tasks. Despite Jev's above-chance action accuracy on distance (48/80) and articulation (47/80), their Brier losses, 0.509155 and 0.508225, exceed the uniform reference of 0.5; their logarithmic losses also exceed $\log 2$. Thus accuracy above chance and numeric probability output do not establish useful uncertainty estimates. In contrast, Jev's adjacency Brier is 0.000120. The task-specific pattern, not a pooled calibration ranking, is the intended diagnostic.

This audit also exposed a bookkeeping bug after inference: canonical JSON key sorting changed the order of floating-point additions. Ten native sum metadata values differed on replay by at most 2.22×10^{-16}, although no vector's eligibility changed. The original producer failed to seal its native lane; all 792 recorded responses were retained without additional calls. Corrected offline analysis is separately versioned and preserves the original failure, vectors and action decisions. Its derived-sum roundoff check is distinct from both the unchanged 10^{-6} vector gate and the failed 0.01 CPU/GPU reproduction criterion.

A prospective TSP wording confirmation. Six late Jev TSP control failures all selected the city closest to start vertex 0, although the actual current endpoint differed. Independent enumeration confirmed the labels. This motivated a bundled state-explicit wording treatment, not a claim to identify an internal mechanism.

Forty newly generated weighted metrics were independently excluded from eighty earlier weighted TSP instances within a refreshed 1,840-record pool. Under the original strict protocol, Jev completes 36/40 original-wording and 33/40 explicit-wording episodes. On the 29 commonly feasible graphs, relative gap improves by 0.3761 (pointwise 95% interval [0.2337, 0.5462]); this conditional comparison does not establish improved completion.

A separately registered action-observation run on those same forty metrics completes all eighty episodes. Mean relative gap falls from 0.5152 to 0.1603; the paired reduction is 0.3550 [0.2463, 0.4729]. Nine strict-native observations remain recorded. This second protocol removes feasibility selection within that comparison, but is a repeated use of the metrics, not a second untouched confirmation set. No prior failed response was retrospectively rescued.

Stronger reasoning models change the picture. Completed earlier *seven-task, legacy-protocol development* runs provide an important counterpoint. GPT-5.4 solves all 200 exact decisions and all 62 feasibly completed construction episodes optimally; two timeouts leave two other constructions incomplete (559 actual calls). GPT-6-Astra solves all 200 exact decisions and 63/64 constructions optimally with no failures (576 calls); its single suboptimal cut has value 20 versus optimum 21. These are not missing columns to paste into the common-interface challenge: the tasks, bank and protocol differ. They nevertheless preclude interpreting weak bounded Qwen results as evidence of universal LLM incapacity.

The subsequently completed *ten-task legacy-interface Astra challenge* uses the same 960 graph instances and references as the inspected canonical challenge. Its frozen runner replays all 1,920 calls with no failures. All 800 exact decisions are correct, and 159/160 constructions are optimal (Table 18). The sole miss is an eight-vertex community partition with $Q = 0.0244444$ versus $Q^\star = 0.08$; independent NetworkX evaluation confirms all forty community objectives, and enumeration of all 128 anchored assignments confirms this optimum.

This result is intentionally separate from the primary matrix: the legacy instructions and option descriptions differ, with zero of 960 full initial requests identical to their canonical counterparts. Astra uses default reasoning and a 4,096-token ceiling rather than the bounded local decoding settings. The result demonstrates that these graph instances are tractable for this stronger configuration; it does not isolate model architecture, protocol effects or equal-compute superiority.

K.1 Completed canonical GPT-5.4 anchor

This separately registered tool-free, default-reasoning GPT-5.4 run uses the identical canonical structural-challenge requests and own histories. It made 1,840 actual calls, with 9 failed attempts. Failures remain in scheduled denominators; no retry or repair was performed. Observed median/p95

Task	Correct / optimal	Feasible	Mean gap
Adjacency	80/80	80/80	–
Degree	400/400	400/400	–
Cycle	80/80	80/80	–
Connectivity	80/80	80/80	–
Distance	80/80	80/80	–
Articulation	80/80	80/80	–
MaxCut	40/40	40/40	0.000000
TSP	40/40	40/40	0.000000
Deterministic LT	40/40	40/40	0.000000
Modularity	39/40	40/40	0.001389

Table 18: Completed Astra legacy-interface challenge on the same graphs as the inspected primary challenge. The first six rows report correct answers; the final four report optimum hits. Mean gaps are task-specific and are not pooled. This is a separate protocol/default-reasoning reference, not an additional column of the canonical four-method matrix.

Exact task	GPT-5.4 (%)	Jev (%)	95% interval (pp)
Adjacency	100.00	100.00	[0.00, 0.00]
Degree	100.00	61.43	[33.75, 43.30]
Cycle	100.00	66.25	[27.50, 40.00]
Connectivity	100.00	85.00	[8.75, 22.50]
Distance	100.00	58.75	[35.00, 46.25]
Articulation	100.00	65.00	[26.25, 43.75]

Table 19: Canonical exact macro-size accuracy. Intervals are paired, size-stratified pointwise GPT-minus-Jev differences, not family-wise tests.

GPT request latency was 7220.20/96561.70 ms. Reasoning budget and hosting differ from the small no-thinking local baselines. These are inspected-bank common-protocol anchors, not the prospective new-seed confirmation or a matched-compute architectural comparison. Request identity here concerns all 960 initial public requests. Later construction requests follow each method's own choices and need not match; neither model receives the other's trajectory or oracle actions. All nine failed attempts are timeouts in construction episodes: four MaxCut, one TSP and four modularity. Across 960 scheduled episodes, all 800 exact answers are correct and all 151 feasible constructions attain exact optima. An additional independent objective check reproduces every feasible construction using NetworkX or exact-rational diffusion. This strengthens the interpretation that the bounded models' failures are not unavoidable properties of the graph instances or the canonical action interface. It does not establish equal-compute superiority, out-of-distribution generalization, or unconditional construction perfection: the nine incomplete episodes remain in every all-scheduled denominator.

Exploratory larger-local-model check. After inspecting the primary results, we registered a small, score-blind selection from the confirmation bank: four cases per exact task and two per construction at each of $n = 8, 12$, retaining binary pairs and degree strata. The resulting 64-episode, 160-decision panel compares a fresh Qwen3.5-27B BF16 run with reused Jev and bounded-Qwen reference traces on exactly the same instances. The 27B configuration keeps the 64-token, no-thinking, legal-choice grammar contract and completes every episode without failure. This is an inspected-bank exploratory extension, not an independent replication.

Task	GPT feasible	GPT optima	Jev optima	GPT gap
MaxCut	36/40	36/40	0/40	0.000
TSP	39/40	39/40	3/40	0.000
Deterministic LT	40/40	40/40	23/40	0.000
Modularity	36/40	36/40	7/40	0.000

Table 20: Canonical construction results. Gaps condition on GPT feasible completion and have different units across rows; they are not a pooled score.

On this panel Jev exceeds bounded 27B on degree (6/8 versus 4/8), connectivity (7/8 versus 6/8), and cycle detection (5/8 versus 4/8), while 27B exceeds Jev on distance (5/8 versus 4/8). Adjacency and articulation tie (Appendix Q). Jev has better mean cut, TSP and community objectives; LT ties, including 2/4 optimum hits for both. Neither reaches any cut, TSP or community optimum on these four-case tasks. These observations concern the specified no-thinking grammar configuration only. They do not establish parameter equivalence or bound 27B's unrestricted capacity; the completed thinking comparison below substantially changes the exact-task interpretation. Historical reference latency is not a controlled timing comparison, and these small denominators support no significance claim.

Thinking improves exact answers but exposes deadline failures. The completed 27B and 9B thinking lanes use the same selected instances and canonical initial requests, but enable thinking, remove grammar constraints, and raise the output-token cap from 64 to 8,192 jointly. The per-request deadline is 180 seconds. Their exact counts are 47/48 and 40/48, versus 33/48 for reused Jev and 30/48 for 27B grammar. Every returned exact answer is correct: 47/47 and 40/40, respectively. The remaining exact cases are timeouts, not observed wrong predictions; 27B's one timeout is a distance query. All 48 scheduled exact cases remain in the reported accuracy denominators.

Both thinking lanes time out within every one of their sixteen construction episodes, leaving zero feasible constructions. Across the whole panel, 27B records 17 timed-out calls among 66 attempts; 9B records 24 among 64. Conditional construction gaps are therefore undefined, not zero, and provide no quality ranking between these configurations and methods that finish. The substantially stronger exact results overturn an interpretation of the bounded comparison as Jev–27B capability equivalence. This is a joint inference-configuration effect, not an isolated causal effect of reasoning.

A separate timeout-only 9B control raises the deadline to 600 seconds while retaining the 8,192-token cap. All sixteen construction attempts then terminate at that token cap, still yielding no feasible trajectories (Table 28). Increasing wall time alone therefore does not resolve these completion failures.

Two additional trained decision readouts. We also evaluate the released Decider-2B v11 and Kev-4B trained inference paths [8, 9, 14, 15], not ordinary next-token substitutes. Both complete all 64 episodes in 160 calls, without execution failures. Decider obtains 24/48 exact answers and Kev 23/48, versus 33/48 for Jev. Neither answers a degree query correctly, despite legal, varied predictions and the full eight- or twelve-class vocabulary. Decider reaches no construction optimum; Kev reaches one LT optimum, compared with Jev's two LT optima. This is not an all-task Jev win: Kev's mean modularity gap is 0.113657, better than Jev's 0.235880. Appendix Q reports taskwise coverage, optimum hits and conditional gaps separately, along with dtype, source-version and environment limitations. Native probability conformance is not evidence of calibration on these

graph tasks.

An encoder-based trained decision model. A separate Laya typed-decisions pilot evaluates a roughly 421M-parameter ModernBERT encoder with its genuine trained choice head [4], using native CPU FP32 inference on the same 64-case panel. Its checkpoint contract permits 1,024 total tokens and a 256-token head. Lossless tokenization checks reject two $n = 12$ LT requests before inference; no graph, question or option is truncated. The remaining 62 episodes require 156 successful forwards, with no later context overflow. Laya obtains 22/48 exact answers versus 33/48 for reused Jev, and no optimal construction among fourteen initially supported cases versus two for Jev. All forty binary answers are `yes`, yielding the constant-yes baseline of 20/40; degree contributes 2/8. Native logits, probability-to-ID mapping and canonical action replay are checked rather than assuming these constant predictions are a parser failure. A separate twenty-call option-order diagnostic preserves `yes` on all ten paired states after reversal, arguing against a fixed-first-option explanation on this selected subset, not establishing a claim about every Laya prompt or task. Appendix R separates input coverage from solution quality and discloses an offline postprocessing recovery.

L Exact contracts, invariants and budgets

Node relabeling does not change truth, but rendering may affect model outputs. Cycle twins match degree sequences, not component count: $m > n - c(G)$ is an exact cycle test for the stated undirected contract. Distance pairs share their threshold and finite distances $h, h + 1$. Articulation compares total component counts before and after deletion; isolated vertices are not articulation points under this definition.

For LT, normalized incoming weights and a fixed one-half threshold are applied synchronously to the two initially chosen seeds. Seeds are not activated one at a time with diffusion between selections. For TSP, prefix cost, the current endpoint, all remaining cities, and final return to 0 enter continuation values. For partitions, vertex 0 fixes complement symmetry without excluding any attainable objective; empty sides remain legal. Modularity search is over at most two groups, including one group. Histories must contain legal, exact-string action IDs, not a repaired subset of malformed model output.

Reference values are obtained by exhaustive partitions/seed pairs or exact TSP dynamic programming and checked independently. Uniform cut expectation is $m/2$; uniform TSP expectation is $2\sum_{\{u,v\}} d_{uv}/(n-1)$. Uniform LT averages all distinct unordered seed pairs. For uniform binary modularity with one fixed vertex, expected modularity is $-\sum_v d_v^2/(8m^2)$. These are expectations of random legal policies, not attainable objective guarantees for one particular rollout.

Why the LT guarantee cannot be imported. Consider vertices a, b, d, c with edges $a \to c$, $b \to c$, $d \to c$. Each edge has weight 1/3 and c requires at least two active parents. Writing $\sigma(S)$ for final spread including seeds, $\sigma(\varnothing) = 0$, $\sigma(\{a\}) = \sigma(\{b\}) = 1$, and $\sigma(\{a, b\}) = 3$. The marginal gain of adding b is 1 at the empty set but 2 at $\{a\}$, violating diminishing returns. This four-vertex example uses the benchmark's exact deterministic diffusion semantics and illustrates why the randomized-threshold theorem does not apply.

M Paired uncertainty for the inspected matrix

Task	Δ (pp)	Pointwise 95% interval	Clusters
Adjacency	40.00	[33.75, 46.25]	40
Degree	43.11	[37.46, 48.88]	400
Cycle	11.25	[2.50, 18.75]	40
Connectivity	35.00	[27.50, 41.25]	40
Distance	8.75	[3.75, 15.00]	40
Articulation	15.00	[6.25, 23.75]	40
MaxCut	0.00	[0.00, 0.00]	40
TSP	7.50	[0.00, 15.00]	40
Deterministic LT	25.00	[5.00, 42.50]	40
Modularity	17.50	[7.50, 30.00]	40

Differences are Jev action minus 4B grammar in percentage points: exact accuracy for the first six rows and optimum-hit rate for the last four. Resampling uses paired identity/construction clusters within each size. Forty clusters means eight per size for these paired binary and optimization tasks. Degree has 400 clusters. The MaxCut zero-width interval reflects the observed all-zero optimum-hit difference, not established equivalence of the underlying models or equal gap quality.

N Paired uncertainty for prospective confirmation

Task	Δ (pp)	Pointwise 95% interval	Clusters
Adjacency	36.25	[30.00, 42.50]	40
Degree	46.77	[41.07, 52.73]	400
Cycle	20.00	[10.00, 30.00]	36
Connectivity	37.50	[31.25, 43.75]	40
Distance	8.75	[3.75, 15.00]	40
Articulation	8.75	[0.00, 17.50]	40
MaxCut	0.00	[0.00, 0.00]	40
TSP	5.00	[0.00, 10.00]	40
Deterministic LT	37.50	[22.50, 52.50]	40
Modularity	5.00	[0.00, 12.50]	40

Conventions are the same as the preceding appendix, but these are new graphs under the pre-inference registration. Cycle has 36 paired clusters, with four at size 8 and eight at each other size. No missing pair is assigned a synthetic model prediction. The construction tasks retain forty clusters each.

O Presentation-control detail

P Probability-loss detail

The artifact includes all five reliability-bin counts and conditional accuracies for each task and method, along with all-scheduled action accuracy, own-valid and common-valid denominators. Vector eligibility is not assumed independent of task difficulty. The 4B vectors are conditional option-logit scores, not calibrated posterior probabilities by definition.

Task	Method	Original	Repeat	Relabel	Edges	Options
Adjacency	Jev action	20/20	20/20	20/20	20/20	20/20
Adjacency	4B grammar	14/20	14/20	12/20	13/20	19/20
Adjacency	9B grammar	12/20	12/20	14/20	13/20	14/20
Adjacency	4B scores	17/20	17/20	15/20	19/20	14/20
Degree	Jev action	15/20	14/20	11/20	12/20	13/20
Degree	4B grammar	3/20	3/20	2/20	2/20	6/20
Degree	9B grammar	9/20	9/20	7/20	10/20	9/20
Degree	4B scores	8/20	8/20	6/20	7/20	10/20
Cycle	Jev action	15/20	15/20	13/20	13/20	14/20
Cycle	4B grammar	10/20	10/20	10/20	10/20	10/20
Cycle	9B grammar	11/20	11/20	10/20	10/20	10/20
Cycle	4B scores	10/20	10/20	10/20	10/20	11/20
Connectivity	Jev action	18/20	18/20	15/20	15/20	19/20
Connectivity	4B grammar	10/20	10/20	10/20	10/20	10/20
Connectivity	9B grammar	10/20	10/20	10/20	10/20	10/20
Connectivity	4B scores	10/20	10/20	10/20	10/20	9/20
Distance	Jev action	11/20	11/20	11/20	12/20	11/20
Distance	4B grammar	10/20	10/20	10/20	10/20	10/20
Distance	9B grammar	10/20	10/20	10/20	9/20	10/20
Distance	4B scores	11/20	11/20	10/20	10/20	10/20
Articulation	Jev action	11/20	11/20	11/20	11/20	10/20
Articulation	4B grammar	10/20	10/20	10/20	10/20	10/20
Articulation	9B grammar	10/20	10/20	10/20	10/20	10/20
Articulation	4B scores	10/20	10/20	10/20	10/20	10/20

Table 21: Correct cases / scheduled cases in each arm. Counts are not independent across arms or paired queries. An unchanged aggregate accuracy does not imply unchanged semantic choices.

Q Completed expanded-model exploratory panel

The selected graphs are reused from the confirmation bank; opaque-ID selection within prespecified pairs/strata does not make this a new held-out evaluation. The 27B configurations use tensor parallelism across two RTX A6000s. Initial public requests are identical across compared configurations, but provider interfaces differ and subsequent requests follow each method's own history. The grammar and trained-native lanes complete all selected episodes; the thinking lanes have the explicit failures below. Each original historical lane is fully replayed before subsetting. Terminal candidate requests, actions, all 64 score rows and summaries are independently replayed and hash-attested. NetworkX/Fraction checks reproduce every feasible construction objective. The paper builder verifies every export seal and source hash, recomputes the CSV denominators and metrics, and requires identical reused reference trajectories across all exports. No failed episode is removed.

Deadline and output-budget interpretation. The 8,192-token cap is not a guarantee of that much decoding before the 180-second wall deadline. For example, 21.3 generated tokens/second

Task	Method	Repeat	Relabel	Edges	Options
Adjacency	Jev action	0/20	0/20	0/20	0/20
Adjacency	4B grammar	0/20	2/20	3/20	7/20
Adjacency	9B grammar	0/20	4/20	3/20	2/20
Adjacency	4B scores	0/20	4/20	2/20	9/20
Degree	Jev action	2/20	6/20	4/20	2/20
Degree	4B grammar	0/20	12/20	11/20	12/20
Degree	9B grammar	0/20	13/20	6/20	9/20
Degree	4B scores	0/20	13/20	6/20	14/20
Cycle	Jev action	0/20	4/20	4/20	3/20
Cycle	4B grammar	0/20	6/20	8/20	8/20
Cycle	9B grammar	0/20	1/20	1/20	1/20
Cycle	4B scores	0/20	0/20	0/20	1/20
Connectivity	Jev action	0/20	5/20	3/20	1/20
Connectivity	4B grammar	0/20	0/20	0/20	0/20
Connectivity	9B grammar	0/20	0/20	0/20	0/20
Connectivity	4B scores	0/20	0/20	0/20	3/20
Distance	Jev action	0/20	0/20	1/20	2/20
Distance	4B grammar	0/20	0/20	0/20	0/20
Distance	9B grammar	0/20	6/20	7/20	6/20
Distance	4B scores	0/20	5/20	7/20	13/20
Articulation	Jev action	2/20	2/20	0/20	1/20
Articulation	4B grammar	0/20	0/20	0/20	18/20
Articulation	9B grammar	0/20	0/20	0/20	20/20
Articulation	4B scores	0/20	0/20	0/20	20/20

Table 22: Choice flips relative to the original arm / both-valid pairs. There are no invalid actions in this completed panel. Edge counts include the two retained unchanged inputs; their separate strata are in the artifact.

permits only about 3,834 tokens in 180 seconds even before other overhead; this illustrative arithmetic is not a controlled speed comparison. A separately registered posthoc 9B control has now completed on all sixteen constructions; only the deadline changes to 600 seconds, with the 8,192-token cap unchanged (at most 112 calls). All sixteen first-step attempts end with `finish_length`, each recording exactly 8,192 output tokens and approximately 239 seconds of client-observed latency, below the relaxed deadline. No response finishes normally, so no action advances a trajectory. We do not salvage a choice from truncated final content, retry, or raise the token cap. All sixteen constructions remain infeasible. Thus, under this registered contract, relaxing the wall deadline exposes a token-limit failure rather than a feasible solution-quality estimate. This is not evidence that the model cannot construct solutions under another prompt, budget or reasoning configuration. Original failures remain unchanged.

Pinned trained methods and compatibility. Decider uses its genuine one-pass restricted-letter readout, BF16 weights and eager inference. The v11 checkpoint requires source version 1.4.0 (commit `15ab28e8`); its plain-choice temperature is 1.164, not the global fallback 1.145. Kev uses the pinned upstream pointer head and LoRA-merged FP32 backbone (source commit `569ea449`), with temperature 2.406050072164233 and an independently pinned Qwen3.5-4B-Base. Model-card and code revisions are cited separately [8, 9, 14, 15]. All 34 registered checkpoint/tokenizer/configuration files are hash-checked; temperatures are independently derived from the Decider configuration and restricted CPU loading of the Kev head metadata, rather than trusted solely from GPU runtime claims. Complete requests retain all original semantic option IDs and descriptions, with an 8,192-token lossless context gate.
The compatible shared runtime uses Python 3.12, Torch 2.13.0, Transformers 5.17.0 and NumPy 2.3.5, with an isolated Accelerate 1.15.0/PEFT 0.21.0 overlay. These are not the full declared

Task	Common	Jev	4B scores	Uniform
Adjacency	80	0.002	0.331	0.693
Degree	382	0.935	2.036	2.312
Cycle	72	0.616	1.045	0.693
Connectivity	80	0.229	1.009	0.693
Distance	80	0.735	0.747	0.693
Articulation	80	0.713	0.729	0.693

Table 23: Logarithmic loss on the common-valid rows from Table 17, in natural-log units. A positive-infinity entry means at least one true label received exactly zero probability, not a missing value. Finite-only averaging is not substituted for an infinite loss.

Task	Jev	27B G	27B T	9B T	Decider	Kev
Adjacency	8/8	8/8	8/8	8/8	7/8	7/8
Degree	6/8	4/8	8/8	7/8	0/8	0/8
Cycle	5/8	4/8	8/8	8/8	4/8	4/8
Connectivity	7/8	6/8	8/8	7/8	4/8	4/8
Distance	4/8	5/8	7/8	7/8	5/8	5/8
Articulation	3/8	3/8	8/8	3/8	4/8	3/8
Exact total	33/48	30/48	47/48	40/48	24/48	23/48

Table 24: Exact correct/scheduled answers on the same selected panel. Each task has four cases at each of $n = 8, 12$. G denotes the 64-token no-thinking grammar setting; T denotes unconstrained thinking with an 8,192-token cap and 180-second deadline. Jev is a reused reference, not fresh inference. Thinking timeouts remain in the denominators; these are descriptive counts, not a population ranking.

upstream environments: Kev specifies Torch below 2.9 and NumPy at least 2.5.3, while Decider specifies NumPy below 2. Unavailable fused kernels use native reference paths. Dtype and deployment are not matched across methods; no latency ranking or full-environment reproduction is claimed. Released temperature fitting is not a calibration guarantee on this selected graph panel.

A limited CPU/GPU numeric check. A separate posthoc control, registered before its fresh CPU forwards, repeats the first $n = 8$ adjacency and first $n = 12$ degree request for each trained model. All four forwards pass the fixed gate of maximum absolute probability difference at most 0.01 plus native-choice agreement. In adjacency/degree order, the differences are approximately 1.49×10^{-8} and 0.002753 for Decider, and 1.19×10^{-7} and 2.91×10^{-7} for Kev. Option keys, argmaxes and input-token counts also agree. The original serialized public inputs are reconstructed without changing values or options; CPU workers use four threads with CUDA uninitialized, and no new GPU inference is performed. This is compatibility on only two requests per model, not exact equality, broad device parity, a quality/calibration guarantee or full-environment reproduction. Agreement also reproduces the incorrect degree choices; it does not make them correct. The earlier SemIf candidate-token failed numerical gate is a distinct experiment and remains unresolved.

Validated failures versus mathematical errors. Both trained methods' eight degree predictions vary and remain within the full legal eight-/twelve-class sets. Recorded option-to-probability mappings and own-history replay agree, and neither prediction vector is explained by a global $+1$ or -1 answer offset. On MaxCut, both always assign every new vertex to

Configuration	Scheduled	Failed	Exact returned	Constructed
Jev	64	0	48/48	16/16
27B G	64	0	48/48	16/16
27B T	64	17	47/48	0/16
9B T	64	24	40/48	0/16
Decider	64	0	48/48	16/16
Kev	64	0	48/48	16/16

Table 25: Completion coverage, separate from correctness. "Failed" counts episodes with an execution failure, all timeouts in the two thinking lanes. "Exact returned" counts feasible exact episodes, not correct answers. Every configuration retains all 64 scheduled episodes. All grammar/native lanes use 160 calls; 27B T and 9B T use 66 and 64, respectively, because timeouts terminate individual trajectories without retries.

Feasible / scheduled

Task	Jev	27B G	27B T	9B T	Decider	Kev
MaxCut	4/4	4/4	0/4	0/4	4/4	4/4
TSP	4/4	4/4	0/4	0/4	4/4	4/4
Deterministic LT	4/4	4/4	0/4	0/4	4/4	4/4
Modularity	4/4	4/4	0/4	0/4	4/4	4/4

Optimum hits / scheduled

Task	Jev	27B G	27B T	9B T	Decider	Kev
MaxCut	0/4	0/4	0/4	0/4	0/4	0/4
TSP	0/4	0/4	0/4	0/4	0/4	0/4
Deterministic LT	2/4	2/4	0/4	0/4	0/4	1/4
Modularity	0/4	0/4	0/4	0/4	0/4	0/4

Table 26: Four constructions per task (two at each size). Feasibility and all-scheduled optimum-hit rates are distinct outcomes. The thinking lanes' 0/4 optimum counts arise from zero completed constructions, not four observed suboptimal solutions. Labels follow Table 24.

B; vertex 0 remains fixed in A. Decider assigns all community vertices to A, yielding verified zero modularity. These feasible objective and exact-answer errors are not parser failures. Conversely, thinking construction timeouts provide no realized completed objective. The four-case construction denominators remain too small for formal significance or universal capability claims.

R Encoder-based typed-decision pilot

The checkpoint and inference code are pinned separately. F16 checkpoint weights are loaded by the upstream CPU path into FP32 without AMP; this is not a GPU timing or equal-precision comparison. Four CPU threads are used, with a 30-second forward deadline and a separate 30-minute worker budget. Initial coverage is 62/64. Both unsupported LT cases exceed the native option-head budget; one also exceeds the total context limit. All 64 remain in scheduled denominators, giving 0/16 Laya and 2/16 Jev construction optimum hits overall. Unsupported inputs are not wrong predictions. Table quality comparisons use the fourteen initially supported constructions, not a retrospectively chosen easy subset.

Task	Jev	27B G	27B T	9B T	Decider	Kev
MaxCut	8.25	9.00	—	—	12.25	12.25
TSP	60.50	146.00	—	—	387.50	360.00
Deterministic LT	1.00	1.00	—	—	4.00	1.50
Modularity	0.235880	0.305421	—	—	0.305421	0.113657

Table 27: Mean absolute objective gap conditional on feasibility, lower being better. Each numeric cell has four feasible episodes; each dash denotes zero feasible episodes and an undefined mean, not zero gap. Units are cut edges, tour cost, active vertices and modularity respectively; they are never pooled. Kev improves the modularity gap over Jev despite lower exact-task accuracy.

Task	180s feasible	600s feasible	600s length stops	600s gap
MaxCut	0/4	0/4	4	–
TSP	0/4	0/4	4	–
Deterministic LT	0/4	0/4	4	–
Modularity	0/4	0/4	4	–

Table 28: Completed timeout-only Qwen9 control on the same sixteen constructions. All four cases per task remain in denominators. The 180-second arm has wall-timeout failures; the 600-second arm has token-limit failures. Conditional objective gaps are undefined in both arms, not zero.

The native API rounds probabilities to four decimals and distinguishes entropy concentration from maximum option probability. Rounded vectors are preserved without renormalization or temperature fitting; neither confidence definition is assumed calibrated. The inference ledger was fully persisted, but an in-memory postprocessor failed on tuple-versus-JSON-list representation in public requests. A separate finalizer replayed the durable JSON ledger without changing inference, the frozen source, registration or original error records. All 64 scores and fourteen feasible construction objectives were independently checked. The exact supervisor wall timer was unavailable after that failure and remains missing rather than reconstructed as a benchmark latency.

Posthoc constant-answer diagnostic. After observing the all-`yes` pattern, we registered a separate control: for each binary task at $n = 8$, choose the lexicographically first positive and negative instance, then evaluate each in original and reversed option order. Semantic IDs and descriptions are retained, and labels are not model inputs. All twenty calls complete: original order yields ten `yes` choices at index zero; reversed order yields ten `yes` choices at index one. Both orders score 5/10. Semantic choices agree on 10/10 pairs, whereas positional indices agree on 0/10. Original-order repeats reproduce the initial-run logits exactly, and all forty initial binary logit vectors are distinct. Full native mask-to-ID checks and an independent ledger verifier support a semantic-`yes` preference rather than a fixed-first-position or observed mapping error in these states. Reversal still changes score values, so this is not a general absence-of-position-bias claim. The ten paired states are adaptively selected diagnostics, not twenty independent examples or a replacement for the initial results. A histogram-key JSON representation issue in the diagnostic replay helper was independently resolved offline, without further inference or alteration of the registered source and original outputs.

Task	Laya CPU	Reused Jev
Adjacency	4/8	8/8
Degree	2/8	6/8
Cycle	4/8	5/8
Connectivity	4/8	7/8
Distance	4/8	4/8
Articulation	4/8	3/8

Table 29: Laya CPU exact-task results on the exploratory panel. All eight instances per task fit losslessly. Historical Jev is independently replayed; these small differences are not a population ranking.

Task	Covered	Laya hits	Jev hits	Laya gap	Jev gap
MaxCut	4/4	0/4	0/4	15.250	8.250
TSP	4/4	0/4	0/4	368.500	60.500
Deterministic LT	2/4	0/2	2/2	3.500	0.000
Modularity	4/4	0/4	0/4	0.318	0.236

Table 30: Initial Laya coverage out of four scheduled constructions per task, followed by optimum hits and mean additive gaps on exactly that supported subset for both methods. LT quality uses only the two $n = 8$ instances. Lower gaps are better, but their units differ across tasks.

S Reproduction and provenance

The data package has SHA-256

`5c1fa041c319b6682586134dba5f3219a68152ba377a24c4b888d2c23b57851a`

and contains 1,356 instances with model-visible and privileged reference files separated. Run the included `release_api.py` in an isolated process to verify data, construct a request, or score a completed history. NetworkX 3.6.1 and Python 3.11 or later suffice for the offline artifact. The separate 952-instance prospective bundle has SHA-256

`a1c468b79e8033981b501d346a91c481d4bac1635a765391c0b816b105255e9c`

and does not overwrite the earlier release. The two bundles contain 2,308 instance records in total; this is not a count of independent graph topologies.

A separate portable action-results package contains all 9,072 primary model episodes and 18,000 decisions across twelve lanes. It reconstructs each own-history public request, checks its hash and legal action, and recomputes mathematical scores and taskwise aggregates using the bundled scorer. Independent extractions replay identically in Python 3.11 and 3.12 with network operations and original-workspace reads denied; no provider SDK, weights or endpoint is required. This package verifies completed mathematical traces, not transport conformance, timing, probability reliability, classical heuristic search or bootstrap intervals. Its exporter refuses incomplete or mock lanes rather than removing failures. Derived floating-point comparisons use absolute 10^{-12} tolerance; IDs, actions, counts and statuses remain exact. Its SHA-256 is

`acdf7c9f07f4df806f90a6d40a54a3aa15600c1b294a270bbc914fd9623942ab`

That portable package covers the primary matrices only. The later GPT, Astra, expanded-model and diagnostic ledgers are separately preserved and verified in the local project; they are not silently included in its 9,072-episode replay claim. The manuscript source archive includes their generated tables and provenance so that the PDF can be rebuilt offline, but is not a complete raw-evidence replay package for those extensions. Preparing and checking their distributable evidence, subject to permissions, remains a public-release requirement.

The original four-configuration tables and size figure are generated by `scripts/build_paper_evidence.py` from sealed real-run attempts, not hand-entered scores. It refuses mock/injected runs, checks artifact hashes, replays every request/history and score, validates token argmax/accounting, and checks equality of initial public requests across methods. It recomputes classical references and exact on-policy continuation loss without any model calls. The generated provenance file includes source and artifact digests.

The twelve-configuration main tables and public website aggregates are generated offline by `scripts/export_twelve_model_publication.py`. This versioned presentation combines the original sealed ten-configuration export with the separately verified BF16 extension; it does not overwrite either experiment. The source archive includes both sets of generated tables. The extension pins `Qwen/Qwen3.8-27B` to revision

```
1d4bf0f2ff6012fd82039f2fa52739d0dd7c60c0
```

and `Qwen/Qwen2.5-72B-Instruct` to revision

```
495f39366efef23836d0cfae4fbe635880d2be31
```

Full BF16 checkpoint admission, bounded no-thinking requests, actual served-tokenizer checks and restored-service receipts are retained locally. The successful extension uses 3,840 inference calls in total. Its earlier zero-call infrastructure attempt is not an extra quality sample. Neither this exporter nor rebuilding the manuscript requires live inference.

Earlier runner validation passed 72 targeted integration tests in both Python 3.11 and 3.12. Original-run per-instance scores compare exactly. Only aggregate float comparisons permit absolute 10^{-12} roundoff, addressing the approximately 5×10^{-17} difference from Python summation changes. This numerical bookkeeping tolerance is unrelated to the failed 0.01 CPU/GPU probability reproduction gate.

The full experimental record retains strict legacy, state-explicit, action-observation, and common-interface protocols separately. Pending runs have no final accuracy; interrupted episodes remain in scheduled denominators. The manuscript build does not require inference credentials or model services.