

Item Lifecycle - Delete Item

Reference

Service: Workload Development

API Version: v1

Called by Microsoft Fabric for deleting an existing item.


Upon item deletion Fabric performs some basic validations and calls this API to notify the workload. The workload is expected to delete the item metadata and free resources.

This API should accept [SubjectAndApp authentication](#) . However, the subject token may be unavailable in some cases.

##Permissions Permissions are checked by Microsoft Fabric.

| |
|---|
| HTTP |
| <code>DELETE https://workload.contoso.com/workload-api-path-placeholder/workspaces/{workspaceId}/items/{itemType}/{itemId}</code> |

URI Parameters

 Expand table

| Name | In | Required | Type | Description |
|----------|------|----------|----------------|----------------|
| itemId | path | True | string uuid | The item ID. |
| itemType | path | True | string | The item type. |

| | | | | |
|-------------|------|------|----------------|-------------------|
| workspaceId | path | True | string uuid | The workspace ID. |
|-------------|------|------|----------------|-------------------|

Responses

 Expand table

| Name | Type | Description |
|--------------------|-------------------------------|--|
| 200 OK | | Successfully deleted. |
| Other Status Codes | ErrorResponse | For error conditions the workload should return an appropriate HTTP error status code (4xx, 5xx) with detailed error information in the response body. |

Examples

Delete item example

Sample Request

HTTP


HTTP

```
DELETE https://workload.contoso.com/workload-api-path-placeholder/workspaces/e5ef604d-e14f-4a59-9133-75d5a0cb9334/items/Contoso.FinanceAnalytics.Forecast/b14cb7e7-d346-4751-9cfd-8c2767d53111
```

Sample Response

Status code: 200


Definitions

 Expand table

| Name | Description |
|--|---------------------------------|
| ErrorExtendedInformation | The extended error information. |
| ErrorResponse | The error response. |
| ErrorSource | The source of the error. |
| NameValuePair | A name-value pair. |

ErrorExtendedInformation

The extended error information.


 Expand table

| Name | Type | Description |
|----------------------|----------------------------------|--|
| additionalParameters | NameValuePair [] | A list of additional parameters specific to the error. |
| errorCode | string | The error code. |
| message | string | The error message. |

| | | |
|-------------------|----------|--|
| messageParameters | string[] | A list of parameters for formatting a localized message. |
|-------------------|----------|--|

ErrorResponse

The error response.

 Expand table

| Name | Type | Description |
|-------------------|--|---|
| errorCode | string | The error code. |
| isPermanent | boolean | Indicates whether the error is permanent or the operation can be retried. |
| message | string | The error message. |
| messageParameters | string[] | A list of parameters for formatting a localized message. |
| moreDetails | ErrorExtendedInformation[] | A list of additional error details. |
| source | ErrorSource | The error source. |

ErrorSource

The source of the error.

 Expand table

| Name | Type | Description |
|------|------|-------------|
|------|------|-------------|

| | |
|----------|--------|
| External | string |
| System | string |
| User | string |

NameValuePair

A name-value pair.

 Expand table

| Name | Type | Description |
|-------|--------|-------------|
| name | string | The name. |
| value | string | The value. |