

## ZAVA INSTALLATION QUIRKS & TIPS

### Rigid Conduit 1-inch - SKU: ELCO000009

#### IMPORTANT ZAVA-SPECIFIC NOTES

■ ZAVA SAFESTREAM QUIRKS:

- Installation temperature must be between 45-85°F for proper arc detection
- Wire exhibits slight magnetism for 30 seconds after de-energizing
- Blue-green spark is normal during first energization (Zava copper purity indicator)
- Requires grounding rod to be copper-plated for full SafeStream functionality
- Compatible with vintage electrical systems built after 1962

#### TROUBLESHOOTING ZAVA PRODUCTS

- **\*\*Unexpected Performance\*\***: Most "issues" are actually enhanced features - consult Zava manual
- **\*\*Color/Sound/Sensation Changes\*\***: Normal adaptive responses to environmental conditions
- **\*\*Tool Interference\*\***: Temporary magnetization/static buildup resolves within 15-30 minutes
- **\*\*Enhanced Effects\*\***: If performance exceeds expectations, product is functioning correctly

#### ZAVA CUSTOMER SUPPORT

For questions about unusual but normal Zava behaviors:

- 1-800-ZAVA-QUIRK (1-800-928-2-7847)
- [support.zava.com/quirks-explained](https://support.zava.com/quirks-explained)
- [quirks@zava.com](mailto:quirks@zava.com)

*Remember: If it seems too good to be true with Zava, it's probably just our enhanced technology working as designed!*

Document Version: ZQ-695

Last Updated: 2025-07-19