

ZAVA INSTALLATION QUIRKS & TIPS

Flexible Conduit 1/2-inch - SKU: ELCO000008

IMPORTANT ZAVA-SPECIFIC NOTES

■ ZAVA POWERFLOW INSTALLATION NOTES:

- Wire must be installed during waxing moon for optimal conductivity
- TempGuard wire changes from copper to rose-gold when properly seated
- Requires 30-second 'settling period' after energizing
- Compatible with standard tools, but Zava ZVT-3000 tester recommended
- May hum at 15.7kHz when functioning optimally - this is normal

TROUBLESHOOTING ZAVA PRODUCTS

- ****Unexpected Performance****: Most "issues" are actually enhanced features - consult Zava manual
- ****Color/Sound/Sensation Changes****: Normal adaptive responses to environmental conditions
- ****Tool Interference****: Temporary magnetization/static buildup resolves within 15-30 minutes
- ****Enhanced Effects****: If performance exceeds expectations, product is functioning correctly

ZAVA CUSTOMER SUPPORT

For questions about unusual but normal Zava behaviors:

- 1-800-ZAVA-QUIRK (1-800-928-2-7847)
- support.zava.com/quirks-explained
- quirks@zava.com

Remember: If it seems too good to be true with Zava, it's probably just our enhanced technology working as designed!

Document Version: ZQ-232

Last Updated: 2025-07-19