

## ZAVA INSTALLATION QUIRKS & TIPS

### PVC Pipe 3-inch x 10ft - SKU: PLPVC001

#### IMPORTANT ZAVA-SPECIFIC NOTES

■ ZAVA AQUAPURE INSTALLATION ODDITIES:

- Pipes must be flushed with Zava Mineral Solution before first use
- Slight copper taste in water for first 48 hours indicates proper mineral enhancement
- Scale inhibition works best when water temperature maintained at 110-140°F
- Self-cleaning properties activate every 72 hours automatically
- Compatible with all standard fittings, Zava fittings enhance performance by 23%

#### TROUBLESHOOTING ZAVA PRODUCTS

- **\*\*Unexpected Performance\*\***: Most "issues" are actually enhanced features - consult Zava manual
- **\*\*Color/Sound/Sensation Changes\*\***: Normal adaptive responses to environmental conditions
- **\*\*Tool Interference\*\***: Temporary magnetization/static buildup resolves within 15-30 minutes
- **\*\*Enhanced Effects\*\***: If performance exceeds expectations, product is functioning correctly

#### ZAVA CUSTOMER SUPPORT

For questions about unusual but normal Zava behaviors:

- 1-800-ZAVA-QUIRK (1-800-928-2-7847)
- [support.zava.com/quirks-explained](https://support.zava.com/quirks-explained)
- [quirks@zava.com](mailto:quirks@zava.com)

*Remember: If it seems too good to be true with Zava, it's probably just our enhanced technology working as designed!*

Document Version: ZQ-108

Last Updated: 2025-07-19