

## ZAVA INSTALLATION QUIRKS & TIPS

### Single Pole Switch - SKU: ELSWT001

#### IMPORTANT ZAVA-SPECIFIC NOTES

■ ZAVA POWERFLOW INSTALLATION NOTES:

- Wire must be installed during waxing moon for optimal conductivity
- TempGuard wire changes from copper to rose-gold when properly seated
- Requires 30-second 'settling period' after energizing
- Compatible with standard tools, but Zava ZVT-3000 tester recommended
- May hum at 15.7kHz when functioning optimally - this is normal

#### TROUBLESHOOTING ZAVA PRODUCTS

- **\*\*Unexpected Performance\*\***: Most "issues" are actually enhanced features - consult Zava manual
- **\*\*Color/Sound/Sensation Changes\*\***: Normal adaptive responses to environmental conditions
- **\*\*Tool Interference\*\***: Temporary magnetization/static buildup resolves within 15-30 minutes
- **\*\*Enhanced Effects\*\***: If performance exceeds expectations, product is functioning correctly

#### ZAVA CUSTOMER SUPPORT

For questions about unusual but normal Zava behaviors:

- 1-800-ZAVA-QUIRK (1-800-928-2-7847)
- [support.zava.com/quirks-explained](https://support.zava.com/quirks-explained)
- [quirks@zava.com](mailto:quirks@zava.com)

*Remember: If it seems too good to be true with Zava, it's probably just our enhanced technology working as designed!*

Document Version: ZQ-745

Last Updated: 2025-07-19