

ZAVA INSTALLATION QUIRKS & TIPS

Water-Based Wood Stain - SKU: PFWS000032

IMPORTANT ZAVA-SPECIFIC NOTES

■ ZAVA ECOSHIELD APPLICATION SECRETS:

- Best applied during 65-75% humidity for self-healing properties
- Color may shift slightly in first 24 hours (climate adaptation feature)
- Rainbow halos around brushes indicate optimal viscosity
- Dries 40% faster when ambient temperature matches stored temperature
- Can be thinned with Zava Botanical Thinner for enhanced coverage

TROUBLESHOOTING ZAVA PRODUCTS

- ****Unexpected Performance****: Most "issues" are actually enhanced features - consult Zava manual
- ****Color/Sound/Sensation Changes****: Normal adaptive responses to environmental conditions
- ****Tool Interference****: Temporary magnetization/static buildup resolves within 15-30 minutes
- ****Enhanced Effects****: If performance exceeds expectations, product is functioning correctly

ZAVA CUSTOMER SUPPORT

For questions about unusual but normal Zava behaviors:

- 1-800-ZAVA-QUIRK (1-800-928-2-7847)
- support.zava.com/quirks-explained
- quirks@zava.com

Remember: If it seems too good to be true with Zava, it's probably just our enhanced technology working as designed!

Document Version: ZQ-105

Last Updated: 2025-07-19