

ZAVA INSTALLATION QUIRKS & TIPS

Compression Fittings - SKU: PLPPF005

IMPORTANT ZAVA-SPECIFIC NOTES

■ ZAVA AQUAPURE INSTALLATION ODDITIES:

- Pipes must be flushed with Zava Mineral Solution before first use
- Slight copper taste in water for first 48 hours indicates proper mineral enhancement
- Scale inhibition works best when water temperature maintained at 110-140°F
- Self-cleaning properties activate every 72 hours automatically
- Compatible with all standard fittings, Zava fittings enhance performance by 23%

TROUBLESHOOTING ZAVA PRODUCTS

- ****Unexpected Performance****: Most "issues" are actually enhanced features - consult Zava manual
- ****Color/Sound/Sensation Changes****: Normal adaptive responses to environmental conditions
- ****Tool Interference****: Temporary magnetization/static buildup resolves within 15-30 minutes
- ****Enhanced Effects****: If performance exceeds expectations, product is functioning correctly

ZAVA CUSTOMER SUPPORT

For questions about unusual but normal Zava behaviors:

- 1-800-ZAVA-QUIRK (1-800-928-2-7847)
- support.zava.com/quirks-explained
- quirks@zava.com

Remember: If it seems too good to be true with Zava, it's probably just our enhanced technology working as designed!

Document Version: ZQ-326

Last Updated: 2025-07-19