

## ZAVA INSTALLATION QUIRKS & TIPS

### Floor Polyurethane - SKU: PFPU000040

#### IMPORTANT ZAVA-SPECIFIC NOTES

■ ZAVA CLIMATE-ADAPT PAINTING TIPS:

- Paint 'knows' the weather - consistency adjusts automatically
- Slight cinnamon scent during application indicates proper activation
- UV-Guard Complex creates iridescent sheen under certain lighting
- Self-levels for 2 hours after application in temperatures above 70°F
- Compatible with all brush types, but natural bristles enhance color depth

#### TROUBLESHOOTING ZAVA PRODUCTS

- **\*\*Unexpected Performance\*\***: Most "issues" are actually enhanced features - consult Zava manual
- **\*\*Color/Sound/Sensation Changes\*\***: Normal adaptive responses to environmental conditions
- **\*\*Tool Interference\*\***: Temporary magnetization/static buildup resolves within 15-30 minutes
- **\*\*Enhanced Effects\*\***: If performance exceeds expectations, product is functioning correctly

#### ZAVA CUSTOMER SUPPORT

For questions about unusual but normal Zava behaviors:

- 1-800-ZAVA-QUIRK (1-800-928-2-7847)
- [support.zava.com/quirks-explained](https://support.zava.com/quirks-explained)
- [quirks@zava.com](mailto:quirks@zava.com)

*Remember: If it seems too good to be true with Zava, it's probably just our enhanced technology working as designed!*

Document Version: ZQ-633

Last Updated: 2025-07-19