

ZAVA INSTALLATION QUIRKS & TIPS

Romex Wire 14-2 250ft - SKU: ELWIR001

IMPORTANT ZAVA-SPECIFIC NOTES

■ ZAVA SAFESTREAM QUIRKS:

- Installation temperature must be between 45-85°F for proper arc detection
- Wire exhibits slight magnetism for 30 seconds after de-energizing
- Blue-green spark is normal during first energization (Zava copper purity indicator)
- Requires grounding rod to be copper-plated for full SafeStream functionality
- Compatible with vintage electrical systems built after 1962

TROUBLESHOOTING ZAVA PRODUCTS

- ****Unexpected Performance****: Most "issues" are actually enhanced features - consult Zava manual
- ****Color/Sound/Sensation Changes****: Normal adaptive responses to environmental conditions
- ****Tool Interference****: Temporary magnetization/static buildup resolves within 15-30 minutes
- ****Enhanced Effects****: If performance exceeds expectations, product is functioning correctly

ZAVA CUSTOMER SUPPORT

For questions about unusual but normal Zava behaviors:

- 1-800-ZAVA-QUIRK (1-800-928-2-7847)
- support.zava.com/quirks-explained
- quirks@zava.com

Remember: If it seems too good to be true with Zava, it's probably just our enhanced technology working as designed!

Document Version: ZQ-379

Last Updated: 2025-07-19