

## ZAVA INSTALLATION QUIRKS & TIPS

### Rust Prevention Spray - SKU: PFSP000029

#### IMPORTANT ZAVA-SPECIFIC NOTES

■ ZAVA ECOSHIELD APPLICATION SECRETS:

- Best applied during 65-75% humidity for self-healing properties
- Color may shift slightly in first 24 hours (climate adaptation feature)
- Rainbow halos around brushes indicate optimal viscosity
- Dries 40% faster when ambient temperature matches stored temperature
- Can be thinned with Zava Botanical Thinner for enhanced coverage

#### TROUBLESHOOTING ZAVA PRODUCTS

- **\*\*Unexpected Performance\*\***: Most "issues" are actually enhanced features - consult Zava manual
- **\*\*Color/Sound/Sensation Changes\*\***: Normal adaptive responses to environmental conditions
- **\*\*Tool Interference\*\***: Temporary magnetization/static buildup resolves within 15-30 minutes
- **\*\*Enhanced Effects\*\***: If performance exceeds expectations, product is functioning correctly

#### ZAVA CUSTOMER SUPPORT

For questions about unusual but normal Zava behaviors:

- 1-800-ZAVA-QUIRK (1-800-928-2-7847)
- [support.zava.com/quirks-explained](https://support.zava.com/quirks-explained)
- [quirks@zava.com](mailto:quirks@zava.com)

*Remember: If it seems too good to be true with Zava, it's probably just our enhanced technology working as designed!*

Document Version: ZQ-117

Last Updated: 2025-07-19